

# The Power Buggy

BY **Indy**



[www.thepowerbuggy.com](http://www.thepowerbuggy.com)

[www.indyequipment.com](http://www.indyequipment.com)

RENTAL FLEET

1-877-320-4639

CONSTRUCTION

MATERIAL HAULING



LANDSCAPING

Proudly Made In The U.S.A.

FARM & RANCH



**iPB-16**



**iPB-21**

# The Power Buggy

BY **Indy**



6500 Schaaf Road  
Independence, OH 44131  
Toll Free: 1-877-320-INDY (4639)  
FAX: 216-446-3989

## Features:

- Simultaneous dump and hydrostatic drive capability allows for feathering of load in forward and reverse.
- Operator's platform and control system allows for comfortable and convenient operation of the unit.
- Two models, 16 ft<sup>3</sup> (453 L) and 21 ft<sup>3</sup> (595 L) capacities.
- Power supplied through heavy duty hydraulic pump and two high efficiency drive motors.
- Foam Filled Tires
- Excellent traction and control with heavy-duty welded chassis.
- Simple, clean control panel.
- Industry's largest and highest efficiency wheel motors allow higher speeds and more reliable braking.
- Foot operated dump lever allows operator to keep both hands on steering handle at all times.
- Foot actuated operating and parking brake.

## SPECIFICATIONS AND DIMENSIONS:

Model	IPB-16 / IPB16E	IPB-21
Wheelbase	43 in (109.2 cm)	43 in (109.2 cm)
Overall Length	103 in (261.6 cm)	101.5 in (257.8 cm)
Overall Width (Single Wheels)	35.5 in (90.2 cm)	N/A
(Dual Wheels)	47 in (119.4 cm)	47 in (119.4 cm)
Overall Height	53 in (134.6 cm)	56 in (142 cm)
Maximum Load	2,500 lbs (1,136 kg)	3,200 lbs (1,455 kg)
Capacity	16 ft (453 L)	21 ft (595L)
Discharge Height	3.5 in (8.9 cm)	5 in (12.7 cm)
Hydraulic Oil - Exxon Nuto #H68	11.5 qt (11.0 L)	11.5 qt (11.0L)
Speed	7.25 mph (11.67 km/h) at 4,000 rpm	7.25 mph (11.67 km/h) at 4,000 rpm
Drive	Hydrostatic	Hydrostatic
Brakes	Hydraulically Controlled	Hydraulically Controlled
Parking Brake	Mechanical	Mechanical
Dump	Variable Hydraulic	Variable Hydraulic
Engine	Honda GX390 13hp / 13hp E-start	Vanguard B&S 18hp
Drive Tires	5.70 x 8 x 19	5.70 x 8 x 19
Steering Tires	4.80 x 8 x 16	4.80 x 8 x 16
Operating Weight	1,260 lbs (571.5 kg)	1,325 (601 kg) Poly / 1480 (671 kg) Steel
Shipping Weight	1,360 lbs (616.9 kg)	1,425 (646 kg) Poly / 1580 (717 kg) Steel

For more information, product demonstration, or details on purchase, lease and rental plans, please contact your local Power Buggy Distributor.  
WWW.THEPOWERBUGGY.COM

Effective Date: January 1st, 2014. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale or we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Indy Equipment & Supply LLC and/or their subsidiaries in the U.S.A. Copyright © 2014 Indy Equipment & Supply LLC