

## Important Installation, Sealing & Cleaning Instructions

- These bricks MUST be sealed with a polymeric sealer to ensure a good service life. They incorporate
  lime coatings that require sealing to withstand cleaning, abrasion, and general weathering.
- The bricks may be sealed either before or after grout is applied.
- If sealed after the application of grout, extra care should be exercised to avoid over-grout during grouting.
- All grouting should be done with a grout bag to minimize over-grout.
- The "smear-grout" technique should never be used on these bricks.
- Acids, and cleansers containing acids, should NEVER be used on these bricks, including after sealing.

We recommend **NanoPave JSS Natural**, manufactured by **Technisoil**, for sealing these bricks. NanoPave JSS Natural is a water-based, VOC-free, polymeric sealer which can usually be purchased locally.

- Use a roller, brush, or spray bottle to apply the NanoPave JSS Natural onto the bricks.
- Coverage for NanoPave JSS Natural rates up to 100 square feet per gallon, depending on surface porosity and joint width .
- Correctly applied, NanoPave JSS Natural will leave little or no sheen.





Since any sealer will produce at least a minute change in the brick's appearance, it is advisable to first test whatever sealer you are using in an inconspicuous location, to be sure the result will be acceptable.

Maintenance cleaning can be done with gentle washing, and if necessary, light brushing with a soft bristle brush. Use clean water, and a mild detergent, if necessary.