

Arrays

Lecture 6

Go to poll.unc.edu

Sign-in via this website then go to pollev.com/compunc

VSCoDe: Open Project -> View Terminal -> `npm run pull` -> `npm start`

Fixing the "Black Screen of Death"

- When you see a screen that looks like the black screen to the right:
- The error may be in a file other than the one you are working on. **The file with the error is this one.**
- The simplest short-term fix in lecture is select all text in the file (Ctrl+A) and then comment it out (Ctrl+/) and save.
- The specific line # of the file that TypeScript *believes* the error is on is this number in parenthesis.

```
Failed to compile.  
./src/lec08-array-algos/02-berry-stats-app.ts  
(43,8): error TS1005: '}' expected.
```

Challenge #1: What are the elements of **a**?

```
let a: number[] = [ 2 ]; // Notice initial element 2

for (let i = 0 ; i < 3; i++) {
    a[a.length] = (i + 1) * 2;
}

print(a);
```

2. What is the printed output when **main** runs?

```
export let main = async () => {
  test("double(3)", 6, double(3));
};

let double = (x: number): number => {
  return x ** 2;
};

let test = (s: string, e: number, a: number): void => {
  if (e === a) {
    print("PASS: " + s);
  } else {
    print("FAIL: " + s);
  }
};
```

How do we **append** an element to an array?

- Given an array **a**, what is the **next** index needed to append?
 - When it is **empty**, or has **0 elements**, the next index is **0**
 - When it has **1 element**, the next index is **1**
 - When it has **2 elements**, the next index is **2**
- **Because of 0-based indexing, we can use the # of elements in an array as the index to use to append a value to the array.**
- Append to an array:

```
a[a.length] = <value>;
```

Organizing a Project into Multiple Files

- As our programs grow in size, we will organize them across multiple files
 - Each file will have related functions and functionality

- You can **export** *functions* and *classes* from one TypeScript file

```
export let aFunc = () => { ... }
```

- And **import** them into *another* TypeScript file

```
import { <function>, <function> } from "./<file>";
```

- Example: **import { foo, bar } from "./library";**
 - These functions would be *exported* from a file named library.ts
 - Note: Only the file with the **main** function needs to its filename to end with `-app.ts`

Test-driven Function Writing

- Before you implement a function, focus on concrete examples of *how the function should behave as if it were already implemented*.
- Key questions to ask:
 1. **What are some *usual* input parameters?**
 - These are called *use cases*.
 2. **What are some valid but *unusual* input parameters?**
 - These are your *edge cases*.
 3. Given those input parameters, **what is your expected return value for each set of inputs?**

Test-Driven Programming: Case Study

- Suppose you want to write a function named **fillZeros**
 - Its purpose is to create and fill an array of length **n** with all **0s**
 - Its signature is this: **fillZeros = (n: number): number[]**
1. **What are some *usual* input parameters?**
 - These are called *use cases*.
 2. **What are some valid but *unusual* input parameters?**
 - These are your *edge cases*.
 3. Given those input parameters,
what is your expected return value for each set of inputs?

Testing Use/Edge Cases Programmatically

- After you have some use and edge cases, implement the skeleton of the function that is *syntactically valid* but *wrong*
 - Typically this means define the function and do nothing inside of the body except return a valid literal value. For example:

```
export let fillZeros = (n: number): number[] => {  
    return [];  
};
```

- Then, turn your use and edge cases into programmatic tests.
- How? With a function that compares an *expected* result with an *actual* result.

Example Test Functions

- Let's briefly look at **test-util.ts**
- It has two functions defined: `testArray`, `testNumber`
 - The first can test the results of a function that returns a number array
 - The second of a function that returns a number
- Let's try adding a test case inside the main function of `array-practice-app.ts`:

```
testArray("fillZeros 2", [0, 0], fillZeros(2));
```

This is the name of your test.

This is your expected result.

This is your actual result. Notice that it's calling the **fillZeros** function with an expected input.

Programmatic Tests Give You Instant Feedback

Test: `testArray("fillZeros 2", [0, 0], fillZeros(2));`

Implementation:

```
export let fillZeros = (n: number): number[] => {  
    return [];  
};
```

Result: FAIL: fillZeros 2
string

-- Expected: 0,0
string

-- Actually:
string

Testing is no substitute for critical thinking...

Is this **fillZeros** correct?

Test: `testArray("fillZeros 2", [0, 0], fillZeros(2));`

Implementation:

```
export let fillZeros = (n: number): number[] => {  
  return [0, 0];  
};
```

Result: **PASS: fillZeros 2**
string

- Passing a test doesn't ensure your function is correct!
- Rules of Thumb:
 - Test 2+ use cases and 1+ edge cases.
 - When a function has if-else statements, try to write a test that reaches each branch.

Follow-along: Implement **fillZeros**

- In `array-practice-app.ts`, add two more test cases:
 - Parameter Input: 1, Expected Result: [0]
 - Parameter Input: 0, Expected Result: []
- In `array-functions.ts`, we'll rewrite the body of the **fillZeros** function to build an array with **n** zeros in it.
 1. Declare a number array variable. Initialize it to an empty array.
 2. Write a loop that iterates n times.
 3. Append a 0 to the array.
 4. After the loop completes, return the array.

```
export let fillZeros = (n: number): number[] => {  
  let a: number [] = [];  
  for (let i = 0; i < n; i++) {  
    a[i] = 0;  
  }  
  return a;  
};
```

4. Suppose you're writing a **fillRange** function

- Its signature is:

```
fillRange(low: number, high: number): number[]
```

- Its purpose is to generate an array of consecutive integers increasing from low and ending with high, inclusive.
- Select the test case (input parameters and expected return value) which you believe is the best example of an **edge case**.

Hands-on: Write Tests for **fillRange**

- The function generates an array of numbers from low to high, inclusive.
- One example use case:
fillRange(0, 2) expects a return value of **[0, 1, 2]**
- In **array-practice-app.ts**:
 1. Write a test for another **use case** you can imagine: inputs 1, 3 – output: [1, 2, 3]
 2. Write a test case for an **edge case** – input: 3, 1 – []
- Once you have two failing tests, one passing, check-in on pollev.com/compunc

Hands-on: Implement **fillRange**

1. Open **array-functions.ts**
2. Hint #1: Look to `fillZeros` as a starting point.
3. Hint #2: What should your loop's counting variable's initial value be?
4. Hint #3: You can append to an array named `a` with: `a[a.length] = <num>`
5. **Check-in once you have your tests passing** and a working **fillRange**.
6. Done? Try improving with a version that rounds down decimals and still works.

Challenge #2. Given the filter function to the left, which of the following definitions of **test** is correct?

```
let filter = (a: number[]): number[] => {  
  let match: number[] = [];  
  for (let i = 0; i < a.length; i++) {  
    let element = a[i];  
    if ( test(element) ) {  
      match[match.length] = a[i];  
    }  
  }  
  return match;  
}
```

```
// A
```

```
let test = (e: number): void => { /* ... */ }
```

```
// B
```

```
let test = (e: string): boolean => { /* ... */ }
```

```
// C
```

```
let test = (e: number): boolean => { /* ... */ }
```

```
// D
```

```
let test = (e: boolean): number => { /* ... */ }
```

Follow-Along: Testing **sum**

- Let's implement a function to total up a sum of all elements in an array
- What are our test cases?

```
testNumber("sum([])", 0, sum([]));  
testNumber("sum([1])", 1, sum([1]));  
testNumber("sum([2, 3])", 5, sum([2, 3]));
```

- Notice the `sum` function takes an array of number values as a parameter and returns a number!
 - So we'll test with the simple **testNumber** function defined in **test-util.ts**

Hands-on: Implementing **sum**

- In `array-functions.ts` implement the `sum` function
- Your algorithm should:
 1. Declare a variable to "accumulate" a sum
 2. Loop through each element in the input array `a` and add its value to your accumulating variable
 3. Return your accumulating variable
- Check-in when your **sum** tests are passing!