

# Working with an Object Library

Lecture 19 - Fall 2018

# Apply to be a UTA

- Applications are open at <http://comp110.com/become-a-uta/>
- Due LDOC at 11:59pm
- Hiring committee is made of 8 elected UTAs

# Final Exams

- We will split up across this room and another. I will let you know when your assigned building and seat are posted!
- Section 1 - Saturday, December 8th at 12pm
- Section 2 - Saturday, December 13th at 4pm
- Do you have a pink slip for 3 exams in 24 hours?
  - Scan it on your phone and email it to me with the subject: **3 in 24 PINK SLIP**
  - Make-ups are nearest reading day prior at 9am
    - Section 1 - Thursday, December 6th at 9am - Sitterson 254
    - Section 2 - Friday, December 12th at 9am - Sitterson 254

1. Given the class Point, what is the output when the code to the right runs?

```
class Point {  
  x: number = 0;  
  y: number = 0;  
  
  quadrant(): number {  
    if (this.x >= 0) {  
      if (this.y >= 0) {  
        return 1;  
      } else {  
        return 4;  
      }  
    } else {  
      if (this.y >= 0) {  
        return 2;  
      } else {  
        return 3;  
      }  
    }  
  }  
}
```

```
let a = new Point();  
a.x = 10;  
a.y = -10;  
  
let b = a;  
b.x = -10;  
b.y = 10;  
  
print(a.quadrant());
```

2. What is printed when the main function below runs?

```
let main = async () => {
  print("F");
  let krackle = new Dog("Krackle");

  let hello = krackle.speak("hello");

  print(krackle.speak("world"));
  print(hello);
}
```

```
class Dog {
  name: string;

  constructor(name: string) {
    print("A");
    this.name = name;
  }

  translate(word: string): string {
    print("B");
    if (word !== "hello") {
      return "C";
    } else {
      return "D";
    }
  }

  speak(word: string): string {
    print("E");
    return this.translate(word);
  }
}
```

# TypeScript and HTML/CSS

- So far, we've made "apps" by creating TypeScript files named "-app.ts"
  - In these apps we have been able to print values and prompt for inputs
- Today we'll see a single-page web app
  - It will be made up of HTML, TypeScript, and CSS
- HTML - (Hyper-Text Markup Language)
  - The primary "document" being loaded into the web browser
  - Our TypeScript code is included by the HTML
- TypeScript
  - The "code" you'll write!
  - Can access HTML and update / change it to present graphics, data, and forms to the user.
- CSS - (Cascading Style Sheets) - The "style" or "theme" of page.

# Today's HTML (1/4)

- We will not spend much time on, nor test on, HTML & CSS in COMP110
- However, to give you a rough sense of how these three pieces fit together, it's worth taking a quick peep...

```
<html>
  <head>
    <title>Intro to CS - Graphics</title>
    <link rel="stylesheet"
          type="text/css"
          href="./style.css">
  </head>
  <body>
    <svg id="artboard"></svg>
    <div id="console"></div>
    <script src="./app-script.ts"></script>
  </body>
</html>
```

# Today's HTML (2/4)

- HTML documents are made up of "tags" describing Elements
- Typically these tags are paired:
  - Open tag: <html>
  - Close tag: </html>
- Tags can be nested inside of one another and must be properly nested (like curly brace blocks in TypeScript)
- The **head** tag is short for "header" and contains meta information about a web page
- The **body** tag is what gets displayed in the web browser.

```
<html>  
  <head>  
    <title>Intro to CS - Graphics</title>  
    <link rel="stylesheet"  
          type="text/css"  
          href="./style.css">  
  </head>  
  <body>  
    <svg id="artboard"></svg>  
    <div id="console"></div>  
    <script src="./app-script.ts"></script>  
  </body>  
</html>
```

# Today's HTML (3/4)

- The "style" of our web page is established by linking to the `./style.css` file in our project folder using this `<link>` tag.
- The TypeScript "script" or "code" of our web page is established by linking to the `./app-script.ts` file in our project folder using the `<script>` tag.
  - The `-.script.ts` suffix is important here!
  - Note: Typically, you'd have to compile a TypeScript file to a JavaScript file on your own before being able to include it in this way. Our programming environment is doing this automatically for you behind the scenes.

```
<html>
  <head>
    <title>Intro to CS - Graphics</title>
    <link rel="stylesheet"
          type="text/css"
          href="./style.css">
  </head>
  <body>
    <svg id="artboard"></svg>
    <div id="console"></div>
    <script src="./app-script.ts"></script>
  </body>
</html>
```

# Today's HTML (4/4)

- The `<svg>` tag stands for "scalable vector graphics" and is where our shapes will be displayed when we render them.
  - Notice: it's **id** is the string "artboard" - we will use this **id** in our code to be able to interact with this element.
- We also have a `<div>` or "division" tag which is where our printed output will be displayed if we use the `print()` function.

```
<html>
  <head>
    <title>Intro to CS - Graphics</title>
    <link rel="stylesheet"
          type="text/css"
          href="./style.css">
  </head>
  <body>
    <svg id="artboard"></svg>
    <div id="console"></div>
    <script src="./app-script.ts"></script>
  </body>
</html>
```

# Graphics

- We'll use the **intros** library to work with SVG graphics
  - We'll import SVG, Shape, Color, etc. classes from "intros/graphics"
- In **app-script.ts**, let's draw our first Shape!
- First, we must establish a connection between an SVG Object in our TypeScript code and the SVG tag in our HTML...
  - We'll setup a global variable to do this outside of the main function...
  - The "artboard" string is referring to the `id` of the SVG tag in the HTML.

```
let artboard = new SVG("artboard");
```

# Hands-on #1) Draw a Rectangle


Rectangle's Constructor's parameters:  
(*width: number, height: number*)

- Inside the main function of *app-script.ts*:
  1. Declare a variable named **r** of type Rectangle.
  2. Initialize **r** by constructing a new Rectangle using the constructor above. Try giving it a `width` of 100 and `height` of 10.
  3. Add it to the shapes Group variable: **`shapes.add(r);`**
  4. Save and refresh your web browser. (Unfortunately, with these HTML-based applications we have to save and then refresh the page ourselves.)
  5. Check-in on [Pollevo.com/comp110](https://www.pollevo.com/comp110)

```
export let main = async () => {  
  
  let shapes = new Group();  
  
  let r = new Rectangle(100, 10);  
  shapes.add(r);  
  
  artboard.render(shapes);  
  
}
```

# Nested Groups of Shapes

- A Group is a special kind of "Shape" object that can hold references to other Shapes
- You can add one Group of shapes to another Group
- This makes it possible to "compose" more complex scenes by breaking each drawing task into smaller functions



# Scaling & Dimensions

- The `introcs` graphics library is automatically scaling and centering our graphics to fit our browser's size.
  - This is usually *really* convenient, but today we want to get a sense positioning.
- In computer graphics, the y-axis tends to be inverted. So larger y numbers move graphics *down* on the screen.
- To get a better sense of how positioning works, let's first add some axes to our drawing.
- We've setup the basis of an `Axes` class that can be used to get a sense of positioning.

# Hands-on: Adding a constructor to the Axes class

- In `Axes.ts`, **define a constructor with 2 parameters**:
  1. `width` which is a number
  2. `height` which is a number
- Assign **both** parameter values **`width`** and **`height`** to the Axes object's respective properties... for example: **`this.height = height;`**
- In **`app-script.ts`**, in main before you setup the Rectangle, declare a variable named **`axes`** and **assign it a new Axes object constructed with arguments `100, 100`**.
- Then, call its **`getShapes`** method and add the resulting Group to the shapes Group in main: **`shapes.add(axes.getShapes());`**
- Check-in once you've made these changes (save every file!) and refreshed to see you have a Y-Axis showing up!

```
// TODO: Declare a constructor with width and
height parameters
constructor(width: number, height: number) {
  this.width = width;
  this.height = height;
}
```

```
let axes = new Axes(100, 100);
shapes.add(axes.getShapes());
```

# Hands-on: Adding an xAxis

- Under the TODO in Axes.ts' getShapes method...
- Declare a variable named xAxis and assign it a new Line object. The Line class' constructor has 4 parameters:
  1. x0 - the x component of the starting point
  2. y0 - the y component of the starting poing
  3. x1 - the x component of the ending point
  4. y1 - the y component of the ending point
- Choose arguments such that the xAxis is centered about 0, 0 and has a total width of this.width (hint: see how the yAxis was constructed)
- Add the xAxis line to the Group of shapes named g
- Check-in when you have both Axes showing!

```
let yAxis = new Line(0, -this.height / 2, 0, this.height / 2);
let xAxis = new Line(-this.width / 2, 0, this.width / 2, 0);
let g = new Group();
g.add(yAxis);
g.add(xAxis);
return g;
```

# Reference Documentation for IntroCS Graphics

- The graphics/shape library reference documentation here:
  - <http://comp110.com/introcs-graphics/>
- Getting practice reading through documentation like this is valuable
  - When building projects in later classes and industry, this is how you'll learn the capabilities of a library
- You'll notice each class and object has many more properties, methods, and constructor variations than we're covering in lecture!

# Painting by Numbers

- What we're going to do from here forward is a bit more free flowing
- We're going to explore working with Shapes and Colors using some math
- This will give us practice making use of constructors, loops, and "composing" object graphs
- There is nothing conceptually new to commit to memory or study from this point forward, this is just us making some art together as a class.

# Hands-on) Draw 10 Circles

Circle's Constructor's parameters:  
(radius: *number*, cx: *number*, cy: *number*)

The cx and cy parameters correspond to the center point of the circle.

In the main function, after you've added the axes to the group...

1. Declare a variable named **count** and initialize it to **10**
2. Write a for-loop using **i** as its counter that will loop **count** times... ***don't forget to increment i inside of the loop!***
3. Inside of the loop, declare a variable named **c**, of type **Circle**
  - Initialize it to a new Circle object using the constructor above
  - radius: 5
  - cy: 0
  - cx: Try multiplying **i** by some amount to space the circles out
4. Add the circle to the group named **g**.
5. Check-in when you have at least 1 circle visible in your scene.

```
let count = 10;
let i = 0;

for (let i = 0; i < count; i++) {
  let c = new Circle(5, i * 10 - 45, 0);
  g.add(c);
}
```

# Let's add Color

- Digital colors are often specified as a combination of red, green, blue (RGB)
- In our graphics library, we will assign *percentage amounts* of RGB using decimal values ranging from 0.0 to 1.0 (0% to 100% respectively)
  - The color white is Red: 1.0, Green: 1.0, Blue: 1.0
  - The color black is Red: 0.0, Green: 0.0, Blue: 0.0
  - Carolina Blue is: Red: 0.2929, Green: 0.6094, Blue: 0.8242

# Follow-along: Adding Color

```
let count = 10;
let i = 0;
while (i < count) {
  let c = new Circle(5, i * 10 - 45, 0);

  let red = 0.2929;
  let green = 0.6094;
  let blue = 0.8242;
  c.fill = new Color(red, green, blue);

  g.add(c);
  i++;
}
```

# Generating colors programmatically (1/2)

- How could we make our circles *increasingly blue* starting from black?
- Start: Color(0.0, 0.0, 0.0)
- End: Color(0.0, 0.0, 1.0)
- We want to pick numbers between 0.0 and 1.0 evenly as we construct each circle.
  - The technical term for this is *linear interpolation*
- We have some variables that will help us: **i** and **count**
- "Percent of Iteration Completed" Formula:  **$i / (\text{count} - 1)$** 
  - Why count - 1? Because we are starting from 0% and want the final loop iteration to be 100%

```
let percent = i / (count - 1);  
  
let c = new Circle(5, i * 20 - 90, 0);  
  
let red = 0;  
let green = 0;  
let blue = percent;
```



# Generating colors programmatically (1/2)

- How could we make our circles *decreasingly green* ending with black?
- Start: Color(0.0, 1.0, 0.0)
- End: Color(0.0, 0.0, 0.0)
- We want to pick numbers between 1.0 and 0.0 evenly as we construct each circle.
- Formula: **1.0 - percent**
  - We can invert our percentage

```
let red: number = 0;  
let green: number = 1 - percent;  
let blue: number = percent;  
c.fill = new Color(red, green, blue);
```

# How would we make a wave?

- We have to go back to our old friend **sine**.
- Let's make a sine wave!
- The Math.sin function expects that we're working in *radians*
- First, let's setup a constant to represent total radians in a circle ( $2 * \pi$ ).
- Then, we'll calculate the center-Y of each circle as a percentage of total radians.




```
let artboard = new SVG("artboard");  
const RADIANS = Math.PI * 2;
```

```
let angle = percent * RADIANS;  
let cy = Math.sin(angle) * 20;  
let c = new Circle(5, i * 10 - 45, cy);
```

# How would get the sine wave to flow over a period of time?

- Currently every circle is placed statically at its sine position
- As time elapses through some **period** (of time) we want to offset its y-value by the percentage of the **period** that has completed
- We can get the current time using the built-in `Date.now()` method. This will give us the number of milliseconds passed since 1/1/1970.
  - How do we convert ms to s?
  - Once we have the current time in seconds, how do we get a period that will cycle through from 0-period as time passes? Hint: modulo!
  - How do we calculate the percentage of the period that has passed?



```
let time = Date.now() / MS_IN_S;
let periodPercent = time % PERIOD / PERIOD;

let count = 10;
let i = 0;
while (i < count) {
    let percent = (i + 1) / count;
    let angle = percent * RADIANS;
    let angleT = periodPercent * RADIANS;
    let cy = Math.sin(angle + angleT) * 20;

    let c = new Circle(5, i * 10 - 45, cy);
```

# How do we get the sine wave to animate?

- We need the main function to be called repeatedly over time...
- Luckily, there is a built-in function that can do this for us!

```
interface VoidFunction {  
    (): void;  
}
```

```
setInterval(f: VoidFunction, milliseconds: number): number
```

- main does not return anything so it satisfies the VoidFunction functional-interface
- So, we can call `setInterval` and passing a reference to the main function. Let's try an interval of 20ms.

```
setInterval(main, 30);
```