

## Halls A, B, C

280,000 square feet of contiguous exhibit space is divisible into Hall A (100,000 square feet), Hall B (100,000 square feet), Hall C1 (40,000 square feet) and Hall C2 (40,000 square feet), or Hall C combined (80,000 square feet). (See Hall C Amenities).

### Exhibit Space Features Include:

- 20 totally covered loading docks. (Minimum of one load leveler per hall.)
- Off-site marshalling yard to accommodate up to 50 semi-tractor trailers available at applicable rates.
- Direct drive-in access into each hall.

### Truck door dimensions are as follows:

- 16' H x 26' W – Hall A
- 16' H x 12' W – Hall B
- 16' H x 23' W – Hall B
- 29' H x 26' W – Hall B
- 16' H x 26' W – Hall C
- 16' H x 26' W – Hall C

- Four freight elevators serve all levels. An additional freight elevator, large enough to accommodate an automobile, serves both the ballroom and exhibit level.
- Four individual show offices, one in each hall.
- Dark-troweled concrete floors.
- Lighting: 471-watt LED High Bay Fixtures at 30' above floor. All fixtures are dimmable and individually addressable on/off, with color temperature of 4000°K. Nominal lighting level of 42.5-foot candles.
- Public address system with overhead speakers for paging accessible from designated public address stations.
- Large concession stand in each hall. Mobile Food Solutions can be used to enhance food service.
- Utilities: Three 120-volt, single-phase, 20-amp duplex outlets and one 208/120-volt, three-phase, 60-amp outlet provided through flush-mounted floor boxes located on 30' centers. Waste water drain and multiple telephone service suitable for voice and data transmission.
- Provided at column locations (90' center): One 480/277-volt, three-phase, 100-amp outlet, portable cold water and compressed air with the capability to pull through the underfloor conduit system to any floor box. Cable television and fiber optics located at each column.
- In addition, 480/277-volt, three-phase, four-wire service and 208/120-volt, three-phase, four-wire service are available from plug-in bus ducts located in the roof structure.
- Floor Load Capacity: 350 PSF live load.

## Hall C Amenities

- Converts to general assembly hall to accommodate up to 5,500 people with portable stage of 40'D x 56'W.
- 471 watt LED High Bay Fixtures at 30' above floor. All fixtures are dimmable and individually addressable on/off, with color temperature of 4000°K. Nominal lighting level of 42.5-foot candles.
- 180" x 150" column clear-span area for greater visibility in general assembly setup.
- Additional 400-amp, 208/120-volt service to portable stage locations.
- Upgraded, permanently installed sound reinforcement system with appropriate controls and microphone jacks for general assembly use.

Hall	Sq. Ft.	10' x 10' Booths
A	100,000	450
B	100,000	450
C	80,000	350
A & B	200,000	900
B & C	180,000	800
C1	40,000	175
C2	40,000	175
A, B & C	280,000	1,250