

STUDIO Translucent Glaze

AVAILABLE COLORS


- Snow Cap **ADSTW** Bamboo **ADSTB** Ice Blue **ADSTI** Fern **ADSTF** Almond **ADSTA** Eucalyptus **ADSTE**
 Silver Sands **ADSTS** Graystone **ADSTG** Timberline **ADSTT** Volcanico **ADSTV**

ambiente

EUROPEAN TILE DESIGN

400 East Pine Street, Suite 210
Seattle, WA 98122

206-524-2113
ambientetile.com



STUDIO Translucent Glaze

AVAILABLE COLORS


- Snow Cap **ADSTW** Bamboo **ADSTB** Ice Blue **ADSTI** Fern **ADSTF** Almond **ADSTA** Eucalyptus **ADSTE**
 Silver Sands **ADSTS** Graystone **ADSTG** Timberline **ADSTT** Volcanico **ADSTV**

Find out the product code simply by putting together the color and the item

Example: **ADSTW** **836**

FIELD TILES

UNDULATED




TRIMS

FINISHING EDGES




- 506** FE 0.5"x5.8"
- 508** FE 0.5"x7.8"
- 500** FE Corner

UNDULATED GLAZED EDGES



- 805** 2.8"x5.8" SGE 5.8"
- 806** 2.8"x5.8" SGE 2.8"
- 807** 2.8"x5.8" DGE Right
- 808** 2.8"x5.8" DGE Left
- 803** 5.8"x5.8" SGE
- 804** 5.8"x5.8" DGE
- 810** 3.8"x7.8" SGE 3.8"
- 811** 3.8"x7.8" SGE 7.8"
- 812** 3.8"x7.8" DGE Left
- 813** 3.8"x7.8" DGE Right
- 814** 1.9"x7.8" SGE 7.8"
- 815** 1.9"x7.8" SGE 1.9"
- 816** 1.9"x7.8" DGE Right
- 817** 1.9"x7.8" DGE Left


FRAMED



933 2.8"x2.8"
(Only comes with Double Glazed Edge)

TRIMS

FRAMED GLAZED EDGES



- 907** 2.8"x5.8" Framed SGE 2.8"
- 908** 2.8"x5.8" Framed SGE 5.8"
- 933** 2.8"x2.8" Framed DGE

BEVELED



940 6" Arabesque Beveled

942 6" Half Arabesque
(Comes with a Glazed Edge)

943 6" Tear Drop Beveled


TRIMS

BEVELED GLAZED EDGES




- 942** Half Arabesque SGE


DECORATIVE ACCESSORIES




HAND PAINTED



504 5.8"x5.8" Universe Deco




505 5.8"x5.8" Planet Deco



301 5.8"x5.8" Vizcaya Deco



103 2.8"x7.8" Palm Beach Border



102 3.8"x7.8" Gables Border



104 1"x7.8" Ponciana Liner




203 1.2"x7.8" Round Bar Liner



205 1"x5.8" Quarter Round




206 Beak




207 0.7"x7.8" Stripe Liner

FINISHING TOUCHES




END CAPS



208 2"x7.8" Chair Molding




209



201 2.8"x7.8" Rail Molding



202



809 5.8"x5.8" Base Board
(Glazed Top Edge)



899

FRAME CORNERS



210



204

ADSTW



ADSTI



ADSTB



ADSTF



ADSTA



ADSTS



ADSTE



ADSTG





INSTALLATION & MAINTENANCE

PRIOR TO INSTALLATION

The surface where the product is going to be installed must be clean and level.

We strongly recommend dry laying prior to installation. Blending of the ceramic tile glaze is key to insuring a pleasing overall look to your room. This will resolve any color or size issues prior to installation and will serve as a review of tile placement.

We recommend all our tiles to be installed using the prevailing guidelines as set forth in the TCNA (Tile Council of North America) Handbook and the ANSI (American National Standards Institute) specifications.

Installation should be carried out by experienced personnel.

CERAMIC TILES

SETTING MATERIALS

For Porcelain Tiles, install with any high-quality adhesive recommended for porcelain tiles. This must also be suitable for the environment they will have to withstand.

Fitting with traditional mortars does not ensure good adhesion.

For Glass tiles, install with any high-quality adhesives recommended for glass floor tiles. This must also be suitable for the environment they will have to withstand. Fitting with traditional mortars does not ensure good adhesion.

For Mud Installations, all setting materials and installation methods should be performed using the prevailing guidelines set by the Tile Council of America and the ANSI Specifications.

GROUT

Unsanded grout is typically used for grout joints 1/8" or smaller.

Sanded grout is recommended for grout joints larger than 1/8", as long as the excess material is removed with a damp sponge. Using notched trowels or grout floats may scratch the tile. Special care should be exercised with high sheen surfaces.

We do not recommend contrasting color grouts on our crackled glazed tiles.

The color of the grout should be as close as possible to the color of your tile.

NOTE: *We use Sanded grout in most of our display boards to keep them intact during shipping.*

METHOD

Follow the appropriate standard ceramic procedures provided by the TCNA (Tile Council of North America) Handbook and the ANSI (American National Standards Institute) specifications.

The surfaces of raised/dimensional decorative accents, borders or liners can be taped off during grouting to facilitate cleanup.

To help keep border, liner and molding grout joints tight, offset the joints between field tile, trim and accent rows.

SEALING

Sealing is not required for Solid Glazes.

Sealing is mandatory for Crackle Glazes. We recommend sealing our crackled glaze tiles with a solvent based penetrating sealer before and after grouting.

1. The sealer penetrates the fine, hairline fissures in the glaze and prevents dirt and dusk darkening the crackle over a period of time.
2. Sealing the crackled glaze makes it easier to maintain and clean.
3. Proper application of the sealer (wipe off any excess from glazed surface) will not harm or change the appearance of the tile.
4. Reapply to grout joints and crackle glazes periodically as needed. When water no longer beads on the surface of the joints, resealing is required.

We recommend the following products and procedures:

Once the tile is mounted on the wall and before grouting, the tile surface must be clean and free of dirt and dust. Use the **FILA MP90 - Natural Look Penetrating Sealer** (Available in our Price List) which is a solvent based

sealer. Apply an even coat of FILAMP90 with a paintbrush or lambswool applicator pad. Wait 24 Hours to allow the product to cure. Apply grout with a sponge evenly distributing grout over joints. **Do not use a grout float.**

NOTE: *When using Contrasting Color Grouts, it is imperative that the tiles are thoroughly sealed to avoid the discoloration from the grout pigment. Please follow the mixing grouting instructions of the Grout Manufacturer.*

Once the grouting is completed and allowed to dry, the surface of the tiles must be cleaned using **FILA CLEANER - Neutral Cleaner** (Available in our Price List) observing the following guidelines: Dilute to 1:30. Clean the surface with a cloth and scrubbing brush. Remove any residue and rinse thoroughly.

After the thorough cleaning of the surface and grout residue, the tile will need to be resealed using the **FILA MP90 - Natural Look Penetrating Sealer** (Available in our Price List) observing the following guidelines: Apply an even coat of FILAMP90 with a paintbrush or lambswool applicator pad. Wipe off product excess after 15 minutes, making sure to rub the product and help its complete penetration into the material. Wait 24 Hours to allow the product to cure.

NOTE: *Future Sealing of the product should be done if you see any discoloration/darkening in the body of the tile. This will vary by end usage, care and maintenance products and tools used.*

If you use any other sealer, please check with the manufacturer for the proper instructions and products to use for sealing crackled glaze ceramic tile.

MAINTENANCE

For walls: clean tile regularly with a non-abrasive/non-acidic, mild and PH neutral cleaner.

We recommend **FILA CLEANER - Neutral Cleaner** (Available in our Price List) for all cleaning purposes of our tile.

Sealer: Reapply to grout joints and crackle glazes periodically as needed. When water no longer beads on the surface of the joints, resealing is required.

PORCELAIN TILES & GLASS MOSAICS

SETTING MATERIALS

For Porcelain tiles, install with any high-quality adhesive recommended for porcelain tiles. This must also be

suitable for the environment they will have to withstand. Fitting with traditional mortars does not ensure good adhesion.

For Glass tiles, install with any high-quality adhesives recommended for glass floor tiles. This must also be suitable

for the environment they will have to withstand. Fitting with traditional mortars does not ensure good adhesion.

For Mud Installations, all setting materials and installation methods should be performed using the prevailing guidelines set by the Tile Council of America and the ANSI Specifications.

GROUT

For Porcelain tiles, we recommend using a minimum of 5/64-inch (0.08" or 2 mm) spacers for a perfect alignment of the tiles. It will also be necessary to make small adjustments by hand to compensate for the natural dimensional variations of the tiles. The joints should be filled in with appropriate materials according to the specifications given by the joint filling material manufacturer. We do not recommend the installation of porcelain tiles without joints.

METHOD

Follow the appropriate standard ceramic, porcelain and glass tile installation procedures provided by the TCNA (Tile Council of North America) Handbook and

the ANSI (American National Standards Institute) specifications.

MAINTENANCE

Clean the tile regularly with a non-abrasive/non-acidic, mild and PH neutral cleaner.

We recommend **FILA CLEANER - Neutral Cleaner** (Available in our Price List) for all cleaning purposes of our tile.

Use products which are suitable to eliminate the remains of mortar, cement, etc. Never use an acidic cleaning agent on newly installed flooring because the acid reacts with the unset cement and can damage the seals, or insoluble compounds can be deposited on the surface of the paving.

Do not use metal scrapers or abrasive pads.

Daily cleaning, after use, will be made particularly easy as it only requires clean water and a very well-wrung cloth. In areas where the tile could be especially messy (kitchens), a detergent with bleach or ammonia can be added to water, although in this case we always recommend giving a final rinse with clear water. Do not use waxes, oils or similar products. In some cases, we can find ourselves in the situation of having to clean very dry and specific stains, which cannot be removed with a damp cloth, but that will disappear if we apply concentrated bleach (the one for floors, not the one used for clothes) and leave it to dry. For especially resistant stains it may be necessary to repeat the process.

PLEASE NOTE

Due to the nature of our tile, a certain amount of variation in color, shading, surface and texture are to be expected.

Use of the tile constitutes acceptance. We assume no responsibility for installation.

The installation information provided is to be used as a guideline only and should be discussed with a professional and accredited tile installer.

For floor surfaces, water, grease, oil, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection and maintenance.

CARE & MAINTENANCE	NERI	STUDIO	RIVIERA	EARTH	OCEAN	HAMPTON	DIAMONDS	PENNY ROUNDS	FLOOR	
									FIELD TILES	MOSAICS
Sealing recommended	Optional	Optional	Optional	Yes-Required*	Yes-Required*	Yes-Required*	Optional	Optional	Optional	Optional
Recommended cleaning	Routine with non-abrasive cleaners									

CHARACTERISTICS	NERI	STUDIO	RIVIERA	EARTH	OCEAN	HAMPTON	DIAMONDS	PENNY ROUNDS	FLOOR	
									FIELD TILES	MOSAICS
Glaze	Solid	Solid with subtle movement	Solid with high color variation	Crackle with subtle movement	Crackle with subtle movement	Crackle	Solid	Solid with subtle movement	Solid	Solid
Surface Sheen	Solid	Glossy	Solid	Semi-Matte	Glossy	Glossy	Glossy	Glossy	Semi-Matte	Semi-Matte
Texture	Smooth	Slightly Undulated	Smooth	Slightly Undulated	Slightly Undulated	Smooth	Smooth	Slightly Undulated	Smooth	Smooth
Color Variation	Slight	Medium	Slight	Medium	Medium	Medium	Slight	Medium	Slight	Slight

APPLICATION GUIDELINES		NERI	STUDIO	RIVIERA	EARTH	OCEAN	HAMPTON	DIAMONDS	PENNY ROUNDS	FLOOR	
										FIELD TILES	MOSAICS
Bathrooms											
Residential	Walls	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
	Floors									✓	✓
	Countertops	✓	✓	✓							✓
Commercial	Walls	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
	Floors										
	Countertops										
Showers / Steamrooms											
Residential	Walls	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
	Floors									✓	✓
Commercial	Walls	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
	Floors										
Kitchens											
Residential	Walls	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
	Floors									✓	✓
	Countertops	✓	✓	✓						✓	✓
Commercial	Walls	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
	Floors										
	Countertops										
Fireplace Surrounds											
Residential	Interior	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
	Exterior**	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
Commercial	Interior	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
	Exterior**	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
Outdoor Cooking / Bar Spaces											
Residential	Walls	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
	Countertops									✓	✓
Commercial	Walls	✓	✓	✓	✓*	✓*	✓*	✓	✓	✓	✓
	Countertops									✓	✓
Pool Waterlines / Water Fountains											
Residential	Exterior**								✓	✓	✓
Commercial	Exterior**								✓	✓	✓

* Crackle tiles must be properly sealed. (See SEALING instructions in INSTALLATION & MAINTENANCE guidelines)
 ** Non-freeze / thaw climates

