

T34712

# Product Information

## # D347

## Double-sided Tissue Tape

### Description

Double coated tissue, coated with a solvent, acrylic adhesion system. #D347 is great for general purpose bonding, fixing, mounting and splicing.

Comparable to Tesa #4959

### Features

- High tack and quick bond
- Good laminating adhesive
- Shears cleanly on plastic
- Hand-Tearable

Carrier	Tissue	
Adhesive	Acrylic	
Liner	60# PE Bleached Kraft	
Total Thickness	3.5 mils	.089 mm
Adhesion to Stainless Steel	49 oz/in	13N/25mm
Service Temperature Range	Short Term: -4F to 212F Long term: -4F to 176F	Short Term: -20°C to 100°C Long Term: -20°C to 80°C
Shear Strength PSTC-7	@77°F (25°C), over 24 hours with 2.3 lbs (1kg) Loading on Stainless Steel plates of 1" x 1" (25mm x 25mm)	

### Application

General purpose bonding and binding, mounting for nameplates, trophies and signs.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

800-545-8273 · 262-835-0748 · Fax: 262-835-0749 · [www.specialtytapes.net](http://www.specialtytapes.net)  
4221 Courtney Road · Franksville, WI 53126