

Cyclonic filtration system	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
Hose Length - ('/m)	2-10'/3.05	2-10'/3.05	2-10'/3.05	1-16'/4.88	2-10'/3.05	2-10'/3.05	2-10'/3.05	2-10'/3.05	2-10'/3.05	2-10'/3.05
Hose Width - ('/cm)	3/7.62	3/7.62	3/7.62	3/7.62	3/7.62	3/7.62	3/7.62	3/7.62	3/7.62	3/7.62
Vacuum Hg Mercury- (text)	15	15	15	10	15	15	15	15	15	15
Vacuum cfm - (text)	575	575	575	575	575	575	575	575	575	575
Suction Hose Storage - ('/m)	STANDARD	STANDARD	STANDARD	NA	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
Control Panel										
Gauges - (text)	VACUUM	VACUUM	VACUUM	VAC&WAT	VACUUM	VACUUM	VACUUM	VAC&WAT	VAC&WAT	VAC&WAT
Boom										
Reach - ('/m)	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Movement - (text)	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Remote Control (text)	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Available Options										
Pressure offloading (reverse flow)	YES	YES	YES	NA	YES	YES	YES	YES	YES	YES
Strong Arm (manual boom)	YES	YES	NA	NA	NA	NA	NA	YES	YES	NA
Hydraulic Boom	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Hot Box water heater	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Air Compressor	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Additional Fresh water options	NA	NA	NA	NA	NA	NA	NA	YES	YES	YES