

PROTECTS YOUR SURFACE • QUICK & EASY INSTALL AND DISMANTLE

Dimensions:	24" x 6" x 15/16" in. (61 cm x 15 cm x 2.4 cm)
Weight	1.35 lbs. (612 grams)/piece
Material	High Impact Grade Polypropylene Copolymer 100% Recyclable
Color:	Granite
UV Stability	1.0 UV Stabilized for Outdoor Use or Storage
Connection System	Built-in positive locking mechanism. Individual treads connect on every edge. Transition edges available.
Load Capacity	34,560 lbs/ft2 (240 psi) or 168,736 kgf/m2
Fire Rating	UL 94 HB
Chemical Resistance to	Acids, Solvents, Petroleum Products
Warranty	5 year limited
NSN Number	7220-01-598-5013



STRONG

Portafloor PRO™ PortaFloor PRO supports over 34,000 psf (240 psi) and is the best temporary flooring system in the world.

ROLLABLE @

Portafloor PRO™ is designed to roll in to place for quick installations and removals. PRO is engineered to be light and lean with large sections that provide additional support and stability.

EASY - 123

Portafloor PRO™ locks together for firm and stable support and is the perfect solution for tent and portable structure flooring.

GREEN 🗳

Portafloor PRO™ is 100% recyclable. PRO was designed to support today's zero footprint and green initiatives. All PortaFloor products have been submitted for Environmental Product Declarations (EPD), and Life Cycle Assessments (LCA) that provide benchmarks for continuous improvement, innovation and LEED credits.





