




SHUZ TUNG MACHINERY INDUSTRIAL CO., LTD.

NO.1325, CHUNG SHAN RD., SECTION 1, TACHIA TOWN, TAICHUNG HSIEN, TAIWAN, R.O.C.
FACTORY:NO, 17-1, HOU LIAO ROAD, TATUNG TSUN, WAIPU HSIANG, TAICHUNG HSIEN, TAIWAN,
TEL:886-4-26831886 FAX:886-4-26836158 E-MAIL: stmc@shuztung.com.tw

HT-90-206 HORIZONTAL TYPE TUBE NOTCHING M/C



SPECIFICATION:

- APPLY TO DIFFERENT MATERIAL SUCH AS STEEL, CRO-MOLY AND ALLOY
- AVAILABLE TO SQUARE TUBE, OVAL TUBE, DROP TUBE, S TYPE TUBE ALSO SMALL ANGLE PROCESS.
- MOVING OF PUNCHING TOOL AND MOULD CLAMPING CONTROLLED BY 7.5HP HYDRAULIC MOTOR
- DRY PROCESS, NO COOLANT REQUIRE
- MAX. THICKNESS OF TUBE: 1.6 - 2.5M/M
- DIAMETER OF TUBE: MAX. 50 M/M
- ANGLE ADJUSTABLE : 0° ~ 180°
- LENGTH OF TUBE:180 ~1,000 M/M
- M/C CYCLE TIME: 6 SEC/PC
- DIMENSION: 1550(L)x1320(W)x1700(H) M/M
- WEIGHT: 1200KGS
- CHANGE-OVER TIME: 5 MIN.