

高精密型/精密型双辊涂布机

GMQ/JMQ PRECISE TWO ROLLERS COATER > >>



精选配置

- ◆ 专为竹木地板、家具台面等平面型材表面涂漆设计
- ◆ 涂布面漆厚度薄，大大节省成本
- ◆ 采用进口电机、变频器，实现输送带、涂布辊的精确调速
- ◆ 两支涂布辊可独立进行调速且拆装便捷
- ◆ 涂布机构高度采用计数表读数，便于操作
- ◆ 设置厚度限位，防止超厚板材进入涂布机
- ◆ 遇到紧急情况，涂布辊可自动上升，保护辊子
- ◆ 挤压辊、刮刀依据不同要求选用不同的工作方法
- ◆ 设置回油槽，实现油漆循环利用

Best accessories

- ◆ Designed for coating surface of bamboo and wooden floor boards and furniture.
- ◆ Reducing thickness of surface coating and production costs.
- ◆ Imported motor and inverter for accurate speed control of conveyor and coating rollers.
- ◆ Separately adjustable speed of 2 coating rollers and easily dismantable.
- ◆ Coater height readable by the counter for operation convenience.
- ◆ The machine can prevent over thickness board into the machine.
- ◆ The coating rollers will rise automatically when meeting emergency.
- ◆ Optional working status of extrusion roller and squeegee.
- ◆ Counter-flow trough designed for excessive paint collected regularly for recycling use.

技术参数 Technical specification

参数	Specifications	GMQ1300A	JMQ1300A	GMQ600A	JMQ600A
涂布宽度	Coating width	1300mm	1300mm	600mm	600mm
涂布厚度	Coating thickness	3-100mm	3-100mm	3-100mm	3-100mm
涂层厚度	Coating layer thickness	10-30μm	10-30μm	10-30μm	10-30μm
送料速度	Feeding speed	MAX23m/min	MAX23m/min	MAX19m/min	MAX19m/min
工作高度	Working height	900±20mm	900±20mm	850±40mm	850±40mm
输送带长度	The length of conveyor belt	1320×3700-3mm	1320×3700-3mm	620×3280-2mm	620×3280-2mm
总功率	Total motor power	10.82KW	9.32KW	5.8KW	5.07KW
输送电机	Feeding motor	1.5kw	1.5KW	0.75kw	0.75kw
升降电机	Rise and decline motor	0.37kw(2只)	0.37kw(2只)	0.37kw(2只)	0.37kw(2只)
涂布辊功率	Coating roller Power	1.5kw(2只)	1.5kw(2只)	0.75kw(2只)	0.75kw(2只)
挤压辊功率	Squeeze	0.75kw(2只)		0.37kw(2只)	
加热箱功率	Heating power	4kw	4kw	2kw	2kw
风扇功率	Fan power	0.038kw(2只)	0.038kw(2只)	0.038kw(2只)	0.038kw(2只)
外形尺寸	Overall dimensions	1950×2600×1650mm	1950×2600×1650mm	1636×1550×1600mm	1636×1550×1600mm
净重	N.W.	1450kg	1400kg	900kg	900kg