

Chongqing Gold Mechanical & Electrical Equipment Co.,Ltd.

Add:9F/10,Jintai Building, Nanping, Nan'an District,Chongqing,400060,China

Phone:0086-23-62984892

Mobile:0086-139 83487420

Skype:berurenpan

Fax:0086-23-62940030

[Msn:beruren@live.cn](mailto:beruren@live.cn)

Web:www.hyoilpurifier.en.alibaba.com

JT Series Collecting-Dehydration Oil-Purifying Equipment



Series of JT automatic Collecting-Dehydration Oil-Purifying equipment is designed to dehydrate the oil by use of filter assemblies and dehydration-filtering elements, which are separately made of hydrophilic and hydrophobic synthetic material. The plant can collect the free and emulsification water to become large drips to subside and drain them expediently. The plant also can demulsify, dehydrate and filter exactly. So they could filter water and impurities in turbine oil or lubrication on-line, especially fit to deal with leaked equipment.

Features of Product

1. The whole equipment designed individually with nice appearance、 low power and low cost for operation.
2. The plant is all made of stainless steel without adding antirust so that working uninterruptedly.
3. The oil-water interfacial apparatus and automatic drained valve could offer exactly detached water level and drain water automatic when it accumulated condign capacity.
4. Electric system control with PLC (touch screen) which could show working condition and operation of all parts clearly. It also can monitor equipments、 automatic control and protect stopping machine. It could use of the equipment operation online without human.

Chongqing Gold Mechanical & Electrical Equipment Co.,Ltd.

Add:9F/10,Jintai Building, Nanping, Nan'an District,Chongqing,400060,China

Phone:0086-23-62984892

Fax:0086-23-62940030

Mobile:0086-139 83487420

[Msn:beruren@live.cn](mailto:Ms:beruren@live.cn)

Skype:berurenpan

Web:www.hyoilpurifier.en.alibaba.com

5. Adopting the special oil pump made in Germany that have good airproof、low noise and long life time.

6. Multilayer filtration including coarse filter、protecting filter、nice filter are all imported from Europe and U.S.A. The effect of control impurities is excellent.

Item	Name of Parameter	Type Unit	JT-50	JT-100	JT-150	JT-200
Technical parameter of the product	Nominal flow capacity	L/min	50	100	150	200
	Working pressure	Mpa	≤0.5			
	Working temperature of Oil	℃	45-65			
	Working power		50Hz 380V 3-Phase 4-Wire			
	Total electric power	KW	1.5	1.5	3	3
	Diameter of inlet outlet hose	mm	32	38	45	50
	Appearance dimension	cm	150x100x140	150x105x140	160x120x150	165x125x160
	Weight of product	Kg	450	500	600	700

Chongqing Gold Mechanical & Electrical Equipment Co.,Ltd.

Add:9F/10,Jintai Building, Nanping, Nan'an District,Chongqing,400060,China

Phone:0086-23-62984892

Fax:0086-23-62940030

Mobile:0086-139 83487420

[Msn:beruren@live.cn](mailto:beruren@live.cn)

Skype:berurenpan

Web:www.hyoilpurifier.en.alibaba.com

The oil index after treatment

Model	Flow (L/min)	Effect of oil purifying	
		cleanness	Water content
JT-50	50	Grade from 5 to 8 of NAS1638	≤100ppm
JT--100	100		
JT-150	150		
JT-200	200		