



RESEARCH PRODUCTS, INC.
OF ALABAMA

POST OFFICE BOX 705 THEODORE, ALABAMA 36590
(251) 653-0031

TECHNICAL DATA

MARSOL BC BILGE CLEANER

DIRECTIONS:

Two methods of cleaning are preferred; wet or dry. The dry method is more efficient but involves more effort. DRY METHOD AT SEA. Pump Bilge down as far as possible to reduce the diluting effect of water. Add one gallon marsol bc per 250-300 square feet of affected bilge hull area. Allow rolling action of vessel to disperse cleaner and dissolve residue. Final stage of cleaning requires sufficient water in bilge to emulsify dissolved grease, oil, and other petroleum residues. Discard liquid in approved manner and ventilate the bilge. DRY METHOD IN PORT. Pump bilge down to containers spray required amount of Marsol BC to all affected surfaces. Allow 30-40 minutes or longer for solvents to work before hosing down entire bilge area with maximum pressure available. Pump slops to container and ventilate bilge. WET METHOD. Used underway only. Add enough water to bilge if necessary to provide adequate working solution level. add two ounces marsol bc per gallon of slops in bilge. Allow rolling action of vessel underway to distribute cleaner and emulsify bilge residues. utilize maximum time available while underway to assure greatest benefit discard slops in approved manner.

TYPICAL PROPERTIES:

| | | |
|------------------|-------|------------------|
| SPECIFIC GRAVITY | | 0.88 |
| APPEARANCE | | COLORLESS LIQUID |
| BOILING POINT | | 350 DEGREES F. |
| FLASH POINT | | 142 DEGREES F. |
| WATER SOLUBILITY | | SLIGHTLY SOLUBLE |

SAFETY DATA:

DO NOT INDUCE VOMITING IF SWALLOWED. SEEK MEDICAL ATTENTION. IF EYE CONTACT OCCURS, FLUSH EYES WITH WATER FOR FIFTEEN (15) MINUTES AND SEEK MEDICAL ATTENTION IMMEDIATELY. IF SKIN CONTACT OCCURS WASH WITH SOAP AND WATER IF IRRITATION PERSIST SEEK MEDICAL ATTENTION. DO NOT BREATHE VAPORS.

TRANSPORTATION:

DOT SHIPPING NAME 1993, COMBUSTIBLE LIQUIDS NOS, (NAPHTHA, PETROLEUM), PGIII

DOT HAZARD CLASS: COMBUSTIBLE

CONSULT MATERIAL SAFETY DATA SHEET FOR FURTHER INFORMATION.