



RESEARCH PRODUCTS, INC.

OF ALABAMA

POST OFFICE BOX 705 • THEODORE, ALABAMA 36590

(251) 653-0031

SAFETY STRIP PAINT STRIPPER

DESCRIPTION: SAFETY STRIP IS A HEAVY DUTY, METHYLENE CHLORIDE BASED, PAINT STRIPPER. SAFETY STRIP WILL REMOVE MOST KINDS OF PAINT FROM METAL, WOOD, FIBERGLASS AND OTHER HARD SURFACES. SAFETY STRIP IS THICKENED TO CLING TO VERTICAL SURFACES.

SAFETY STRIP MAY BE USED BY APPLYING A THIN COAT TO THE PAINTED SURFACE THEN ALLOW 1 TO 2 MINUTES FOR PAINT TO LOOSEN. REMOVE USING A SCRAPER NOR HIGH PRESSURE WATER SPRAY.

** DO NOT ALLOW SAFETY STRIP TO DRY

TYPICAL PROPERTIES

SPECIFIC GRAVITY	1.32	
APPEARANCE	CLEAR THICK LIQUID	
BOILING POINT	90.5	DEGREES F.
FLASH POINT	NONE	DEGREES F.
WATER SOLUBILITY	<1%	

SAFETY DATA:

CONTAINS METHYLENE CHLORIDE. AVOID EYE AND SKIN CONTACT. HARMFUL IF SWALLOWED. RUBBER GLOVES AND EYE PROTECTION ARE REQUIRED WHEN USING THIS PRODUCT. VAPORS ARE HARMFUL. ADEQUATE VENTILATION IS REQUIRED WHEN USING THIS PRODUCT.

TRANSPORTATION:

DOT SHIPPING NAME: UN1593, DICHLOROMETHANE, 6.1, PGIII

DOT HAZARD CLASS: TOXIC

CONSULT MATERIAL SAFETY DATA SHEET FOR FURTHER INFORMATION.