

	MONOS					VICTORY MONO	SPECIAL BINOCULARS			
										
	MiniQuick® 5x10 T*	4x12 T*	6x18 T*	8x20 T*	10x25 T*	3x12	8x56 GA T* Dialyt	7x50 GA T* Marine	8x30 GA Dialyt	20x60 S Classic Image Stabilization
Magnification	5x	4x	6x	8x	10x	3X	8x	7x	8x	20 x
Objective Diameter	10 mm	12 mm	18 mm	20 mm	25 mm	12 mm	56 mm	50 mm	30 mm	60 mm
Exit Pupil	2.0 mm	3.0 mm	3.0 mm	2.5 mm	2.5 mm	4.0 mm	7.0 mm	7.1 mm	7.8 mm	3 mm
Twilight Factor	7.0	6.9	10.4	12.6	15.8	6.0	21.2	18.7	15.5	34.6
Field of View (ft/1000 yds)	300	540	360	330	264	660	330	390	360	156
Close Focus	13.12 ft	1.48 ft	0.98 ft	9.84 ft	14.78 ft	0.66 ft	13.12 ft	13.12 ft	22.96 ft	45.93 ft
Diopter Range	>+/-4 dpt	>+/-4 dpt	>+/-4 dpt	>+/-4 dpt	>+/-4 dpt	>+/-4 dpt	+/-3.5 dpt	+9/-6 dpt	+/-6 dpt	+/-4 dpt
Eye Relief	16.5 mm	15.0 mm	15.0 mm	15.0 mm	15.0 mm	12.0 mm	19.0 mm	18.0 mm	15.0 mm	13.0 mm
Water Resistant	sealed against spray water									
Functional Temperature Range	-4/+104°F									
Height	4.45 in	2.40 in	3.35 in	3.66 in	4.29 in	1.89 in	9.37 in	5.67 in	5.55 in	10.5 - 10.8 in
Width	-	-	-	-	-	-	5.63 in	8.47 in	4.49 in	6.33 in
Weight	0.81 oz.	1.59 oz.	2.05 oz.	2.72 oz.	3.10 oz.	1.90 oz.	35.65 oz.	42.34 oz.	21.16 oz.	58.55 oz.
Order Numbers	52 20 10	52 20 50	52 20 51	52 20 52	52 20 53	52 20 12	52 56 58	52 55 05	52 35 14	52 60 00

		VICTORY RF				VICTORY PRF
						
		8x45 T* RF	10x45 T* RF	8x56 T* RF	10x56 T* RF	8x26 T* PRF
Magnification		8x	10x	8x	10x	8x
Objective Diameter		45 mm		56 mm		26 mm
Exit Pupil		5.6 mm	4.5 mm	7 mm	5.6 mm	3.25 mm
Twilight Factor		19.0	21.2	21.2	23.7	14.4
Field of View (ft/1000 yds)		375	330	345	330	330
Close Focus		approx. 18 ft		approx. 16 ft		—
Diopter Range		+/- 3.5 dpt				+/- 3.5 dpt
Eye Relief		16 mm	15.5 mm	17 mm	16 mm	17.5 mm
LotuTec®		yes		yes		yes
Nitrogen Filling		yes		yes		—
Waterproof		yes		yes		yes
Height		6.6 in		7.64 in	7.5 in	1.88 in
Width		5.3 in		5.47 in		3.85 in
Weight (with battery)		35 oz.		40.59 oz		10.93 oz.
Specifications – Laser Rangefinder						
Laser Class		1		1		1 M
Measuring Range¹		10 yds to 1300 yds		10 yds to 1300 yds		10 yds to 1300 yds
Accuracy		10 – 600 yds +/- 1 yds Over 600 yds +/- .5 %		10 – 600 yds +/- 1 yds Over 600 yds +/- .5 %		10 – 600 yds +/- 1 yds Over 600 yds +/- .5 %
Measurement time		Approx. 0.5 sec., max (Average)		Approx. 0.5 sec., max (Average)		Approx. 1.5 sec., max (Average)
Battery		CR 2 (Lithium 3V)		CR 2 (Lithium 3V)		CR 2 (Lithium 3V)
Battery Life (68°F)		>10,000		>10,000		>2,000
Order Numbers	Black	52 45 16	52 45 18	52 56 20	52 56 22	52 45 61

		VICTORY FL							VICTORY COMPACT	
										
		8x32 T* FL	10x32 T* FL	7x42 T* FL	8x42 T* FL	10x42 T* FL	8x56 T* FL	10x56 T* FL	8x20 T*	10x25 T*
Magnification		8x	10x	7x	8x	10x	8x	10x	8x	10x
Objective Diameter		32 mm	32 mm	42 mm	42 mm	42 mm	56 mm	56 mm	20 mm	25 mm
Exit Pupil		4.0 mm	3.2 mm	6.0 mm	5.25 mm	4.2 mm	7.0 mm	5.6 mm	2.5 mm	2.5 mm
Twilight Factor		16.0	17.9	17.1	18.3	20.5	21.2	23.7	12.6	15.8
Field of View (ft/1000 yds)		WA 420	WA 360	WA 450	WA 405	WA 330	WA 390	WA 330	354	285
Close Focus		6.56 ft	6.56 ft	6.56 ft	6.56 ft	6.56 ft	9.84 ft	9.84 ft	8.53 ft	13.12 ft
Diopter Range		+/-4.0 dpt	+/-4.0 dpt	+/-4.0 dpt	+/-4.0 dpt	+/-4.0 dpt	+/-4.0 dpt	+/-4.0 dpt	+/-3.0 dpt	+/-3.0 dpt
Eye Relief		15.5 mm	15.2 mm	16.0 mm	16.0 mm	16.0 mm	16.0 mm	16.0 mm	13.5 mm	13.5 mm
Interpupillary Distance		52–74 mm	52–74 mm	54–76 mm	54–76 mm	54–76 mm	55–76 mm	55–76 mm	32–74 mm	32–74 mm
LotuTec®		yes	yes	yes	yes	yes	yes	yes	yes	yes
Nitrogen Filling		yes	yes	yes	yes	yes	yes	yes	yes	yes
Waterproof		400 mbar							400 mbar	
Functional Temperature Range		-22/+145°F							-4/+104°F	
Height		4.61 in	4.61 in	5.98 in	6.34 in	6.34 in	7.40 in	7.40 in	3.62 in	4.33 in
Width		4.57 in	4.57 in	5.04 in	5.04 in	5.04 in	5.71 in	5.71 in	3.82 in	3.82 in
Weight		19.75 oz.	19.75 oz.	26.10 oz.	26.63 oz.	26.98 oz.	48.08 oz.	44.09 oz.	7.94 oz.	8.82 oz.
Accessories										
	3x12 Tripler with Adapter	49 01 24								
	Binofix	52 83 87								
	Air Cell Comfort Strap	52 91 13								
Order Numbers	Black	52 32 30	52 32 31	52 45 40	52 45 41	52 45 42	52 56 08	52 56 10	52 20 78	52 20 79
	Green	52 32 32	52 32 33	52 45 50	52 45 51	52 45 52	52 56 11	52 56 12		

VICTORY RF, PRF, FL & COMPACT

T* = Carl Zeiss T* multi-coating. FL = Fluoride Glass. WA = Binoculars with Wide Angle Eye Pieces. ¹ = Measuring range depends on weather, reflectivity and size of object.

	CONQUEST										CONQUEST COMPACT	
												
	8x30 T*	10x30 T*	8x40 T*	10x40 T*	12x45 T*	15x45 T*	8x50 T*	10x50 T*	8x56 T*	10x56 T*	8x20 T*	10x25 T*
Magnification	8x	10x	8x	10x	12x	15x	8x	10x	8x	10x	8x	10x
Objective Diameter	30 mm	30 mm	40 mm	40 mm	45 mm	45 mm	50 mm	50 mm	56	56	20 mm	25 mm
Exit Pupil	3.75 mm	3.0 mm	5.0 mm	4.0 mm	3.75 mm	3.0 mm	6.25 mm	5.0 mm	7	5.6	2.5 mm	2.5 mm
Twilight Factor	15.5	17.3	17.9	20.0	23.2	26.0	20.0	22.4	21.2	23.7	12.6	15.8
Field of View (ft/1000 yds)	360	288	360	315	240	192	330	300	330	315	330	264
Close Focus	9.84 ft	9.84 ft	9.84 ft	9.84 ft	16.40 ft	16.40 ft	10.50 ft	10.50 ft	13.1	13.1	10.83 ft	18.05 ft
Diopter Range	+/-4 dpt	+/-7 dpt	+/-4 dpt	+/-5 dpt	+/-3 dpt	+/-5 dpt	+/-4 dpt	+/-5 dpt	+/-4 dpt	+/-5 dpt	+/-2 dpt	+/-2 dpt
Eye Relief	14.6 mm	14.6 mm	16.0 mm	16.0 mm	14.6 mm	14.6 mm	16.0 mm	16.0 mm	16.0 mm	16.0 mm	15.0 mm	15.0 mm
Interpupillary Distance	54-74 mm	54-74 mm	54-74 mm	54-74 mm	54-76 mm	54-76 mm	54-74 mm	54-74 mm	54-74 mm	54-74 mm	27-73 mm	27-73 mm
LotuTec®	-	-	-	-	-	-	-	-	-	-	-	-
Nitrogen Filling	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	-	-
Waterproof	400 mbar		400 mbar		400 mbar		400 mbar		400 mbar		sealed against spray water	
Functional Temperature Range	-4/+131°F		-4/+131°F		-4/+131°F		-4/+131°F		-4/+131°F		-4/+104°F	
Height	5.20 in	5.20 in	6.02 in	6.02 in	6.42 in	6.42 in	7.36 in	7.36 in	7.28 in	7.28 in	3.66 in	4.33 in
Width	4.53 in	4.53 in	5.04 in	5.04 in	4.69 in	4.69 in	5.24 in	5.24 in	5.47 in	5.47 in	3.66 in	3.82 in
Weight	17.46 oz.	17.99 oz.	28.92 oz.	28.92 oz.	21.34 oz.	21.87 oz.	31.92 oz.	31.92 oz.	33.5 oz.	33.5 oz.	6.53 oz.	7.05 oz.
Accessories												
3x12 Tripler with Adapter	49 00 54	49 00 54	49 00 53	49 00 53	49 00 54	49 00 54	49 00 53	49 00 53	49 00 53	49 00 53		
Binofix	52 83 87											
Air Cell Comfort Carrying Strap	52 91 13											
Order Numbers	52 32 08	52 32 10	52 45 08	52 45 10	52 45 12	52 45 15	52 50 08	52 50 10	52 50 12	52 50 14	52 20 73	52 20 74

T* = Carl Zeiss T* multi-coating.