

	VICTORY DIARANGE				VICTORY VARIPPOINT									
	M 2.5-10x50 T*	M 3-12x56 T*	11-4x24 T*	1.5-6x42 T*	2.5-10x42 T*	2.5-10x50 T*	3-12x56							
Magnification	2.5-10x	3.0-12x	1.1x	4x	1.5x	6x	2.5x	10x	2.5x	10x	3.0x	12x		
Effective Lens Diameter	37.7-50.0 mm	44.0-56.0 mm	16.3 mm	24.0 mm	22.6 mm	42.0 mm	37.3 mm	42.0 mm	37.7 mm	50.0 mm	44.0 mm	56.0 mm		
Exit Pupil Diameter	5.0-5.0 mm	14.7-4.7 mm	14.8 mm	6.0 mm	15.0 mm	7.0 mm	15.0 mm	4.2 mm	15.0 mm	5.0 mm	14.7 mm	4.7 mm		
Twilight Factor	7.1-22.4	8.5-25.9	3.1	9.8	4.2	15.9	7.1	20.5	7.1	22.4	8.5	25.9		
Field of View (ft/100 yds)	43.5 - 12.0	37.5 - 10.5	108.0	30.9	72.0	20.7	43.5	12.0	43.5	12.0	37.5	10.5		
Diopter Range	+2/-4 dpt	+2/-4dpt	+2/-4dpt		+2/-4dpt		+2/-4dpt		+2/-4dpt		+2/-4dpt			
Eye Relief (inches)	3.54	3.54	3.54		3.54		3.54		3.54		3.54			
Parallax-Free (yards)	300.0	300.0	109.4		109.4		109.4		109.4		109.4			
Square Adjustment Range (in/100 yds)	64.8/50.4	50.4/36.0	117.4		73.4		43.9		43.9		36.7			
Adjustment per Click (in/100 yds)	1/4	1/4	1/3		1/3		1/3		1/3		1/3			
Center Tube Diameter	56.5 mm	62.5 mm	30.0 mm		30.0 mm		30.0 mm		30.0 mm		30.0 mm			
Eye Piece Tube Diameter	45 mm	45 mm	40 mm		40 mm		40 mm		40 mm		40 mm			
Objective Tube Diameter	56.5 mm	62.5 mm	30.0 mm		48.0 mm		48.0 mm		56.0 mm		62.0 mm			
LotuTec®	yes	yes	yes		yes		yes		yes		yes			
Nitrogen Filled	yes	yes	yes		yes		yes		yes		yes			
Waterproof	400 mbar	400 mbar	400 mbar		400 mbar		400 mbar		400 mbar		400 mbar			
Functional Temperature Range	-13/+122°F	-13/+122°F	-13/+122°F		-13/+122°F		-13/+122°F		-13/+122°F		-13/+122°F			
Length	13.19 in	14.17 in	11.81 in		12.99 in		12.99 in		13.11 in		14.06 in			
Weight with Rail	Non-Illuminated	-	-		-		-		-		-			
	Illuminated	31.75 oz.	34.39 oz.	16.83 oz.		19.40 oz.		19.40 oz.	20.46 oz.		22.57 oz.			
Weight without Rail	Non-Illuminated	-	-		-		-		-		-			
	Illuminated	-	-	15.87 oz.		18.52 oz.		18.52 oz.	19.22 oz.		21.34 oz.			
Measuring Range (yards)	10 - max. 999	10 - max. 999												
Measuring Accuracy	± 650 yds +/- 1 yds // >650 yds +/- 0.5%													
Measuring Duration	max. 0.5 sec													
Order Numbers	With Inner Rail	52 17 87	52 17 97	52 17 06		52 17 16		52 17 26	52 17 36		52 17 46			
	Without Inner Rail	-	-	52 17 07		52 17 17		52 17 27	52 17 37		52 17 47			

T\* = Carl Zeiss T\* multi-coating.

	VICTORY DIAVARI														Z-POINT		COMPACT POINT	
	1.5-6x42 T*	2.5-10x42 T*	2.5-10x50 T*	3-12x56 T*	4-16x50 T* FL	6-24x56 T* FL	6-24x72 T* FL											
Magnification	1.5x	6.0x	2.5x	10.0x	2.5x	10.0x	3.0x	12.0x	4.0x	16.0x	6.0x	24.0x	6.0x	24.0x	1x	1.05x		
Effective Lens Diameter	22.6 mm	42.0 mm	37.3 mm	42.0 mm	37.7 mm	50.0 mm	44.0 mm	56.0 mm	50.0 mm	50.0 mm	56.0 mm	56.0 mm	72.0 mm	72.0 mm	ø 0.82 in	0.90 x 0.63 in		
Exit Pupil Diameter	5.0 mm	7.0 mm	5.0 mm	4.2 mm	15.0 mm	5.0 mm	14.7 mm	4.7 mm	12.5 mm	3.1 mm	9.3 mm	2.3 mm	12.0 mm	3.0 mm				
Twilight Factor	4.2	15.9	7.1	20.5	7.1	22.4	8.5	25.9	11.3	28.3	16.9	36.7	16.9	41.6				
Field of View (ft/100 yds)	72.0	22.7	43.5	12.0	43.5	12.0	37.5	10.5	26.7	7.5	18.3	5.1	18.3	5.1				
Diopter Range	+2/-3 dpt	+2/-3dpt	+2/-3dpt		+2/-3dpt		+2/-3dpt		+2/-3dpt		+2/-3dpt		+2/-3dpt					
Eye Relief (inches)	3.54	3.54	3.54		3.54		3.54		3.54		3.54		3.54					
Parallax-Free (yards)	109.4	109.4	109.4		109.4		55-∞		55-∞		55-∞		55-∞					
Square Adjustment Range (in/100 yds)	73.4	43.9	43.9		36.7		W: 43.2 / E: 59.4		W: 25.2 / E: 57.6		W: 25.2 / E: 57.6							
Adjustment per Click (in/100 yds)	1/3	1/3	1/3		1/3		1/3		1/4		1/4							
Center Tube Diameter	30 mm	30 mm	30 mm		30 mm		30 mm		30 mm		30 mm		34 mm					
Eye Piece Tube Diameter	40 mm	40 mm	40 mm		40 mm		45 mm		45 mm		45 mm		45 mm					
Objective Tube Diameter	48 mm	48 mm	56 mm		62 mm		56 mm		62 mm		80 mm							
LotuTec®	yes	yes	yes		yes		yes		yes		yes		yes					
Nitrogen Filled	yes	yes	yes		yes		yes		yes		yes		yes					
Waterproof	400 mbar	400 mbar	400 mbar		400 mbar		400 mbar		400 mbar		400 mbar		400 mbar					
Functional Temperature Range	-13/+122°F	-13/+122°F	-13/+122°F		-13/+122°F		13/+122°F		-13/+122°F		-13/+122°F		-13/+122°F					
Length	12.28 in	12.28 in	12.52 in		13.54 in		13.24 in		15.24 in		14.89 in							
Weight with Rail	Non-Illuminated	16.47 oz.	16.47 oz.		17.43 oz.		19.58 oz.		-		-		-					
	Illuminated	-	-	18.41 oz.		20.56 oz.		-		-		-						
Weight without Rail	Non-Illuminated	5.52 oz.	15.52 oz.		16.23 oz.		18.38 oz.		25.06 oz.		29.30 oz.		37.42 oz.					
	Illuminated	-	-	17.21 oz.		19.37 oz.		26.12 oz.		30.36 oz.		37.42 oz.						
Order Numbers	Non-Illuminated	52 17 10	52 17 20	52 17 30	52 17 40	-	-	-	-	-	-	-	-	-	52 17 60 (Picatinny)	52 17 60 (Picatinny / Weaver)		
	Illuminated	-	-	52 17 34	52 17 44	-	-	-	-	-	-	-	-	-	52 17 67 (Weaver)	52 17 62 (Blaser)		
Order Numbers	Non-Illuminated	52 17 11	52 17 21	52 17 31	52 17 41	52 17 77	52 17 74	-	-	-	-	-	-	-	-	-		
	Illuminated	-	-	52 17 35	52 17 45	52 17 79	52 17 73	52 17 95	-	-	-	-	-	-	-	-		

T\* = Carl Zeiss T\* multi-coating, FL = Fluoride Glass.

**new** **new** **new**

**new**

	CONQUEST								
	3-9x40 MC	3.5-10x44 MC	4.5-14x44 AO MC	3-9x50 MC	3.5-10x50 MC	4.5-14x50 AO MC	6.5-20x50 AO MC	3-12x56 MC	
Magnification	3-9x	3.5-10x	4.5-14x	3-9x	3.5-10x	4.5-14x	6.5-20x	3-12x	
Effective Lens Diameter	40 mm	44 mm	44 mm	50 mm	50 mm	50 mm	50 mm	56 mm	
Exit Pupil Diameter	13.3-4.4 mm	12.6-4.4 mm	9.7-3.1 mm	11.4-5.6 mm	11.4-4.8 mm	10.8-3.6 mm	7.7-2.5 mm	18.7-4.7 mm	
Twilight Factor	8.5/19.0	9.9/20.9	12.7/24.8	8.5/21.2	9.9/22.9	12.7/26.5	18.0/31.6	13.0/25.9	
Field of View (ft/100 yds)	33.9 - 11.01 ft	35.1 - 11.7 ft	24.9 - 8.4 ft	37.5 - 12.9 ft	35.1 - 11.7 ft	25.5 - 8.8 ft	17.7 - 5.7 ft	27.6 - 9.9 ft	
Diopter Range	+2/-3dpt	+2/-3dpt	+2/-3dpt	+2/-3dpt	+2/-3dpt	+2/-3dpt	+2/-3dpt	+2/-3dpt	
Eye Relief	4.0 in	3.5 in	3.5 in	3.5 in	3.5 in	3.5 in	3.5 in	3.2 in	
Parallax Free (yds)*	100*	100*	30 - ∞	100*	100*	30 - ∞	50 - ∞	100	
Square Adjustment Range (in/100 yds)	64.1	64.9	42.8	74.9	65.9	E68.0 W45.0	E45.4 W28.8	34.2	
Adjustment Per Click (in/100 yds)	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	
Center Tube Diameter	1 in	1 in	1 in	1 in	1 in	1 in	1 in	30 mm	
Eye Piece Tube Diameter	41 mm	41 mm	41 mm	41 mm	41 mm	41 mm	41 mm	38 mm	
Objective Tube Diameter	46 mm	50 mm	50 mm	56 mm	56 mm	56 mm	56 mm	62 mm	
LotuTec®	-	-	-	-	-	-	-	-	
Nitrogen Filled	yes	yes	yes	yes	yes	yes	yes	yes	
Reticle in Image Plane	2	2	2	2	2	2	2	1	
Length	12.9 in	12.7 in	13.9 in	12.4 in	13.2 in	14.0 in	15.6 in	15.3 in	
Weight	15.17 oz.	15.87 oz.	17.11 oz.	16.58 oz.	17.11 oz.	19.75 oz.	21.83 oz.	25.78 oz.	
Order Numbers	Black	52 14 60	52 14 20	52 14 30	52 14 80	52 14 85	52 14 90	52 14 50	52 14 70
	Silver	52 14 64	52 14 24	52 14 34	52 14 84	52 14 89	52 14 94	52 14 54	-