CGP350SET GE Café™ 30" Built-In Gas Cooktop

Dimensions and Installation Information

AGA Requirement: All gas cooktop models require 7/16" free area below cooktop height to combustible material. Requires 18" minimum from countertop to adjacent overhead cabinets.

Note: If installing with a GE Profile[™] Telescopic Downdraft System, consult both cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft.

Electrical Rating: 120V, 60Hz, 5A


Installation With Single Wall Oven Information:

30" Gas Cooktops are approved for use over select GE 27" and 30" Wall Ovens and Warming Drawers. 30" and 36" Gas cooktops are approved for use over select 30" Wall Ovens and Warming Drawers. Refer to cooktop and wall oven/warming drawer installation instructions packed with product for current dimensional data.

Installation Information: Before installing, consult installation instructions, packed with product, for current dimensional data.

For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at geappliances.com or call GE Answer Center® service, 800.626.2000.





CGP350SET GE Café™ 30" Built-In Gas Cooktop

Features and Benefits

- Deep-recessed cooktop Deep-recessed cooktop contains spills in one area that's easy to wipe clean
- Sealed cooktop burners Burner elements are sealed to the cooktop to keep foods and liquid contained on the cooktop, making cleaning painless
- 20,000 BTU tri-ring burner Three-in-one burner is designed for accelerated boiling and gentle simmering
- Non-stick griddle Prepare pancakes, eggs, bacon and more on the large, non-stick surface
- Precise Simmer burner Allows for low, even heat distribution that is ideal delicate foods and sauces
- Deluxe cast grates Premium cast iron grates deliver the highest level of cooktop performance
- Model CGP350SETSS Stainless Steel

