



Quality Appliances Since 1969

SUMMIT APPLIANCE DIVISION

SPECIALTY APPLIANCE CATALOG

FEATURING REFRIGERATORS AND FREEZERS FOR THE MEDICAL, INSTITUTIONAL AND SCIENTIFIC MARKETS



MODEL NUMBERS IN BLUE TYPE IN THIS CATALOG ARE ETL-S or UL-S LISTED, (MEET NSF-7 STANDARDS FOR FOODSERVICE USE) AND MEET CALCODE STANDARDS FOR USE IN CALIFORNIA.



- REFRIGERATORS
- FREEZERS
- MICROWAVE OVENS
- ADA COMPLIANT MODELS
- LOW TEMPERATURE FREEZERS
- COMMERCIAL REFRIGERATORS
- COMMERCIAL FREEZERS
- DRAWER REFRIGERATORS
- DRAWER FREEZERS
- ALL-IN -ONE KITCHENS
- ICE-MAKERS
- FROST-FREE FREEZERS
- WASHERS AND DRYERS



ALL PRODUCTS IN THIS CATALOG ARE U.L. APPROVED AND 100% CFC-FREE

SUMMIT Appliance Division
Phone: 718-893-3900

Felix Storch, Inc.
Fax 718-842-3093

770 Garrison Avenue, Bronx, NY 10474 USA
Email: sales@summitmedicalrefrigerators.com

Visit our website at: www.summitmedicalrefrigerators.com

24" WIDE ALL-REFRIGERATORS

FF7 All-Refrigerator with Automatic Defrost

FF7 models are approved for commercial use, and carry ETL Sanitation approval (complies with ANSI-NSF Standard 7). Available in white, black or stainless steel. The interior light on these models is controlled with a on/off rocker switch. FF7 models have one of the widest and deepest shelves in the industry, and can accommodate trays up to 19 1/2 inches by 16 inches. FF7 models are all automatic defrost, and feature adjustable shelves and oversized commercial compressors. Capable of 34-46 degree F operation (1-8 °C).

FF7LBIMED	Special FF7 for medical storage. Built-in capable with internal air circulation fan, hospital grade plug, NIST traceable thermometer and front mounted lock. Temp range: 1-8° C
FF7LBIMEDADA	Same as above for ADA counters (32" high)
FF7LBLBIMED	Same as FF7LBIMED in black with lock and glass shelves. Optional stainless steel shelves.
FF7LBLBIMEDADA	Same as FF7LBIMEDADA in black for ADA counters.
FF7L	Commercial all-refrigerator with lock. No fans
FF7LBL	Same as above in black with glass shelves.
FF7	Commercial all-refrigerator without lock
FF7LAB	FF7 with keypad lock, internal air circulation fan, hospital grade plug, alarm and NIST thermometer with min-max readings.

FF6 All-Refrigerator with Automatic Defrost

FF6 is one of SUMMIT's most popular refrigerators for medical offices, pharmacies, and hospitals. FF6 models are all automatic defrost; feature adjustable shelves and are capable of 36-46 degree F operation (2-8 °C). They all utilize our unique hidden evaporator (behind the rear wall) for a clean, seamless interior liner. FF6 models all have door shelves, for even more convenience. Available in white or stainless steel. FF6 models with the '-7' option are approved for foodservice use.

FF6LBIMED-7	Special FF6 for medical storage. Built-in capable with internal air circulation fan, hospital grade plug, NIST traceable thermometer with alarm and front-mounted lock. Temperature range 2 to 8 degrees C (36 to 46 degrees F).
FF6LBIMEDADA-7	Same as above for ADA counters (32" high)
FF6-7LAB	FF6 with keypad lock, internal air circulation fan, hospital grade plug, alarm and NIST thermometer with min-max readings. Temperature range 2 to 8 ° C (36 to 46° F)
FF6L	All-refrigerator with door storage, front lock
FF6	Same as above without lock
FF6L-7	FF6L approved for foodservice use (ETL-S)
FF6-7	FF6 approved for foodservice use (ETL-S)

OPTIONS FOR ANY FF6, FF7, FS62 or SCFF55 MODEL

Keypad Lock	Add a front mounted keyless (keypad) lock to any SUMMIT model (standard on lab series) Battery operated. Accepts 10 user codes.
AC Keypad	Add a front mounted keyless (keypad) lock to any SUMMIT model, powered by the refrigerator's line cord. No batteries are needed.
SSTB	Add a wrapped stainless steel door and pro stainless steel handle to any FF6, FF7, FS62 or SCFF55 model.
CSS	Add a full stainless steel cabinet and fully wrapped stainless steel door with a pro handle to any FF6, FF7, FS62 or SCFF55 model.
"AM" Suffix AGION™	Apply AGION™ anti-microbial stainless steel finish to any model above with "CSS" or "SSTB" finish. Included stainless steel handles are also anti-microbial.
DT	Add a precision digital temperature control to any FF6, FF7, FS62 or SCFF55 model (front mounted in the kick plate).
SS Shelves	Replace standard wire or glass shelves with a set of stainless steel shelves. Heavy gauge with folded edges for safety.
CASTERS	Heavy duty 6 inch NSF approved casters mounted to the bottom frame of the units. Seismic or flanged 6" legs are also optional.



FF6 / FF6L / FF6L-7 / FF6-7 interior. FF6LBIMED is similar with air circulation fan. All-refrigerator with automatic defrost.

All FF6 / FF7 Models

- All-Refrigerator
- Automatic defrost (static)
- 24 inches wide
- 24 inches deep
- 33.5 or 32" high versions for ADA
- Large shelves
- Interior light



Exterior of all FF6L models and FF7L models in white. Door is reversible with center lock.



FF7 interior. (shown with CSS cabinet finish). Approved for commercial use with large adjustable shelves (wire shelves on white cabinets, glass shelves are standard on black or St. Steel cabinets).



FF7CSS interior. Commercial refrigerator shown with CSS (full stainless steel cabinet and wrapped door).



Two under-counter models shown side by side with wrapped stainless steel doors (SSTB). Order one unit with RHD and one unit with LHD.



FF7 / FF6 models shown with a programmable keypad lock. Standard on Lab models.

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
FF7LBIMED	33.25	23.625	23.5	5.5	White	White	Reversible	Front
FF7LBIMEDADA	32	23.625	23.5	5.5	White	White	Reversible	Front
FF7LBLBIMED	33.25	23.625	23.5	5.5	Black	Black	Reversible	Front
FF7LBLBIMEDADA	32	23.625	23.5	5.5	Black	Black	Reversible	Front
FF7L	33.25	23.625	23.5	5.5	White	White	Reversible	Front
FF7LBL	33.25	23.625	23.5	5.5	Black	Black	Reversible	Front
FF7	33.25	23.625	23.5	5.5	White	White	Reversible	None
FF7LAB	33.25	23.625	23.5	5.5	White	White	Reversible	Keypad
FF6LBIMED-7	33.5	23.625	23.5	5.3	White	White	Reversible	Front
FF6LBIMEDADA-7	32	23.625	23.5	5.3	White	White	Reversible	Front
FF6-7LAB	33.5	23.625	23.5	5.3	White	White	Reversible	Keypad
FF6L	33.5	23.625	23.5	5.3	White	White	Reversible	Front
FF6	33.5	23.625	23.5	5.3	White	White	Reversible	None
FF6L-7	33.5	23.625	23.5	5.3	White	White	Reversible	Front
FF6-7	33.5	23.625	23.5	5.3	White	White	Reversible	None

Models in Blue are approved for foodservice and CALCODE use (meet NSF-7)

SUMMIT Appliance Division
Phone: 718-893-3900

Felix Storch, Inc. 770 Garrison Avenue,
Fax 718-842-3093

Bronx, NY 10474 USA
Email: sales@summitmedicalrefrigerators.com

Visit our website at: www.summitmedicalrefrigerators.com

24" WIDE ALL-FREEZERS

CHOOSE FROST-FREE OR MANUAL DEFROST

FS62 Low Temperature (-25°C) Front Opening Freezer

Model FS62 is our workhorse front-opening manual defrost freezer. Fully finished for under-counter or freestanding use, this freezer includes extra-thick 100 mm wall insulation, a commercial grade cooling system, three interior drawers for convenience and temperature retention when opened, and a reversible door. Available with or without a front lock, and in versions that meet foodservice standards (ETL-S meets NSF-7). Features include a power indicator light, an adjustable thermostat and an ideal 24 inch width. Optional finishes include a frame for custom panels or a wrapped stainless steel door with pro handle.

FS62LBIMED-7	Special FS62 for medical storage. Built-in capable with hospital grade plug and NIST traceable external temperature display. Manual defrost freezer with lock.
FS62LBIMEDADA-7	Same as above for ADA counters (32" high).
FS62L	Commercial grade freezer designed to operate at -25 degrees C. Manual defrost with lock.
FS62	Same as above without lock.
FS62L-7	Same as FS62L, approved for foodservice use
FS62-7	Same as FS62, approved for foodservice use.



FS62 / FS62L interior. All-freezer, commercial grade, operates at -25°C, Three removable baskets on fixed shelves. Reversible door.



SCFF55LBL-IM / SCFF55LBLMED-IM FROST-FREE all-freezer with forced air cooling and installed ice-maker. Shown in black (above)—also available in white.



SCFF55 (at left) SCFF55L SCFF55LMED (interior) FROST-FREE all-freezer for freestanding or built-in use. Shown in white—also available in black (above) or with a complete stainless steel cabinet. Full 5 c.f. of capacity with adjustable shelves and reversible door on base models.



FS62LBIMED / FS62LBIMEDADA Freezer with commercial construction. Standard lock, hospital grade cord and external alarm / thermometer installed. -25°C operation capable.

Only SUMMIT offers the option of under-counter freezers with manual defrost or frost-free, including CALCODE compliant models. Frost free models have an optional ice-maker (Must be factory installed. Base unit is not ice-maker ready).

SCFF55 Built-In FROST-FREE Freezer

Bring the convenience of frost-free operation to under-counter freezers, with SUMMIT SCFF55. Available in 3 cabinet finishes with a choice of door styles and handles, including our wrapped stainless steel door with a professional 12 inch towel bar handle or a choice of 7 door colors.

Model SCFF55 (all versions) is suitable for built-in use with a choice of an optional stainless steel frame for custom panels or a wrapped stainless steel door. An ice-maker is available on models below with suffix 'IM'.

Model SCFF55 has fan-forced interior cooling for even temperature distribution, an adjustable thermostat, and never needs defrosting. The foamed in place insulation and solid foamed door also enhance energy efficiency.

The interior offers some of the largest shelves in the industry, capable of holding trays up to 19 1/2 inches wide by 16 inches deep. All shelves are adjustable. Features include a reversible door on all base models.

Frost-free freezer model SCFF55 is an exact match to SUMMIT COMMERCIAL all-refrigerator FF-7, and makes a perfect side by side set.

SCFF55	Frost-free freezer in white (built-in capable), with forced air interior cooling.
SCFF55L	Frost-free freezer in white (built-in capable), with forced air interior cooling. Front lock.
SCFF55LBL	Same as above in black, but with glass shelves.
SCFF55LMED	Same as SCFF55L with hospital grade cords and plugs and NIST external temperature displays.
SCFF55LBLMED	Same as SCFF55LBL with hospital grade cords and plugs and NIST external temperature displays.
SCFF55LMED-IM	Frost-free freezer with forced air interior cooling, front lock, hospital grade cords and ice-maker.
SCFF55LBLMED-IM	Same as above in Black.
SCFF55L-IM	Frost-free freezer with built-in capability, forced air interior cooling, front lock and ice-maker.
SCFF55LBL-IM	Same as above in black.



Also see our 3 drawer freezers in stainless steel on Page 7, FROST-FREE chest freezers on Page 10; "cube" low freezers on Page 4, and low-temperature freezers on Page 11.

SCFF55L / SCFF55LMED (shown at left) are frost-free freezers with a lock. Shown in white, also available in black or stainless steel.

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
FS62LBIMED-7	33.5	23.625	23.5	4	White	White	Reversible	Front
FS62LBIMEDADA-7	32	23.625	23.5	4	White	White	Reversible	Front
FS62L	33.5	23.625	23.5	4	White	White	Reversible	Front
FS62	33.5	23.625	23.5	4	White	White	Reversible	None
FS62L-7	33.5	23.625	23.5	4	White	White	Reversible	Front
FS62-7	33.5	23.625	23.5	4	White	White	Reversible	None
SCFF55LMED	33.25	23.625	23.5	5.0	White	White	Reversible	Front
SCFF55LBLMED	33.25	23.625	23.5	5.0	Black	Black	Reversible	Front
SCFF55LMED-IM	33.25	23.625	23.5	5.0	White	White	Reversible	Front
SCFF55LBLMED-IM	33.25	23.625	23.5	5.0	Black	Black	Reversible	Front
SCFF55L	33.25	23.625	23.5	5.0	White	White	Reversible	Front
SCFF55LBL	33.25	23.625	23.5	5.0	Black	Black	Reversible	Front
SCFF55L-IM	33.25	23.625	23.5	5.0	White	White	Reversible	Front
SCFF55LBL-IM	33.25	23.625	23.5	5.0	Black	Black	Reversible	Front
SCFF55	33.25	23.625	23.5	5.0	White	White	Reversible	None

Models in Blue are approved for foodservice and CALCODE use (meet NSF-7)

SUMMIT Appliance Division
Phone: 718-893-3900

Felix Storch, Inc. 770 Garrison Avenue,
Fax 718-842-3093

Bronx, NY 10474 USA

Email: sales@summitmedicalrefrigerators.com

Visit our website at: www.summitmedicalrefrigerators.com

CUBE SIZED ALL-REFRIGERATORS OR ALL-FREEZERS

FFAR2L All-refrigerator with automatic defrost

FFAR2L is an ideal choice for most customers needing a "cube" sized refrigerator, as it offers the convenience of automatic defrost and a front lock. Generous 1.8 c.f. of capacity, a reversible door and door storage are standard. This model is a perfect match to our all-freezer, model FS20L. Finish options include a fully wrapped stainless steel cabinet and door, and versions approved for food-service use (ETL-S equal to NSF-7).

FFAR2L-7MED	Refrigerator with front lock, hospital grade cord and NIST traceable external temperature display and alarm. Internal fan for even temperature performance. UL and ETL-S listed for foodservice use. Temperature range 2 to 8° C (36 to 46° F).
FFAR2L	All-refrigerator with front mounted lock.
FFAR2L-7	Same as above. Approved for commercial use.
FFAR2L-CSS	FFAR2L with fully wrapped stainless steel cabinet and door. Stainless steel handle.
FFAR2L-CSS-7	Same as above, but approved for commercial use. ETL-Sanitation listed (meets NSF-7 standards).
"AM" Suffix	Add Agion™ anti-microbial coating to any above model with 'CSS' stainless steel finish



FFAR2L-CSS / FAR2LCS7 (interior) models shown here with stainless steel cabinet and wrapped stainless steel door (CSS suffix).



FS20LCS5 / FS20L-CSS-7 / FFAR2LCS5 / FFAR2LCS5-7 "cube" sized refrigerator or freezer (closed) Standard front lock.



FS20L-7C55 MED freezer with hospital grade cord and front lock. Ideal for vaccine and medical storage. Standard external NIST traceable thermometer / alarm installed.



FFAR2L / FFAR2L7 interior. "Cube" sized refrigerator. Reversible door and door storage are standard. Installed with a front mounted lock. Med models have an internal fan for more even temperature throughout.



FS20L / FS20L-7 (interior) -20°C freezer. Manual defrost with a standard front lock. Shown in white.

FFAR2L-7MED / FS20L7MED models (closed, at right). Ideal for vaccine and medical storage. Standard external NIST certified thermometer and alarm, a hospital grade (green dot) cord, and a front lock are standard on "MED" series refrigerators and freezers. An internal air circulation fan is included in model FFAR2LMED. Models **FFAR2L / FFAR2L7 / FS20L** and **FS20L7** appear the same without thermometer on the front door (lock is standard).



Buy the perfect "cube" sized refrigerator or freezer. Choose an all-refrigerator with automatic defrost—or an all freezer capable of -20°C operation (manual defrost). Models are available with approvals for standard use, or for foodservice use (-7 option). All models have front locks.

Available in white or full stainless steel cabinets and wrapped doors. Optional AGION™ anti microbial coated stainless steel.

Reversible doors allow a perfect side by side set!

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
FFAR2L-7MED	20	20	21	1.8	White	White	Reversible	Front
FFAR2L	20	20	21	1.8	White	White	Reversible	Front
FFAR2L-7	20	20	21	1.8	White	White	Reversible	Front
FFAR2L-CSS	20	20	21	1.8	S.Steel	S.Steel	RHD/LHD	Front
FFAR2L-7C55	20	20	21	1.8	S. Steel	S.Steel	RHD/LHD	Front
FS20L-7MED	20	20	21	1.6	White	White	Reversible	Front
FS20L	20	20	21	1.6	White	White	Reversible	Front
FS20L-7	20	20	21	1.6	White	White	Reversible	Front
FS20L-CSS	20	20	21	1.6	S.Steel	S.Steel	RHD/LHD	Front
FS20L-7C55	20	20	21	1.6	S.Steel	S.Steel	RHD/LHD	Front

Models in Blue are approved for foodservice and CALCODE use (meet NSF-7)

SUMMIT Appliance Division
Phone: 718-893-3900

Felix Storch, Inc. 770 Garrison Avenue,
Fax 718-842-3093

Bronx, NY 10474 USA
Email: sales@summitmedicalrefrigerators.com

Visit our website at: www.summitmedicalrefrigerators.com

COMPACT REFRIGERATOR-FREEZERS FOR MEDICAL USE

FEATURING OUR MED-SERIES ('MED' SUFFIX) MODELS, WITH FEATURES AND PERFORMANCE ENHANCED FOR LABORATORY, MEDICAL AND SCIENTIFIC APPLICATIONS

CT66LBIMED	Refrigerator-freezer with front lock. Suitable for built-in (fully enclosed under a counter) or freestanding use. Hospital grade cords, and a NIST traceable thermometer/alarm are standard. All SUMMIT CT66 models feature our unique dual evaporator, for separate cooling of the refrigerated and freezer sections, with a freezer capable of maintaining under 5°F. Auto-defrost refrigerated section and manual defrost freezer. Reversible doors.
CT66LBIMEDADA	Same as above but 32" high for ADA counters.
CP35LLMED	Two-door under-counter refrigerator-freezer with two side-mounted locks. Hospital grade cords and 2 NIST traceable thermometers with alarms. Internal fan in refrigerator compartment. All SUMMIT CP35 models have 0°F freezer sections.
CP35LLMEDADA	Same as above but 32" high for ADA counters.
CM45LMED	Manual defrost refrigerator-freezer with front lock. Hospital grade cord, NIST traceable thermometer, alarm and internal air circulation fan. Reversible door.
S19LMED	Manual defrost "cube" sized refrigerator-freezer with front lock. Hospital grade cords and NIST traceable thermometer. Reversible door.
CT66L	Freestanding refrigerator-freezer with dual evaporator cooling. Front lock and reversible door. Auto-defrost refrigerated section and manual defrost freezer. Freezer section can operate below 5°F.
CT66L-ADA	Same as above but 32" high for ADA counters.
CP35LL	Two-door compact refrigerator-freezer with two side locks and reversible doors. Auto-defrost refrigerated section and manual defrost freezer.
CM45L	Under-counter refrigerator-freezer with front mounted lock. Reversible doors. Manual defrost.
S19L	Compact "cube" sized refrigerator-freezer with flush back, reversible door and front-mounted lock. Manual defrost.
Options for CT66	On any CT66 models, add "SSTB" for a wrapped stainless steel door and pro handle; "CSS" for a full stainless steel cabinet and wrapped door, or "FR" for a stainless steel frame to accept custom panels or "BI" for built-in use (front-breathing).
"AM" Suffix	Add Agion™ anti-microbial coating to any CT66 model with "SSTB" or "CSS" stainless steel finish



CP35LLMED - Two door refrigerator-freezer with hospital grade cord. Two side locks are also standard along with a NIST traceable thermometer and alarm. For proper lock placement, order RHD or LHD swing. Zero degree freezer (F) for vaccines is manual defrost, and refrigerated section is automatic defrost with an air circulation fan.



CT66LBIMED (interior) - built-in unit with hospital grade cord, front door lock, convenient door storage and reversible door. NIST traceable alarm / thermometer and interior light are included. Dual evaporator cooling.

CT66LSSTB - (closed). Photo illustrates an SSTB door finish on any CT66L model (with front lock). Handle is also stainless steel. Available on 'MED' series.



S19L (interior on left and exterior on right) - "Cube" sized refrigerator-freezer with standard front lock. Manual defrost, reversible door. White. Ideal for offices, break rooms and lounges. For foodservice use, or medical applications, see our FFAR2L and FS20L models on Page 4.

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
CT66LBIMED	33.5	23.625	23.5	5.3	White	White	Reversible	Front
CT66LBIMEDADA	32	23.625	23.5	5.3	White	White	Reversible	Front
CP35LLMED	33.5	19.75	20	2.9	White	White	RHD/LHD	Side(2)
CP35LLMEDADA	32	19.75	20	2.9	White	White	RHD/LHD	Side(2)
CM45LMED	34	19.5	22	4.3	White	White	Reversible	Front
S19LMED	20.5	18.5	20	1.7	White	White	Reversible	Front
CT66L	33.5	23.625	23.5	5.3	White	White	Reversible	Front
CT66L-ADA	32	23.625	23.5	5.3	White	White	Reversible	Front
CP35LL	33.5	18.75	20	2.9	White	White	RHD/LHD	Side(2)
CM45L	34	19.5	22	4.3	White	White	Reversible	Front
S19L	20.5	18.5	20	1.7	White	White	Reversible	Front

Models in Blue are approved for foodservice and CALCODE use (meet NSF-7)



CM45L - Under-counter refrigerator-freezer (manual defrost) with front-mounted lock. Reversible door with door storage. **CM45LMED** adds a hospital grade cord, internal air circulation fan and a NIST traceable alarm with thermometer.

SUMMIT Appliance Division Felix Storch, Inc. 770 Garrison Avenue, Bronx, NY 10474 USA
Phone: 718-893-3900 Fax 718-842-3093 Email: sales@summitmedicalrefrigerators.com
Visit our website at: www.summitmedicalrefrigerators.com

COMPACT NO-FROST ALL-REFRIGERATORS

FF560LMED	All-refrigerator, auto-defrost, front lock, reversible door. Hospital grade cord and NIST traceable thermometer. Includes an ice-bank and internal air circulation fan for more even temperature performance, and a reversible door. Large 4.4 c.f. capacity in an easy to fit size. Temperature range 2 to 8 degrees C (36 to 46 degrees F).
FF510LMED	All-refrigerator, with auto-defrost, reversible door and front lock. Includes a hospital grade cord and NIST certified thermometer. No internal fans.
FF520LMED	Same as above with black cabinet.
FF28LMED	Compact all-refrigerator, auto-defrost, reversible door with front lock. Includes a hospital grade cord and NIST certified thermometer. Internal fan. Temperature range 2 to 8 degrees C (36 to 46 degrees F).
FF29BLMED	Same as above with black cabinet.
FF510L	All refrigerator, auto-defrost, reversible door, front lock.
FF520L	Same as above in black.
FF28L	Compact all-refrigerator, auto-defrost, reversible door with front lock..
FF29BL	Same as above in black. Door shelves.
Keypad lock	Add a front mounted keyless (keypad) lock to any model above. Battery operated.
AC Keypad	Add a front mounted keyless (keypad) lock to any model above powered from the appliance line.



FF29BL / FF29BLMED - Black compact refrigerator with energy efficient design. Adjustable shelves and door storage for large bottles. Has one piece seamless interior liner. All-refrigerator with automatic defrost, front lock and reversible door.

For larger all-refrigerators see models FF6 and FF7 on Page 2
For a smaller all-refrigerator see Model FFAR2-L on Page 4
For full size all refrigerators, see Models on Pages 8 and 10



FF28L / FF28LMED White compact refrigerator with energy efficient design. Adjustable shelves and door storage for large bottles. Has one piece seamless interior liner. All-refrigerator with automatic defrost, front lock and reversible door.

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
FF560LMED	34	20.25	21	4.4	White	White	Reversible	Front
FF510LMED	34	20	21	4.0	White	White	Reversible	Front
FF520LMED	34	20	21	4.0	Black	Black	Reversible	Front
FF28LMED	24.5	18.75	18	2.5	White	White	Reversible	Front
FF29BLMED	24.5	18.75	18	2.5	Black	Black	Reversible	Front
FF510L	34	20	21	4.0	White	White	Reversible	Front
FF520L	34	20	21	4.0	Black	Black	Reversible	Front
FF28L	24.5	18.75	18	2.5	White	White	Reversible	Front
FF29BL	24.5	18.75	18	2.5	Black	Black	Reversible	Front

FF560LMED ALL-REFRIGERATOR

Model **FF560LMED** was designed by SUMMIT from feedback from our many customers in the scientific and medical community. It was designed to be an affordable, compact storage refrigerator, but capable of maintaining lower temperatures than most compact refrigerators, and with the features most often requested: including automatic defrost, an internal air circulation fan for even cooling; a hospital grade plug, a professionally mounted NIST certified external readout thermometer with minimum and maximum values and alarm, an interior light, a front lock, a reversible door and useful door storage. Adjustable temperature range 36 to 46 degrees F (2° C to 8° C).

FF560LMED (at right) All-refrigerator, auto-defrost; spacious interior with four shelves (3 are adjustable) and additional door shelves for convenience. Internal fan, light, hospital grade cord (green dot), and NIST certified thermometer and alarm. Front lock. Temperature range 2 to 8 degrees C (36 to 46 degrees F). Reversible door and useful tabletop.



All 'MED' units are installed with hospital grade cords and plugs (green dot) and NIST traceable external, professionally mounted thermometers with high temperature alarms. All models include a front mounted lock; or choose an optional battery operated keyless keypad lock or AC powered keypad lock (from the appliance's line cord). Keypads allow 10 user programmed codes + master. Most 'MED' models also include internal air circulation fans.



FF510L / FF510LMED (White finish)

FF520L / FF520LMED (Black finish)

All models:

All refrigerator (auto-defrost) with front lock. Reversible door, large shelf area and door shelves for convenience.

'MED' Models:

- Hospital grade cords (green dot)
- NIST traceable alarm with temperature display (installed)

(FF510LMED and FF520LMED do not have internal air circulation fans)



SUMMIT Appliance Division Felix Storch, Inc. 770 Garrison Avenue, Bronx, NY 10474 USA
 Phone: 718-893-3900 Fax 718-842-3093 Email: sales@summitmedicalrefrigerators.com
 Visit our website at: www.summitmedicalrefrigerators.com

COMPACT FREEZERS—CHEST, UPRIGHT AND DRAWER

FS40LMED	FS40LMED is a front-opening freezer with a flat door liner and 4 interior drawers (removable) to keep contents frozen and conserve energy. Reversible door and featured with a hospital grade plug, NIST traceable thermometer, alarm and front lock.
CF05MED	Chest freezer with 5.3 c.f. of capacity. Manual defrost with front lock, hospital grade cord and NIST traceable thermometer and alarm.
SCF401SSMED	Stainless steel chest freezer, counter balanced hinges, basket for storage, with hospital grade cord, front lock and NIST traceable thermometer with alarm.
SPF5DSSTB	Three drawer manual defrost freezer. All stainless steel, suitable for built-in or freestanding use.
SCFF552D	Two drawer frost-free freezer with exterior and interior in stainless steel.
SCFF55IM2D	Two drawer frost-free freezer w/ice maker, with exterior and interior in stainless steel. Ice maker must be factory installed.
FS60	Front opening, 5.0 cubic foot compact freezer with door storage, RHD only, manual defrost.
FS60L (replaces FS56L)	Same as above with side mounted lock. Replaces model FS56L with same capacity and features.
FS40L	Front opening freezer with four interior baskets, front lock. Reversible door, manual defrost.
SCF401SS	Chest freezer with full stainless steel exterior: counter balanced lid, and basket. White seamless interior, manual defrost
CF05	Manual defrost chest freezer with counter balanced lid.

Models in Blue are approved for foodservice and CALCODE use (meet NSF-7)

COMPACT CHEST FREEZERS



SCF401SS / SCF401SSMED - Built for durability with stainless steel cabinet and metal counter balanced hinges. "MED" model adds a lock, hospital grade cord and NIST Traceable alarm with thermometer. Manual defrost.

CF05 / CF05MED - Manual defrost chest freezer with seamless liner and 5.3 c.f. of capacity. "MED" models adds a front lock, hospital grade cord, and NIST traceable alarm with thermometer.



Drawer freezers

The convenience of drawers, with the durability and elegance of stainless steel in a choice of 2 or 3 drawers. The two drawer **FROST-FREE SCFF552D** has the option of a factory installed icemaker, (Model SCFF55IM2D). Internal fan for air circulation.

3 drawer **SPF5DSSTB** is manual defrost. All models have interior drawers and full exteriors of stainless steel.



SPF5DSSTB - Manual defrost (no internal fans) three drawer freezer, fully stainless steel. Full stainless steel towel bar handles.

SCFF55IM2D / SCFF552D Frost-free freezer with two drawers; forced air cooling system. Stainless steel throughout. Full pro handles.

FRONT-OPENING, UNDER-COUNTER FREEZERS



FS40L / FS40LMED - Easy to fit, front opening freezer. 4 see-through baskets for energy conservation and convenience. Front lock and reversible door. "MED" model adds a hospital grade cord and a NIST traceable alarm and external temperature display.

FS60 / FS60L (replaces FS56L) Large capacity (5.0 c.f.) manual defrost freezer with open shelves and door shelves. RHD only. Made in North America. FS60L has a side lock.

BUILT-IN UNDER-COUNTER ICE-MAKERS

Model	Description	Dimensions	<ul style="list-style-type: none"> - UL Approved - NSF Approved - Built-in capable - 44 lbs ice/day - Use with drain - Optional Pump - Clear Ice - Refreshes ice on each cycle - Reversible door - Overflow switch - Electronic controls
BIM-44	Indoor, black with stainless steel door	33½" H X 14 ¾" W X 23 ¾" D	
BIM40OS	Indoor or outdoor, all stainless steel	33½" H X 14 ¾" W X 23 ¾" D	
BIM44ADA	Same as BIM44, but 32.5 inches high for ADA counters	32½" H X 14 ¾" W X 23 ¾" D	
BIM40OS-ADA	Same as BIM40OS, but 32.5 inches high for ADA counters	32½" H X 14 ¾" W X 23 ¾" D	

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
FS40LMED	34	20	21	3.0	White	White	Reversible	Front
CF05MED	35	23.5	25.8	5.3	White	White	Lift-up	Front
SCF401SSMED	35	23.5	25.8	5.0	S.Steel	S.Steel	Lift-up	Front
SPF5DSSTB	33.25	23.75	23.5	3 Drawers	S.Steel	S.Steel	Drawers	None
SCFF55IM2D	33.25	23.75	23.5	2 Drawers	S.Steel	S.Steel	Drawers	None
FS60	33.5	21.5	25.5	5.0	White	White	RHD	None
FS60L (replaces FS56L)	33.5	22.5	25.5	5.0	White	White	RHD	Side
FS40L	34	20	21	3.0	White	White	Reversible	Front
SCF401SS	35	23.5	25.8	5.0	S.Steel	S.Steel	Lift-up	None
CF05	35	23.5	25.8	5.3	White	White	Lift-up	None



BIM-44 / BIM44ADA



BIM-40OS / BIM40OSADA

SUMMIT Appliance Division Felix Storch, Inc. 770 Garrison Avenue, Bronx, NY 10474 USA
 Phone: 718-893-3900 Fax 718-842-3093 Email: sales@summitmedicalrefrigerators.com
 Visit our website at: www.summitmedicalrefrigerators.com

COMMERCIAL STORAGE REFRIGERATORS AND FREEZERS

SUMMIT offers three models of commercial *all-refrigerators*, with U.L. and U.L.-Sanitation (equal to NSF-7 standards) approvals and 3 models of *all freezers*, all with approval for foodservice applications. These models feature a top-mounted digital thermostat, so you can precisely set the interior temperature. Choose from 18, 20 or 25 cubic feet. All feature fan-forced cooling and frost-free operation. Adjustable shelves, door storage and large 6 inch NSF approved casters (two with brakes) for portability. Finished with a large stainless steel towel bar handle for ease of opening. A lock is standard. For permanent installations, models are available without casters (subtract 6 inches from overall height) but with 4 large level legs. Units are shipped with casters mounted in a custom base (requires two people for unpacking). Complies with CALCODE regulations in California.

FROST-FREE ALL-REFRIGERATORS

SCUR18	Front-opening all-refrigerator approved for foodservice use with frost-free operation, digital thermostat, and stainless steel handle. Large casters. 18 c.f. of capacity, lock, adjustable shelves; door shelves, one piece seamless interior liner, and interior light.
SCUR20	Same as above with 20 c.f. of capacity
SCUR25	Same features as SCUR18 with 25 c.f. of capacity.

FROST-FREE ALL-FREEZERS

SCUF18	Front-opening all-freezer approved for foodservice use with frost-free operation, digital thermostat, and stainless steel handle. Large casters. 18 c.f. of capacity, lock, adjustable shelves; door shelves, one piece seamless interior liner, and interior light.
SCUF20	Same as above with 20 c.f. of capacity.
SCUF25	Same features as SCUF18 with 25 c.f. of capacity.

Model	Height (") (with casters)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
SCUR18	78	30	32	17.7	White	White	RHD	Front
SCUR20	78	33	31.5	20.1	White	White	RHD	Front
SCUR25	79	35.75	34.3	25.0	White	White	RHD	Front
SCUF18	78	30	32	17.7	White	White	RHD	Front
SCUF20	78	33	31.5	20.1	White	White	RHD	Front
SCUF25	79	35.75	34.3	24.7	White	White	RHD	Front

Models in Blue are approved for foodservice and CALCODE use (meet NSF-7)



At left **SCUR20** or **SCUF20** interior. Precision digital thermostat is externally mounted at top for convenience. Below: **SCUR18** interior. 6 inch casters are standard.



Optional 6" legs or seismic legs can replace casters.

- Precision digital thermostat with external display
- Interior light
- 6 inch casters standard (pre-mounted)
- U.L and U.L Sanitation approved (meets NSF-7)
- 27 inch stainless steel handle

STANDARD FULL-SIZE STORAGE ALL-REFRIGERATORS



R18 - 17.6 cubic foot auto-defrost all-refrigerator with static defrost system (no internal fans). **R18FF** has fan forced cooling and is frost-free.



FFAR10 - 10 cubic foot refrigerator with fan forced air circulation.

R18 (replaces R17)	All refrigerator with static system (no internal fans), auto-defrost
R18FF (replaces R17)	As above with forced air fan cooled interior. Frost-free operation.
FFAR10MED	All-refrigerator, large shelf and door storage, hospital grade plug, side lock, NIST traceable thermometer with alarm, fan cooled interior, automatic defrost. Order LHD or RHD.
FFAR10FC-7MED	Same as with UL-S (equal to NSF-7) for foodservice use.
FFAR10LAB	Same as FFAR10 with keypad lock and alarm standard.
FFAR10	Base model of FFAR10 with fan cooled interior standard.
VKS670	Two door all-refrigerator (one zone) with no internal fans.

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
R18 (replaces R17)	67.5	30	32	17.6	White	White	Reversible	None
R18FF (replaces R17)	67.5	30	32	17.6	White	White	Reversible	None
FFAR10MED	55	23.625	23.5	10.1	White	White	RHD / LHD	Side
FFAR10FC-7MED	55	23.625	23.5	10.1	White	White	RHD / LHD	Side
FFAR10LAB	55	23.625	23.5	10.1	White	White	RHD / LHD	Side
FFAR10	55	23.625	23.5	10.1	White	White	Reversible	None
VKS670	73	23.625	24	12.0	White	White	Reversible	None

SSTB Option Add a wrapped stainless steel door and pro handle to any **FFAR10**

LOCK Option Add a side lock to any model above (two required for **VKS670**)

Models in Blue are approved for foodservice and CALCODE use (meet NSF-7)



At left:
FFAR10MED
FFAR10FC-7
FFAR10LAB
Interior.
Auto-defrost
All-refrigerator

At right:
SSTB door
(wrapped
stainless steel
with pro
handle)
Available on
any **FFAR10**.



SUMMIT Appliance Division Felix Storch, Inc. 770 Garrison Avenue, Bronx, NY 10474 USA
Phone: 718-893-3900 Fax 718-842-3093 Email: sales@summitmedicalrefrigerators.com
Visit our website at: www.summitmedicalrefrigerators.com

FULL-SIZE REFRIGERATOR-FREEZERS

For many applications where a special medical or laboratory refrigerator or freezer is not required, SUMMIT offers a large selection of standard household refrigerator-freezers, all manufactured in North America or Europe for top quality and all with the features you demand. Our three largest models (15, 18 or 21 c.f.) all include standard front-mounted locks, and locks are optional on all other models. Choose from frost-free models, or cycle defrost models for applications where fan cooling is not desired. For a full selection of household and commercial refrigerators or freezers, visit www.summitappliance.com.

CTR21LLF	Frost-free, two door refrigerator, front-lock, top freezer, glass shelves.
CTR18LLF	Frost-free, two door refrigerator, front-lock, top freezer, glass shelves.
CTR15LLF	Frost-free, two door refrigerator, front-lock, top freezer, wire shelves
FF882	Ideally sized, 24 inch wide and 24 inch deep, frost-free refrigerator-freezer with extra shelves, door shelves and reversible doors.
CP133	Our best selling cycle defrost refrigerator-freezer (manual defrost freezer and automatic defrost refrigerated compartment) with static cooling (no fans); reversible doors, interior light, adjustable shelves and door storage. Only 24 inches wide and deep and under 60" high.
CP97	Thin lined, recessed handles, reversible door, cycle-defrost refrigerator-freezer; only 21 1/4 inches wide for narrow spaces.
CP89	Thin line, reversible door, ADA compliant, cycle defrost ref.-freezer.

Since 1969, SUMMIT has specialized in refrigerators for hard-to-fit spaces. The models here represent a small selection of our full line. Visit www.summitappliance.com or call our sales office if you need sizes not shown here or elsewhere in this catalog.

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
CP171MED	82.5	24.75*	24	11.0	White	White	Reversible	2 Side
CTR21LLF	68.25	29.75	31	20.5	White	White	Reversible	Front
CTR18LLF	65.625	29.75	30	18.2	White	White	Reversible	Front
CTR15LLF	59.375	28	31	14.8	White	White	Reversible	Front
FF882	60.5	23.5	24	8.8	White	White	Reversible	None
CP133	59.75	23.625	24	9.5	White	White	Reversible	None
CP97	56.75	21.25	24	8.3	White	White	Reversible	None
CP89	44	18.75	24	5.8	White	White	Reversible	None



Top Left - **CP89** Cycle defrost, thin line, two door refrigerator-freezer

Top Right - **CP97** Cycle defrost, thin line, two door refrigerator-freezer

Left - **FF882** Frost-free 24 inch wide, 24 inch deep refrigerator-freezer

Below - **CP133** cycle defrost 24 inch wide, 24 inch deep refrigerator-freezer



TWO-DOOR REFRIGERATOR-FREEZER WITH TWO COMPRESSORS AND INDEPENDENT TEMPERATURE CONTROLS!

Model CP171-MED is a top refrigerator with a bottom freezer. It starts with two compressors and two precision digital thermostats allowing independent control of the fresh and frozen sections, and superb cooling. The unit comes with a hospital grade (green dot) plug and two side locks. The refrigerator section is automatic defrost, and the freezer section is manual defrost. The unit has no internal fans and no defrost heaters. The refrigerator section offers a large shelf area and door shelves, while the freezer compartment has three pull-out drawers for energy efficiency and temperature stability. Reversible doors, and only 24 inches wide* and 24 inches deep. Also available in stainless steel. Shown open at right, and closed at far right. The two digital thermostats display the interior temperature of each compartment, and can be easily set by the user. Thoughtful interior design. Built for SUMMIT in Denmark. Optional alarms.

* Base unit is 23.625 inches wide. Side locks add 1 inch. Locks can be omitted to fit into 24 inch opening.



CTR15LLF
CTR18LLF
CTR21LLF

Frost-free, top-freezer refrigerator-freezers in three popular sizes; for kitchens, residences and break rooms. Optional ice-maker available.

What does cycle defrost mean, and how is it different than frost-free?

We're frequently asked this question, and here is the explanation. Cycle defrost pre-dated frost free by a few decades. Cycle defrost is a mechanical design, putting the evaporator (the part of a refrigerator that removes heat from the contents) in a position that water dripping from it can be collected. During the "off" cycle of the compressor, (the "motor" of a refrigerator or freezer), ice melts, gravity helps it drip down, where a tray and piping remove the accumulated water and it is evaporated. Thus, a cycle defrost refrigerator does build some ice, but removes it itself on a "cycle". A freezer is not usually cycle defrost, because the temperature is normally too low to melt the ice layer (although SUMMIT offers some models with full auto-defrost in both the refrigerator and freezer compartments utilizing the same concept). Frost-free design incorporates a timer and defrost heater, that periodically heats the evaporator to melt the ice. This design allows the evaporator to be placed anywhere and in any shape, as fans are used to distribute cold air when the compressor is running. In the US, frost free has grown in popularity on large household refrigerators, due to convenience, while mass production allowed its cost to become the same or lower than cycle defrost. In the scientific community, frost-free is not desired for certain applications, as there may be a greater temperature swing during the heater operation. At SUMMIT, we continue to market a large product line incorporating cycle defrost, for customers that continue to have the need for storage free from fans and internal heaters. But, in step with the majority of users, we continue to expand and innovate our line of frost-free refrigerators and freezers. The choice is yours.



Exclusive front lock locks both doors at once.

SUMMIT Appliance Division
Phone: 718-893-3900

Felix Storch, Inc. 770 Garrison Avenue,
Fax 718-842-3093
Visit our website at: www.summitmedicalrefrigerators.com

Bronx, NY 10474 USA
Email: sales@summitmedicalrefrigerators.com

FROST-FREE CHEST REFRIGERATORS OR FREEZERS

**EXCLUSIVE FAN COOLED INTERIORS FOR EVEN TEMPERATURE PERFORMANCE
NO DEFROSTING EVER- AND A CHOICE OF 6 SIZES. ALL HAVE
COMMERCIAL (UL AND UL-S) APPROVAL FOR FOODSERVICE OR MEDICAL USE.**

SUMMIT SCFF and SCFR series chest freezers bring the convenience of frost-free operation to a product category normally available in manual defrost only. A large choice of sizes, all with powerful cooling systems and fan forced interior cooling for even temperature performance. Storage baskets included, and one piece seamless interior liners. Counter-balanced lids, recessed handle, and foamed lids for energy savings. Made in the U.S.A. with cabinets from Canada.

FROST-FREE CHEST ALL-REFRIGERATORS

SCFR50	5.5 c.f. capacity frost-free all-refrigerator
SCFR70	8.5 c.f. capacity frost-free all-refrigerator with front lock
SCFR120	13.5 c.f. capacity frost-free all-refrigerator with front lock
SCFR150	15.5 c.f. capacity frost-free all-refrigerator with front lock
SCFR220	21 c.f. capacity frost-free all-refrigerator with front lock
SCFR250	23.5 c.f. capacity frost-free all-refrigerator with front lock
MED OPTION	Add a digital thermostat, hospital grade cord, stainless steel corner guards, and NIST traceable thermometer with alarm to any model above (add suffix "MED" and add 4 inches to width). All "MED" models will have a front lock..

FROST-FREE CHEST ALL-FREEZERS

SCFF50	5.5 c.f. capacity frost-free freezer.
SCFF70	8.5 c.f. capacity frost-free freezer with front lock.
SCFF120	13.5 c.f. capacity frost-free freezer with front lock
SCFF150	15.5 c.f. capacity frost-free freezer with front lock.
SCFF220	21 c.f. capacity frost-free freezer with front lock.
SCFF250	23.5 c.f. capacity frost-free freezer with front lock.
MED OPTION	Add a digital thermostat, hospital grade cord, stainless steel corner guards, and exterior NIST thermometer to any model above (add suffix "MED" and add 4 inches to width). All "MED" models will have a front lock.



SCFF120 / SCFR120 shown open.



SCFF220 / SCFR220 Frost-free chest freezer or matching frost-free chest refrigerator, shown closed.



SCFF70MED. Photo reflects appearance of any "MED" model chest refrigerator or freezer.

Special Applications: The cooling used system on our SCFF / SCFR series is capable of a wide range of temperature settings when paired with a digital thermostat and a variety of coolants. For low temperature, or exacting performance needs, call our sales department. By special order we can accommodate ranges of -35°C (-31°F) up to 10° C (50° F)

"MED" models have digital thermostats, NIST traceable alarms and temperature displays, stainless steel corner protectors, and hospital grade (green dot) cords.



SCFF50 / SCFR50 shown open.

Why settle for a manual defrost chest freezer, when SUMMIT makes it so easy to go **frost-free** with chest freezers, and matching **frost-free** chest refrigerators in 6 sizes; from an easy-to-fit 5.5 c.f. all the way up to 24 cubic feet.

All models utilize a rugged commercial, NSF approved, cooling system; made in the USA and designed for years of demanding service. All are UL and UL Sanitation (equal to NSF-7) listed for commercial, foodservice or any other use.

Eliminate messy, expensive and inconvenient defrosting forever!

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
SCFR50	35	31.5	24	5.5	White	White	Lift-up	None
SCFR70	35	42	24	8.5	White	White	Lift-up	Front
SCFR120	35	46	29	13.5	White	White	Lift-up	Front
SCFR150	35	54	29	15.5	White	White	Lift-up	Front
SCFR220	35	65	29	21.0	White	White	Lift-up	Front
SCFR250	35	74	29	24.0	White	White	Lift-up	Front
SCFF50	35	31.5	24	5.5	White	White	Lift-up	None
SCFF70	35	42	24	8.5	White	White	Lift-up	Front
SCFF120	35	46	29	13.5	White	White	Lift-up	Front
SCFF150	35	54	29	15.5	White	White	Lift-up	Front
SCFF220	35	65	29.5	21.0	White	White	Lift-up	Front
SCFF250	35	74	29.5	24.0	White	White	Lift-up	Front

"MED" models are 4 inches wider. Height and depth remain the same.

Models in Blue are approved for foodservice and CALCODE use (meet NSF-7)

SUMMIT Appliance Division Felix Storch, Inc. 770 Garrison Avenue, Bronx, NY 10474 USA
Phone: 718-893-3900 Fax 718-842-3093 Email: sales@summitmedicalrefrigerators.com
Visit our website at: www.summitmedicalrefrigerators.com

LOW TEMPERATURE LABORATORY FREEZERS

For low temperature applications, SUMMIT offers a wide choice of low temperature freezers, with a choice of -30°C, -35°C or -40°C operation. All utilize R-404 and 12 models are UL and UL-S approved for most applications, including foodservice use (-40°C freezers are U.L. approved). All chest freezers feature our precision digital thermostat and feature a front lock and are manual defrost. For convenience in busy workplaces, most models feature low-temperature warning labels, stainless steel corner protectors and an all metal thermostat housing. Other features include: foamed, durable counter-balanced lids, foamed in place insulation in all cabinets, and fan cooled compressors.

-30°C Freezers

FCL44	Compact freezer with lift-up lid, -30°C operation, and front lock. Manual defrost. Includes an external NIST certified digital thermometer and alarm.
VT65	Front opening freezer capable of -30°C with extra thick insulation, 3 pull-out drawers for extra temperature stability and energy savings. NIST traceable thermometer and alarm are included. Front lock, manual defrost.
VT85 (replaces FCL88)	Chest freezer capable of -30°C with NIST traceable thermometer and alarm. Digital thermostat. (Note: the capacity and width of this model have increased from 2007 versions of this model). Front lock, manual defrost. Stainless steel corner protectors, optional casters, 6" legs or seismic legs.
VT125	Chest freezer capable of -30°C with NIST traceable thermometer and alarm. Digital thermostat. (Note: the capacity and width of this model have increased from 2007 versions of this model). Front lock, manual defrost. Stainless steel corner protectors, optional casters, 6" legs or seismic legs.
VT175	Chest freezer capable of -30°C with NIST traceable thermometer and alarm. Digital thermostat. Front lock, manual defrost. Stainless steel corner protectors, optional casters, 6" legs or seismic legs.
VT175IB	Same as above with included ice-bank. See details below.
VT225	Chest freezer capable of -30°C with NIST traceable thermometer and alarm. Digital thermostat. Front lock, manual defrost. Stainless steel corner protectors, optional casters, 6" legs or seismic legs.

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
FCL44	33.5	22	24	4.0	White	White	Lift-up	Front
VT65	33.5	23.625	23.5	4.0	White	White	Reversible	Front
VT85	35	45	24	10.0	White	White	Lift-up	Front
VT125	35	49	29	14.8	White	White	Lift-up	Front
VT175	35	58	29	16.5	White	White	Lift-up	Front
VT175IB	35	58	29	14.2	White	White	Lift-up	Front
VT225	35	69	29	21.7	White	White	Lift-up	Front
VLT65	33.5	23.625	23.5	4.0	White	White	Reversible	Front
VTL85	35	45	24	10.0	White	White	Lift-up	Front
VLT125	35	49	29	14.8	White	White	Lift-up	Front
VLT175	35	58	29	16.5	White	White	Lift-up	Front
VLT175IB	35	58	29	14.2	White	White	Lift-up	Front
VLT225	35	69	29	21.7	White	White	Lift-up	Front
VT257	35.25	45	24	7.3	White	White	Lift-up	Front
VT317	35.25	49.6	24	8.4	White	White	Lift-up	Front
VT357	35.25	61.5	24	11.0	White	White	Lift-up	Front

-35°C Freezers

VLT65	Front opening freezer capable of -35°C with extra thick insulation, 3 pull-out drawers for extra temperature stability and energy savings. NIST traceable thermometer and alarm are included. Front lock, manual defrost. Optional casters, legs or seismic legs.
VTL85	Chest freezer capable of -35°C with NIST traceable thermometer and alarm. Digital thermostat. (Note: the capacity and width of this model have increased from the 2007 model). Front lock, manual defrost. Optional casters, legs or seismic legs.
VLT125	Chest freezer capable of -35°C with NIST traceable thermometer and alarm. Digital thermostat. (Note: the capacity and width of this model have increased from the 2007 model). Front lock, manual defrost. Optional casters, legs or seismic legs.
VLT175	Chest freezer capable of -35°C with NIST traceable thermometer and alarm. Digital thermostat. Front lock, manual defrost. Optional casters, legs or seismic legs.
VLT175IB	Same as above with included ice-bank. See details below.
VLT225	Chest freezer capable of -35°C with NIST traceable thermometer and alarm. Digital thermostat. Front lock, manual defrost. Optional casters, legs or seismic legs.

-40°C Freezers

VT257	Chest freezer capable of -40°C with lock and digital thermostat. Front lock, manual defrost. 100mm insulation for reduced energy loss and better reliability.
VT317	Same as above in 50 inch width
VT357	Same as above in 61.5 inch width



VT 257 (-40°C) Low Temp. Freezer



VLT Chest series



VT65 / VLT65



FCL44



Interior—VT / VLT series

Models in Blue are approved for foodservice and CALCODE use (meet NSF-7)

ICE-BANK OPTION FOR ANY CHEST FREEZER

Unique ice-bank reserve provides protection for frozen contents for up to 42 hours* in cases of loss of power.



VT175IB / VLT175IB
Illustrated.

Ice-bank holding plates can be added to any chest type freezer in SUMMIT's line. (capacity is reduced by 12 to 15% per freezer, and shipping weight is increased by 18 to 20%). Optional casters, legs or seismic legs.

Summit's ice-bank technology provide a reserve capacity of non-toxic, fluid-filled cold plates that can help protect contents in event of power failures, inadvertent disconnecting of the power supply or malfunction of the freezer. A battery powered alarm is provided to warn of increasing temperatures, and will display the high and low temperatures recorded in the freezer. The ice-bank is fully installed and is maintenance-free. Model VT175IB has over 3" of insulation in the exterior walls.

* Tests by an independent testing laboratory (Intertek/ETL) conducted at an ambient temperature of 70 degrees F (21°C) showed that when contents (75% filled) were stabilized at -22°F (-30°C), and power was turned off, contents were held below freezing (32° F or 0°C) for over 42 hours. Individual results will vary based on ambient temperature, percentage of capacity used, and frequency of lid opening. Full test results are presented on our website.

SUMMIT Appliance Division
Phone: 718-893-3900

Felix Storch, Inc. 770 Garrison Avenue,
Fax 718-842-3093

Bronx, NY 10474 USA
Email: sales@summitmedicalrefrigerators.com

Visit our website at: www.summitmedicalrefrigerators.com

SPECIALTY ALL-REFRIGERATORS

A selection of under-counter all-refrigerators, all UL and UL-S listed for foodservice applications, and all with automatic defrost, with a choice of glass door models, or stainless steel drawer models.

SCR600LBIMED	Built-in all-refrigerator with glass door and front lock. Hospital grade cord and NIST traceable thermometer. Automatic defrost and reversible door. Interior fan for even cooling.
SCR600LBIMEDADA	Same as above in 32" height for ADA counters.
SP6DSSTB-7MED	Three drawer refrigerator with hospital grade cords and NIST traceable thermometer. Approved for foodservice use. All stainless steel, including interior drawers. Fully automatic defrost with three pro stainless steel towel bar handles. Internal air circulation fan for even temperature.
SP6DS2D-7MED	Two drawer refrigerator with a hospital grade cord and NIST traceable thermometer. Approved for foodservice use and fully automatic defrost. All stainless steel including drawer interiors.
SCR600L	Glass door all refrigerator with automatic defrost. Front mounted lock for freestanding use. Wire shelves.
SCR600BL	Same as above in black with glass shelves.
SP6DS-7	Three drawer refrigerator with recessed handles. All stainless steel including the interior drawers. Approved for foodservice use. Fully automatic defrost with internal fan.
SP6DSSTB-7	Same as above with full stainless steel towel bar handles.
SP6DS2D-7	Two drawer refrigerator. Approved for foodservice use. All stainless steel including interior drawers. Automatic defrost with an internal air circulation fan.



SP6DS2D-7 / SP6DS2D-7MED
Two-drawer no-frost all stainless steel (exterior and interior drawers) refrigerator has 2 full horizontal stainless steel handles. Perfectly matches drawer freezer SCFF55IM2D. U.L. and U.L.S (equal to NSF-7) listed. Suitable for built-in or freestanding installation.



SP6DS-7 Three drawer no-frost refrigerator with full stainless steel exterior and drawer interiors. Recessed handles for tight spaces. U.L. and U.L.S (equal to NSF-7) listed. Suitable for built-in or freestanding installation.



SP6DSSTB-7 / SP6DSSTB-7MED
Three drawer, no-frost, all-refrigerator with full stainless steel exterior and interior drawers and three full stainless steel towel bar handles. U.L. and U.L.S (equal to NSF-7) listed. Suitable for built-in or freestanding installation. 'MED' model has NIST traceable alarm and hospital grade cord.



SCR600LBIMED / SCR600LBIMEDADA Glass door, commercial all-refrigerator, with automatic defrost, and our unique "hidden" evaporator for a clean interior. Reversible door, interior light (on rocker switch), large adjustable shelves (hold pans up to 19 1/2 X 15 1/2). "MED" models have NIST traceable thermometer, alarm, hospital grade plug and internal air circulation.



SCR600L Glass door, commercial all-refrigerator, with automatic defrost, static cooling system (no fans) and our unique "hidden" evaporator for a clean interior. Reversible door, interior light, UL and ETL-S (equal to

NSF-7) listed. Front lock, wire shelves and tabletop.



SCR600BL Glass door, commercial all-refrigerator with automatic defrost, front lock, static cooling system (no fans) and our unique "hidden" evaporator for a clean interior. Reversible door, interior light, UL and UL-S listed. Photo shows optional stainless steel handle).



SCR600BLCSS shown with optional 'CSS' stainless steel cabinet (includes 'TB' handle)

SUMMIT offers some of the most innovative 24" wide refrigerators on the market. Three models of drawer refrigerators, and a selection of glass door models, including models modified for medical use. All these models feature our unique "hidden" evaporator (behind the rear wall) for the cleanest interior in the industry and some of the largest shelves available. Oversized compressors enhance the cooling and performance.

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
SCR600LBIMED	33.5	23.625	23.5	5.5	White	Glass	Reversible	Front
SCR600LBIMEDADA	32	23.625	23.5	5.5	White	Glass	Reversible	Front
SP6DSSTB-7MED	33.25	23.75	23.5	3 Drawers	S.Steel	S.Steel	Drawers	None
SP6DS2D-7MED	33.25	23.75	23.5	2 Drawers	S.Steel	S.Steel	Drawers	None
SCR600L	33.5	23.625	23.5	5.5	White	Glass	Reversible	Front
SCR600BL	33.5	23.625	23.5	5.5	Black	Glass	Reversible	Front
SP6DS-7	33.25	23.75	23.5	3 Drawers	S.Steel	S.Steel	Drawers	None
SP6DSSTB-7	33.25	23.75	23.5	3 Drawers	S.Steel	S.Steel	Drawers	None
SP6DS2D-7	33.25	23.75	23.5	2 Drawers	S.Steel	S.Steel	Drawers	None

Models in Blue are approved for foodservice and CALCODE use (meet NSF-7)

SUMMIT Appliance Division
Phone: 718-893-3900

Felix Storch, Inc. 770 Garrison Avenue, Bronx, NY 10474 USA

Fax 718-842-3093

Email: sales@summitmedicalrefrigerators.com

Visit our website at: www.summitmedicalrefrigerators.com

32" HIGH REFRIGERATORS FOR ADA COUNTERS

This page is a small selection of our complete ADA line. See our complete ADA catalog online at www.summitappliance.com

AL650	Under-counter refrigerator-freezer with dual evaporator cooling, five degree (F) freezer and door storage. ADA compliant; manual defrost freezer section and auto-defrost refrigerated section.
AL650L	Same as above with front lock.
AL750	Under-counter all refrigerator with auto-defrost. Reversible door, large shelves. ADA compliant.
AL750L	Same as above with front lock.
FF6L7-AL	All-refrigerator, fully auto-defrost, door storage and front lock. ADA compliant.
FF7L-AL	All-refrigerator, fully auto-defrost with front lock. ADA compliant. Reversible doors, large shelves.
ALF620L	Under-counter, freestanding all-freezer. Manual defrost, reversible door and front lock. ADA compliant.
SCFF55LAL	Frost-free all-freezer, 24 inches wide with fan cooled interior, front lock, 5 c.f. of volume, and reversible door. Built-in capable or freestanding.
FF41AL	Under-counter refrigerator-freezer with automatic defrost (both freezer and refrigerator section) and reversible door. White. ADA compliant.
CP35LLAL	Compact two door refrigerator w/two side locks. Dual evaporator. Zero degree (F) freezer; ADA compliant.



AL650 / AL650L
(at left)
Refrigerator-freezer with dual evaporator cooling. Manual defrost freezer can operate at five degrees F plus automatic defrost refrigerated section. Interior light, door shelves, adjustable shelves, lock (on Model AL650L) and reversible door. Models in black or stainless steel are also available. Designed for lower ADA counters, but fully finished for freestanding use.



AL750 / AL750L
(at left)
All-refrigerator with full automatic defrost. Interior light (on rocker switch), large adjustable shelves, lock (on Model AL750L) and reversible door. Models in black or stainless steel are also available.

FF41-AL (below)
Fully automatic defrost refrigerator-freezer with adjustable shelves, door shelves and a reversible door. Made in North America. Optional wrapped stainless steel door.

OPTIONAL FINISHES FOR MODELS ABOVE

SSTB	Apply a wrapped stainless steel door and stainless steel towel bar handle to any model above except CP35LLAL.
CSS	Apply a complete stainless steel cabinet finish (includes an SSTB door) to any model above except FF41AL or CP35LLAL.
AM (Agion™ anti-microbial steel)	Apply an antimicrobial coating to any SSTB or CSS finish on the models above.



FF6LAL All-refrigerator with automatic defrost, door shelves, interior light, front lock and adjustable shelves.



FF7L-AL
(at left)
All-refrigerator with full automatic defrost and front lock. ETL-S listed meets commercial standards for foodservice use. Shown with optional stainless steel shelves.



ALF620L All-freezer with manual defrost, three interior baskets, front lock capable of -25°C operation.



CP35LLAL Two-door refrigerator with 0 degree (F) freezer. Two side locks.

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
AL650	32	23.625	23.5	5.1	White	White	Reversible	None
AL650L	32	23.625	23.5	5.1	White	White	Reversible	Front
AL750	32	23.625	23.5	5.5	White	White	Reversible	None
AL750L	32	23.625	23.5	5.5	White	White	Reversible	Front
FF6LAL	32	23.625	23.5	5.5	White	White	Reversible	Front
FF7LAL	32	23.625	23.5	5.5	White	White	Reversible	Front
ALF620L	32	23.625	23.5	4.0	White	White	Reversible	Front
SCFF55LAL	32	23.625	23.5	4.0	White	White	Reversible	Front
FF41AL	32	18.75	20	3.6	White	White	Reversible	None
CP35LLAL	32	19.75	20	2.9	White	White	Reversible	2 side

Models in Blue are approved for foodservice and CALCODE use (meet NSF-7)

SUMMIT Appliance Division
Phone: 718-893-3900

Felix Storch, Inc. 770 Garrison Avenue,
Fax 718-842-3093

Bronx, NY 10474 USA
Email: sales@summitmedicalrefrigerators.com

Visit our website at: www.summitmedicalrefrigerators.com

REFRIGERATORS FOR OFFICES AND BREAK ROOMS

24 inch wide under-counter refrigerator-freezers

BI605FF	Built-in, auto-defrost refrigerator-freezer with front-breathing bottom condenser and precision digital thermostat.
BI605BFF	Same as above in black.
BI605	Built-in, auto-defrost refrigerator with front-breathing bottom condenser. White cabinet and door. Manual defrost
BI605B	Same as above in black.
SSVH option	Add a wrapped stainless steel door and pro handle to any BI605
FR option	Add a frame to any BI605 or CT66 to accept custom panels.
CT70	Freestanding, manual defrost refrigerator-freezer with reversible door, crisper and adjustable shelves.
CT66	Freestanding refrigerator-freezer with dual evaporator, reversible door, crisper and adjustable shelves. Manual defrost freezer and auto-defrost refrigerated section
CT66B	Same as above in black with standard glass shelves.
CT67	Freestanding refrigerator-freezer with dual evaporator; reversible door with black frame for panel and glass shelves. White cabinet.

Full size frost-free refrigerator-freezers

CTR21	Two door, frost-free refrigerator-freezer with top freezer and glass shelves. Reversible doors; Capacity - 20.5 c.f.
CTR18	Same as above. Capacity - 18.2 c.f.
CTR15	Same as above. Capacity - 14.8 c.f.
FF1410	Frost-free refrigerator with deluxe interior, glass shelves and reversible doors. Large capacity, but only 26 inches deep
FF1251	Frost-free refrigerator-freezer with deluxe interior, adjustable shelves and reversible doors. 26 inches wide and deep.
FF1062	Frost-free refrigerator-freezer with deluxe interior, adjustable shelves and reversible doors. 24 inches wide.

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
BI605FF	34.5	23.75	25	6.0	White	White	Reversible	None
BI605BFF	34.5	23.75	25	6.0	Black	Black	Reversible	None
BI605	34.5	23.75	25	6.0	White	White	Reversible	None
BI605B	34.5	23.75	25	6.0	Black	Black	Reversible	None
CT70	34	23.75	23.5	6.0	White	White	Reversible	None
CT66	33.25	23.625	23.5	5.1	White	White	Reversible	None
CT66B	33.25	23.625	23.5	5.1	Black	Black	Reversible	None
CT67	33.25	23.625	23.5	5.1	White	White	Reversible	None
FF41	33.5	18.75	21	3.6	White	White	Reversible	None
FF43	33.5	18.75	21	3.6	Black	Black	Reversible	None
FF41SSTB	33.5	18.75	21	3.6	White	S.Steel	RHD/LHD	None
FF43SSTB	33.5	18.75	21	3.6	Black	S.Steel	RHD/LHD	None
CM40	34	18.75	22	3.7	White	White	Reversible	None
S19R	20.25	18.5	20	1.7	White	White	Reversible	None
CTR21	68.25	29.625	31	20.5	White	White	Reversible	None
CTR18	65.375	29.625	30	18.2	White	White	Reversible	None
CTR15	59.5	28	31	14.8	White	White	Reversible	None
FF1410	69.75	26	26	12.6	White	White	Reversible	None
FF1251	65.5	26	26	11.4	White	White	Reversible	None
FF1062	63.5	23.5	24	9.4	White	White	Reversible	None

Compact Refrigerator-freezers

FF41	Under-counter refrigerator-freezer with automatic defrost and reversible door. White finish, reversible door
FF43	Same as above in black finish
FF41SSTB	FF41 with wrapped stainless steel door and pro handle
FF43SSTB	FF43 with wrapped stainless steel door & pro towel bar handle.
CM40	Compact refrigerator-freezer with manual defrost
S19R	Flush back "cube" sized refrigerator-freezer; manual defrost



At left, **BI605** / **BI605FF** interior. Shown in white, also available in black. Built-in 6 c.f. refrigerator-freezer, in manual or full auto-defrost versions.



At right, **BI605SSVH** / **BI605FFSSVH** refrigerator-freezer shown with wrapped stainless steel door and pro handle.



CT70, large capacity under-counter refrigerator-freezer



At left, **FF41**, fully auto-defrost (in both the refrigerator and freezer sections). Shown in white. At right, **FF43SSTB**, same in black but with wrapped stainless steel door & pro handle. Optional anti-microbial finish.



CM40, manual defrost, value priced refrigerator-freezer.



CT66, dual evaporator, freestanding refrigerator-freezer, 24 inches wide. Freezer will keep ice cream frozen! Shown in white, also available in black. (**CT66B**), or in white with front lock (**CT66L**)



CT67, dual evaporator, freestanding refrigerator with five degree (F) freezer, glass shelves and frame to accept custom panels. Reversible door, interior light, door storage and vegetable crisper.

At SUMMIT, we stock a full line of major appliances. If you can't find what you need in this catalog; please call us!



FF1251 interior shown. **FF1410** is similar with 3" extra height.



CTR18 exterior shown. **CTR15** and **CTR21** are similar.



FF1062 interior shown.

SUMMIT Appliance Division Felix Storch, Inc. 770 Garrison Avenue, Bronx, NY 10474 USA
 Phone: 718-893-3900 Fax 718-842-3093 Email: sales@summitmedicalrefrigerators.com
 Visit our website at: www.summitmedicalrefrigerators.com

SPECIALTY MAJOR APPLIANCES

SUMMIT offers a wide array of major appliances for the household, commercial, medical, scientific and hospitality markets. A selected sampling of some that are used by our scientific and medical customers for their residential or break-room or back-office applications are shown below. For our complete product line, please visit our full website: www.summitappliance.com or call our sales department and request our full catalog.

ALL-IN-ONE KITCHENS

C301	30" fully assembled combination kitchen with two electric burners (110V), refrigerator, and full one piece stainless steel top with sink. Storage cabinet with shelf. Faucet included; complete with line cord.
C39	Same features in a 39 inch wide size.
C48	Same in a 48 inch wide size. Includes a larger 24 inch wide deluxe refrigerator-freezer (Model CT67)
C60	Same as C48 in a 60 inch width. Model CT67 refrigerator-freezer is included. Two base cabinets with shelf.

SUMMIT ALL-IN-ONE KITCHENS

4 Sizes, all with a single stamped stainless steel top with sink and solid disk burners (110V) for a no-spill, easy clean surface.



C-39 (39 inch wide) all-in-one kitchen with two electric burners, full stainless steel top, sink (faucet included) and storage cabinet.



C-301 has all the features of C39 in just 30" of width.

ADA WASHERS, DRYERS AND DISHWASHERS

SPW1102ADA	Energy Star front-load washer designed to fit under lower ADA counters. European built.
SPDE1112ADA	Matching 220V dryer for ADA counters.
DW2432ADA	Ultra quiet European built dishwasher with stainless steel interior for ADA counters.
SPWD1160C	Combination washer-dryer in one unit. 110V operation. Convenient for small loads.



C-48 (48 inch wide) all-in-one kitchen with two electric burners, full stainless steel top, sink (faucet included) and 24" wide refrigerator-freezer with frame.



C-60 (60 inch wide) all-in one kitchen with one piece stainless steel top, two burners, sink and 24" wide refrigerator.

MICROWAVE OVENS

SCM850	800 watt all stainless steel (interior and exterior) with rotary dial, and turntable
SM900W	800 watt microwave with rotary turntable, touchpad and interior light in white.
SM900B	Same as above in black.
SM1100W	1000 watt microwave oven with rotary turntable, touchpad and interior light in white.
SM1100B	Same as above in black.

SUMMIT SPW1102ADA and SPDE1112ADA are European designed and built, with stainless steel interiors, all the quality and features of top European brands, and easy to fit 24 inch width and ADA (32") height.



SUMMIT under-counter front-load washer, dryer and combination washer dryer—available in standard or ADA height.



SUMMIT SM900 (white) on left, and SM900B (Black) on right.



SCM-850 has an interior and exterior of stainless steel. Rotary dial is simple to use, and features include a turntable, full handle, and variable power.



SUMMIT DW2432ADA dishwasher is built-in Europe with ultra-quiet design; stainless steel interior, deluxe adjustable racking and exceeds Energy Star guidelines.

MICROWAVE OVEN MODELS SM1100 (not shown) ARE SIMILAR IN APPEARANCE TO SM900

Model	Height (inches)	Width (inches)	Depth (inches)	Capacity (c.f.)	Cabinet Finish	Door Finish	Door Swing	Lock
SCM850	12	21	15	0.8	S.Steel	S.Steel	Left	None
SM900W	12	18	14	0.7	White	White	Left	None
SM900B	12	18	14	0.7	Black	Black	Left	None
SM1100W	12	21	16	1.0	White	White	Left	None
SM1100B	12	21	16	1.0	Black	Black	Left	None
C301	39.5	30	24	3.6	White	White	Sink and cabinet on right	None
C39	39	39	24	3.6	White	White	Sink and cabinet on left	None
C48	39	48	24	5.1	White	White	Sink and cabinet on left	None
C60	39	59.5	24	5.1	White	White	Sink on right Two cabinets	None
SPW1102ADA	32.25	24	24	12 lbs.	White	White	Reversible	None
SPDE1112ADA	32.25	24	24	12 lbs.	White	White	Reversible	None
SPWD1160C	33.5	24	24	11 lbs.	White	White	RHD	None
DW2432ADA	32	24	24	12 settings	White	White	Downward	None

SUMMIT Appliance Division Felix Storch, Inc. 770 Garrison Avenue, Bronx, NY 10474 USA
 Phone: 718-893-3900 Fax 718-842-3093 Email: sales@summitmedicalrefrigerators.com
 Visit our website at: www.summitmedicalrefrigerators.com

OPTIONS FOR SUMMIT REFRIGERATORS AND FREEZERS

KEYPAD LOCK	Install a keypad (keyless) lock on most front-opening refrigerators and freezers, and program your own codes. Battery powered. Emergency override on battery failure with codes and one 9V battery.
AC Keypad	Keypad lock powered from the appliance's line cord. No batteries needed. Emergency override in case of power failure with codes and one 9V battery. 10 user-defined codes plus 1 master.
ALARM	Install high temperature warning alarm on selected refrigerators or freezers. Displays interior temperature and saves min. and max.
BI (Built-in)	Modify selected units for built-in applications (BI suffix) includes base with 4 large level legs. Available on base refrigerators CT66, CT67, FF6, FF7 and SCR600; and base freezer FS62. Standard on SCFF55, drawer units and models beginning with "BI".
CASTERS	Add 6 inch heavy duty casters (2 locking & 2 standard) to selected models.
DOLLY	Custom dolly (ships fully assembled) with locking casters for 24 inch models. Adjustable length and depth
DT (Digital thermostat)	Install an electronic thermostat on most models. Choice of Celsius or Fahrenheit models (F is standard). Allows user to accurately set internal temperature (a 2 to 3 degree variance above and below the set-point is normal during on/off cycles).
FC (Fan cooling)	Add an internal air circulation fan to selected models. Available on FF6, FF7, SCR600, SCR310L, FF510L, FF520L, FF560L, FFAR2L, FF28L and FF29L models. Call our sales dept. for availability on other models.
FR (Frame)	Add a stainless steel frame to selected under-counter models to accept custom panels. Available on base models FF6, FF7, CT66, CT67, FS62, SCFF55 and BI605. Standard on some built-in models.
HG (Hospital grade Plug)	Install a U.L. approved hospital grade line cord (green dot) to any model in our line.
L (LOCK)	Install a side mounted key lock on any model without a standard lock. Some models require two locks (see below)
LL (2 Locks)	Install two side mounted locks on any two door model.
LLF (Front locks for 2 door models)	Mount a front lock on models with two-doors. Available on selected models only (Call our sales department for availability).
LHD	Door reversal (on reversible door models) to left hand door swing (As you face refrigerator, hinges will be on left side). RHD is standard on all models.
TH (Thermometer)	Mount solar powered external readout thermometer on most models. Probe measures air temperature inside appliance.
TT (NIST Traceable Thermometer)	Mount NIST traceable precision digital external thermometer (meets most Health Dept. specs.) Probe is mounted in liquid to accurately measure temperature of contents. Professionally installed.
AM (Agion™ Anti-Microbial coating)	Stainless steel cabinets or wrapped stainless steel doors can be constructed of genuine AGION™ steel (add suffix-AM). Available on selected models only. Handles on treated models are also Agion™.
SS Shelves (Stainless steel shelves)	Add a set of stainless steel shelves to replace standard glass or wire shelves. Available on base models FF6, FF7, SCR600, CT66, CT67, FFAR10, SCFF55, BI540, AL650 and AL750.
LEGS (Flanged) LEGS (Seismic)	Add 6 inch legs to selected appliances. Choose from flanged (to attach to floor) or seismic (to attach to rods).
COLORS	Add a wrapped door in a choice of 7 colors to accent your décor. Available on Models FF6, FF7, CT66, CT67, FS62 and SCFF55. Choice of red, blue, cream, black, silver vein, gold vein and copper.
IB (Ice Bank)	Add ice-bank holding plates to any chest freezer in our line.



Keypad lock assemblies (Suffix **KEYPAD**) are available in white or black to match your appliance, and can be battery or AC powered (Suffix **AC KEYPAD**)



SUMMIT NIST traceable thermometer (Suffix **TT**), at left or NIST traceable alarm, (Suffix **ALARM**) at right, meet many health department and regulatory agency requirements. Both can be professionally installed on any SUMMIT appliance (standard on most 'MED' models).



Digital thermostats (suffix **DT**) can be installed on many SUMMIT models for more precise operation. Displays the interior temperature and the set-point is displayed with one touch of a button. Installed in an all-metal housing.

Adjustable dolly (Suffix **DOLLY**) fits most models with footprints of 24 inches wide by 24 inches deep or under. Shipped in a separate box with your appliance.



At left, our exclusive side locks, Suffix 'L', in chrome or white to match your appliance, fit any refrigerator. Our exclusive two-door lock, above (Suffix **LLF**) fit selected two door models, including all CTR series.



Blue door shown with white handle on FF7



Red door shown with white handle on CT66



Ice-bank installed in a chest freezer. (Illustrated in VT175IB)



FC Air circulation fan (shown on SCR600L)



Casters, at left, (Suffix **CASTERS**), fit most 24 inch wide counter height models, and many other models. Thermometer, above (Suffix **TH**) can be installed on any SUMMIT model (on two-door models be sure to specify which compartment, or order two units installed (Suffix **THTH**))

SUMMIT Appliance Division
Phone: 718-893-3900

Felix Storch, Inc. 770 Garrison Avenue,
Fax 718-842-3093

Bronx, NY 10474 USA
Email: sales@summitmedicalrefrigerators.com

Visit our website at: www.summitmedicalrefrigerators.com