



## 3M™ Overhead Projector Model 2000

Designed for professionals on the go, this totally portable projector makes an excellent travelling companion. Big on features, the 3M™ Overhead Projector Model 2000 delivers 1,600 lumens of light for crisp resolution and superior clarity. Weighing only 14 pounds, this lightweight unit packs plenty of heavyweight performance, and can be easily folded into its own carrying case for instant portability. Built-in lamp storage provides a place for an extra lamp for uninterrupted presentations, and ultra-quiet convection cooling eliminates distracting fan noise. Affordable performance and built-in quality make the 3M overhead projector Model 2000 the ideal portable solution for mobile users.

### KEY FEATURES

- Compact and self-contained so it can be easily folded into its own carrying case
- Easy to carry as a briefcase, and compact enough to fit in a car trunk or under the seat of an airplane
- Optical stage constructed with a hard coated finish that resists scratching and reduces the chance of damage during ordinary use
- Built-in lamp storage space
- Made from a durable, scuff-resistant material designed to retain its good looks while standing up to handling and storage
- Ultra quiet convection cooling eliminates fan noise that could distract from your presentation
- Convenient carry handle
- One-year manufacturer's warranty

### TECHNICAL SPECIFICATIONS

#### Optical Performance

- Lens: 11.5" (293 mm) singlet
- Illumination (typical): 1,600 lumens
- Projection stage: 10.5" x 10.5" (267 mm x 267 mm)

#### Lamp Description

- Lamp changer: No
- Type: EVW
- Life: 50 hours
- Voltage: 82 volts
- Watts: 250 watts

#### Physical Characteristics

- Height (top of head): 21.5" (540 mm)
- Base height: 5" (127 mm)
- Width: 13" (330mm)
- Length: 19" (482 mm)
- Weight: 14 lbs. (6.4kg.)

#### Electrical Requirements

- Voltage: 120V AC, 60 Hz
- Power cord length: 10' (3 m)
- Agency approval: UL/CUL
- International models available

#### Mechanical

- Thermal protection circuit: Cuts power to the lamp if the projector exceeds safe operating temperature

#### Order Number:

78-9236-3732-2

Specification subject to change

1-800-328-1371

[www.3M.com/meetings](http://www.3M.com/meetings)

# 3M

**3M Visual Systems Division**  
Building A145-5N-01  
6801 River Place Blvd.  
Austin, TX 78726-9000

**3M Canada**  
P.O. Box 5757  
London, Ontario, Canada  
N6A 4T1

**3M Mexico, S.A. de C.V.**  
Apartado Postal 14-139  
Mexico, D.F. 07070  
Mexico



*Recycled paper,  
40% pre-consumer,  
10% post-consumer*

Litho in U.S.A. © 3M 1997  
78-6970-5611-3 (012715.0)LP