

Every effort has been made to ensure the accuracy of the information contained in this Product Guide, but the company accepts no liability for any errors or omissions.

Unless previously agreed in writing, all transactions are subject to our standard Terms and Conditions of sale, available on request or from our website, at www.status.co.uk

52-715-2170-10

www.status.co.uk

## Welcome

### to the latest Status Instruments Product Guide

Here at Status we've been designing, manufacturing and supplying top-quality process instrumentation for over 40 years - and in that time, we have acquired a following of loyal customers, who return to us year after year, and have come to appreciate our ongoing promise - that what goes into our products is **inspiration**, **dedication and application** – and what comes out is **performance**, **reliability and value**.

### **Quality counts**

Quality has always been a priority for us at every level, and we operate a quality system approved to BS EN ISO9001:2015.

Our products also comply with the following accreditations:















### Where you'll find us working





**Automation** 









**Chemical** 



Construction



Energy



Food and

**Beverage** 



**Materials** 

Handling





**Automotive** 



Oil, Gas and

**Petrochemical** 



**Pharmaceutical** 



Water and Waste

### **Calibration Service**

We recommend that all instrumentation should be re-calibrated every 12 months. Please contact us to discuss this further, or visit www.status.co.uk for more details.

### **Ordering**

Please place your order directly with the distributor who sent you this Guide. If you acquired this Guide independently, please contact Status directly, and we will be able to help you.

Telephone	+44 (0) 1684 296818
Website	www.status.co.uk
Sales	sales@status.co.uk
Technical support	support@status.co.uk

## **Contents**

## How to use this Guide

This Product Guide is divided into sections, as listed opposite.

Each section shows what the range has to offer, and the products are then listed individually with their relevant specification details beneath.

If you can't find exactly what you're looking for, or you require something specific that is not listed, please call us and we can discuss custom designs and tailored solutions.

**Please note:** some sections have been re-ordered for 2024.

	Product group	Page	Typical warranty
	Signal conditioning	4	5 years
	In-head transmitters	12	5 years
	In-head transmitters, analogue	16	5 years
	Rail-mounted transmitters	18	5 years
	In-head and DIN-rail transmitters, voltage output	20	5 years
9	Temperature transmitters and loop-powered displays	22	5 years
	Temperature transmitters - other packages	24	5 years
	Field-mounted indicators and switches - pressure	<b>26</b>	5 years
	Probe assemblies	28	1 year on sensor
9	Humidity and temperature transmitters, indicators and switches	30	5 years 1 year on sensor
	Panel meters	32	5 years
	Wireless transmitters	34	1 year 1 year on sensor
	Field-mounted indicators and switches - pressure	36	5 years
	Pressure transmitters	38	1 year
10			

Versatility of displays

Free apps and software

Solution overview

**Legacy products** 

**The Application Guide** 



## **Signal conditioning**



RTD, thermocouple, potentiometer, resistance or mV input. active / passive mA or voltage output.




mA / voltage conditioner with active / passive mA or voltage input and outputs.




Load cell input signal conditioner with active / passive mA or voltage output.



Dual inputs, frequency and pulse counter. Active / passive mA or voltage and relay output.



	Vs Q
V	
	<i>§</i>
mA	Q ±v



N/A


N/A N/A N/A

N/A

N/A N/A N/A N/A

Yes - 4-wire

EN BS 61326



_	
Z	
_	

Pt100	
RTD other types	
Resistance	
Potentiometer	
Thermocouple	

Inermocouple			
Voltage			
Current			
Frequency			
Pulse counter			

162	
(10 to 10,500) Ω	
1 k $\Omega$ to 100 k $\Omega$ auto sense	
K, J, N, E, T, R, S, L, U, B, C(W5), D(W3), G(W)	
(-100 to +200) mV	
N/A	Ī
N/A	
N/A	
N/A	Ī

N/A
N/A
N/A
N/A
N/A
(-50 to +50) VDC
(-50 to +50) mA (active / passive)
N/A
N/A
N/A

N/A
N/A
N/A
N/A
N/A
N/A
N/A
0.01 Hz to 65 kHz
Yes
N/A

See datasheet for
full details and specific
output combinations

Load cell

See datasheet for	
full details and specific	
output combinations	

mA - active / passive
Voltage
Bi-polar voltage

mA - active / passive
Voltage
Bi-polar voltage

mA - active / passive
Voltage
Bi-polar voltage

mA - active / passive	
Voltage	
Bi-polar voltage	
Pulse (closed contact relay)	

_	U
$\bigcirc$	
•	
	IS

Sulation				
Output z	ero/s	pan	alig	jn

Outp	ut ze	ero/	span	alig	nme	nt t	o in	put		
User	offse	et								

ser linearisation	
emote reset	
mbient operating	
urar cupply	

163
Yes
Yes - resistance / potentiometer / mV
N/A
(-30 to +70) °C
Universal, (10 to 48) VDC
and (10 to 32) VAC
Yes - output
N/A
PC
N/A
N/A
17 5 mm

EN BS 61326

Yes
Yes
N/A
Yes
N/A
(-30 to +70) °C
Universal, (10 to 48) VDC and (10 to 32) VAC
Yes - input and output
N/A
PC
N/A
Flow formulae
17.5 mm

EN BS 61326

Yes	Yes
Yes - push-button	Yes
Yes - tare	N/A
Yes	K Factor mete
Tare	Yes
(-30 to +70) °C	(-30 to +70)
Universal, (10 to 48) VDC and (10 to 32) VAC	Universal, (10 and (10 to 32
Yes - output	Yes - output
Yes	Yes
PC	PC
N/A	Yes
N/A	Yes
17.5 mm	17.5 mm

Yes
Yes
N/A
K Factor meter correction
Yes
(-30 to +70) °C
Universal, (10 to 48) VDC
and (10 to 32) VAC
Yes - output
Yes
PC
Yes
Yes
17.5 mm

EN BS 61326

# GENERAL

OSEL IIII	carisation	
Remote	reset	
Ambien	t operating	
Power s	upply	
Loop po	wer supply	
Sensor e	excitation	
Configu	ration	
Totalise		
Maths fo	unctions	
Width		

:IV	C.	/ U	K	
		۰		٠,

## **Signal conditioning**



RTD, thermocouple, passive mA, mV input, 3-wire voltage output.



RTD, thermocouple, passive mA, mV input, with 2 change-over relay outputs.



RTD, potentiometer, resistance input, with 2 change-over relay outputs.

Yes

N/A N/A

N/A

N/A

N/A

(10 to 10,500) Ω


1k  $\Omega$  to 100 k $\Omega$  auto sense




Loop-powered input, with 2 change-over relay outputs.

mA	+
ţ Ţ Ţ	
mV –	
Yes	

Yes
N/A
N/A
N/A
K, J, N, E, T, R, S
(-10 to +75) mV
(–10 to +25) mA Passive
N/A
N/A
N/A



Yes
N/A
N/A
N/A
K, J, N, E, T, R, S
(-10 to +75) mV
(-10 to +25) mA Passive
N/A
N/A
N/A



1	N/A
1	N/A
1	N/A
(	(4 to 20) mA Passive
1	N/A
1	N/A
-	N/A

INPUT

OUTPUT See datasheet for full details and specific output combinations

Pt100

**RTD** other types

**Potentiometer** 

Thermocouple

Resistance

Voltage

Current

Frequency

Load cell

**Pulse counter** 

Voltage - 3 wire

EN BS 61326

2 x (250 VAC @	2 1A) C/O relay	

N/A
N/A
N/A
N/A
N/A
(4 to 20) mA Passive
N/A
N/A
N/A

2 x (250 VAC @ 1A) C/O relay

GENERAL

Isolation Output zero/span alignment to input User offset **User linearisation** Remote reset **Ambient operating Power supply Loop power supply Sensor excitation** Configuration **Totalise Maths functions** Width

V	/es
Y	es es
١	J/A
١	J/A
١	I/A
(-	−30 to +70) °C
(	15 to 28) VDC
١	I/A
N	I/A
Р	PC
١	I/A
١	I/A
1	7.5 mm

Yes
N/A
N/A
N/A
N/A
(-30 to +70) °C
24 VDC
N/A
N/A
PC
N/A
N/A
17.5 mm

Y	es - relays
Ν	/A
Ν	/A
Ye	es - resistance / potentiometer
Ν	/A
(-	-30 to +70) °C
U	niversal, (10 to 48) VDC
а	nd (10 to 32) VAC
Ν	/A
Ν	/A
Р	С
Ν	/A
Ν	/A
1	7.5 mm

Yes - relays
N/A
N/A
Yes
N/A
(-30 to +70) °C
(4 to 20) mA loop
N/A
N/A
PC
N/A
Yes - flow formula
17.5 mm

**EMC / UKCA** 

EN BS 61326

EN BS 61326

## **Signal conditioning**




Universal signal conditioner with current or voltage, and 2 change-over relay outputs.




Dual-channel RTD, thermocouple, potentiometer, mV input with active / passive mA or voltage outputs.



Dual-channel mA / voltage conditioner with active / passive mA or voltage input and outputs.



Single channel



### **TYPE**

### Pt100

### **RTD other types**

Resistance **Potentiometer** 

Thermocouple

Voltage

Current

Frequency

**Pulse Counter** 

**Load Cell** 

See datasheet for full details and specific

Yes
N/A
(20 to 400) Ω
1 kΩ to 1 MΩ
K, J, N, E, T, R, S, L, U, B, C, D, G
$\pm$ 50 mV, $\pm$ 200 mV, $\pm$ 1 V, $\pm$ 10 V
±30 mA (active / passive)
N/A
N/A
N/A

Yes
Yes
N/A
1 $k\Omega$ to 100 $k\Omega$ auto sense
K, J, N, E, T, R, S, L, U, B, C, D, G
N/A

N/A
N/A
N/A
N/A
N/A
±50 VDC
±50 mA (active / passive)
N/A
N/A
N/A

**Dual channel** 

output combinations

Vo	ltage

EN BS 61326

Yes (see website for more details)

mA - active / passive

2 x (250 VAC @ 1A) C/O Relay

mA - active /	passive
Voltage	

EN BS 61326

N/A

Optional programmable maths outputs to include average, sum and splitter functions

mA - active / passive	
Voltage	
Optional programmable maths outputs to	

# OUTPUT

GENERAL

INPUT

**Isolation** 

Output zero/span alignment to input

**User offset** 

**User linearisation** 

Remote reset

**Ambient operating** 

**Power supply** 

Loop power supply **Sensor excitation** 

Configuration

Totalise

**Maths functions** 

Width

**EMC / UKCA** 

SIL

Yes
Yes - push-button
N/A
N/A
N/A
(-30 to +70) °C
Universal, (22 to 300) VDC and (24 to 250) VAC
Input and output
Yes - mA loop
PC - push-button
N/A
N/A
22 mm

Yes N/A
N/A
Yes
Yes
N/A
(-30 to +70) °C
Universal, (22 to 300) VDC and (24 to 250) VAC
Output, both channels
Yes - both channels
PC / DIP switch - pre-set ranges
N/A
Yes
22 mm

include average, sum and splitter functions
Yes
N/A
N/A
Yes
N/A
(-30 to +70) °C
Universal, (22 to 300) VDC and (24 to 250) VAC
Input and output, both channels
Yes - both channels
PC
N/A
Yes
22 mm
EN BS 61326

N/A

## Signal conditioning



(4 to 20) mA current loop isolator.



Converts DC voltage to an isolated (4 to 20) mA signal.


Isolating current loop booster.




(4 to 20) mA current loop isolator.





Isolating current loop splitter.






NB: may be supplied in previous-style housing







<b>—</b>
<b></b>
₾
Z
_

Range

Type

(4 to 20) mA passive

(4 to 20) mA

(4 to 20) mA active

DC voltage

(4 to 20) mA passive

Any between (-10 to 100) VDC

(4 to 20) mA passive

(4 to 20) mA

2 x (4 to 20) mA passive

(4 to 20) mA

(4 to 20) mA passive

(4 to 20) mA

OUTPUT

**Volt drop Maximum loop supply** Isolation

**Maximum load** 

**Power supply** 

**Ambient operating** temperature

Width

Input 5.0 VDC typical Input 35 VDC 500 VDC Output 500 Ω Input loop  $(0 \text{ to } +70)^{\circ}\text{C}$ 12.5 mm

N/A Output 30 VDC 500 VDC N/A Output loop  $(0 \text{ to } +70)^{\circ}\text{C}$ 12.5 mm

(4 to 20) mA passive

2 x 2-wire (4 to 20) mA passive

Input and output 2.7 VDC

2 x 2-wire (4 to 20) mA passive

Input and outputs 5.0 VDC

Input and output 32 VDC

500 VDC

GENERAL

**APPROVALS** 

**EMC / UKCA** 

EN BS 61326

EN BS 61326

Input and output 2.7 VDC Input and output 35 VDC 500 VDC Output 1200 Ω All loops  $(0 \text{ to } +70)^{\circ}\text{C}$ 12.5 mm

Input and output 35 VDC 500 VDC Output 1200 Ω All loops  $(0 \text{ to } +70)^{\circ}\text{C}$ 12.5 mm

Outputs 1200 Ω All loops  $(0 \text{ to } +70) ^{\circ}\text{C}$ 12.5 mm

EN BS 61326

EN BS 61326

## **In-head** transmitters

(4 to 20) mA output



**203P** 

In-head

Pt100 transmitter; push-button configuration.



Thermocouple transmitter; push-button configuration.



Potentiometer transmitter; push-button configuration.



**206P** 

Pt100 transmitter;

PC configuration.


In-head





Thermocouple transmitter; PC configuration.




Thermistor transmitter; PC / push-button









In-head







<b>IPUT</b>	
=	

**TYPE** 


Pt100
Other RTD sensors
Resistance
Potentiometer
Thermocouple type
<i>V</i> oltage
Current
Thermistor

Yes - 2, 3 wire
N/A
N/A
N/A
N/A
N/A
N/A
N/A

(4 to 20) mA

In-head
N/A
N/A
N/A
N/A
K, J, N, E, T, R, S
(-10 to +70) mV
N/A
N/A

(4 to 20) mA



Yes - 2, 3 wire
N/A
N/A
N/A
N/A
N/A
N/A
N/A

(4 to 20) mA

In-head	In-head
N/A N/A	N/A Yes - Pt500, Pt1000
V/A	N/A
V/A	N/A
ζ, J, N, E, T, R, S	N/A
(-10 to +70) mV	N/A
V/A	N/A
N/A	Yes



**APPROVALS** 

	Isolation
_	<b>Custom linearisation</b>
7	Output zero/span alignment to input
2	User offset
<del>빌</del>	Display
ENERAL	Ambient operating
ש	Power supply
	Configuration

Push-button 43 mm dia.
43 mm dia.
N/A
N/A
N/A
Yes
EN BS 61326

N/A	Yes
N/A	N/A
Yes - push-button	Yes - push-button
N/A	N/A
N/A	N/A
(-40 to +85) °C	(-40 to +85) °C
(10 to 30) VDC	(10 to 30) VDC
Push-button	Push-button
43 mm dia.	43 mm dia.
N/A	N/A
N/A	N/A
N/A	N/A

Yes

EN BS 61326

(	(4 to 20) mA
N	/A
N	/A
Ye	es - push-button
N	/A
Ν	/A
(-	-40 to +85) °C
(1	10 to 30) VDC
Р	ush-button
4	3 mm dia.

N/A

N/A

N/A

N/A

EN BS 61326

N/A
N/A
N/A
Yes
N/A
(-40 to +85) °C
(10 to 30) VDC
PC
43 mm dia.
N/A
N/A
N/A

Yes

(-10 to +70) mV	N/A
N/A	N/A
N/A	Yes
(4 to 20) mA	(4 to 20) mA
Yes	N/A
N/A	N/A
N/A	Yes - push-button
Yes	N/A
N/A	N/A
(-40 to +85) °C	(-40 to +85) °C
(10 to 30) VDC	(10 to 30) VDC
PC	Push-button / PC
43 mm dia.	43 mm dia.
N/A	N/A
N/A	N/A
N/A	N/A
Yes	N/A
EN BS 61326	EN BS 61326

## **In-head** transmitters

(4 to 20) mA output

TTR 200





RTD, potentiometer, resistance transmitter; PC configuration. **IS-approved version: TTR200X.**  TTC 200

TTC

**200X** 

In-head

N/A

N/A

N/A

N/A

N/A

N/A

custom

(-100 to +200) mV



SEM **210** MKII



**SEM 310** MKII



TTR **200X** 




Thermcocouple, mV transmitter; PC configuration. **IS-approved version: TTC200X.**  SEM **210X** MKII

RTD, thermocouple, potentiometer, resistance, mV transmitter; PC configuration. **IS-approved version: SEM210X.** 



HART 5,6,7 compatible RTD, thermocouple, potentiometer, resistance, mV transmitter; PC configuration. **IS-approved version: SEM310X.** 



### In-head

Very 2 2 anim
Yes - 2, 3 wire
Yes - 2, 3 wire
(10 to 100 k) Ω
1 k $\Omega$ to 100 k $\Omega$ auto sense
N/A
N/A
N/A
N/A



In-head, dual input

1 k $\Omega$  to 100 k $\Omega$  auto sense

(-1000 to +1000) mV

N/A

N/A

K, J, N, E, T, R, S, L, U, B, C, D, G

Yes - 2, 3, 4 wire

Yes - 2, 3, 4 wire

(10 to 10,500) Ω

### In-head, dual input

Yes - 2, 3, 4 wire
Yes - 2, 3, 4 wire
(10 to 10,500) Ω
1 k $\Omega$ to 100 k $\Omega$ auto sense
K, J, N, E, T, R, S, L, U, B, C, D, G
custom
(-1000 to +1000) mV
N/A
N/A

OUTPUT

**GENERAL** 

**APPROVALS** 

INPUT

**TYPE** 

Pt100

Resistance

Voltage

Current

Thermistor

Potentiometer Thermocouple type

Other RTD sensors

Isolation	
Custom linearisation	
Output zero/span alignment to input	
User offset	
Display	
Ambient operating	
Power supply	
Configuration	
Width / diameter	

ATEX		
UKEX		
IEC Ex		
Vibration test		
EMC / UKCA		
SIL		

Yes - 2	2, 3 wire
Yes - 2	2, 3 wire
(10 to	100 k) Ω
1 kΩ t	o 100 kΩ auto sense
N/A	
N/A	
N/A	
N/A	

(4 to 20) mA	
No	

No
Resistance / potentiometer
Yes
Yes
N/A
(-40 to +85) °C
(10 to 30) VDC
PC
43 mm dia.
Yes
Voc

Yes	
Yes	
Yes	
Yes	
EN BS 61326	
N/A	

(4 to 20) mA		

K, J, N, E, T, R, S, L, U, B, C, D, G

Yes
Yes - mV
Yes
Yes
N/A
(-40 to +85) °C
(10 to 30) VDC
PC
43 mm dia.
Yes
Vaa

45 IIIII dia.
Yes
Yes
Yes
Yes
EN BS 61326
N/A

## (4 to 20) mA

Yes
Yes
Yes
Yes
N/A
(-40 to +85) °C
(10 to 30) VDC
PC
44 mm dia.

44 IIIII Uld.
Yes
Yes
Yes
Yes
EN BS 61326
Yes (see website for more details)

(4 to 20) mA HART	
Yes	
Yes	

Yes
Yes
Yes
Yes
N/A
(-40 to +85) °C
(10 to 30) VDC
PC and HART configurator
44 mm dia.

Yes
Yes
Yes
Yes
EN BS 61326
Yes (see website for more details)

## **In-head transmitters,** analogue

(4 to 20) mA output

for applications that require a rapid response



High-accuracy analogue (4 to 20) mA Pt100 transmitter.




High-accuracy analogue (4 to 20) mA thermocouple transmitter.



Analogue (4 to 20) mA Pt100 transmitter.



Analogue (4 to 20) mA thermocouple transmitter.



7	ľV	P	F

Pt100

Pt100 difference

Resistance

**Potentiometer** 

Thermocouple type

Voltage




### In-head

N/A N/A N/A N/A K, J, T, R, S

### In-head

Yes - 2, 3 wire N/A N/A N/A N/A N/A



### In-head

N/A N/A N/A N/A K, J, T (-10 to +70) mV



INPUT

Output zero/span alignment to input

**User offset** 

**Display** 

**Ambient operating** 

**Power supply** 

Configuration

Width / diameter

GENERAL

APPROVALS

**ATEX** 

**EMC / UKCA** 

(4 to 20) mA

In-head

Option D

Option Z

Option W

N/A

N/A

Yes - 2, 3 wire

Yes - potentiometer

N/A N/A

 $(0 \text{ to } +70)^{\circ}\text{C}$ 

(10 to 45) VDC

Factory-set 53 mm dia.

EN BS 61326

(4 to 20) mA

N/A

Yes - potentiometer N/A

N/A  $(0 \text{ to } +70)^{\circ}\text{C}$ 

(10 to 45) VDC Factory-set

53 mm dia.

Yes EN BS 61326 (4 to 20) mA

Yes - potentiometer

N/A  $(0 \text{ to } +70)^{\circ}C$ 

N/A

(10 to 30) VDC

Solder link / potentiometer 43 mm dia.

N/A

EN BS 61326

(4 to 20) mA

Yes - potentiometer

N/A N/A

(0 to +70) °C

(10 to 30) VDC

Solder link / potentiometer

43 mm dia.

N/A

## **Rail-mounted** transmitters



Pt100 transmitter; PC configuration.



Thermocouple transmitter; PC configuration.



Thermistor transmitter; PC configuration.



RTD, thermocouple, potentiometer, resistance, mV transmitter; PC configuration.

**Dual input** 




HART 5,6,7 compatible RTD, thermocouple, potentiometer, resistance, mV transmitter; PC configuration.




IS-approved.




RTD, potentiometer, resistance Thermcocouple transmitter; transmitter; PC configuration. PC configuration. IS-approved.



Single channel



Single channel



**Dual input** 

Single or dual channel

(4 to 20) mA


Yes

Yes

Yes

N/A

EN BS 61326



Single	or	dual	channel	

_	
5	
<b>T</b>	
Z	

Pt100	
Other RTD se	nsors
Resistance	
Potentiomet	er
Thermocoup	le type
3.7 Le	
Voltage	
Current	

**TYPE** 

t100	Yes - 2, 3 wire
ther RTD sensors	Yes
esistance	N/A
otentiometer	N/A
hermocouple type	N/A
oltage	N/A
urrent	N/A
hermistor	N/A

N/A

N/A

N/A

N/A

EN BS 61326

N/A
N/A
N/A
N/A
K, J, N, E, T, R, S, L, U, B, C, D, G
N/A
N/A
N/A

Yes - 2, 3, 4 wire
Yes - 2, 3, 4 wire
(10 to 10,500) Ω
1 k $\Omega$ to 100 k $\Omega$ auto sense
K, J, N, E, T, R, S, L, U, B, C, D, G
custom
(-1000 to +1000) mV
N/A
N/A

Yes - 2, 3, 4 wire
Yes - 2, 3, 4 wire
(10 to 10,500) Ω
1 kΩ to 100 kΩ auto sense
K, J, N, E, T, R, S, L, U, B, C, D, G
custom
(-1000 to +1000) mV
N/A
N/A

Yes - 2, 3 wire	N/A
Yes - 2, 3 wire	N/A
N/A	N/A
Yes	N/A
N/A	K, J, N,
N/A	(-100
N/A	N/A
N/A	N/A

Single of dual chainlei
N/A
N/A
N/A
N/A
K, J, N, E, T, R, S, L, U, B, C, D, G
(-100 to +200) mV
N/A
N/A



	Isolation
	<b>Custom linearisation</b>
1	Output zero/span
П 5	alignment to input
	User offset
	Ambient operating

Width	
ATEX	
UKEX	
IEC Ex	
EMC / UKCA	
SIL	

**Power supply** Configuration

(4 to 20) mA	
N/A	
N/A	
Yes	
Yes	
(-30 to +70) °C	
(10 to 30) VDC	
PC	
12.5 mm	

Yes
N/A
Yes
Yes
(-30 to +70) °C
(10 to 30) VDC
PC
12.5 mm
N/A
N/A

N/A

N/A

EN BS 61326

(4 to 20) mA

N/A
N/A
Yes
Yes
(-30 to +70) °C
(10 to 30) VDC
PC
12.5 mm
21/2
N/A
N/A
N/A

EN BS 61326

N/A

(4 to 20) mA

(4 to 20) mA
· ·
Yes
Yes
Yes
Yes
(-30 to +70) °C
(10 to 30) VDC
PC
17.5 mm

, 65
Yes
Yes
(-30 to +70) °C
(10 to 30) VDC
PC
17.5 mm
N/A
N/A
N/A
EN BS 61326
Yes (see website for more details)

(4 to 20) mA HART
Yes
Yes
Yes
Yes
(-30 to +70) °C
(10 to 30) VDC
PC / HART configurator
17.5 mm

(10 to 50) 10 C
PC / HART configurator
17.5 mm
N/A
N/A
N/A
EN BS 61326
Yes (see website for more deta

N/A
N/A
N/A
N/A
K, J, N, E, T, R, S, L, U, B, C, D, G
(-100 to +200) mV
N/A
N/A

(4 to	20)	mΑ

N/A	N/A
Yes - resistance / potentiometer	Yes
Yes	Yes
Yes	Yes
(-30 to +70) °C	(-30 to +70) °C
(10 to 30) VDC	(10 to 30) VDC
PC	PC
22 mm	22 mm
1.4	

**APPROVALS** 

## **In-head and DIN-rail** temperature transmitters

**Voltage output** 



Pt100 transmitter; PC configuration.




Pt100 transmitter; PC configuration.




Thermistor transmitter; PC / push-button configuration.





Thermistor transmitter; PC configuration.



		Vo Vs
	Ę	<u></u>
In-head	In head	







$\vdash$
$\supset$
₾
Z
_

TYPE	
Pt100	
Other RTD sensors	
Resistance	
Potentiometer	
Thermocouple type	
Voltage	
Current	
Thermistor	

Yes - 2, 3 wire
N/A

Voltage (0 to 10) V

EN BS 61326

Single Channel	
Yes - 2, 3 wire	
Yes	
N/A	

Voltage (0 to 10) V

III IICau	Siligle Chaillei
N/A	N/A
Yes - Pt1000, Pt500	Yes - Pt1000, Pt500
N/A	N/A
Yes	Yes



GENERAL

Custom linearisation	
Output zero/span alignment to input	
User offset	
Display	
Ambient operating	
Power supply	
Configuration	
Width / diameter	

١	N/A
١	N/A
١	N/A
١	Yes
1	N/A
(	(–40 to +85) °C
(	(15 to 30) VDC
F	PC
4	43 mm dia.
١	N/A
١	V/A
1	V/A
1	V/A

· coage (c as ve) ·
N/A
N/A
Yes
Yes
N/A
(-30 to +70) °C
(15 to 30) VDC
PC
12.5 mm
N/A
N/A
N/A
N/A
EN BS 61326

	N/A
_	N/A
	N/A
	Yes
	N/A
	(-40 to +85) °C
	(15 to 30) VDC
	PC
	43 mm dia.
	N/A
	N/A
	N/A
	N/A
	EN BS 61326

Voltage (0 to 10) V

Single channel
N/A
Yes - Pt1000, Pt500
N/A
Yes

Voltage (0 to 10) V

N/A	
N/A	
Yes	
Yes	
N/A	
(-30 to +70) °C	
(15 to 30) VDC	
PC	
12 5 mm	

N/A
N/A
N/A
N/A
EN BS 61326

UKEX **IEC Ex** 

**Vibration test** 

EMC / UKCA

## **Temperature** transmitters and loop-powered displays

DM650LP could be used with in-head transmitters or an existing loop.

Please also see DM720 for compact panel-mount option (see page 34).

Mechanical

Thermocouple

Linearisation/offset

**Ambient operating** 

**Environmental rating** 

**Power supply** 

Configuration

**Battery life** 

**Enclosure** 

Pt100

Current **Voltage** 




(4 to 20) mA loop-powered LCD process indicator with relay and

USB



(4 to 20) mA loop-powered LCD process indicator with relay and datalogging, and optional battery datalogging, and optional battery



Sensor / surface mount

### Sensor / surface mount

N/A	N/A
N/A	N/A
N/A	N/A
N/A	N/A
(4 to 20) mA loop	(4 to 20) mA loop
N/A	N/A
Both	Both


INPUT

Display	
Relay	
Oata download	
Custom messaging	
Patalogging	
Max / min	

Pressure and media temperature **Humidity and media temperature** 

4	
~	
뿌	
Ū	

**APPROVALS EMC / UKCA ATEX** 



6-digit LCD (7.9 mm)	6-digit LCD (7.9 mm)
Yes - 1 relay	Yes - 1 relay
USB / NFC	USB / NFC
Yes	Yes
Yes - up to 5000 points	Yes - up to 5000 points
Yes - via datalogging	Yes - via datalogging
(-30 to +70) °C	(-30 to +70) °C
(4 to 20) mA loop	(4 to 20) mA loop
2 years typical	2 years typical
SCH4	SCH55
IP67	IP67
USB and NFC (some functions)	USB and NFC (some functions
EN BS 61326	EN BS 61326
N/A	N/A



Head-mounted RTD, thermocouple transmitter with integrated LCD display. PC configuration.



Head-mounted universal dual input transmitter, with HART 5, 6, 7 and integrated LCD display. PC configuration.



ATEX-approved head-mounted universal dual input transmitter, with HART 5, 6, 7 and integrated LCD display. PC configuration.


In-head, dual input (SCH55)

Sensor / surface mount



## In-head (SCH4)

In-head (SCH4) Sensor / surface mount	In-head, dual input (SCH55) Sensor / surface mount
Yes - 2, 3 wire	Yes - 2, 3, 4 wire
Yes - 2, 3 wire	Yes - 2, 3, 4 wire
N/A	(10 to 10,500) <b>Ω</b>
N/A	1 kΩ to 100 kΩ auto sense
K, J, N, E, T, R, S, B	K, J, N, E, T, R, S, L, U, B, C, D,
	G custom
N/A	(-1000 to +1000) mV
(0 to 25) mA	N/A
N/A	N/A



	(0 to 2
Isolation	Yes

All-in-one transmitter and

Mechanical

Other RTD sensors

Thermocouple type

Pt100

Resistance

Voltage Current

**Thermistor** 

Potentiometer

display

<b>Custom linearisati</b>	on
Output zero/span	
alignment to input	t
User offset	
Display	
<b>Ambient operating</b>	J
Power supply	
Configuration	
Data download	
Dimensions	

N/A

N/A

N/A

EN BS 61326

Ŋ	ATEX
₹	UKEX
APPRO\	IEC Ex
	EMC / UKCA
	SIL

GENERAL

(0	to 23) mA Sense	(4 to 20) mA HART
Ye	25	Yes
Ye	es - mA	Yes
N/	/A	Yes
Ye	es - temp	Yes
6-	digit LCD (7.9 mm)	Multifunctional LCD
(-	-20 to +70) °C	(-25 to +85) °C
(1	5 to 30) VDC	(12 to 30) VDC
PC	C / push-button / NFC	PC and HART configurator
Da	atalogging via NFC / USB	N/A
(56	ee datasheet)	(see datasheet)
N/	/Α	N/A

N/A

N/A

EN BS 61326

Yes (see website for more details)

Yes - 2, 3, 4 wire
Yes - 2, 3, 4 wire
(10 to 10,500) Ω
1 kΩ to 100 kΩ auto sense
K, J, N, E, T, R, S, L, U, B, C, D,
G custom
(-1000 to +1000) mV
N/A
N/A
(4 to 20) mA HART
Yes
Yes
Yes
Yes
Multifunctional LCD
(-25 to +85) °C
(12 to 30) VDC
PC and HART configurator
N/A
(see datasheet)
Yes - Ex ia, Ex D
Yes - Ex ia, Ex D

Yes - Ex ia, Ex D

Yes (see website for more details)

## **Temperature** transmitters

**Other packages** 




MA head-mounted RTD, potentiometer, resistance transmitter.



OEM transmitter - build into your own



Space-saving 'all-in-one' Pt100 sensor and transmitter.




In-head

Yes - 2, 3 wire

Yes - 2, 3 wire (10 to 10,500) Ω

1 k $\Omega$  to 100 k $\Omega$  auto sense





TYI	PE
-----	----

_
_
_
_
lack
_

Pt100 Other RTD sensors

Resistance

**Potentiometer** 

Thermocouple type

**Voltage** 

Current

**Thermistor** 

N/A

N/A Yes

### **PCB Board**

In-head
---------

(4 to 20) mA

N/A

N/A

N/A

Yes

N/A

Yes - 2, 3 wire
N/A

Yes - 2, 3 wire
N/A

OUTPUT

GENERAL

**APPROVALS** 

### Isolation

**Custom linearisation** 

Output zero/span alignment to input

**User offset** 

Display

**Ambient operating** 

**Power supply** 

Configuration

**Dimensions** 

**EMC / UKCA** 

(4 to 20) mA

N/A

Yes - resistance / potentiometer

Yes N/A

 $(-40 \text{ to } +85) ^{\circ}\text{C}$ 

(10 to 30) VDC

PC

(see data sheet)

EN BS 61326

(4 to 20) mA

N/A N/A N/A Yes N/A

(-40 to +85) °C (10 to 30) VDC PC

30 x 15 mm

(-40 to +85) °C (10 to 30) VDC PC (see data sheet)

EN BS 61326

EN BS 61326

### **Field mounted indicators** and switches

- temperature

The DM650 series has the sensor supplied separately.



LCD battery-powered Pt100 and thermocouple thermometer, with relay and datalogging.




ATEX-approved LCD battery-powered Pt100 and thermocouple thermometer, with relay and datalogging.



Large-digit LCD battery-powered Pt100 and thermocouple thermometer.



Large-digit LCD battery-powered Pt100 and thermocouple thermometer, with two relays and datalogging.



### Mechanical

INPUT

Pt100

Thermocouple

**RTD** - other options

Linearisation/offset

OUTPUT

**Display** 

Relay

**Data download** 

**Custom messaging** 

**Datalogging** 

Max / min

GENERAL

**Ambient operating** 

**Power supply** 

**Battery life** 

**Enclosure** 

**Environmental rating** 

Configuration

**APPROVALS** 

**ATEX UKEX** 

**IEC Ex** 

**EMC / UKCA** 

Sensor / surface mount

K, J, T, R, S, E, L, N, U, B, C, D, G

Offset

6-digit LCD (7.9 mm)

Yes - 1 relay

USB / NFC

Yes - up to 5000 points

Yes - via datalogging

 $(-30 \text{ to } +70) ^{\circ}\text{C}$ 

Battery 3.6 V lithium

2 years typical

SCH4

IP67

USB

N/A

N/A N/A

EN BS 61326

Sensor / surface mount

K, J, T, R, S, E, L, N, U, B, C, D, G

Offset

6-digit LCD (7.9 mm)

N/A NFC

Yes - up to 1500 points Yes - via datalogging

 $(-30 \text{ to } +70)^{\circ}\text{C}$ Battery 3.6 V lithium 2 years typical SCH4

IP67 Push-button and NFC (some functions)

Yes Yes EN BS 61326

8888

Sensor / surface / panel mount

K, J, T, R, S, N, E

Yes

Offset

NFC

6-digit LCD (15.8 mm)

N/A

N/A N/A

Yes

 $(-30 \text{ to } +70) ^{\circ}\text{C}$ 

2 x AA 1.5V alkaline, or lithium

2 years typical, depending on battery type Stainless steel 100mm diameter

IP65

Push-button

EN BS 61326

N/A N/A

**NFC** Sensor / surface / panel mount

K, J, T, R, S, E, L, N, U, B, C, D, G

Both

6-digit LCD (15.8 mm)

Yes - 2 relays

USB / NFC

Yes - up to 5000 points

Yes, and relay condition

 $(-30 \text{ to } +70) ^{\circ}\text{C}$ 

Battery 3.6 V lithium

2 years typical Stainless steel 100mm diameter

IP65

USB

N/A N/A

N/A

### **Probe assemblies**

### **Probes**

## Transmitters/ Displays Many will suit those are

Many will suit; these are just some examples

### **Heads**

### **Thermowells**



We pride ourselves on being able to supply probe assemblies for almost any specification.


To that end, we have shown here our range of probe styles, in combination with some of our compatible transmitters, heads and thermowells, and other accessories.

Simply follow the left-to-right progression shown at the top of the page to compile your requirement.


The typical diagrams below show what factors can be specified when ordering probes and thermowells - which include temperature range and immersion depth, but can also accommodate special threads, diameters and other details if required.

If you would like to know more, or discuss a specific requirement, please call our sales team.

### **Typical probe specification diagram**



### Typical thermowell specification diagram



























(items shown not necessarily to scale)









































29

## **Humidity and temperature** transmitters, indicators and switches



Cost-effective dual-channel humidity / temperature transmitter. Duct or wall mount.




Dual-channel humidity / temperature transmitter. Duct, wall or remote mount. Note: replaceable sensors

**USB** 

 $(-30 \text{ to } +70) ^{\circ}\text{C}$ 




Dual-channel humidity / temperature transmitter with display. Duct, wall or remote mount. Note: replaceable sensors



LCD battery-powered humidity and temperature indicator, with relay and datalogging.

\* Supply voltage (15 to 30) VDC when display fitted.



Temperature range	
Humidity (RH)	

**Temperature** 

INPUT

**Humidity (RH)** 

Output c	hannels

**Datalogging** 

Output choices:	Temperature
	Humidity
	Dewpoint
	ΔTd - difference between dewpoint temperature and temperature
	Direct thermistor option
	Data download


	Direct diciniistor option	
	Data download	
lug-in sensor		
lounting option	, cable / sensor length	
Display		

Display	
Configuration	
Power supply	
Ambient operating temperature	(electronics, not sensor)

	$(-30 \text{ to } +70)^{\circ}$		
	(10 to 90) %		
	±0.5 °C		
	±3% RH		
	2 x (4 to 20) n		
	N/A		
	Default		
	Default		
	Programmable		
mperature	Programmable		
	Yes - single ch		
	N/A		
	No		
	Wall - 120		
	Duct - 120		
	N/A		
	PC		
	(10 to 30) VD0		
ot sensor)	$(-30 \text{ to } +70)^{\circ}$		
	EN BS 61326		

% °C USB Vs O + Vs O + Vs O +
(-30 to +70) °C
(10 to 90) %
±0.5 ℃
±3% RH
2 x (4 to 20) mA
N/A
Default
Default
Programmable
Programmable
Yes - single channel option only
N/A
No
Wall - 120 mm
Duct - 120, 250 mm
N/A
PC
(10 to 30) VDC *
(-30 to +70) °C

(10 to 90) %
±0.5 °C
±2% RH
2 x (4 to 20) mA
Yes
Default
Default
Programmable
Programmable
N/A
USB / NFC
Yes
Wall - 110 mm Duct - 120, 250 mm
N/A
PC and NFC (some functions)
(10 to 30) VDC *
(−30 to +70) °C
EN BS 61326



EN BS 61326

EN BS 61326

GENERAL

EMC / UKCA

## **Panel** meters



Loop-powered panel meter.



Pt100 / Thermocouple 4-digit panel meter with output options.




Current / voltage 4-digit panel meter 6-digit universal panel meter. with output options.






6-digit universal panel meter with rate /totaliser.

Panel meter housing accessory available







(96 x 48) mm panel mount

DM

3420





(96 x 48) mm panel mount

ľ	VI (	ec	h	a	n	į	Cá	al

Thermocouple	
Current	
Voltage	
Frequency / pulse	
Remote digital inputs	
User linearisation	

(48 x 24	l) mm	panel	mount

N/A
N/A
Yes (passive)
N/A
N/A
N/A
N/A

(96 x 48)	mm	panel	mount
-----------	----	-------	-------

` ′ '
Yes
K, J, T, R, S, E, L, N. B
N/A

N/A N/A

Yes (active or passive)
(0 to 1) (1 to 5) (0 to 10) VDC
N/A
N/A
Yes

Yes
K, J, T, R, S, E, L, N. B
Yes (active or passive)
±100 mV, ±1 VDC, ±10 VDC
N/A
Yes - with comms
Yes

(96 x 48) mm panel mount

Yes
K, J, T, R, S, E, L, N. B
Yes (active or passive)
±100 mV, ±1 VDC, ±10 VDC
N/A
Yes - with comms
Yes

See datasheet for full details and specific output combinations

4-digit LED process display

EN BS 61326

2 x relay (250 VAC @ 5 A) POD Current (active or passive) POD 4-digit LED process display

	2 x relay (250 VAC @ 5 A) POD	
Current (active or passive) POI		
	4-digit LED process display	

EN BS 61326

2 x relay (250 VAC @ 5 A) POD
Current (active or passive) POD
RS485 Modbus (RJ45)
6-digit LED process display

GENERAL

Isolation
Display
Ambient operating
Power supply
Loop power supply
Sensor excitation
Configuration
Max / min display
Comms
TFML maths functions

**EMC / UKCA** 

N/A	Yes
IV/A	162
4-digit LED 10 mm	4-digit LE
(-10 to +60) °C	(-30 to +
(4 to 20) mA loop	(20 to 35)
	(90 to 253
N/A	Output (o
N/A	N/A
Push-button	Push-butt
N/A	N/A
N/A	N/A
N/A	N/A


Yes
4-digit LED 14.2 mm
(-30 to +60) °C
(20 to 35) VDC <b>or</b>
(90 to 253) VAC
Output (option)
N/A
Push-button
N/A
N/A
N/A
EN BS 61326

	6-digit LED p
Yes	Yes
4-digit LED 14.2 mm	6-digit LED 1
(-30 to +60) °C	(-30 to +60
(20 to 35) VDC <b>or</b>	(20 to 35) VI
(90 to 253) VAC	(90 to 253) \
Input, output (option)	Input, outpu
N/A	N/A
Push-button	Push-button
Yes	Yes
N/A	Option
N/A	Yes - with co


6-digit LED process display	6-digit LED process display	
Yes	Yes	
6-digit LED 14.2 mm	6-digit LED 14.2 mm	
(-30 to +60) °C	(-30 to +60) °C	
(20 to 35) VDC <b>or</b>	(20 to 35) VDC <b>or</b>	
(90 to 253) VAC	(90 to 253) VAC	
Input, output (option)	Input, output (option)	
N/A	N/A	
Push-button / comms option	Push-button / comms option	
Yes	Rate / total	
Option	Option	
Yes - with comms	Yes - with comms	
EN BS 61326	EN BS 61326	

## Wireless transmitters





Head mount in SCH4 or SCH11



**RTD options** Potentiometer Thermocouple Voltage **Custom linearisation User offset** 

Measurement data on ISM band 868.4MHz

Yes Up to 10 k $\Omega$  autosense J, K, T, L, U, E, N, S, R, B, C, D (0 to 50) mV Yes - set on receiver Yes - set on receiver Yes - transmit

EN BS 61326

Yes

Communication

**Transmit / receive range Transmitter / receiver links Ambient operating Power supply** 

**Configuration with programming module** 

Width

**TYPE** 

Pt100


INPUT

OUTPUT

GENERAL

**APPROVALS** 


EMC / UKCA





Wireless receiver for up to 16 x WTX700





<del>1</del> ΩΩ >

35

D	IN	rail

2-12-1411	
From radio signal	From radio signal
From radio signal	From radio signal
From radio signal	From radio signal
From radio signal	From radio signal
From radio signal	From radio signal
From radio signal	From radio signal
Yes - potentiometer / mV range	Yes - potentiometer / mV range
Yes - receive	Yes - receive
4 x current - active / passive <b>or</b> voltage	2 x current - active / passive <b>or</b> voltage
	2 off (250 VAC @ 3A) C/O relay
RS485 Modbus for up to 16 x WTX700	RS485 Modbus for up to 16 x WTX700
300 m line of sight	300 m line of sight
Links up to 16 x WTX700 transmitters	Links up to 16 x WTX700 transmitters
(-20 to +50) °C	(-20 to +50) °C
(110 to 240) VAC or (20 to 30) VDC	(110 to 240) VAC or (20 to 30) VDC
PC / push-button	PC / push-button
22.5 mm	22.5 mm
EN BS 61326	EN BS 61326

## **Field mounted** indicators and switches


- pressure



LCD battery-powered pressure and media temperature indicator with relay and datalogging.



Large-digit LCD battery-powered pressure and media temperature indicator, with two relays and datalogging.



### Mechanical

### Pt100

Thermocouple

Pressure and media temperature

**Humidity and media temperature** 

**Current** 

Voltage

Linearisation/offset

# OUTPUT

INPUT

**Display** 

Relay

**Data download** 

**Custom messaging** 

**Datalogging** 

Max / min

### **Ambient operating**

**Power supply** 

**Battery life** 

**Enclosure** 

**Environmental rating** 


Configuration

APPROVALS

GENERAL

**ATEX** 

EMC / UKCA



### Sensor / surface mount

N/A

N/A

Yes - sensor included, ¼" BSP thread (adaptors available)

N/A

N/A

N/A

Pressure

6-digit LCD 7.9 mm

Yes - 1 relay

USB / NFC

Yes

Yes - up to 5000 points

Yes - via datalogging

 $(-30 \text{ to } +70) ^{\circ}\text{C}$ 

Battery 3.6 V lithium

2 years typical


SCH4

IP67

USB and NFC (some functions)

N/A

EN BS 61326



### Sensor / surface / panel mount

N/A

N/A

Yes - sensor included, ¼" BSP thread (adaptors available)

N/A

N/A

Pressure

6-digit LCD 15.8 mm

Yes - 2 relays

USB / NFC

Yes

Yes - up to 3600 points

Yes, and relay option

(-30 to +70) °C

Battery 3.6 V lithium

2 years typical

Stainless steel 100mm diameter

IP65

USB

N/A

## **Pressure** transmitters

Pressure transmitters can be customised with specialised fittings (such as hygienic tri-clamps, flushed diaphragms, etc) including our pressure digital gauges DM650PM and DM670PM (see pages 30 / 31).



Pressure transmitter.

**NFC** 



Pressure transmitter with



High specification pressure transmitter with ATEX version.



High specification pressure transmitter with ATEX / IECEx version.



High specification liquid level transmitter with ATEX / IECEx version.



High specification corrosive media level transmitter.

# **PRESSURE**

OUTPUT

GENERAL

Range from zero Range options Other ranges

Type

Gauge Absolute **Sealed gauge** 

2-wire (4 to 20) mA loop-powered

**Voltage output Datalogging** Linearisation

**Standard basic accuracy Operating temperature Process temperature** Diaphragm material

Material of body and process connection Standard seals Standard cable Configuration Display

1/4" BSP 1/4" NPT 1/2" BSP 1/2" BSP flush Other to order

Open or closed ends **ATEX** UKEX **IEC Ex** EMC / UKCA

USB NFC

(>-0.1 to 600) Bar (>-0.1 to 600) Bar Please enquire Please enquire Yes Yes Yes Yes N/A N/A

display.


Yes x 2 (temp and pressure) Yes x 2 (temp and pressure) N/A N/A Yes Yes Yes (pressure & process) Yes (pressure & process)


See datasheet See datasheet (-20 to +70) °C (-20 to +70) °C (-40 to +110) °C (-40 to +110) °C 316 stainless steel 316 stainless steel 316 stainless steel 316 stainless steel Viton Viton N/A N/A PC via USB PC via USB N/A 6-digit LCD (7.9mm)

Yes Yes adaptor adaptor adaptor adaptor adaptor adaptor Yes Yes N/A N/A N/A N/A N/A N/A N/A N/A

EN BS 61326


EN BS 61326






EN BS 61326

EN BS 61326





(> - 0.1 to 600) Bar	(>-0.1 to 1000) Bar	(>0.5 to 250) mH20	(>1 to 250) mH20
N/A	N/A	N/A	N/A
v	· ·	V	V
Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes
N/A	Yes	N/A	N/A
Yes	Yes	Yes	Yes
Yes (optional)	Yes (optional)	N/A	N/A
N/A	N/A	N/A	N/A
N/A	N/A	N/A	N/A
See datasheet	See datasheet	See datasheet	See datasheet
(-20 to +125) °C	(-40 to +125) °C	(-5 to +80) °C	(-5 to +80) °C
(-20 to +150)°C	(-40 to +150) °C	(-5 to +80) °C	(-5 to +80) °C
316 stainless steel	316 stainless steel	316 stainless steel	316 stainless steel with Teflon protection
303 stainless steel	303 stainless steel	303 stainless steel	PVDF
Viton	Viton	Viton	Viton
N/A	N/A	1m PUR	1m PUR
Fixed	Fixed	Fixed	Fixed
N/A	N/A	N/A	N/A
Yes	Yes	N/A	N/A
Yes	Yes	N/A	N/A
Yes	Yes	N/A	N/A
Yes	Yes	N/A	N/A
Yes	Yes	N/A	N/A
N/A	N/A	Yes	Yes
V	V	v	A1/A
Yes	Yes	Yes	N/A
Yes	Yes	Yes	N/A
N/A	Yes	Yes	N/A

EN BS 61326

**APPROVALS** 

## The versatility of our displays

### Status offer display and mounting solutions for every need, at every level

We will configure and build to your exact requirements - including choice of cap, blanking plugs, and entry ports (½" BSP, M20, M24, M16)

Please note that supplied with the DM650, at no extra cost:

- Relay option.
- Datalogging capability.

### Using our DM650 as an example:



### SCH4

Here a DM650 is mounted in our standard SCH4 head - a robust ABS plastic enclosure, which is suitable for most purposes.



### SCH15

A DM650 is mounted in our SCH15 stainless steel enclosure, when extra strength and protection are needed.



### **SCH55**


ATEX displays can be used with ATEX transmitters, within approved enclosures like our SCH55, to create costeffective ATEX assemblies.

Every assembly can function either as a remote battery-powered display, or if combined with one of our in-head transmitters, as a costeffective loop-powered system.

For our range of in-head transmitters, see pages 12 - 17.



Various entry port combinations can be specified:



Blanking plugs and higher caps are also available.

**Further options** Check out our all-in-one displays - like the SEM710 or SEM320 - or create solutions using our panel meter range.

## Free software and apps





## Accessing and processing data from Status products couldn't be simpler. Or cheaper.

We offer a comprehensive range of free apps for tablets and smart devices, plus free SpeedLink software for Windows PC.



### RTD Pt100 Converter

converts between Ohms, Pt100, Pt500, Pt1000, °Celsius and °Fahrenheit.



## Temperature Convertor

converts temperature readings between °Celsius, °Fahrenheit and °Kelvin.



## Thermocouple Convertor

converts thermocouple and mV readings between °Celsius, °Fahrenheit and °Kelvin.



### **Process to Signal**

converts a process signal value, in any engineering unit, into a control signal in milliamps, millivolts, or volts. For use in temperature measurement, process control, and signal conditioning.



### **USB ViewLink**

using USB on-the-go, ViewLink connects directly to your Status devices, allowing you to view real-time live data, including input and output variables, TAG data and devicespecific variables (such as a batch counter for the SEM1600F).



### **NFC LogLink**

for use with our DM670/DM650 series to download datalogs, manipulate data, then send via email and to the cloud.



### **NFC Link**

NFC Link is a free configuration utility compatible with the latest products from Status Instruments, allowing users to configure standard parameters for our DM650 and SEM710 instrumentation series. Visit our app shop to read more.



### SpeedLink configuration software for Windows PC

Basic and advanced configuration software for Status instrumentation.



- Easy configuration, with the use of drop-down menus
- Quick-connect, for easy recognition of products
- Tools and help screens, to guide you through the process
- Basic and advanced function options in product
- Pre-set selections and custom type areas

### **Solution overview**


### For every application, there is a Status product, and a practical solution.

We pride ourselves on being able to offer the kind of technical support that will help you diagnose opportunities, recognise the optimum solution and specify the appropriate Status products.

Every application contains a series of processes, which we look at as 'journeys', from source to final output.

The basic principle is shown below, and opposite we show how Status can help you 'journey' from sensor output (or from any mA or V process signal) to arrive at the outcome you require.


By asking you a series of consultative questions, your needs can be analysed, mapped and assessed, then accommodated with products from the Status range.




### We're always there for you

We offer a service that we believe is second to none, with every facility and provision you could ever need. And all you have to do is ask.







# The Application Guide




Industries, environmental conditions

and circumstantial factors mean that although many applications for Status products may be broadly similar, they are rarely exactly the same. That's why we've developed a series of **Application Guides**, which not only help you identify the appropriate Status products for your needs, but show you how best to apply and adapt them to your circumstances, so you can retrieve, process and deliver all the data you need, precisely as you need it.

**Visit our website to view our Application Guide resources** - or call us, and we can discuss your requirements, and advise about a range of innovative solutions, that will deliver improved efficiency, real cost savings ... and total peace of mind.

Here are some examples of how our Application Guide can help and inform.



The weight of a tank mounted on 4 loadcells is measured by an SEM1600B, which takes their average output (equivalent to tank weight) and converts this into a voltage or (4 to 20) mA signal – in this example, for the DM3420 to measure as volume.



THERMOCOUPLE 1419A TEMPERATURE MEASUREMENT


POTENTIONAL MOVEMENT


RESISTANCE -LINEAR MOVEMENT



Our in-head transmitter range can accept RTD and thermocouple sensors as well as Ohmic, mV and potentiometer sensors. A sensor calibration function is provided to help minimise sensor error.


A DM650PM is measuring the water level in the tank via pressure. When the level is above the minimum then the rainwater is sent to the irrigation system.






Continuous level measurement in process vessels can call for high-accuracy linearisation. The DM3600 can interface with any level transmitter output and linearise any vessel shape, with up to 60 co-ordinate pairs.

The DM3600A can be used with almost any level sensor to measure 'head' upstream of a flume or weir. Standard software allows power 3/2 and 5/2 flow linearisation, giving a (4 to 20) mA output proportional to flow.





COMMON FLOW CHOUS ARE STANDARD IN THE DM3600A. IT CAN BE PROGRAMMED SO A RELAY CLOSURE EVERY IX'CUBIC METRES SENDS A SIGNAL FOR AN EXTERNAL TOTALISER.



An SEM1750 powers the SEM710HM, and sends two loops to the panel meter and PLC for further control. The panel meter has its relay output programmed to alarm if the dewpoint reaches a critical level.


Accurate measurement of flow over a wide flow range can be problematic, as the turndown of the flowmeter could provide inaccurate measurement at extremes of span.





The SEM1750 can be used with almost any sensor to measure differential. In this common application in rivers and waterways, two level sensors measure level up- and downstream of a weed screen.

An SEM1600F counting items on a belt. The product can be programmed to count each item that passes the digital sensor.
When a number of readings equal to a batch size has gone through, a relay can switch.



## **Legacy Products**

These Status products, and those listed opposite, are no longer available.

So here's how to replace them...



Because the Status product range is constantly evolving and growing, you might find that if you try to re-order a trusted and long-serving product, it may no longer be available in its original form.

So we thought it would be helpful to list here all discontinued products, and show you which of our current models would replace them. Then you can be sure to get the right state-of-the-art Status product, to serve you for many more years to come.

We also still have available to special order a number of older products, which are not included in the main body of this Product Guide.

As always, if you need more specific help or advice, please call us and we'll be happy to assist you.

In fact, we're happy to look at user requirements on a case-by-case basis, and will build unique products to special order (subject to MOQ).

Discontinued product	Description	Replacement
DM3430	High-voltage/current true RMS panel meter	
DM4000U	Panel meter	DM3600U
DM4000A	Panel meter	DM3600A
DM4000C	Panel meter	
DM440	Digital temperature indicator	DM650TM
DM4500	Panel meter series	
DM500	Loop-powered LCD indicator	DM700
DM540X	ATEX field-mounted display	DM640X
DM650VI	Voltage process indicator with relay	
DM660	Large Pt100 digital indicator	DM670TM
HTR200/1V	MA head-mounted RTD, potentiometer, resistance transmitter with voltage output	t
MEDACS 2100 Series	Universal input single-channel signal conditioner	SEM1700 - most functions
MEDACS 2200 Series	Universal input dual-channel signal conditioner	SEM1720 / SEM1750 most functions
MEDACS 2300 Series	Frequency input single-channel signal conditioner	SEM1600/F most functions
MEDACS 2400 Series	Frequency input dual-channel signal conditioner	SEM1600/F most functions
PTX24	Process pressure transmitter	PTX19
SEM108P	In-head temperature transmitter	SEM206P
SEM110X	Analogue ATEX in-head transmitter	call us
SEM1100	Powered isolating voltage to current / current to voltage convertor	SEM1700
SEM1010	Provides isolated power for a transmitter derived from a powered loop.	SEM1700 (some functions)
SEM1401 / 1402	Loop-powered trip amplifier	SEM1636
SEM1500/TC	Thermocouple DIN rail temperature transmitter	SEM1605/TC
SEM1503P	Pt100 DIN rail temperature transmitter	SEM1605/P
SEM1504/P	4-wire Pt100 DIN rail temperature transmitter	SEM1615
SEM161 / 162	Humidity and temperature transmitter	SEM710HM
SEM1603	Rail-mounted temperature transmitter for Pt100 or thermocouple sensors	SEM1605P/TC
SEM1610	Universal temperature transmitter, DIN rail mount	SEM1615
SEM164	Humidity and temperature transmitter	SEM160, SEM161 or SEM162
SEM165HP	High-temperature humidity and temperature transmitter	No direct replacement for higher temperature version
SEM167H1C	Wall-mounted humidity transmitter with power supply and output options	SEM162
SEM167H1P	Duct-mounted humidity transmitter with power supply and output options	SEM162
SEM167H1R	Remote mount humidity transmitter with power supply and output options	SEM162
SEM205X	ATEX temperature transmitter	TTR200X
SEM210 MKI	Universal in-head temperature transmitter	SEM210 MKII
SEM213P	Manual push-button Pt100 4-20mA DIN rail temperature transmitter	SEM1605/P
SEM213TC	Manual push-button thermocouple 4-20mA DIN rail temperature transmitter	SEM1605/TC
SEM215	PC-programmable universal 4-20mA DIN rail temperature transmitter with user linearisation feature	SEM1615
SEM230X	ATEX DIN-rail universal transmitter	call us
SEM310 MKI	Universal HART in-head temperature transmitter	SEM310 MKII
SEM315 MKI	DIN rail Universal HART temperature transmitter	SEM315 MKII