MILLBURN TOWNSHIP PUBLIC SCHOOLS

MILLBURN HIGH SCHOOL

462 Millburn Ave., Millburn, NJ 07041

LOCAL GOVERNMENT ENERGY AUDIT PROGRAM FOR NEW JERSEY BOARD OF PUBLIC UTILITIES

May 2014

Prepared by:



6 Campus Drive Parsippany, NJ 07054 (973) 538-2120

CHA PROJECT NO. 28330

TABLE OF CONTENTS

1.0 EX	RECUTIVE SUMMARY	1
2.0 BL	JILDING INFORMATION AND EXISTING CONDITIONS	4
3.0 UT	FILITIES	9
4.0 Be	enchmarking	14
5.0 EN	NERGY CONSERVATION MEASURES	15
5.1	ECM-1 Replace Door Sweeps and Seals	16
5.2	ECM-6 Smart Controller Window AC Units	16
5.3	ECM-9 Install VFDs and Premium Efficiency Motors on Air Handling Units	17
5.4	ECM-10 Replace RTUs	17
5.5	ECM-12 Retro-Commission Temperature Controls	18
5.6	ECM-14 Install Kitchen Hood Controller	19
5.7	ECM-15 Install Walk-in Cooler / Freezer Controls	19
5.8	ECM-17 Install Vending Misers	20
5.9	ECM-L1 Lighting Replacement / Upgrades	20
5.10	ECM-L2 Install Lighting Controls (Occupancy Sensors)	21
5.11	ECM-L3 Lighting Replacements with Controls (Occupancy Sensors)	21
5.12	Additional O&M Opportunities	22
6.0 PF	ROJECT INCENTIVES	23
6.1	Incentives Overview	23
6.1.1	New Jersey Smart Start Program	23
6.1.2	Direct Install Program	23
6.1.3	New Jersey Pay For Performance Program (P4P)	24
6.1.4	Energy Savings Improvement Plan	25
6.1.5	Renewable Energy Incentive Program	26
7.0 AL	TERNATIVE ENERGY SCREENING EVALUATION	27
7.1	Solar	27
7.1.1	ECM-S1 Photovoltaic Rooftop Solar Power Generation	27
7.1.1	ECM-S2 Solar Thermal Hot Water Generation	28

7.2	Combined Heat and Power Plant					
7.3	Win	d Powered Turbines	29			
7.4	Den	and Response Curtailment	30			
8.0 (CONCL	JSIONS & RECOMMENDATIONS	32			
APPE	ENDICE A B C D	Utility Usage Analysis and List of Third Party Energy Suppliers Equipment Inventory ECM Calculations and Cost Estimates New Jersey BPU Incentive Programs i. Smart Start ii. Direct Install iii. Pay For Performance Incentive Program (P4P) iv. Energy Savings Improvement Plan (ESIP) Photovoltaic (PV) Solar Power Generation Analysis Photos EPA Portfolio Manager				

REPORT DISCLAIMER

This audit was conducted in accordance with the standards developed by the American Society of Heating, Refrigerating, and Air-Conditioning Engineers (ASHRAE) for a Level II audit. Cost and savings calculations for a given measure were estimated to within ±20%, and are based on data obtained from the owner, data obtained during site observations, professional experience, historical data, and standard engineering practice. Cost data does not include soft costs such as engineering fees, legal fees, project management fees, financing, etc.

A thorough walkthrough of the building was performed, which included gathering nameplate information and operating parameters for all accessible equipment and lighting systems. Unless otherwise stated, model, efficiency, and capacity information included in this report were collected directly from equipment nameplates and /or from documentation provided by the owner during the site visit. Typical operation and scheduling information was obtained from interviewing staff and spot measurements taken in the field.

List of Common Energy Audit Abbreviations

- A/C Air Conditioning
- AHS Air Handling Unit
- BMS Building Management System
- Btu British thermal unit
- CDW Condenser Water
- CFM Cubic feet per minute
- CHW Chilled Water
- DCV Demand Control Ventilation
- DDC Direct Digital Control
- DHW Domestic Hot Water
- DX Direct Expansion
- EER Energy Efficiency Ratio
- EF Exhaust Fan
- EUI Energy Use Intensity
- Gal Gallon
- GPD Gallons per day
- GPF Gallons Per Flush
- GPH Gallons per hour
- GPM Gallons per minute
- GPS Gallons per second
- HHW Heating Hot Water
- HID High Intensity Discharge
- HP Horsepower
- HRU Heat Recovery Unit
- HVAC Heating, Ventilation, Air Conditioning
- HX Heat Exchanger
- kbtu/mbtu One thousand (1,000) Btu
- kW Kilowatt (1,000 watts)
- kWh Kilowatt-hours
- LED Light Emitting Diode
- mbh Thousand Btu per hour
- mmbtu One million (1,000,000) Btu
- OCC Occupancy Sensor
- PSI Pounds per square inch
- RTU Rooftop Unit
- SBC System Benefits Charge
- SF Square foot
- UH Unit Heater
- V Volts
- VAV Variable Air Volume
- VSD Variable Speed Drive
- W Watt

1.0 EXECUTIVE SUMMARY

This report summarizes the energy audit performed by CHA for Millburn Township Public Schools, in connection with the New Jersey Board of Public Utilities (NJBPU) Local Government Energy Audit (LGEA) Program. The purpose of this report is to identify energy savings opportunities associated with major energy consumers and inefficient practices. Low-cost and no-cost are also identified during the study. This report details the results of the energy audit conducted for the building listed below:

Building Name	Address	Square Feet	Construction Date
Millburn High School	462 Millburn Ave., NJ 07041	201,858	1955

The potential total annual energy and cost savings for the energy conservation measures (ECM) identified in the survey are shown below:

Building Name	Electric Savings (kWh)	NG Savings (therms)	Total Savings (\$)	Payback (years)
Millburn High School	411,778	17,994	66,362	9.9

Each individual measure's annual savings are dependent on that measure alone, there are no interactive effects calculated. There are three options shown for Lighting ECM savings; only one option can be chosen. Incentives shown (if any) are based only on the SmartStart Incentive Program. Other NJBPU or local utility incentives may also be available/ applicable and are discussed in Section 5.0.

Each measure recommended by CHA typically has a simple payback period of 15 years or less to be consistent with the requirements of the Energy Savings Improvement Plan (ESIP) which has a maximum payback period of 15 years. Occasionally, we will recommend an ECM that has a longer payback period, based on the need to replace that piece(s) of equipment due to its age, such as a boiler for example.

The following table provides a detailed summary of each ECM for the building surveyed, including costs, savings, SmartStart incentives and payback.

Summary of Energy Conservation Measures

ECM #	Energy Conservation Measure	Est. Costs (\$)	Est. Savings (\$/year)	Payback w/o Incentive	Potential Incentive (\$)*	Payback w/ Incentive	Recommended
1	Door Sweeps and Seals	2,305	298	7.7	0	7.7	Υ
6	Smart Window A/C Controller	1,200	338	3.6	0	3.6	Υ
9	Install VFDs on AHUs	19,047	2,466	7.7	0	7.7	Υ
10	Replace Rooftop Units	152,000	706	67.7	0	67.7	Υ
12	Retro-Commission Temperature Controls	69,967	21,280	3.3	0	3.3	Υ
14	Kitchen Hood Controller	30,787	5,917	5.2	0	5.2	Υ
15	Walk-In Cooler/Freezer Controls	20,625	172	120.1	0	120.1	Υ
17	Install Vending Misers	840	881	1.0	0	1.0	Υ
L1**	Lighting Replacements	454,693	31,345	14.5	10,000	14.2	N
L2**	Lighting Controls	10,287	6,937	1.5	1,590	1.3	N
L3	Lighting Replacements w/ Controls	464,980	34,304	13.6	11,590	13.2	Y
	Total	657,550	66,362	9.9	11,590	9.7	
	Total (Recommended)	657,550	66,362	9.9	11,590	9.7	

The following alternative energy measures are also recommended for further study:


Photovoltaic (PV) Rooftop Solar Power Generation - 270 kW System

If Millburn Township Public Schools implements the recommended ECMs, energy savings would be as follows:

	Existing Conditions	Post Recommended ECMs	Percent Savings
Costs (\$)	354,927	288,565	19%
Electricity (kWh)	2,220,800	1,809,022	19%
Natural Gas			
(therms)	80,896	62,902	22%
Site EUI			
(kbtu/SF/Yr)	77.6	61.7	

^{*} Incentive shown is per the New Jersey SmartStart Program.

** These ECMs are not included in the Total, as they are alternate measures not recommended.



2.0 BUILDING INFORMATION AND EXISTING CONDITIONS

The following is a summary of building information related to HVAC, plumbing, building envelope, lighting, kitchen equipment and domestic hot water systems as observed during CHAs site visit. See appendix B for detailed information on mechanical equipment, including capacities, model numbers and age.


Building Name: Millburn High School

Address: 462 Millburn Ave., Millburn, NJ 07041

Gross Floor Area: 201,858 sq.ft. **Number of Floors:** 3 and basement

Year Built: 1955

Additions: 1996, 2002, & 2009



Description of Spaces: Classrooms, offices, cafeteria, auditorium, stage, gymnasiums, computer lab, media center, storage rooms, toilet rooms and mechanical rooms.

Description of Occupancy: The school serves 1,600 students from 9th to 12th grade. There are 180 school faculty and staff members.

Number of Computers: The school has approximately 240 desktop and laptop computers.

Building Usage: Hours of operation are 7:35 AM to 2:35 PM Monday through Friday, with various after-school activities. Custodial staff are on site in two shifts, from 6:00 AM to 3:00 PM, and 2:30 PM to 11:00 PM, 10 months per year.

Construction Materials: Structural steel framing with concrete masonry unit exterior walls, insulation unknown but assumed to vary with age: greater insulation thicknesses assumed for more recent construction. Interior walls mostly sheetrock and painted concrete. Interior and exterior walls are in fair to good condition.

Façade: Concrete masonry units and brick

Roof: The building has several wings which have flat roofs, and are covered with adhered membrane or stone ballast. Roofing over the auditorium and the old gym are pitched and covered with an adhered membrane. Insulation in attic spaces is unknown but assumed to vary with age: higher insulation thicknesses are typically found in more recent construction. Roof color varies from is light gray to dark gray.

Windows: Double hung double pane windows with aluminum frames. Windows are in good condition and no ECMs associated with window replacement were evaluated.

Exterior Doors: Most exterior doors are steel jacketed without windows. Main entrance doors are steel framed storefront style. Some of the sweeps and seals are in poor condition, and these should be replaced. An ECM has been included to address this issue.

Heating Ventilation & Air Conditioning (HVAC) Systems

Heating: Two (2) natural gas fired hot water H.B. Smith cast iron sectional boilers, installed in 2003, provide heat for most of the school. Each of these boilers is rated for 2,850 MBH. Two (2) B&G base mounted pumps (DTWP-1 and DTWP-2) circulate the heating water around the building. These pumps are powered by 15.0 HP Baldor motors which have a NEMA nominal efficiency of 87.5% and operate in a lead/lag manner. Both pumps are controlled by Danfoss VFDs. The building utilizes a two-pipe hydronic piping system that circulates hot water in the winter months, and chilled water in the summer months. Change-over between the two systems is typically April 15 in the spring, and October 15 in the fall, with final decision on timing made by the school principal. Terminal units include unit ventilators, floor mounted fan coils, cabinet heaters, air handling units, unit heaters, and finned radiation.

Additional heat is provided into the newer 2009 sections of the school by two (2) Patterson Kelly Mach Series hot water boilers manufactured in 2008, with a capacity of approximately 1.8 million BTUHs each. Two base mounted Taco pumps, operating in a lead-lag manner, circulate the hot water around the building.

The D classroom wing is a 3 story wing supplied by three (3) Carrier packaged energy recovery rooftop units that provide gas fired heat and DX air conditioning for classrooms on each floor; these units also provide general building pressure relief. The C wing is similarly served by three (3) packaged McQuay energy recovery rooftop units of indeterminate age. The old gymnasium is served by two 1.5 HP air handling units located in a mechanical equipment room. The new gymnasium is served by two (2) packaged Trane energy recovery heating-only RTUs, with some external ductwork lacking insulation.

The Paul W. Rossey Library is essentially a separate building within the courtyard of the school, and is heated by a gas fired Weil McLain hot water firetube boiler. This boiler has an output of 408 MBH and an efficiency of 79%. Heating hot water is pumped to a 1987 Carrier air handling unit and a 1988 Carrier air handling unit, by a fractional HP B&G inline circulator pump. The Carrier AHUs have 3.0 HP supply fans and deliver heated and conditioned air via a ducted distribution system to the interior of the library.

Cooling: Much of the high school is cooled by a 250 ton Trane helical rotary chiller installed outside on a concrete pad by the loading dock at the west end of the school. The chiller is only utilized during the summer months, and a single base mounted 5.0 HP B&G pump located in the Boiler Rm supplies serves it. Chilled water pumped from the chiller is routed into the main two-pipe hydronic piping system at a 3-way valve, and from there pumps DTWP-1 and DTWP-2

circulate the chilled water around the building. The chiller is not available in the winter but is filled with propylene glycol and then drained.

Due to the fact that most of the school is heated and cooled utilizing a two-pipe hydronic system, some terminal units are valved off during the summer months. For example, chilled water running through perimeter finned tube radiation has caused condensation issues, while not providing much cooling. Shutting off the isolation valves to these types of units has helped to minimize these problems.

The Paul W. Rossey Library is cooled by two (2) Carrier air handling units [1987&1988] outfitted with DX cooling coils. This air is delivered to the interior of the space by a ducted distribution system. A couple offices within the library have wall-mounted Friedrich split AC units with DX condensing units installed outside.

Many areas of the school are cooled by individual Trane DX rooftop and air handling units, which vary in tonnage from 3 tons to 15 tons. See chart below for a listing of areas served.

Several classrooms in the Industrial Arts wing are cooled by fractional tonnage air conditioning units installed in windows. These are left in place year-round and are not covered in the winter-time. Since these are not automatically controlled, these window ACs may be inadvertently left on while the building is un-occupied. An ECM addressing this issue is evaluated.

Ventilation: Ventilation is provided by a combination of rooftop units, air handling units, and classroom unit ventilators. These units are equipped with outside air dampers which automatically modulate and vary the percentage of outside air entering the space, based on indoor and outdoor air temperatures. See table below for a listing of some rooftop and air handling units:

AHU-1	Cafeteria
AHU-2	Gymnasium
AHU-3	Gymnasium
AHU-S01	Auditorium
RTU-1	Weight Room
RTU-2	Computer Rm 215
RTU-3	Computer Rm 142
RTU-4	Music Room
HV-1	Boys Locker Rm
HV-2	Girls Locker Rm
Unit Ventilators	Classrooms

See Appendix B for more detailed equipment data

In general, the building mechanical ventilation systems are adequate and no associated ECMs are included.

Exhaust: Exhaust fans are used to ventilate toilet rooms and the kitchen. A 12'x4' kitchen range hood and associated ductwork connects to a roof mounted centrifugal upblast exhaust fan. Classroom laboratories are exhausted with propeller tube axial fans. Centrifugal exhaust fans, installed on the roof, provide exhaust for toilet rooms. In general building exhaust is adequate and no associated ECMs are included.

Controls Systems

Boiler operation is manual control; with at least one boiler running all day and all night during the colder months. Boiler switching is also performed manually; as well as boiler temperature. The high school's newest HVAC equipment such as ERU, air handling units, and the newer unit ventilators are controlled by a centralized DDC Siemens controls system. But even here, control is limited to only a few points, such as temperature setpoints—over-ride on operations such as damper and valve positions are not available. Older equipment such as the boilers, pumps, and other terminal units are manually controlled. Access to the DDC system is not available on-site, but is limited to one or two individuals who control setpoints on individual pieces of equipment from a head end at the Education Center or from a remote laptop. An ECM for retro-commissioning of the controls systems is included that will address the cost and savings for these issues.

Domestic Hot Water Systems

The High School has several different domestic hot water heaters. In the Boiler Room there is a 2007 Rheem gas fired DHW unit with 90 gallons capacity and 533.3 gallons per hour recovery. A 2008 Rheem gas fired DHW heater located in a mechanical room has 119 gallons capacity and 184 gallons per hour recovery. The Paul W. Rossey Library contains an electric State Industries water heater, and this has 30 gallons storage capacity. Two electric heating elements provide recovery for this unit: a 4500 watt upper element, and a 3500 watt lower element. In all cases domestic hot water is pumped around the school/building to restrooms and sinks by fractional horsepower circulator pumps. No domestic hot water related ECMs are included.

<u>Kitchen Equipment</u>

The kitchen contains one 12'x4' (approximate size) range exhaust hood, which is ducted and exhausted to an exterior rooftop exhaust fan. An ECM for the installation of a kitchen hood controller is evaluated. There is one True double-door type reach-in freezer, one Beverage Air triple-door type reach-in cooler, and another double door Traulsen reach in cooler. One Bally walk-in cooler is also in the kitchen, which utilizes a Heatcraft evaporator system to maintain its 40°F temperature. An ECM which evaluates walk-in cooler controls is included. For the most part the cooking equipment (such as the bread ovens) are manufactured by both Metro and Blodgett, and are natural gas fired. Dishes are washed by a Hobart automatic dishwasher.

Plumbing Systems

The building contains low flow lavatories (2.2 GPM or less), and toilets and urinals are also of the low flush volume variety (1.6 GPF for toilets and 1.0 GPF for urinals). Newer fixtures utilize electronic sensors to monitor water flow; older fixtures are spring loaded to perform the same task. Water usage is primarily toilet rooms, the kitchen, and lavatories; and all fixtures appear to be in good condition. No ECMs for plumbing fixtures were considered.

Plug Load

This school has computers, copiers, smart boards, residential appliances (microwave, refrigerator), printers and portable electric heaters (personal) which contribute to the plug load in the building. An ECM for the installation of vending misers is evaluated.

Lighting Systems

Most of the lighting within this school is primarily 4' T8 linear fluorescent fixtures with electronic ballasts, and in most cases the number of lamps per fixture is two, three, or four. However a

significant percentage of lighting (~15%) is still T12, particularly in: the older industrial arts wing, and some corridors. Compact fluorescents round out the remaining interior lights. Exterior lighting consists of both 38 watt PAR floodlights, and 150W metal halide wallpack lamps. Lights in all of the newest areas are operated by occupancy sensors, in the rest of the school lights are controlled by manual switches. Three lighting ECMs have been included which include adding occupancy sensors to the existing lighting, replacement of the T-8 lighting with LED lighting and a third ECM that evaluates the effect of occupancy sensors used with the LED lighting upgrades.

3.0 UTILITIES


Utilities used by the building are delivered and supplied by the following utility companies:

	Electric		Natural Gas
	New Jersey		PSEG
Deliverer	Power & Light		
Supplier	New Jersey		Compass
	Power & Light		


For the 12-month period ending in March 2014, the utilities usages and costs for the building were as follows:


Electric					
Annual Consumption	2,220,800	kWh			
Annual Cost	\$266,271	\$			
Blended Unit Rate	\$0.120	\$/kWh			
Supply Rate	\$0.095	\$/kWh			
Demand Rate	\$6.78	\$/kW			
Peak Demand	862.7	kW			
Natu	iral Gas				
Annual Consumption	103,096	Therms			
Annual Cost	\$88,656	\$			
Unit Rate	\$0.856	\$/therm			
Water					
Annual Usage 2,308,000 Gallons/yr					
Annual Cost	20,466	\$			
Rate	0.009	\$/gallon			


Blended Rate: Average rate charged determined by the annual cost / annual usage Supply Rate: Actual rate charged for electricity usage in kWh (based on most recent electric bill) Demand Rate: Rate charged for actual electrical demand in kW (based on most recent electric bill)




It can be seen from the chart above that electricity usage at the High School tends to peak in the late spring and early fall, which are times of maximum cooling at highest building occupancies.







Natural gas usage (shown above for three accounts) is greatest during the winter heating months and is least during the cooling months. This type of load profile is typical when natural gas is used primarily for heating from boilers and RTUs and is used only minimally by the domestic hot water heater.



See Appendix A for a detailed utility analysis.

Under New Jersey's energy deregulation law, the supply portion of the electric (or natural gas) bill is separated from the delivery portion. The supply portion is open to competition, and customers can shop around for the best price for their energy suppliers. The electric and natural gas distribution utilities will still deliver the gas/ electric supplies through their wires and pipes – and respond to emergencies, should they arise – regardless of where those supplies are purchased. Purchasing the energy supplies from a company other than your electric or gas utility is purely an economic decision; it has no impact on the reliability or safety of the service.

Comparison of Utility Rates to NJ State Average Rates*							
Utility Units School Average Rate NJ Average Rate							
Electricity	\$/kWh	\$0.12	\$0.12				
Natural Gas \$/Therm		\$0.86	\$0.95				
Fuel Oil	\$/Gal		\$3.62				

* Per U.S. Energy Information Administration (2013 data - Electricity and Natural Gas, 2012 data - Fuel Oil)

This school on average pays about the same rate for their electricity and a lower rate for natural gas than the average commercial building in New Jersey. It is not recommended that this school shop for a third party utility supplier for both electric and natural gas.


Additional information on selecting a third party energy supplier is available here:


http://www.state.nj.us/bpu/commercial/shopping.html.

See Appendix A for a list of third-party energy suppliers licensed by the Board of Public Utilities to sell within the building's service area.

The charts below represent estimated utility end-use utility profiles for the building. The values used within the charts were estimated from a review of the utility analysis and the energy savings calculations.


Site End-Use Utility Profile





Most of the electricity consumed by educational facilities is used to for lighting, cooling, and plug loads such as computers and copiers; most of the natural gas is used for space heating. Each school's energy profile is different, and the following charts represent typical utility profiles for K-12 schools per U.S. Department of Energy.

Typical End-Use Utility Profile for Educational Facilities



Courtesy: E source; from Commercial Building Energy Consumption Survey, 1999 data

4.0 Benchmarking

The EPA Portfolio Manager benchmarking tool provides a site and source Energy Use Intensity (EUI), as well as an Energy Star performance rating for qualifying building types. The EUIs are provided in kBtu/ft²/year, and the performance rating represents how energy efficient a building is on a scale of 1 to 100, with 100 being the most efficient. In order for a building to receive an Energy Star label, the energy benchmark rating must be at least 75. As energy use decreases from implementation of the proposed measures, the Energy Star rating will increase.

The site EUI is the amount of heat and electricity consumed by a building as reflected in utility bills. Site energy may be delivered to a facility in the form of primary energy, which is raw fuel burned to create heat or electricity, such as natural gas or oil; or as secondary energy, which is the product created from a raw fuel such as electricity or district steam. To provide an equitable comparison for different buildings with varying proportions of primary and secondary energy consumption, Portfolio Manager uses the convention of source EUIs. The source energy also accounts for losses incurred in production, storage, transmission, and delivery of energy to the site, which provide an equivalent measure for various types of buildings with differing energy sources. The results of the benchmarking are contained in the table below.

Building	Site EUI kBtu/ft²/yr	Source EUI Btu/ft²/yr	Energy Star Rating (1-100)
High School	76.3	158.6	43

The building has a below average Energy Star Rating Score (50 being the median score). It is likely that a combination of factors contribute to this low score—older inefficient air handling units and RTUs; sections of the school pre-dominantly lit by T12s; and control components in need of retro-commissioning. By implementing the measures discussed in this report, it is expected that the EUI can be further reduced and the Energy Star Rating increased.

The Portfolio Manager account can be accessed by entering the username and password shown below at the login screen of the Portfolio Manager website (https://www.energystar.gov/istar/pmpam/).

5.0 ENERGY CONSERVATION MEASURES

The following types of energy savings opportunities are identified in this section of the report:

- Energy conservation measures (ECMs) are energy savings recommendations that typically require a financial investment. For these areas of opportunity, CHA prepared detailed calculations, as summarized in this section and in Appendix C. In general, additional savings may exist from reductions in maintenance activities associated with new equipment or better controls; however for conservatism, maintenance savings are not accounted for in this report; instead the only savings which are reported are those derived directly from reductions in energy which can be tracked by the utility bills.
- Operational and Maintenance measures (O&M) consist of low- or no-cost operational opportunities, which if implemented would have positive impacts on overall building operation, comfort levels, and/or energy usage. There are no estimated savings, costs or paybacks associated with the O&M measures included as part of this study.

Energy savings were quantified in the form of:

- electrical usage (kWh=Kilowatt-hour),
- electrical demand (kW=kilowatts),
- natural gas (therms=100,000 Btu),
- propane gas (gallons=91,650 Btu),
- fuel oil (gallons =138,700 Btu), and
- water (kgal=1,000 gallons).

These recommendations are influenced by the time period that it takes for a proposed project to "break even" referred to as "Simple Payback". Simple payback is calculated by dividing the estimated cost of implementing the ECM by the energy cost savings (in dollars) of that ECM.

Another financial indicator of the performance of a particular ECM is the Return on Investment or ROI, which represents the benefit (annual savings over the life of a project) of an investment divided by the cost of the investment. The result is expressed as a percentage or ratio.

Two other financial analyses included in this report are Internal Rate of Return (IRR) and Net Present Value (NPV). Internal Rate of Return is the discount rate at which the present value of a project costs equals the present value of the project savings. Net Present Value is the difference between present value of an investment's future net cash flows and the initial investment. If the NPV equals "0", the project would equate to investing the same amount of dollars at the desired rate. NPV is sometimes referred to as Net Present Worth. These values are provided in the Summary Tab in Appendix C.

5.1 ECM-1 Replace Door Sweeps and Seals

It was noted during the site visit that the seals and sweeps were showing wear on many of the exterior doors, and daylight was visible between the door and frame.

The seals around exterior doors fail over time. This leads to infiltration of unconditioned outside air or exfiltration of conditioned air resulting in increased heating energy usage. This measure calls for the replacement of all exterior door seals. Replacement of these seals will result in a reduction of the buildings heating and cooling loads, therefore providing natural gas and electricity savings. The linear footage of gap and wind speed is used to estimate the infiltration rate, which is then multiplied by the BIN weather data and the equipment efficiencies to determine the annual energy savings.

The implementation cost and savings related to this ECM are presented in Appendix C and summarized below:

ECM-1 Replace Window and Door Seals

Budgetary Cost	Annual Utility Savings			ROI	Potential	Payback (without	Payback (with	
Cost	El	ectricity	Natural Gas Total Incentive*	incentive	incentive)	incentive)		
\$	kW	kWh	Therms	\$	%	\$	Years	Years
2,305	0	0	346	298	0.9	0	7.7	7.7

^{*} Does not qualify for Incentive from the New Jersey SmartStart Program. See section 6.0 for other incentive opportunities

This measure is recommended.

5.2 ECM-6 Smart Controller Window AC Units

Only about 5% of the building is cooled by window a/c units which can be occasionally left on by occupants when they leave the room.

This ECM evaluates the installation of programmable "smart" timers that interrupt the electrical supply to the window air conditioners when cooling is not needed due to the room being unoccupied. The timers are configurable to operate as a standalone timer or they can be wirelessly interconnected to provide remote temperature control using software.

The implementation cost and savings related to this ECM are presented in Appendix C and summarized below:

ECM-6 Smart Controller Window AC Units

Budgetary Cost		Annua	l Utility Savings		ROI	Potential Incentive*	Payback (without	Payback (with	
Cost	Electricity		Natural Gas	Total		incentive	incentive)	incentive)	
\$	kW kWh		Therms	\$		\$	Years	Years	
1,200	0 2,814		0	338	3.2	0	3.6	3.6	

^{*} Does not qualify for Incentive from the New Jersey SmartStart Program. See section 6.0 for other incentive opportunities

This measure is recommended.

5.3 ECM-9 Install VFDs and Premium Efficiency Motors on Air Handling Units

The existing 1.5 HP and 3.0 HP motors on the air handling units for the gymnasium and the Paul W. Rossey Library are not controlled by variable frequency drives (VFDs). Ideally fans are perfectly selected to match the needs of a system operating a maximum capacity. Most times 1) fans are over-sized somewhat for safety, and 2) the system is operating at less than full heating capacity. VFDs allow fans to run at slower RPMs to better meet the needs of the system and in the process, energy is saved.

To implement this ECM, the existing motors would be removed and new motors and VFDs installed in their place. Piping and wiring modifications would be needed.

The implementation cost and savings related to this ECM are presented in Appendix C and summarized below:

ECM-9 Install VFDs and Premium Efficiency Motors on Air Handling Units

Budgetary Cost		Annua	l Utility Savings		ROI	Potential Incentive*	Payback (without	Payback (with incentive)	
Cost	El	ectricity	Natural Gas	Total		incentive	incentive)		
\$	kW	kWh	Therms	\$		\$	Years	Years	
19,047	5.9	20,927	0	2,466	1.4	0	7.7	7.7	

^{*} Does not qualify for Incentive from the New Jersey SmartStart Program. See section 6.0 for other incentive opportunities.

This measure is recommended.

5.4 ECM-10 Replace RTUs

Several of the High School rooftop units (RTUs) contain DX cooling and natural gas heating and at 18-19 years old, are all at the end of their useful lives. It is recommended that these units be replaced with new models that will operate at a higher energy efficiency ratio (EER). This ECM assesses the replacement of each of the RTUs in question and gives the resulting energy savings.

It is assumed in the performance of this calculation that the operating hours, number of units, and capacity stays the same. Since the existing models are at the end of their useful lives and are in need of replacement, the energy savings result from the installation of high efficiency units over and above replacing the existing units with standard efficiency models.

The implementation cost and savings related to this ECM are presented in Appendix C and summarized below:

ECM-10 Replace RTUs

Budgetary		Annua	l Utility Savings		ROI	Potential Incentive*	Payback (without	Payback (with	
Cost	EI	ectricity	Natural Gas	Total		incentive	incentive)	incentive)	
\$	kW kWh		Therms	\$		\$	Years	Years	
47,800	0	5,886	0	706	(0.7)	0	67.7	67.7	

* Incentive shown is per the New Jersey SmartStart Program. See section 6.0 for other incentive opportunities.

This measure is recommended.

5.5 ECM-12 Retro-Commission Temperature Controls

The High School contains HVAC equipment of varying vintage. It is likely that many of these units have components such as dampers and sensors that have not been recently checked or calibrated. Commissioning is the process of verifying that systems are designed, installed, functionally tested, and capable of being operated and maintained according to the owner's operational needs. Retro-commissioning is the same systematic process applied to existing buildings.

Both controls and components of the heating and cooling systems present saving opportunities during the retro-commissioning process. Over time, temperature sensors or thermostats may drift out of synch. Poorly calibrated sensors can increase heating and cooling loads and lead to occupant discomfort. The following procedure is recommended:

- Calibrate the indoor and outdoor building sensors. Calibration of room thermostats, duct thermostats, humidistats, and pressure and temperature sensors should be in accordance with the original design specifications. Calibrating these controls may require specialized skills or equipment and may require outside expertise.
- Inspect damper and valve controls to verify proper functioning. Check pneumatically controlled dampers for leaks in the compressed-air hoses.
 Dampers should also be examined for proper opening and closing. Stiff dampers can cause improper modulation of the amount of outside air being used in the supply airstream. In some cases, dampers may be wired in a single position or disconnected, violating minimum outside air requirements.
- Review building operating schedules. HVAC controls must be adjusted to heat
 and cool the building properly during occupied hours. Occupancy schedules can
 change frequently over the life of a building, and control schedules should be
 adjusted accordingly. When the building is unoccupied, the temperature should
 be set back to save heating or cooling energy; however, minimal heating and
 cooling may be required when the building is unoccupied. In cold climates, for
 example, heating may be needed to keep water pipes from freezing.

The implementation cost and savings related to this ECM are presented in Appendix C and summarized below:

ECM-12 Retro-Commission Temperature Controls

Budgetary Cost		Annua	l Utility Savings		ROI	Potential Incentive*	Payback (without	Payback (with	
Cost	Electricity		Natural Gas	Total		incentive	incentive)	incentive)	
\$	kW kWh		Therms	\$	%	\$	Years	Years	
69,967	0	99,936	10,800	21,280	3.6	0	3.3	3.3	

^{*} Does not qualify for Incentive from the New Jersey SmartStart Program. See section 6.0 for other incentive opportunities

This measure is recommended.

5.6 ECM-14 Install Kitchen Hood Controller

The kitchen contains one 12'x4' (approximate size) range exhaust hood that is ducted and exhausted via exhaust fan EF-1 located on the roof. A rooftop unit supplies the make-up air for the kitchen.

Installing a variable speed hood control system was evaluated. Upon activation of the system, the hood lights will turn on and the fans reach a preset minimum speed of 10 and 50 percent. When cooking appliances are turned on, the fan speed will increase based on temperature sensed in the exhaust duct. During cooking, an optical sensor will sense particulates entering the hood and the speed will increase to 100 percent until smoke and heat are removed.

Energy saving is calculated from reduction of exhaust fan speed and the amount of heated air diffused from other heated rooms.

The implementation cost and savings related to this ECM are presented in Appendix C and summarized as follows:

ECM-14 Install Kitchen Hood Controller

Budgetary Cost		Annua	l Utility Savings		ROI	Potential Incentive*	Payback (without	Payback (with	
Cost	Electricity		Natural Gas	Total		incentive	incentive)	incentive)	
\$	kW	kWh	Therms	\$	%	\$	Years	Years	
30,787	0 227		6,848	5,917	1.9	0	5.2	5.2	

^{*} Does not qualify for Incentive from the New Jersey SmartStart Program. See section 6.0 for other incentive opportunities.

This measure is recommended.

5.7 ECM-15 Install Walk-in Cooler / Freezer Controls

One (1) large walk-in refrigerator keeps food at 40°F. Installing a walk-in cooler/ freezer control system was assessed. The system will monitor both dry and wet bulb temperature within the walk-in unit and allow evaporators and compressors to modulate up and down based on enthalpy set points rather than by dry bulb temperature alone. Savings is a result of reduced run time of evaporator fans, compressors and door heaters.

The implementation cost and savings related to this ECM are presented in Appendix C and summarized as follows:

ECM-15 Install Walk-in Cooler / Freezer Controls

Budgetary Cost		Annua	l Utility Savings		ROI	Potential Incentive*	Payback (without	Payback (with	
Cost	EI	ectricity	Natural Gas	Total		incentive	incentive)	incentive)	
\$	kW kWh		Therms	\$	%	\$	Years	Years	
20,625	0 1,431		0	172	(0.9)	0	120.1	120.1	

^{*} Incentive shown is per the New Jersey SmartStart Program. See section 6.0 for other incentive opportunities.

This measure is recommended.

5.8 ECM-17 Install Vending Misers

The building presently has two (2) cold beverage vending machines and one snack type vending machine in the building.

Vending machines operate continuously 24 hours per day, seven (7) days a week. Installing controls such as timers or occupancy sensors allow the machines to turn on only when a customer is present or when the compressor must run to maintain the product at the desired temperature. By implementing this measure electrical energy savings could be realized.

The calculation uses electrical consumption and annual electrical cost as the baseline, vs. the reduced electrical consumption and cost for the proposed case. The difference between the two values is the energy savings.

The implementation cost and savings related to this ECM are presented in Appendix C and summarized below:

ECM-17 Install Vending Misers

Budgetary Cost		Annua	l Utility Savings		ROI	Potential Incentive*	Payback (without	Payback (with	
Cost	Electricity		Natural Gas	Total		incentive	incentive)	incentive)	
\$	kW kWh		Therms	\$		\$	Years	Years	
840	0 7,343		0	881	14.7	0	1.0	1.0	

^{*} Incentive shown is per the New Jersey SmartStart Program. See section 6.0 for other incentive opportunities.

This measure is recommended.

5.9 ECM-L1 Lighting Replacement / Upgrades

Most of the lighting within this school is primarily 4' T8 linear fluorescent fixtures with electronic ballasts, and in most cases the number of lamps per fixture is two, three, or four. However a significant percentage of lighting (~15%) is still T12, particularly in: the older industrial arts wing, and some corridors. Compact fluorescents round out the remaining interior lights. Exterior lighting consists of both 38 watt PAR floodlights, and 150W metal halide wallpack lamps.

Overall energy consumption can be reduced by replacing inefficient bulbs and linear fluorescent bulbs with more efficient LED technology. To compute the annual savings for this ECM, the energy consumption of the current lighting fixtures was established and compared to the proposed fixture power requirement with the same annual hours of operation. The difference between the existing and proposed annual energy consumption was the energy savings. These calculations are based on 1 to 1 replacements of the fixtures, and do not take into account lumen output requirements for

a given space. A more comprehensive engineering study should be performed to determine correct lighting levels.

Supporting calculations, including assumptions for lighting hours and annual energy usage for each fixture, are provided in Appendix C and summarized below:

ECM-L1 Lighting Replacement / Upgrades

Budgetary Cost		Annua	l Utility Savings		ROI	Potential Incentive*	Payback (without	Payback (with incentive)	
Cost	Ele	ectricity	Natural Gas	Total		incentive	incentive)		
\$	kW	kWh	Therms	\$	%	\$	Years	Years	
454,693	103 242,071		0	31,345	(0.2)	10,000	14.5	14.2	

^{*} Incentive shown is per the New Jersey SmartStart Program. See section 6.0 for other incentive opportunities.

This measure is not recommended in lieu of ECM L3.

5.10 ECM-L2 Install Lighting Controls (Occupancy Sensors)

Lights in all of the newest areas are operated by occupancy sensors, in the older section of the school lights are controlled by manual switches.

Review of the comprehensive lighting survey determined that lighting in the older areas could benefit from installation of occupancy sensors to turn off lights when the areas are unoccupied.

This measure recommends installing occupancy sensors for the current lighting system. Using a process similar to that utilized in Section 5.7.1, the energy savings for this measure was calculated by applying the known fixture wattages in the space to the estimated existing and proposed times of operation for each fixture.

The implementation cost and savings related to this ECM are presented in Appendix C and summarized below:

ECM-L2 Install Lighting Controls (Occupancy Sensors)

Budgetary Cost		Annua	l Utility Savings		ROI	Potential Incentive*	Payback (without	Payback (with	
Cost	Electricity		Natural Gas	Total		incentive	incentive)	incentive)	
\$	kW kWh		Therms	\$	%	\$	Years	Years	
10,287	0 73,021		0	6,937	7.5	1,590	1.5	1.3	

^{*} Incentive shown is per the New Jersey SmartStart Program. See section 6.0 for other incentive opportunities.

This measure is not recommended in lieu of ECM L3.

5.11 ECM-L3 Lighting Replacements with Controls (Occupancy Sensors)

This measure is a combination of ECM-L1 and ECM-L2; recommending replace/upgrade the current lighting fixtures to more efficient ones and installing occupancy sensors on the new lights. Interactive effects of the higher efficiency lights and occupancy sensors lead the energy and cost savings for this measure to not be cumulative or equivalent to

the sum of replacing the lighting fixtures alone and installing occupancy sensors without the lighting upgrade. The implementation cost and savings related to this ECM are presented in Appendix C and summarized below:

ECM-L3 Lighting Replacements with Controls (Occupancy Sensors)

Budgetary Cost		Annua	l Utility Savings		ROI	Potential Incentive*	Payback (without	Payback (with	
Cost	Electricity		Natural Gas	Total		incentive	incentive)	incentive)	
\$	kW kWh		Therms	\$	%	\$	Years	Years	
464,980	103 273,215		0	34,304	(0.1)	11,590	13.6	13.2	

^{*} Incentive shown is per the New Jersey SmartStart Program. See section 6.0 for other incentive opportunities.

This measure is recommended.

5.12 Additional O&M Opportunities

This list of operations and maintenance (O&M) - type measures represent low-cost or no-cost opportunities, which if implemented will have a positive impact on the overall building operations, comfort and/or energy consumption. The recommended O&M measures for this building are as follows:

- Install Covers on Window Air Conditioners
- Clean Window AC filters before each season
- Wrap all exposed ductwork with high performance grade external insulation
- Set computers monitors to turn off and computers to sleep mode when not in use
- Look for the ENERGY STAR® label when purchasing Window AC units or Kitchen Appliances
- Disconnect unnecessary or unused small appliances and electronics when not in use to reduce phantom loads
- Train custodians to turn off lights and set HVAC temperatures to minimum levels when rooms are unoccupied
- Develop an Energy Master Plan to measure and track energy performance
- Educate students and staff about how their behavior affects energy use. Create student energy patrols to monitor and inform administration when energy is being wasted.
- During the winter, Custodians should ensure all windows are closed as part of cleaning routine

6.0 PROJECT INCENTIVES

6.1 Incentives Overview

The following sections give detailed information on available incentive programs including New Jersey Smart Start, Direct Install, New Jersey Pay for Performance (P4P) and Energy Savings Improvement Plan (ESIP). If the School District wishes to and is eligible to participate in the Energy Savings Improvement Plan (ESIP) program and/or the Pay for Performance Incentive Program (P4P), it cannot participate in either the Smart Start or Direct Install Programs. Refer to Appendix D for more information on the Smart Start program.

6.1.1 New Jersey Smart Start Program

For this energy audit, The New Jersey Smart Start Incentives are used in the energy savings calculations, where applicable. This program is intended for medium and large energy users and provides incentives for:

- Electric Chillers
- Gas Chillers
- Gas Heating
- Unitary HVAC
- Ground Source Heat Pumps
- Variable frequency Drives/ motors
- Refrigeration
- Prescriptive and performance lighting and lighting controls

The equipment is procured using a typical bid-build method, installed and paid for and then the incentives are reimbursed to the owner.

Refer to Appendix D for more information on the Smart Start program.

6.1.2 Direct Install Program

The Direct Install Program applies to smaller facilities that have a peak electrical demand of 200 kW or less in any of the previous 12 months. Buildings must be located in New Jersey and served by one of the state's public, regulated electric utility companies.

Direct Install is funded through New Jersey's Clean Energy Program and is designed to provide capital for building energy upgrade projects to fast track implementation. The program will pay up to 70% of the costs for lighting, HVAC, motors, refrigeration, and other equipment upgrades with higher efficiency alternatives. If a building is eligible for this funding, the Direct Install Program can reduce the implementation cost of energy conservation projects.

The Direct Install program has specific HVAC equipment and lighting requirements and is generally applicable only to smaller package HVAC units, small boilers and lighting retrofits.

The program pays a maximum amount of \$75,000 per building, and up to \$250,000 per customer per year. Installations must be completed by an approved Direct Install participating contractor, a list of which can be found on the New Jersey Clean Energy Website. Contractors will coordinate with the applicant to arrange installation of recommended measures identified in a previous energy assessment, such as this energy audit. The incentive is reimbursed to the owner upon successful replacement and payment of the equipment.

The building qualifies for this program because its electrical demand is less than the maximum peak electrical demand of 200 kW for the last 12 month period.

Refer to Appendix D for more information on this program.

6.1.3 New Jersey Pay For Performance Program (P4P)

The building may be eligible for incentives from the New Jersey Office of Clean Energy. The most significant incentives are available from the New Jersey Pay for Performance (P4P) Program. The P4P program is designed to offset the cost of energy conservation projects for facilities that pay the Societal Benefits Charge (SBC) and whose demand (kW) in any of the preceding 12 months exceeds 100 kW. This demand minimum has been waived for buildings owned by local governments or municipalities and non-profit organizations and *is not applicable to public schools*. Facilities that meet this criterion must also achieve a minimum performance target of 15% energy reduction by using the EPA Portfolio Manager benchmarking tool before and after implementation of the measure(s). Additionally, the overall return on investment (ROI) must exceed 10%. If the participant is a municipal electric company customer, and a customer of a regulated gas New Jersey Utility, only gas measures will be eligible under the Program. Available incentives are as follows:

Incentive #1: Energy Reduction Plan – This incentive is designed to offset the cost of services associated with the development of the Energy Reduction Plan (ERP). The ERP must include a detailed energy audit of the desired ECMs, energy savings calculations (using building modeling software) and inputting of all utility bills into the EPA Portfolio Manager website.

Incentive Amount: \$0.10/SFMinimum incentive: \$5,000

Maximum Incentive: \$50,000 or 50% of Facility annual energy cost

The standard incentive pays \$0.10 per square foot, up to a maximum of \$50,000, not to exceed 50% of facility annual energy cost, paid after approval of application. For building audits funded by the New Jersey Board of Public Utilities, which receive an initial 75% incentive toward performance of the energy audit, facilities are only eligible for an additional \$0.05 per square foot, up to a maximum of \$25,000, rather than the standard incentive noted above. The ERP must be completed by a Certified Energy Manager (CEM) and submitted along with the project application.

Incentive #2: Installation of Recommended Measures – This incentive is based on projected energy savings as determined in Incentive #1 (Minimum 15% savings must be achieved), and is paid upon successful installation of recommended measures.

<u>Electric</u>

- Base incentive based on 15% savings: \$0.09/ per projected kWh saved.
- For each % over 15% add: \$0.005 per projected kWh saved.
- Maximum incentive: \$0.11/ kWh per projected kWh saved.

<u>Gas</u>

- Base incentive based on 15% savings: \$0.90/ per projected Therm saved.
- For each % over 15% add: \$0.05 per projected Therm saved.
- Maximum incentive: \$1.25 per projected Therm saved.

Incentive cap: 25% of total project cost

Incentive #3: Post-Construction Benchmarking Report – This incentive is paid after acceptance of a report proving energy savings over one year utilizing the Environmental Protection Agency (EPA) Portfolio Manager benchmarking tool.

Electric

- Base incentive based on 15% savings: \$0.09/ per projected kWh saved.
- For each % over 15% add: \$0.005 per projected kWh saved.
- Maximum incentive: \$0.11/kWh per projected kWh saved.

<u>Gas</u>

- Base incentive based on 15% savings: \$0.90/ per projected Therm saved.
- For each % over 15% add: \$0.05 per projected Therm saved.
- Maximum incentive: \$1.25 per projected Therm saved.

Combining Incentives #2 and #3 will provide a total of \$0.18/ kWh and \$1.8/therm not to exceed 50% of total project cost. Additional Incentives for #2 and #3 are increased by \$0.005/kWh and \$0.05/therm for each percentage increase above the 15% minimum target to 20%, calculated with the EPA Portfolio Manager benchmarking tool, not to exceed 50% of total project cost.

For the purpose of demonstrating the eligibility of the ECM's to meet the minimum savings requirement of 15% annual savings and 10% ROI for the Pay for Performance Program, all ECM's identified in this report have been included in the incentive calculations The results for the building are shown in Appendix C, along with more detailed program information in appendix D.

6.1.4 Energy Savings Improvement Plan

The Energy Savings Improvement Program (ESIP) allows government agencies to make energy related improvements to their facilities and pay for the costs using the value of energy savings that result from the improvements. Under the recently enacted Chapter 4 of the Laws of 2009 (the law), the ESIP provides all government agencies in New Jersey with a flexible tool to improve and reduce energy usage with minimal expenditure of new financial resources.

ESIP allows local units to use "energy savings obligations" (ESO) to pay for the capital costs of energy improvements to their facilities. This can be done over a maximum term of 15 years. ESOs are not considered "new general obligation debt" of a local unit and

do not count against debt limits or require voter approval. They may be issued as refunding bonds or leases. Savings generated from the installation of energy conservation measures pay the principal of and interest on the bonds; for that reason, the debt service created by the ESOs is not paid from the debt service fund, but is paid from the general fund.

For local governments interested in pursuing an ESIP, the first step is to perform an energy audit. Pursuing a Local Government Energy Audit through New Jersey's Clean Energy Program is a valuable first step to the ESIP approach. The "Local Finance Notice" outlines how local governments can develop and implement an ESIP for their facilities. The ESIP can be prepared internally if the entity has qualified staff. If not, the ESIP must be implemented by an independent contractor and not by the energy savings company producing the Energy Reduction Plan.

The ESIP approach may not be appropriate for all energy conservation and energy efficiency improvements. Local units should carefully consider all alternatives to develop an approach that best meets their needs. Refer to Appendix D for more information on this program.

6.1.5 Renewable Energy Incentive Program

The Renewable Energy Incentive Program (REIP) is part of New Jersey's efforts to reach its Energy Master Plan goals of striving to use 30 percent of electricity from renewable sources by 2020.

Incentives for sustainable bio-power projects and for energy storage projects are currently under development, with competitive solicitations for each of those technologies expected to begin in the first quarter of 2014. The wind program is currently on hold.

New solar projects are no longer eligible for REIP incentives, but can register for Solar Renewable Energy Certificates (SRECs) through the SREC Registration Program (SRP).

7.0 ALTERNATIVE ENERGY SCREENING EVALUATION

7.1 Solar

7.1.1 ECM-S1 Photovoltaic Rooftop Solar Power Generation

The building was evaluated for the potential to install rooftop photovoltaic (PV) solar panels for power generation. Present technology incorporates the use of solar cell arrays that produce direct current (DC) electricity. This DC current is converted to alternating current (AC) with the use of an electrical device known as an inverter. The amount of available roof area determines how large of a solar array can be installed on any given roof. The table below summarizes the approximate roof area available on the building and the associated solar array size that can be installed.

Available Roof	Potential PV
Area	Array Size
(Ft ²)	(kW)
34,375	270

The PVWATTS solar power generation model was utilized to calculate PV power generation; this model is provided in Appendix E.

Installation of (PV) arrays in the state New Jersey will allow the owner to participate in the New Jersey Solar Renewable Energy Certificates Program (SREC). This is a program that has been set up to allow entities with large amounts of environmentally unfriendly emissions to purchase credits from zero emission (PV) solar-producers. An alternative compliance penalty (ACP) is paid for by the high emission producers and is set each year on a declining scale of 3% per year. One SREC credit is equivalent to 1000 kilowatt hours of PV electrical production; these credits can be traded for period of 15 years from the date of installation. Payments that will be received by the PV producer (school) will change from year to year dependent upon supply and demand. There is no definitive way to calculate an exact price that will be received by the PV producer for SREC credits over the next 15 years. Renewable Energy Consultants estimates an average of \$155/SREC for 2013 and this number was utilized in the cash flow for this report.

The system costs for PV installations were derived from recent solar contractor budgetary pricing in the state of New Jersey and include the total cost of the system installation (PV panels, inverters, wiring, ballast, controls). The cost of installation is currently about \$4.00 per watt or \$4,000 per kW of installed system, for a typical system. There are other considerations that have not been included in this pricing, such as the condition of the roof and need for structural reinforcement. Photovoltaic systems can be ground mounted if the roof is not suitable, however, this installation requires a substantial amount of open property (not wooded) and underground wiring, which adds more cost. PV panels have an approximate 20 year life span; however, the inverter device that converts DC electricity to AC has a life span of 10 to 12 years and will most likely need to be replaced during the useful life of the PV system.

The implementation cost and savings related to this ECM are presented in Appendix E and summarized as follows:

Photovoltaic (PV) Rooftop Solar Power Generation - 270 kW System

Budgetary Cost	Annual Utility Savings		Total Savings	New Jersey Renewable SREC	Payback (without SREC)	Payback (with SREC)	Recommended	
	Elec	tricity	Natural Gas					Ä
\$	kW	kWh	Therms	\$	\$	Years	Years	Y/N
1,080,000	270.0	351,900	0	42,192	61,583	25.6	10.4	FS

Note: CHA typically recommends a more detailed evaluation be conducted for the installation of PV Solar arrays when the screening evaluations shows a payback of less than 20 years. Therefore, this ECM is recommended for further study. Before implementation is pursued, the school district should consult with a certified solar PV contractor.

7.1.1 ECM-S2 Solar Thermal Hot Water Generation

Active solar thermal systems use solar collectors to gather the sun's energy to heat a fluid. An absorber in the collector (usually black colored piping) converts the sun's energy into heat. The heat is transferred to circulating water, antifreeze, or air for immediate use or is storage for later utilization. Applications for active solar thermal energy include supplementing domestic hot water, heating swimming pools, space heating or preheating air in residential and commercial buildings.

A standard solar hot water system is typically composed of solar collectors, heat storage vessel, piping, circulators, and controls. Systems are typically integrated to work alongside a conventional heating system that provides heat when solar resources are not sufficient. The solar collectors are usually placed on the roof of the building, oriented south, and tilted at the same angle as the site's latitude, to maximize the amount of solar radiation collected on a yearly basis.

Several options exist for using active solar thermal systems for space heating. The most common method is called a passive solar hot water system involves using glazed collectors to heat a liquid held in a storage tank (similar to an active solar hot water system described above which requires pumping). The most practical system would transfer the heat from the panels to thermal storage tanks and then use the pre-heated water for domestic hot water production. DHW is presently produced by natural gas fired water heaters and, therefore, this measure would offer natural gas utility savings. Unfortunately, the amount of domestic hot water that is currently used by this school is very small. Installing a solar domestic hot water system is not recommended due to the limited amount of domestic hot water presently consumed by the school.

This measure is not recommended.

7.2 Combined Heat and Power Plant

Combined heat and power (CHP), cogeneration, is self-production of electricity on-site with beneficial recovery of the heat byproduct from the electrical generator. Common CHP equipment includes reciprocating engine-driven, micro turbines, steam turbines,


and fuel cells. Typical CHP customers include industrial, commercial, institutional, educational institutions, and multifamily residential facilities. CHP systems that are commercially viable at the present time are sized approximately 50 kW and above, with numerous options in blocks grouped around 300 kW, 800 kW, 1,200 kW and larger. Typically, CHP systems are used to produce a portion of the electricity needed by a facility some or all of the time, with the balance of electric needs satisfied by purchase from the grid.

Any proposed CHP project will need to consider many factors, such as existing system load, use of thermal energy produced, system size, natural gas fuel availability, and proposed plant location. The building has sufficient need for electrical generation and the ability to use most of the thermal byproduct during the winter; however thermal usage during the summer months does not exist. Thermal energy produced by the CHP plant in the warmer months will be wasted. An absorption chiller could be installed to utilize the heat to produce chilled water; however, there is no chilled water distribution system in the building. CHP is not recommended due to the building's limited summer thermal demand.

This measure is not recommended.

7.3 Wind Powered Turbines

Wind power is the conversion of kinetic energy from wind into mechanical power that is used to drive a generator which creates electricity by means of a wind turbine. A wind turbine consists of rotor and blades connected to a gearbox and generator that are mounted onto a tower. Newer wind turbines also use advanced technology to generate electricity at a variety of frequencies depending on the wind speed, convert it to DC and then back to AC before sending it to the grid. Wind turbines range from 50 – 750 kW for utility scale turbines down to below 50 kW for residential use. On a scale of 1 (the lowest) to 7 (the highest), Class 3 and above (wind speeds of 13 mph or greater) are generally considered "good wind resource" according to the Wind Energy Development Programmatic EIS Information Center hosted by the Bureau of Land Management. According to the map below, published by NREL, Newark, NJ is classified as Class 1 at 50m, meaning the city would not be a good candidate for wind power.



This measure is not recommended.

7.4 Demand Response Curtailment

Presently, electricity is delivered by PSE&G, which receives the electricity from regional power grid RFC. PSE&G is the regional transmission organization (RTO) that coordinates the movement of wholesale electricity in all or parts of 13 states and the District of Columbia including the State of New Jersey.

Utility Curtailment is an agreement with the utility provider's regional transmission organization and an approved Curtailment Service Provider (CSP) to shed electrical load by either turning major equipment off or energizing all or part of a facility utilizing an emergency generator; therefore, reducing the electrical demand on the utility grid. This program is to benefit the utility company during high demand periods and utility provider offers incentives to the CSP to participate in this program. Enrolling in the program will require program participants to drop electrical load or turn on emergency generators during high electrical demand conditions or during emergencies. Part of the program also will require that program participants reduce their required load or run emergency generators with notice to test the system.

A pre-approved CSP will require a minimum of 100 kW of load reduction to participate in any curtailment program. From March 2013 through February 2014 the following table summarizes the electricity load profile for the building.

Building Electric Load Profile

			Onsite		
Peak Demand	Min Demand	Avg Demand	Generation	Eligible? Y/N	
kW	kW	kW	Y/N	Y/N	
862.7	485.4	581.3	N	N	

This measure is not recommended because the building does not have adequate load to meet the required minimum load reduction.

8.0 CONCLUSIONS & RECOMMENDATIONS

The LGEA energy audit conducted by CHA for the building identified potential annual savings of \$66,362/yr with an overall payback of 11.5 years, if the recommended ECMs are implemented.

The potential annual energy and cost savings are shown in the following table.

Electric Savings (kWh)	Natural Gas Savings (therms)	Total Savings (\$)	Payback (years)	
411,778	17,994	66,362	9.9	

The following projects should be considered for implementation:


- Replace Door Sweeps and Seals
- Install Window A/C Controller
- Install Variable Frequency Drives
- Replace HVAC Rooftop Units
- Retro-Commission Temperature Controls
- Kitchen Hood Controller
- Install Walk-In Cooler / Freezer Controls
- Install Vending Misers
- Lighting Replacement / Upgrades
- Install Lighting Controls (Occupancy Sensors)
- Lighting Replacements with Controls (Occupancy Sensors)

The following alternative energy measures are recommended for further study:

• Photovoltaic (PV) Rooftop Solar Power Generation – 270 kW System

If NPS implements the recommended ECMs, energy savings would be as follows:

	Existing Conditions	Post Recommended ECMs	Percent Savings
Costs (\$)	354,927	288,565	19%
Electricity (kWh)	2,220,800	1,809,022	19%
Natural Gas (therms)	80,896	62,902	22%
Site EUI (kbtu/SF/Yr)	77.6	61.7	





Annual Utilities

12-month Summary

El	ectric			
Annual Usage	2,220,800	kWh/yr		
Annual Cost	266,271	\$		
Blended Rate	0.120	\$/kWh		
Consumption Rate	0.095	\$/kWh		
Demand Rate	6.78	\$/kW		
Peak Demand	862.7	kW		
Min. Demand	485.4	kW		
Avg. Demand	581.3	kW		
	Natı	ıral Gas		
Account Number	PG000008137005858622	PG000008137006658622	PG000008137007458622	
Annual Usage	4,090	74,333	24,673	therms/yr
Annual Cost	3,697	62952	22007	\$
Rate	0.904	0.847	0.892	\$/therm
V	/ater			
Annual Usage	2,308,000	gallons/yr		
Annual Cost	20,466	\$		
Rate	0.009	\$/gallon		

Utility Bills: Account Numbers

Account Number	School Building	<u>Location</u>	Type Notes
100 004 697 544	Millburn High School	462 Millburn Avenue, Millburn, NJ 07041	Electricity
8137005858622	Millburn High School	462 Millburn Avenue, Millburn, NJ 07041	Natural Gas
8137006658622	Millburn High School	462 Millburn Avenue, Millburn, NJ 07041	Natural Gas
8137007458622	Millburn High School	462 Millburn Avenue, Millburn, NJ 07041	Natural Gas
1018-210025955098	Millburn High School	462 Millburn Avenue, Millburn, NJ 07041	Water

For Service at: Millburn High School Account No.: 100 004 697 544

G28133686

Meter No.: **Electric Service** Delivery -Jersey Central Power & Light Jersey Central Power & Light Supplier -


				Provider Charges	3	Usage (kWh) vs. Dema	ind (kW) Charges		Unit Costs	
	Consumption	Demand	Delivery	Supplier	Total	Consumption	Demand	Blended Rate	Consumption	Demand
Month	(kWh)	(kW)	(\$)	(\$)	(\$)	(\$)	(\$)	(\$/kWh)	(\$/kWh)	(\$/kW)
December-12	147520	620.5			16519.92	12,569.98	3949.94	0.11	0.09	6.37
January-13	136960	745.6			16355.15	11,595.82	4759.33	0.12	0.08	6.38
February-13	243520	541.4			24006.11	20,567.95	3438.16	0.10	0.08	6.35
March-13	200960	546.9			23998.26	20,524.52	3473.74	0.12	0.10	6.35
April-13	155520	546.9			16632.26	13,158.52	3473.74	0.11	0.08	6.35
May-13	198720	802.2			24726.75	19,228.88	5497.87	0.12	0.10	6.85
June-13	238720	846.4			28890.22	23,085.60	5804.62	0.12	0.10	6.86
July-13	180160	678.7			22080.14	17,439.36	4640.78	0.12	0.10	6.84
August-13	172160	745.9			21775.16	16,668.01	5107.15	0.13	0.10	6.85
September-13	190720	862.7			23972.48	18,455.51	5516.97	0.13	0.10	6.40
October-13	176960	679.4			21475.26	17,144.24	4331.02	0.12	0.10	6.37
November-13	220480	620.5			25294.73	21,344.79	3949.94	0.11	0.10	6.37
December-13	143040	609.6			17703.78	12,899.27	4804.51	0.12	0.09	7.88
January-14	167680	609.6			19882.46	15,119.28	4763.18	0.12	0.09	7.81
February-14	175680	485.4			19839.33	16,763.49	3075.84	0.11	0.10	6.34
Total (All)	2,748,800	862.70	\$0.00	\$0.00	\$323,152.01	\$256,565.22	\$66,586.79	\$0.12	\$0.09	\$6.70
Total (last 12-months)	2,220,800	862.70	\$0.00	\$0.00	\$266,270.83	\$211,831.47	\$54,439.36	\$0.12	\$0.10	\$6.78

1.) Number of kWh of electric energy used per month

- 2.) Number of kW of power measured
- Number of kW of power measured
 Delivery provider
 Electric charges from Supply provider

- 5.) Total charges (Delivery + Supplier)6.) Charges based on the number of kWh of electric energy used
- 7.) Charges based on the number of kW of power measured 8.) Total Charges (\$) / Consumption (kWh)
- 9.) Consumption Charges (\$) / Consumption (kWh)
- 10.) Demand Charges (\$) / Demand (kW)

No data provided, most recent rate used No data provided, interpolated value




For Service at: Millburn High School
Account No.: PG000008137005858622

Meter No:

Natural Gas Service Delivery - PSE&G Supplier - Compass

		Charges					Unit Costs						
Month	Consumption (Therms)	D	elivery (\$)	,	Supply (\$)		Total (\$)		elivery 'I herm)		Supply Therm)	(\$/	Total Therm)
April-13	473	\$	171.52	\$	255.87	\$	427.39	\$	0.363	\$	0.541	\$	0.904
May-13	272	\$	103.33	\$	147.00	\$	250.33	\$	0.380	\$	0.540	\$	0.920
June-13	250	\$	96.20	\$	136.10	\$	232.30	\$	0.385	\$	0.544	\$	0.929
July-13	136	\$	57.79	\$	76.22	\$	134.01	\$	0.425	\$	0.560	\$	0.985
August-13	76	\$	37.41			\$	37.41	\$	0.492	\$	-	\$	0.492
September-13	53	\$	29.46	\$	41.86	\$	71.32	\$	0.556	\$	0.790	\$	1.346
October-13	226	\$	88.76	\$	24.10	\$	112.86	\$	0.393	\$	0.107	\$	0.499
November-13	260	\$	114.83	\$	115.86	\$	230.69	\$	0.442	\$	0.446	\$	0.887
December-13	459	\$	200.86	\$	204.51	\$	405.37	\$	0.438	\$	0.446	\$	0.883
January-14	543	\$	238.71	\$	253.41	\$	492.12	\$	0.440	\$	0.467	\$	0.906
February-14	635	\$	273.62	\$	320.80	\$	594.42	\$	0.431	\$	0.505	\$	0.936
March-14	707	\$	298.76	\$	409.75	\$	708.51	\$	0.423	\$	0.580	\$	1.002
Total	4,090					\$	3,696.73					\$	0.904




For Service at: Millburn High School Account No.: PG000008137006658622

Meter No:

Natural Gas Service Delivery - PSE&G Supplier - Compass

		Charges						Uı	nit Costs		
Month	Consumption (Therms)	Delivery (\$)		Supply (\$)		Total (\$)	Delivery 5/ I herm)		Supply 5/ I nerm)	(\$	Total (Therm)
April-13	10,935	\$ 1,302.51	\$	5,983.02	\$	7,285.53	\$ 0.119	\$	0.547	\$	0.666
May-13	3,820	\$ 544.87	\$	2,090.51	\$	2,635.38	\$ 0.143	\$	0.547	\$	0.690
June-13	548	\$ 181.42	\$	299.42	\$	480.84	\$ 0.331	\$	0.546	\$	0.877
July-13	431	\$ 166.17	\$	234.09	\$	400.26	\$ 0.386	\$	0.543	\$	0.929
August-13	0	\$ 104.24	\$	-	\$	104.24	#DIV/0!		#DIV/0!	#	:DIV/0!
September-13	619	\$ 193.25	\$	-	\$	193.25	\$ 0.312	\$	-	\$	0.312
October-13	326	\$ 151.00	\$	280.67	\$	431.67	\$ 0.463	\$	0.861	\$	1.324
November-13	1,592	\$ 2,250.17	\$	709.29	\$	2,959.46	\$ 1.413	\$	0.446	\$	1.859
December-13	8,305	\$ 3,683.70	\$	3,697.36	\$	7,381.06	\$ 0.444	\$	0.445	\$	0.889
January-14	12,328	\$ 4,547.14	\$	5,752.96	\$	10,300.10	\$ 0.369	\$	0.467	\$	0.836
February-14	17,092	\$ 5,478.05	\$	8,625.65	\$	14,103.70	\$ 0.321	\$	0.505	\$	0.825
March-14	18,337	\$ 6,061.63	\$	10,614.90	\$	16,676.53	\$ 0.331	\$	0.579	\$	0.909
Total	74,333				\$	62,952.02				\$	0.847




For Service at: Millburn High School Account No.: PG000008137007458622

Meter No:

Natural Gas Service Delivery - PSE&G Supplier - Compass

		Charges					Unit Costs					
Month	Consumption (Therms)	Delivery (\$)		Supply (\$)		Total (\$)		Delivery 5/ I herm)		Supply / I herm)	(\$	Total / I herm)
April-13	3,833	\$ 546.21	\$	2,095.96	\$	2,642.17	\$	0.143	\$	0.547	\$	0.689
May-13	1,461	\$ 293.63	\$	800.27	\$	1,093.90	\$	0.201	\$	0.548	\$	0.749
June-13	509	\$ 175.93	\$	277.64	\$	453.57	\$	0.346	\$	0.545	\$	0.891
July-13			\$	21.77	\$	21.77	:	#DIV/0!	#	#DIV/0!	7	#DIV/0!
August-13	0	\$ 104.24			\$	104.24	:	#DIV/0!	#	#DIV/0!	7	#DIV/0!
September-13	2	\$ 104.54	\$	-	\$	104.54	\$	52.270	\$	-	\$	52.270
October-13	60	\$ 112.94	\$	0.95	\$	113.89	\$	1.882	\$	0.016	\$	1.898
November-13	396	\$ 857.47	\$	176.38	\$	1,033.85	\$	2.165	\$	0.445	\$	2.611
December-13	2,825	\$ 1,397.52	\$	1,257.73	\$	2,655.25	\$	0.495	\$	0.445	\$	0.940
January-14	4,185	\$ 1,689.48	\$	1,953.12	\$	3,642.60	\$	0.404	\$	0.467	\$	0.870
February-14	5,681	\$ 1,980.12	\$	2,867.05	\$	4,847.17	\$	0.349	\$	0.505	\$	0.853
March-14	5,721	\$ 1,982.24	\$	3,312.06	\$	5,294.30	\$	0.346	\$	0.579	\$	0.925
Total	24,673				\$	22,007.25					\$	0.892




For Service at: Millburn High School Account No.: 1018-210025955098

Meter No.: 60768167

Water & Sewer Service Delivery - New Jersey American Water

Supplier -

Month	Total (\$)	Gallons	\$/Gallon
Mar-13	\$ 2,867.56	354000	\$ 0.008
Apr-13	\$ 2,313.09	281000	\$ 0.008
May-13	\$ 3,063.64	385000	\$ 0.008
Jun-13	\$ 2,794.23	343000	\$ 0.008
Jul-13	\$ 1,495.11	162000	\$ 0.009
Aug-13	\$ 2,406.26	281000	\$ 0.009
Sep-13	\$ 3,371.40	431000	\$ 0.008
Oct-13	\$ 386.92	20000	\$ 0.019
Nov-13	\$ 443.13	15000	\$ 0.030
Dec-13	\$ 435.08	11000	\$ 0.040
Jan-14	\$ 447.84	13000	\$ 0.034
Feb-14	\$ 441.46	12000	\$ 0.037
Total	\$ 20,465.72	2308000	0.009



JCP&L SERVICE TERRITORY

Last Updated: 10/24/12

$*\underline{CUSTOMER\ CLASS} - R - RESIDENTIAL\ C - COMMERCIAL\ I - INDUSTRIAL$

Supplier	Telephone & Web Site	*Customer Class
AEP Energy, Inc. 309 Fellowship Road, Fl.2 Mount Laurel, NJ 08054	(866) 258-3782 www.aepenergy.com	C/I ACTIVE
Alpha Gas and Electric, LLC 641 5th Street Lakewood, NJ 08701	(855) 553-6374 www.alphagasandelectric.com	R/C ACTIVE
Ambit Northeast, LLC 103 Carnegie Center Suite 300 Princeton, NJ 08540	(877) 30-AMBIT (877) 302-6248 www.ambitenergy.com	R/C ACTIVE
AP Gas & Electric, LLC 10 North Park Place, Suite 420 Morristown, NJ 07960	(855) 544-4895 www.apge.com	R/C/I ACTIVE
Astral Energy LLC 16 Tyson Place Bergenfield, NJ 07621	(201) 384-5552 www.astralenergyllc.com	R/C/I ACTIVE
BBPC, LLC d/b/a Great Eastern Energy 116 Village Blvd. Suite 200 Princeton, NJ 08540	(888) 651-4121 www.greateasternenergy.com	C/I ACTIVE
Champion Energy Services, LLC 72 Avenue L Newark, NJ 07105	(877) 653-5090 www.championenergyservices.com	R/C/I ACTIVE
Choice Energy, LLC 4257 US Highway 9, Suite 6C Freehold, NJ 07728	888-565-4490 www.4choiceenergy.com	R/C ACTIVE
Clearview Electric, Inc. 505 Park Drive Woodbury, NJ 08096	(888) CLR-VIEW (800) 746-4702 www.clearviewenergy.com	R/C/I ACTIVE
Commerce Energy, Inc. 7 Cedar Terrace Ramsey, NJ 07446	1-866-587-8674 www.commerceenergy.com	R ACTIVE
ConEdison Solutions Cherry Tree Corporate Center 535 State Highway Suite 180 Cherry Hill, NJ 08002	(888) 665-0955 www.conedsolutions.com	C/I ACTIVE
Constellation NewEnergy, Inc. 900A Lake Street, Suite 2 Ramsey, NJ 07446	(866) 237-7693 www.constellation.com	R/C/I ACTIVE
Constellation Energy 900A Lake Street, Suite 2 Ramsey, NJ 07446	(877) 997-9995 www.constellation.com	R ACTIVE
Direct Energy Business, LLC 120 Wood Avenue Suite 611 Iselin, NJ 08830	(888) 925-9115 www.directenergybusiness.com	C/I ACTIVE

Direct Energy Services, LLC	(866) 547-2722	C/I
120 Wood Avenue	www.directenergy.com	ACTIVE
Suite 611	www.uncetenergy.com	ACTIVE
Iselin, NJ 08830		
Discount Energy Group, LLC	(800) 282-3331	R/C ACTIVE
811 Church Road, Suite 149	www.discountenergygroup.com	We herry E
Cherry Hill, NJ 08002	www.discodiffenergygroup.com	
Dominion Retail, Inc. d/b/a Dominion Energy	(866) 275-4240	R/C
Solutions	www.dom.com/products	ACTIVE
395 Route 70 West, Suite 125	www.dom.com products	Merry E
Lakewood, NJ 08701		
DTE Energy Supply, Inc.	(877) 332-2450 www.dtesupply.com	C/I ACTIVE
One Gateway Center,	(877) 332-2430 <u>www.utcsuppry.com</u>	CHACIIVE
Suite 2600		
Newark, NJ 07102		
	(977) 966 9192	D/C
Energy Plus Holdings LLC	(877) 866-9193	R/C
309 Fellowship Road	www.energypluscompany.com	ACTIVE
East Gate Center, Suite 200		1
Mt. Laurel, NJ 08054	(0.5.5) 2.42	
Energy.me Midwest LLC	(855) 243-7270 <u>www.energy.me</u>	R/C/I
90 Washington Blvd		ACTIVE
Bedminster, NJ 07921		
Ethical Electric Benefit Co. d/b/a Ethical Electric	(888) 444-9452	R/C ACTIVE
100 Overlook Center, 2nd Fl.	www.ethicalelectric.com	
Princeton, NJ 08540		
FirstEnergy Solutions Corp.	(800) 977-0500	C/I
300 Madison Avenue	www.fes.com	ACTIVE
Morristown, NJ 07962		
Gateway Energy Services	(800) 805-8586	R/C/I
Corp.	www.gesc.com	ACTIVE
44 Whispering Pines Lane		
Lakewood, NJ 08701		
GDF SUEZ Energy Resources	(866) 999-8374	C/I
NA, Inc.	www.gdfsuezenergyresources.com	ACTIVE
333 Thornall Street		
Sixth Floor		
Edison, NJ 08819		
Glacial Energy of New Jersey, Inc.	(888) 452-2425	C/I
75 Route 15 Building E	www.glacialenergy.com	ACTIVE
Lafayette, NJ 07848		
Green Mountain Energy	(866) 767-5818	C/I
Company	www.greenmountain.com/commercial-	ACTIVE
211 Carnegie Center Drive	home	
Princeton, NJ 08540	<u></u>	1
Hess Corporation	(800) 437-7872	C/I
1 Hess Plaza	www.hess.com	ACTIVE
Woodbridge, NJ 07095	www.ness.com	ACTIVE
HIKO Energy, LLC	(888) 264-4908	R/C
655 Suffern Road	(888) 204-4908 www.hikoenergy.com	ACTIVE
Teaneck, NJ 07666	www.mkoenergy.com	ACTIVE
	(977) 200 7155	B/07
HOP Energy, LLC d/b/a Metro Energy, HOP Fleet	(877) 390-7155 <u>www.hopenergy.com</u>	R/C/I
Fueling, HOP Energy Fleet Fueling		ACTIVE
1011 Hudson Avenue		
Ridgefield, NJ 07657		
		<u> </u>

IDT Energy, Inc.	(973) 438-4380	R/C
550 Broad Street	www.idtenergy.com	ACTIVE
Newark, NJ 07102	www.indebielgy.com	11011,2
Independence Energy Group, LLC	(877) 235-6708	R/C ACTIVE
211 Carnegie Center	www.chooseindependence.com	INC ACTIVE
Princeton, NJ 08540	www.enoosemacpenaence.com	
Integrys Energy Services, Inc.	(877) 763-9977	C/I
99 Wood Ave, South, Suite 802	www.integrysenergy.com	ACTIVE
Iselin, NJ 08830	www.megryschergy.com	ACTIVE
Liberty Power Delaware, LLC	(866) 769-3799	R/C/I
3000 Atrium Way	www.libertypowercorp.com	ACTIVE
Suite 273	www.nbertypowercorp.com	ACTIVE
Mt. Laurel, NJ 08054		
· ·	(966) 760 2700	D/C/I
Liberty Power Holdings, LLC 3000 Atrium Way	(866) 769-3799	R/C/I ACTIVE
Suite 273	www.libertypowercorp.com	ACTIVE
Mt. Laurel, NJ 08054		
,	(200) 247 244	G (T
Linde Energy Services	(800) 247-2644	C/I
575 Mountain Avenue	www.linde.com	ACTIVE
Murray Hill, NJ 07974		
Marathon Power LLC	(888) 779-7255	R/C/I
302 Main Street	www.mecny.com	ACTIVE
Paterson, NJ 07505		
NATGASCO, Inc.	(973) 678-1800 x. 251	R/C
532 Freeman St.	www.supremeenergyinc.com	ACTIVE
Orange, NJ 07050		
NextEra Energy Services New	(877) 528-2890 Commercial	R/C/I
Jersey, LLC	(800) 882-1276 Residential	ACTIVE
651 Jernee Mill Road	www.nexteraenergyservices.com	
Sayreville, NJ 08872		
NJ Gas & Electric	(866) 568-0290	R/C/I
1 Bridge Plaza fl.2	www.NJGandE.com	ACTIVE
Fort Lee, NJ 07024		
Noble Americas Energy	(877) 273-6772	C/I
Solutions	www.noblesolutions.com	ACTIVE
The Mac-Cali Building		
581 Main Street, 8th Floor		
Woodbridge, NJ 07095		
North American Power and	(888) 313-9086	R/C/I
Gas, LLC	www.napower.com	ACTIVE
222 Ridgedale Ave.	www.mapower.com	, ACTIVE
Cedar Knolls, NJ 07927		
Palmco Power NJ, LLC	(877) 726-5862	R/C/I
One Greentree Centre	www.PalmcoEnergy.com	ACTIVE
10,000 Lincoln Drive East, Suite 201	www.rameoEnergy.com	ACTIVE
Marlton, NJ 08053		
	(800) ENERGY-9 (363-7499)	R/C
Pepco Energy Services, Inc. 112 Main St.	www.pepco-services.com	ACTIVE
Lebanon, NJ 08833	www.pepco-services.com	ACTIVE
	(055) 22 DOWED (76027)	D/C/Z
Plymouth Rock Energy, LLC	(855) 32-POWER (76937)	R/C/I
338 Maitland Avenue	www.plymouthenergy.com	ACTIVE
Teaneck, NJ 07666	(000) 201 2000	O/F 4 C/F
PPL EnergyPlus, LLC	(800) 281-2000	C/I ACTIVE
811 Church Road	www.pplenergyplus.com	
Cherry Hill, NJ 08002		

Public Power & Utility of New	(888) 354-4415	R/C/I
Jersey, LLC	www.ppandu.com	ACTIVE
39 Old Ridgebury Rd. Suite 14	www.ppanau.com	HOTTVE
Danbury, CT 06810		
Reliant Energy	(877) 297-3795 (877) 297-3780	R/C/I
211 Carnegie Center	www.reliant.com/pjm	ACTIVE
Princeton, NJ 08540	www.monanteesna.pjiii	1101112
ResCom Energy LLC	(888) 238-4041	R/C/I
18C Wave Crest Ave.	http://rescomenergy.com	ACTIVE
Winfield Park, NJ 07036	<u>intprivescomencing jucom</u>	1101112
Respond Power LLC	(877) 973-7763	R/C/I
10 Regency CT	www.respondpower.com	ACTIVE
Lakewood, NJ 08701	······································	1101112
South Jersey Energy	(800) 800-266-6020	C/I
Company	www.southjerseyenergy.com	ACTIVE
1 South Jersey Plaza	www.soudigerseyenergy.com	1101112
Route 54		
Folsom, NJ 08037		
Sperian Energy Corp.	(888) 682-8082	R/C/I
1200 Route 22 East, Suite 2000	(000) 002-0002	ACTIVE
Bridgewater, NJ 08807		ACTIVE
Bridge water, 110 00007		
Starion Energy PA Inc.	(800) 600-3040	R/C/I
101 Warburton Avenue	www.starionenergy.com	ACTIVE
Hawthorne, NJ 07506		
Stream Energy	(877) 369-8150	R
309 Fellowship Road	www.streamenergy.net	ACTIVE
Suite 200		
Mt. Laurel, NJ 08054		
UGI Energy Services, Inc. d/b/a GASMARK	(856) 273-9995	C/I
224 Strawbridge Drive	www.ugienergyservices.com	ACTIVE
Suite 107		
Moorestown, NJ 08057		
Verde Energy USA, Inc.	(800) 388-3862	R/C/I
50 East Palisades Avenue	www.lowcostpower.com	ACTIVE
Englewood, NJ 07631		
Viridian Energy	(866) 663-2508	R/C/I
2001 Route 46	www.viridian.com	ACTIVE
Waterview Plaza		
Suite 310		
Parsippany, NJ 07054		
Xoom Energy New Jersey, LLC	(888)997-8979	R/C/I
744 Broad Street	www.xoomenergy.com	ACTIVE
Newark, NJ 07102		
YEP Energy	(855) 363-7736 <u>www.yepenergyNJ.com</u>	R/C/I
89 Headquarters Plaza North		ACTIVE
#1463		
Morristown, NJ 07960		
Your Energy Holdings, LLC One International	(855) 732-2493	R/C/I
Boulevard Suite 400	www.thisisyourenergy.com	ACTIVE
Mahwah, NJ 07495-0400		

PSE&G GAS SERVICE TERRITORY Last Updated: 10/24/12

$*\underline{CUSTOMER\ CLASS} - R - RESIDENTIAL\ C - COMMERCIAL\ I - INDUSTRIAL$

Supplier	Telephone & Web Site	*Customer Class
Ambit Northeast, LLC 103 Carnegie Center Suite 300	(877)-30-AMBIT (877) 302-6248	R/C
Princeton, NJ 08540	www.ambitenergy.com	ACTIVE
Astral Energy LLC 16 Tyson Place Bergenfield, NJ 07621	888-850-1872 www.astralenergyllc.com	R/C/I ACTIVE
BBPC, LLC Great Eastern Energy 116 Village Blvd. Suite 200	888-651-4121	C/I
Princeton, NJ 08540	www.greateasternenergy.com	ACTIVE
Clearview Electric Inc. d/b/a Clearview Gas 1744 Lexington Ave.	800-746-4720	R/C
Pennsauken, NJ 08110	www.clearviewenergy.com	ACTIVE
Colonial Energy, Inc. 83 Harding Road	845-429-3229	C/I
Wyckoff, NJ 07481	www.colonialgroupinc.com	ACTIVE
Commerce Energy, Inc. 7 Cedar Terrace	(888) 817-8572	R
Ramsey, NJ 07746	www.commerceenergy.com	ACTIVE
Compass Energy Services, Inc. 1085 Morris Avenue, Suite 150 Union, NJ 07083	866-867-8328 908-638-6605 <u>www.compassenergy.net</u>	C/I ACTIVE
ConocoPhillips Company 224 Strawbridge Drive, Suite 107	800-646-4427	C/I
Moorestown, NJ 08057	www.conocophillips.com	ACTIVE
Consolidated Edison Energy, Inc. d/b/a Con Edison Solutions 535 State Highway 38, Suite 140	888-686-1383 x2130 www.conedenergy.com	
Cherry Hill, NJ 08002	www.concucrergy.com	

Consolidated Edison Solutions, Inc.	888-665-0955	C/I
Cherry Tree Corporate Center 535 State Highway 38, Suite 140 Cherry Hill, NJ 08002	www.conedsolutions.com	ACTIVE
Constellation NewEnergy-Gas	(800) 900-1982	C/I
Division, LLC 900A Lake Street, Suite 2 Ramsey, NJ 07466	www.constellation.com	ACTIVE
Direct Energy Business, LLC	888-925-9115	C/I
120 Wood Avenue, Suite 611 Iselin, NJ 08830	www.directenergy.com	ACTIVE
Direct Energy Services, LLP	866-348-4193	R
120 Wood Avenue, Suite 611 Iselin, NJ 08830	www.directenergy.com	ACTIVE
Gateway Energy Services Corp.	800-805-8586	R/C/I
44 Whispering Pines Lane Lakewood, NJ 08701	www.gesc.com	ACTIVE
UGI Energy Services, Inc.	856-273-9995	C/I
d/b/a GASMARK 224 Strawbridge Drive, Suite 107 Moorestown, NJ 08057	www.ugienergyservices.com	ACTIVE
Global Energy Marketing, LLC	800-542-0778	C/I
129 Wentz Avenue Springfield, NJ 07081	www.globalp.com	ACTIVE
Great Eastern Energy	888-651-4121	C/I
116 Village Blvd., Suite 200 Princeton, NJ 08540	www.greateastern.com	ACTIVE
Greenlight Energy	718-204-7467	С
330 Hudson Street, Suite 4 Hoboken, NJ 07030	www.greenlightenergy.us	ACTIVE
Hess Energy, Inc.	800-437-7872	C/I
One Hess Plaza Woodbridge, NJ 07095	www.hess.com	ACTIVE
Hess Small Business Services, LLC One Hess Plaza	888-494-4377	C/I
Woodbridge, NJ 07095	www.hessenergy.com	ACTIVE
HIKO Energy, LLC 655 Suffern Road	(888) 264-4908	R/C
Teaneck, NJ 07666	www.hikoenergy.com	ACTIVE

Hudson Energy Services, LLC 7 Cedar Street	877- Hudson 9	С
Ramsey, NJ 07446	www.hudsonenergyservices.com	ACTIVE
IDT Energy, Inc.	877-887-6866	R/C
550 Broad Street Newark, NJ 07102	www.idtenergy.com	ACTIVE
Integrys Energy Services – Natural	800-536-0151	C/I
Gas, LLC 99 Wood Avenue South		
Suite #802 Iselin, NJ 08830	www.integrysenergy.com	ACTIVE
Intelligent Energy	800-927-9794	R/C/I
2050 Center Avenue, Suite 500 Fort Lee, NJ 07024	www.intelligentenergy.org	ACTIVE
Keil & Sons, Inc.	1-877-797-8786	R/C/I
d/b/a Systrum Energy 1 Bergen Blvd.		
Fairview, NJ 07022	www.systrumenergy.com	ACTIVE
Major Energy Services, LLC 10 Regency CT	888-625-6760	R/C/I
Lakewood, NJ 08701	www.majorenergy.com	ACTIVE
Marathon Power LLC	888-779-7255	R/C/I
302 Main Street Paterson, NJ 07505	www.mecny.com	ACTIVE
Metromedia Energy, Inc.	800-828-9427	С
6 Industrial Way Eatontown, NJ 07724	www.metromediaenergy.com	ACTIVE
Metro Energy Group, LLC	888-53-Metro	R/C
14 Washington Place Hackensack, NJ 07601	www.metroenergy.com	ACTIVE
MxEnergy, Inc.	800-758-4374	R/C/I
900 Lake Street Ramsey, NJ 07446	www.mxenergy.com	ACTIVE
NATGASCO (Mitchell Supreme) 532 Freeman Street	800-840-4GAS	С
Orange, NJ 07050	www.natgasco.com	ACTIVE
New Energy Services LLC	800-660-3643	R/C/I
101 Neptune Avenue Deal, New Jersey 07723	www.newenergyservicesllc.com	ACTIVE

New Jersey Gas & Electric	866-568-0290	R/C
1 Bridge Plaza, Fl. 2 Fort Lee, NJ 07024	www.NJGandE.com	ACTIVE
Noble Americas Energy Solutions The Mac-Cali Building 581 Main Street, 8th fl.	877-273-6772	C/I
Woodbridge, NJ 07095	www.noblesolutions.com	ACTIVE
North American Power & Gas, LLC d/b/a North American Power 197 Route 18 South Ste. 3000 East Brunswick, NJ 08816	(888) 313-9086 <u>www.napower.com</u>	R/C/I ACTIVE
Palmco Energy NJ, LLC One Greentree Centre 10,000 Lincoln Drive East, Suite 201	877-726-5862	R/C/I
Marlton, NJ 08053	www.PalmcoEnergy.com	ACTIVE
Pepco Energy Services, Inc. 112 Main Street	800-363-7499	C/I
Lebanon, NJ 08833	www.pepco-services.com	ACTIVE
Plymouth Rock Energy, LLC 338 Maitland Avenue	855-32-POWER (76937)	R/C/I
Teaneck, NJ 07666	www.plymouthenergy.com	ACTIVE
PPL EnergyPlus, LLC 811 Church Road - Office 105 Cherry Hill, NJ 08002	800-281-2000 www.pplenergyplus.com	C/I ACTIVE
Respond Power LLC	(877) 973-7763	R/C/I
10 Regency CT Lakewood, NJ 08701	www.respondpower.com	ACTIVE
South Jersey Energy Company 1 South Jersey Plaza, Route 54	800-266-6020	C/I
Folsom, NJ 08037	www.southjerseyenergy.com	ACTIVE
S.J. Energy Partners, Inc. 208 White Horse Pike, Suite 4	800-695-0666	R/C
Barrington, NJ 08007	www.sjnaturalgas.com	ACTIVE
Spark Energy Gas, L.P. 2105 CityWest Blvd, Ste 100	800-411-7514	R/C/I
Houston, Texas 77042	www.sparkenergy.com	ACTIVE
Sprague Energy Corp. 12 Ridge Road	855-466-2842	C/I
Chatham Township, NJ 07928	www.spragueenergy.com	ACTIVE

Stuyvesant Energy LLC	800-640-6457	C
10 West Ivy Lane, Suite 4 Englewood, NJ 07631	www.stuyfuel.com	ACTIVE
Stream Energy New Jersey, LLC	(973) 494-8097	R/C
309 Fellowship Road Suite 200	www.stroomonorgy.not	ACTIVE
Mt. Laurel, NJ 08054	www.streamenergy.net	ACTIVE
Systrum Energy	877-797-8786	R/C/I
1 Bergen Blvd. Fairview, NJ 07022	www.systrumenergy.com	ACTIVE
Woodruff Energy	800-557-1121	R/C/I
73 Water Street	1 66	A CONTENT
Bridgeton, NJ 08302	www.woodruffenergy.com	ACTIVE
Woodruff Energy US LLC	856-455-1111	C/I
73 Water Street, P.O. Box 777	800-557-1121	
Bridgeton, NJ 08302	www.woodruffenergy.com	ACTIVE
Xoom Energy New Jersey, LLC	888-997-8979	R/C/I
744 Broad Street		
Newark, NJ 07102	<u>www.xoomenergy.com</u>	ACTIVE
Your Energy Holdings, LLC	(855) 732-2493	R/C/I
One International Boulevard		
Suite 400		
Mahwah, NJ 07495-0400	www.thisisyourenergy.com	ACTIVE

Back to main supplier information page



Description	QTY	Manufacturer Name	Model No.	Serial No.	Equipment Type / Utility	Capacity/Size /Efficiency	Location	Areas/Equipment Served	Date Installed	Remaining Useful Life (years)
B-1	1	H.B. Smith	Cast iron sectional	310754	Hot Water Boiler	2850400 BTUH / 80% eff.	Boiler Rm	Building	2003	19
B-2	1	H.B. Smith	Cast iron sectional	310755	Hot Water Boiler	2850400 BTUH / 80% eff.	Boiler Rm	Building	2003	19
Burner-1	1	Powerflame	C3-G-25	100310754	Gas Burner	4517 MBH max	Boiler Rm	Boiler #1	2003	19
Burner-2	1	Powerflame	C3-G-25	100310755	Gas Burner	4517 MBH max	Boiler Rm	Boiler #1	2003	19
DHW-1	1	Rheem	GX90-550A	URNG0607P0048	Domestic hot water heater	90 gallons / 80% thermal eff.	Boiler Rm	Building	2007	8
DTWP-1	1	B&G	G025131-8	37F368X532	Base mtd pump	15 HP / 87.5%	Boiler Rm	Building	N/A	N/A
DTWP-2	1	B&G	G025131-8	37F368X532	Base mtd pump	15 HP / 87.5%	Boiler Rm	Building	N/A	N/A
CHWP-3	1	B&G	AV1118411TD11027	N/A	Base mtd pump	5 HP / 87.5%	Boiler Rm	Building	N/A	N/A
B-3	1	Patterson Kelly	Mach Series	M706-08-2658-A	HW Boiler	N/A	Mechanical Equip Rm	Building	2008	24
B-4	1	Patterson Kelly	Mach Series	M513-07-1721-A	HW Boiler	N/A	Mechanical Equip Rm	Building	2007	23
DHW-2	1	Rheem	HE119-160N	0608T1707N	Domestic hot water heater	119 gallons / 80% eff.	Mechanical Equip Rm	Building	2008	9
P-4, 5	2	Taco	N/A	N/A	Base mtd pump	N/A	Mechanical Equip Rm	Building	N/A	N/A
ACCU-1	1	McQuay	ALP0370827-ER10	STN80W00127	Air cooled condensing unit	N/A	Roof	C-wing	N/A	N/A
RTU	1	McQuay	RDS800CYA	FBOUO11200367	Rooftop unit	N/A	Roof	C-wing	N/A	N/A
RTU Lennox	1	Lennox	LCA060SN1G	5601L07739	Rooftop unit	N/A	Roof	C-wing	2001	7
					Air cooled condensing					
ACCU-2	1	McQuay	ALP0370827-ER10	STN80W00153	unit Air cooled condensing	N/A	Roof	C-wing	N/A	N/A
ACCU-3	1	McQuay	ALP0373S27-ER10	STNU011200112	unit	N/A	Roof	C-wing	N/A	N/A
RTU	1	McQuay	RDS802CLA	FBOUO11200371-00	Rooftop unit	N/A	Roof	C-wing	N/A	N/A
Chiller	1	Trane	RTAC-250A	UO4CO4379	Chiller	250 tons / eff. Unknown	Exterior	Building	2004	10
RTU	1	Carrier	48SD-030040511SB	3208G21079	Rooftop unit	N/A	Roof	D-wing	2008	9
RTU	1	Carrier	48AYS025	3208U22750	Rooftop unit	N/A Roof		D-wing	2008	9
EF-5	1	Greenheck	CBRU-1-10-30	11231031-0001	Hi-static fan	N/A	Roof	D-wing	N/A	N/A
RTU	1	Carrier	48AKS030-NT22081	3208U22772	Rooftop unit	N/A	Roof	D-wing	2008	9
RTU	1	Carrier	48AYS030-NT22080	3208U22765	Rooftop unit	N/A	Roof	D-wing	2008	9
AHU	1	Trane	CC0B08AUBK	K90C08185	Air handling unit	N/A	Mechanical Equip Rm	Old gymnasium	N/A	N/A
AHU-2	1	Trane	MMCCB025UA0A0UA	K04A10618	Air handling unit	N/A	Mechanical Equip Rm	Old gymnasium	N/A	N/A
AHU-3	1	Trane	MMCCB025UA0A0UA	K04A10623	Air handling unit	N/A	Mechanical Equip Rm	Locker Rm	N/A	N/A
DHW-3	1	State Industries	ES630DORT	E05A091623	Domestic electric hot water heater	30 gallons / 98% efficient	Mechanical Equip Rm	Library	2005	6
RTU	1	Trane	GRCA25PDMF0N6CE105C0	F04A00655	Rooftop unit	N/A	Roof	N/A	N/A	N/A
RTU	1	Trane	YCD241C3HCCA	405100223D	Rooftop unit	20 ton / 11.0 EER	Roof	N/A	2004	5
Cond. Unit	1	Trane	2TTA2036A3000AA	3314YJL3F	Condensing unit	3 tons / 8.45 EER Roof N/A		N/A	2003	4
RTU	1	York	D4CE060A25A	(S)NGHM104961	Rooftop unit	5 tons / 10.5 EER	Roof	N/A	1998	-1
Split cond. Unit	1	Sanyo	SAP91C	01449-43XX	Condensing unit	N/A	Roof	N/A	N/A	N/A
RTU-1	1	Trane	YHC06DA3RMA	404101217	RTU	N/A	Roof	N/A	2006	7
RTU	1	N/A	PGB090210-3	102630694	RTU	13 tons / Eff. Unknown	Roof	N/A	N/A	N/A
RTU	1	Trane	GRDA15GDBB0NICK105C0 PCV	A96F37459	RTU	N/A	Roof	N/A	1996	2
RTU	1	Trane	GRDA15GDBB0NICK105C0 PCV	A96F37458	RTU	N/A	Roof	N/A	1996	2
RTU	1	Trane	GRCA25PDMF0N6CE105C0	F04A00654	RTU	N/A	Roof	N/A	2004	10
Cond. Unit	1	Trane	2TTA2036A3000AA	3314YJ13F	Condensing unit	3 tons / 8.45 EER	Ground	N/A	2003	9
AHU	1	Carrier	09BB-012300	Z795312	Air handling unit	N/A	Mechanical Equip Rm	Library	1987	-7
AHU	1	Carrier	50BD-024550	Q897547	Air handling unit	N/A	Mechanical Equip Rm	Library	1988	-6
B-5	1	Weil McLain	H-676-W8	N/A	Hot Water Boiler	416 MBH / 80% eff.	Mechanical Equip Rm	Library	1988	-1
-	1 Well McCell 11-070-W			*				,		

	gnting & Audit input						<mark>/8 </mark> \$/KVV					
					EXISTING CO	NDITIONS					Potrofit	
			No. of			Watts per					Retrofit Control	
	Area Description	Usage	Fixtures	Standard Fixture Code	Fixture Code	Fixture	kW/Space	Exist Control	Annual Hours	Annual kWh		
Field	Unique description of the location - Room number/Room	Describe Usage Type	No. of	Lighting Fixture Code	Code from Table of Standard Fixt		(Watts/Fixt) * (Fixt	Pre-inst. control	Estimated	(kW/space) *	Retrofit control	Notes
Code	name: Floor number (if applicable)	using Operating Hours	fixtures		Wattages	Table of	No.)	device		(Annual Hours)	device	
			before the			Standard			the usage group			
			retrofit			Fixture Wattages						
35LED	Rm 375 Fine Arts	classrooms	16	T 32 R F 3 (ELE)	F43ILL/2	90	1.44	occ	2400	3,456	C-OCC	
35LED	Rm 376	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	occ	2400	2,592	C-OCC	
4LED	Stairway	stairway	2	2B 34 R F 2 (u) (MAG)	FU2EE	72	0.14	breaker	3200	461	none	
35LED	Faculty Toilet Mens	Restroom w/ OCC	1	T 32 R F 3 (ELE)	F43ILL/2	90	0.09	OCC	1000	90	none	
35LED	Faculty Toilet Womens	Restroom w/ OCC	1	T 32 R F 3 (ELE)	F43ILL/2	90	0.09	000	1000	90	none	
35LED 35LED	Corridor Rm 374	Hallways classrooms	13 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	1.17 1.08	breaker occ	2280 2400	2,668 2,592	none	
35LED	Rm 373	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	1.08	OCC	2400	2,592	000	
35LED	Rm 372	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	OCC	2400	2,592	occ	
35LED	Rm 371	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	occ	2400	2,592	occ	
35LED	Rm 370	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	occ	2400	2,592	occ	
35LED	Corridor	Hallways	2	T 32 R F 3 (ELE)	F43ILL/2	90	0.18	breaker	2280	410	none	
121	Corridor	Hallways	2	W 34 P F 4	F44EE	144	0.29	breaker	2280	657	none	
121	corridor	Hallways	2	W 34 P F 4	F44EE	144	0.29	breaker	2280	657	none	
35LED 35LED	Boys toilet Girls toilet	Restroom w/ OCC Restroom w/ OCC	3	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.27 0.27	occ	1000	270 270	none none	
35LED	Custodial closet	Storage/Janitor	1	T 32 R F 3 (ELE)	F43ILL/2	90	0.27	SW	500	45	none	
35LED	Corridor	Hallways	6	T 32 R F 3 (ELE)	F43ILL/2	90	0.54	breaker	2280	1,231	none	
35LED	Rm 275	classrooms	16	T 32 R F 3 (ELE)	F43ILL/2	90	1.44	OCC	2400	3,456	occ	
35LED	Rm 276	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	occ	2400	2,592	occ	
4LED	Stairway	stairway	2	2B 34 R F 2 (u) (MAG)	FU2EE	72	0.14	breaker	3200	461	none	
35LED	Faculty Toilet Mens	Restroom w/ OCC	1	T 32 R F 3 (ELE)	F43ILL/2	90	0.09	occ	1000	90	none	
35LED 35LED	Faculty Toilet Womens	Restroom w/ OCC	1	T 32 R F 3 (ELE)	F43ILL/2	90	0.09	000	1000	90	none	
35LED 35LED	Corridor Rm 374	Hallways classrooms	13 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	1.17 1.08	breaker occ	2280 2400	2,668 2,592	none	
35LED	Rm 273	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	occ	2400	2,592	000	
35LED	Rm 272	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	occ	2400	2,592	occ	
35LED	Rm 271	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	occ	2400	2,592	occ	
35LED	Rm 270	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	OCC	2400	2,592	occ	
35LED	Corridor	Hallways	2	T 32 R F 3 (ELE)	F43ILL/2	90	0.18	breaker	2280	410	none	
121	Corridor	Hallways	2	W 34 P F 4	F44EE	144	0.29	breaker	2280	657	none	
121	corridor	Hallways	2	W 34 P F 4	F44EE	144	0.29	breaker	2280	657	none	
35LED 35LED	Boys toilet Girls toilet	Restroom w/ OCC Restroom w/ OCC	3	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.27	000	1000	270	none	
35LED	Custodial closet	Storage/Janitor	1	T 32 R F 3 (ELE)	F43ILL/2	90	0.27	occ sw	500	270 45	none none	
35LED	Corridor	Hallways	6	T 32 R F 3 (ELE)	F43ILL/2	90	0.54	breaker	2280	1,231	none	
35LED	Rm 275	classrooms	16	T 32 R F 3 (ELE)	F43ILL/2	90	1.44	occ	2400	3,456	occ	
35LED	Rm 276	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	OCC	2400	2,592	OCC	
4LED	Stairway	stairway	2	2B 34 R F 2 (u) (MAG)	FU2EE	72	0.14	breaker	3200	461	none	
35LED	Faculty Toilet Mens	Restroom w/ OCC	1	T 32 R F 3 (ELE)	F43ILL/2	90	0.09	occ	1000	90	none	
35LED	Faculty Toilet Womens	Restroom w/ OCC	1	T 32 R F 3 (ELE)	F43ILL/2	90	0.09	000	1000	90	none	
35LED 35LED	Corridor Rm 374	Hallways classrooms	13 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	1.17 1.08	breaker	2280 2400	2,668 2,592	none	
35LED	Rm 273	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	occ	2400	2,592	000	
35LED	Rm 272	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	occ	2400	2,592	000	
35LED	Rm 271	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	occ	2400	2,592	occ	
35LED	Rm 270	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	OCC	2400	2,592	occ	<u> </u>
35LED	Corridor	Hallways	2	T 32 R F 3 (ELE)	F43ILL/2	90	0.18	breaker	2280	410	none	
121	Corridor	Hallways		W 34 P F 4	F44EE	144	0.29	breaker	2280	657	none	
121	corridor Pous tailet	Hallways	2	W 34 P F 4	F44EE	144	0.29	breaker	2280	657	none	
35LED	Boys toilet Girls toilet	Restroom w/ OCC Restroom w/ OCC	3	T 32 R F 3 (ELE)	F43ILL/2	90	0.27	000	1000	270	none	
35LED 35LED	Custodial closet	Storage/Janitor	1	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.27 0.09	occ sw	1000 500	270 45	none none	
35LED	Custodial closet	Hallways	6	T 32 R F 3 (ELE)	F43ILL/2	90	0.54	breaker	2280	1,231	none	
6LED	classroom 140	classrooms	36	T 34 R F 4 (MAG)	F44EE	144	5.18	SW	2400	12,442	OCC	
6LED	classroom 142	classrooms	24	T 34 R F 4 (MAG)	F44EE	144	3.46	SW	2400	8,294	occ	
6LED	storage	Storage/Janitor	4	T 34 R F 4 (MAG)	F44EE	144	0.58	SW	500	288	none	
35LED	classroom 141	classrooms	10	T 32 R F 3 (ELE)	F43ILL/2	90	0.90	SW	2400	2,160	000	
35LED	classroom 143	classrooms	18	T 32 R F 3 (ELE)	F43ILL/2	90	1.62	SW	2400	3,888	occ	
41LED	Corridor	Hallways	10	1B 40 R F 2 (MAG)	F42SS	94	0.94	breaker	2280	2,143	none	
6LED 41LED	Dance Gym Dance Gym	classrooms	36 6	T 34 R F 4 (MAG) 1B 40 R F 2 (MAG)	F44EE F42SS	144 94	5.18 0.56	SW	2400 2400	12,442 1,354	none	
40LED	Corridor	classrooms Hallways	9	T 32 R F 2 (ELE)	F4255	60	0.56	sw breaker	2280	1,354	none none	
18LED	Rm 137	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	breaker	2400	3,226	OCC	
18LED	RM 136	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	-
18LED	Rm 135	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	OCC	
18LED	Rm 134	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	
18LED	Rm 133	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	
18LED	Rm 132	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	000	
18LED	Rm 131	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	000	
18LED	Rm 130	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	OCC	

5/30/2014 Page 2, Existing

Cost of Electricity:

\$0.095 \$6.78 \$/kW

Existing Er	gnting & Audit input					Ψ0.	/8 \$/KVV					
					EXISTING CO	ONDITIONS					Retrofit	
			No. of			Watts per					Control	
	Area Description	Usage	Fixtures	Standard Fixture Code	Fixture Code	Fixture	kW/Space	Exist Control	Annual Hours	Annual kWh		
Field	Unique description of the location - Room number/Room	Describe Usage Type	No. of	Lighting Fixture Code	Code from Table of Standard Fix		(Watts/Fixt) * (Fixt	Pre-inst. control	Estimated	(kW/space) *	Retrofit control	Notes
Code	name: Floor number (if applicable)	using Operating Hours	fixtures before the		Wattages	Table of Standard	No.)	device		(Annual Hours)	device	
			retrofit			Fixture			the usage group			
			Tetront			Wattages						
18LED	Rm 129	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	sw	2400	3,226	OCC	
18LED	Rm 232	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	OCC	
18LED	Rm 233	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	
18LED	Rm 234	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	OCC	
18LED	Rm 235 Rm 236	classrooms classrooms	12 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112 112	1.34 1.34	SW SW	2400 2400	3,226 3,226	000	
18LED	Rm 237	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	000	
18LED	Rm 238	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	
18LED	Rm 239	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	
18LED	Rm 240	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	
18LED	Rm 241	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	OCC	
18LED	Rm 242	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	OCC	
18LED	Rm 243	classrooms	12	T 32 R F 4 (ELE)	F44ILL F44ILL	112 112	1.34	SW	2400 1000	3,226	000	
18LED	Boys toilet Girls toilet	Restroom w/ OCC Restroom w/ OCC	3	T 32 R F 4 (ELE)	F44ILL F44ILL	112	0.34 0.34	SW SW	1000	336	none none	
18LED	Boys toilet	Restroom w/ OCC	3	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112	0.34	SW	1000	336 336	none	
18LED	Girls toilet	Restroom w/ OCC	3	T 32 R F 4 (ELE)	F44ILL	112	0.34	SW	1000	336	none	
41LED	Corridor	Hallways	12	1B 40 R F 2 (MAG)	F42SS	94	1.13	breaker	2280	2,572	none	
41LED	Corridor	Hallways	14	1B 40 R F 2 (MAG)	F42SS	94	1.32	breaker	2280	3,000	none	
4LED	Stairway	stairway	3	2B 34 R F 2 (u) (MAG)	FU2EE	72	0.22	breaker	3200	691	none	
4LED	Stairway	stairway	3	2B 34 R F 2 (u) (MAG)	FU2EE	72	0.22	breaker	3200	691	none	
18LED	classroom 122	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	
18LED 18LED	classroom 123	classrooms	16 16	T 32 R F 4 (ELE)	F44ILL F44ILL	112	1.79 1.79	SW	2400 2400	4,301	000	
18LED	classroom 124 classroom 125	classrooms classrooms	12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112 112	1.79	SW SW	2400	4,301 3,226	000	
18LED	classroom 126	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	000	
18LED	Rm 226	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	
18LED	Rm 227	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	
18LED	Rm 228	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	sw	2400	3,226	OCC	
18LED	Rm 229	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	
18LED	Rm 230	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	occ	
18LED	Rm 231	classrooms	12	T 32 R F 4 (ELE)	F44ILL	112	1.34	SW	2400	3,226	OCC	
9LED	New Gymnasium	Gymnasium	24	High Bay MH 200 35 Feet High	MH200/1	232	5.57	SW	2912	16,214	none	
41LED 35LED	Corridor classroom 115	Hallways classrooms	15 9	1B 40 R F 2 (MAG) T 32 R F 3 (ELE)	F42SS F43ILL/2	94	1.41 0.81	breaker sw	2280 2400	3,215 1,944	none	
35LED	classroom 117	classrooms	16	T 32 R F 3 (ELE)	F43ILL/2	90	1.44	SW	2400	3,456	occ	
35LED	classroom 118	classrooms	16	T 32 R F 3 (ELE)	F43ILL/2	90	1.44	SW	2400	3,456	OCC	
35LED	classroom 119	classrooms	16	T 32 R F 3 (ELE)	F43ILL/2	90	1.44	SW	2400	3,456	occ	
35LED	classroom 121	classrooms	16	T 32 R F 3 (ELE)	F43ILL/2	90	1.44	SW	2400	3,456	occ	
35LED	classroom 120	classrooms	16	T 32 R F 3 (ELE)	F43ILL/2	90	1.44	SW	2400	3,456	occ	
6LED	storage	Storage/Janitor	1	T 34 R F 4 (MAG)	F44EE	144	0.14	SW	500	72	none	
35LED	office	Offices	2	T 32 R F 3 (ELE)	F43ILL/2	90	0.18	SW	2400	432	OCC	
35LED	office	Offices Offices	3	T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.27	SW	2400 2400	648	000	
35LED 35LED	office Cafeteria	Cafeteria	64	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.18 5.76	SW SW	1600	432 9,216	occ none	
24LED	Weight Rm	Gymnasium	24	1B 32 P F 2 (ELE)	F43ILL/2	60	1.44	SW	2912	4,193	none	
41LED	Media Center	classrooms	48	1B 40 R F 2 (MAG)	F42SS	94	4.51	SW	2400	10,829	OCC	
24LED	Boys Locker Rm	Locker	16	1B 32 P F 2 (ELE)	F42LL	60	0.96	sw	2800	2,688	occ	
24LED	Girls Locker Rm	Locker	16	1B 32 P F 2 (ELE)	F42LL	60	0.96	SW	2800	2,688	occ	
35LED	Music 101	classrooms	18	T 32 R F 3 (ELE)	F43ILL/2	90	1.62	OCC	2400	3,888	none	
35LED	Music 100	classrooms	22	T 32 R F 3 (ELE)	F43ILL/2	90	1.98	occ	2400	4,752	none	
35LED	Classroom 102	classrooms	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.08	occ	2400	2,592	none	
35LED 24LED	Classroom 103	classrooms	12 17	T 32 R F 3 (ELE)	F43ILL/2 F42LL	90	1.08	OCC brooker	2400	2,592	none none	
24LED	Corridor classroom 208	Hallways classrooms	17	1B 32 P F 2 (ELE) 1B 32 P F 2 (ELE)	F42LL F42LL	60 60	1.02 0.84	breaker sw	2280 2400	2,326 2,016	none	
24LED	classroom 209	classrooms	14	1B 32 P F 2 (ELE)	F42LL F42LL	60	0.84	SW	2400	2,016	occ	
24LED	classroom 210	classrooms	14	1B 32 P F 2 (ELE)	F42LL	60	0.84	SW	2400	2,016	occ	
24LED	classroom 211	classrooms	14	1B 32 P F 2 (ELE)	F42LL	60	0.84	sw	2400	2,016	occ	
24LED	classroom 207	classrooms	14	1B 32 P F 2 (ELE)	F42LL	60	0.84	SW	2400	2,016	occ	
18LED	Boys Rm	Restroom w/ OCC	4	T 32 R F 4 (ELE)	F44ILL	112	0.45	SW	1000	448	none	
18LED	Girls Rm	Restroom w/ OCC	4	T 32 R F 4 (ELE)	F44ILL	112	0.45	SW	1000	448	none	
4LED	Stairway	stairway	2	2B 34 R F 2 (u) (MAG)	FU2EE	72	0.14	breaker	3200	461	none	
18LED	Toilet rm	Restroom w/ OCC	3	T 32 R F 4 (ELE)	F44ILL	112	0.34	SW	1000	336	none	
18LED	Toilet rm	Restroom w/ OCC	18	T 32 R F 4 (ELE)	F44ILL CFT36/1	112 51	0.34	SW	1000 2280	336	none	
262 261LED	front vestibule Auditorium	Hallways Auditorium		B CF 36 W PAR 38 SP	H100/1	100	0.92 4.80	breaker sw	1820	2,093 8,736	none none	
261LED	Auditorium	Auditorium		PAR 38 SP	H100/1	100	1.50	SW	1820	2,730	none	
1	Auditorium	Auditorium	30	SQ 13 W CF 2 (MAG)	CFQ13/2	31	0.93	SW	1820	1,693	none	
18LED	Stage	Auditorium	16	T 32 R F 4 (ELE)	F44ILL	112	1.79	SW	1820	3,261	none	
35LED	Music classroom 202	classrooms	18	T 32 R F 3 (ELE)	F43ILL/2	90	1.62	SW	2400	3,888	occ	
35LED	Music classroom 201	classrooms	20	T 32 R F 3 (ELE)	F43ILL/2	90	1.80	SW	2400	4,320	OCC	

5/30/2014 Page 3, Existing

Cost of Electricity:

\$0.095 \$6.78 \$/kW

			EXISTING CONDITIONS									
			No. of			Watts per					Retrofit Control	
	Area Description	Usage	Fixtures	Standard Fixture Code	Fixture Code	Fixture	kW/Space	Exist Control	Annual Hours			
Field	Unique description of the location - Room number/Room	Describe Usage Type	No. of	Lighting Fixture Code	Code from Table of Standard Fixture		(Watts/Fixt) * (Fixt	Pre-inst. control	Estimated	(kW/space) *	Retrofit control	Notes
Code	name: Floor number (if applicable)	using Operating Hours	fixtures		Wattages	Table of	No.)	device		(Annual Hours)	device	
			before the			Standard			the usage group	P		
			retrofit			Fixture						
18LED	Storage	Storage/Janitor	4	T 32 R F 4 (ELE)	F44ILL	Wattages 112	0.45	SW	500	224	none	
35LED	Corridor	Hallways	10	T 32 R F 3 (ELE)	F43ILL/2	90	0.90	breaker	2280	2.052	none	
9LED	Old Gymnasium	Gymnasium	32	High Bay MH 200 35 Feet High	MH200/1	232	7.42	SW	2912	21,619	none	
40LED	Old Girls Locker Rm	Locker	28	T 32 R F 2 (ELE)	F42LL	60	1.68	SW	2800	4,704	none	
40LED	Old Boys Locker Rm	Locker	32	T 32 R F 2 (ELE)	F42LL	60	1.92	SW	2800	5,376	none	
40LED	New Girls Locker rm	Locker	20	T 32 R F 2 (ELE)	F42LL	60	1.20	SW	2800	3,360	none	
40LED	New Boys Locker rm	Locker	20	T 32 R F 2 (ELE)	F42LL	60	1.20	SW	2800	3,360	none	
40LED	Training Rm	Locker	8	T 32 R F 2 (ELE)	F42LL	60	0.48	SW	2800	1,344	none	
24LED	Corridor	Hallways	36	1B 32 P F 2 (ELE)	F42LL	60	2.16	breaker	2280	4,925	none	
1 40LED	Vestibules Gym storage	Hallways Storage/Janitor	12	SQ 13 W CF 2 (MAG) T 32 R F 2 (ELE)	CFQ13/2 F42LL	31 60	0.37 0.24	breaker sw	2280 500	848 120	none	
20LED	Boys Rm	Restroom w/ OCC	6	S 32 C F 1 (ELE)	F42LL F41LL	32	0.24	SW	1000	120	none	
20LED	Girls Rm	Restroom w/ OCC	6	S 32 C F 1 (ELE)	F41LL	32	0.19	SW	1000	192	none	
35LED	Principals office	Offices	4	T 32 R F 3 (ELE)	F43ILL/2	90	0.36	SW	2400	864	none	
35LED	Asst principals office	Offices	4	T 32 R F 3 (ELE)	F43ILL/2	90	0.36	SW	2400	864	none	
35LED	Conference Rm	Conference	3	T 32 R F 3 (ELE)	F43ILL/2	90	0.27	SW	1200	324	OCC	
4LED	Stairway	stairway	2	2B 34 R F 2 (u) (MAG)	FU2EE	72	0.14	breaker	3200	461	none	
24LED	Health classroom	classrooms	16	1B 32 P F 2 (ELE)	F42LL	60	0.96	SW	2400	2,304	OCC	
24LED	Team Rm	Locker	14	1B 32 P F 2 (ELE)	F42LL	60	0.84	SW	2800	2,352	none	
18LED	Storage	Storage/Janitor	3	T 32 R F 4 (ELE)	F44ILL	112	0.34	SW	500	168	none	
40LED	Training Rm	Locker	4	T 32 R F 2 (ELE)	F42LL	60	0.24	SW	2800	672 168	none	
18LED 117	Storage Exterior	Storage/Janitor Outdoor Lighting	3 12	T 32 R F 4 (ELE) CF 23	F44ILL CFS23/1	112 23	0.34 0.28	sw breaker	500 4368	1,206	none none	
227LED	Exterior	Outdoor Lighting	13	70 W MH Wall Pack	MH70/1	95	1.24	breaker	4368	5,394	none	
142LED	Exterior	Outdoor Lighting	3	MH 100	MH100/1	128	0.38	breaker	4368	1,677	none	
ITZEED	Exterior	Cutdoor Lighting	-	IWIT 100	IVII 1100/1	120	0.30	Dicarci	4300	1,077	Hone	
						+				+		
						+				+		
						 				 		
						1				†		
						1				1		
						1						
						1						
						1						
						1				ļ		
						+				+		
						+				1		
						 				 		
						+				+		
	Total		1,896			†	180.70			425,079		
			1,000	1	L	1	130.10	1		723,013	·	

5/30/2014 Page 4, Existing



used for NPV)	3

				Metric Ton Carbon				
Utility Costs			Yearly Usage	Dioxide Equivalent	Building Area	Α	st	
\$	0.120	\$/kWh blended		0.000420205	201,858	Electric	Natural Gas	Fuel Oil
\$	0.095	\$/kWh supply	2,220,800	0.000420205		\$ 266,271	\$ 88,656	
\$	6.78	\$/kW	862.7	0				_
\$	0.86	\$/Therm	80,896	0.00533471				
\$	8.87	\$/kgals	2,308	0				
\$	0.009	\$/Gal	2.308.000					

		Mil	<mark>lburn H</mark>	ligh Scl	nool			_															
Recommend?		Item			Sa	vings			Cost	Simple	Life	Equivalent CO ₂	NJ Smart Start	Direct Install	Payback w/		Simple Proje	cted Lifetime	Savings		ROI	NPV	IRR
Y or N			kW	kWh	therms	No. 2 Oil gal	Water kgal	\$		Payback	Expectancy	(Metric tons)	Incentives	Eligible (Y/N)	Incentives	kW	kWh	therms	kgal/yr	\$		<u> </u>	
Υ	ECM-1	Replace Door Sweeps & Seals	0.0	0	346	0	0	298	\$ 2,305	7.7	15	1.8		N	7.7	0.0	0	5,197	0	\$ 4,470	0.9	\$1,253	9.7%
Υ	ECM-6	Smart Controller Window AC Units	0.0	2,814	0	0	0	338	\$ 1,200	3.6	15	1.2		N	3.6	0.0	42,203	0	0	\$ 5,064	3.2	\$2,831	27.4%
Υ	ECM-9	Install VFDs on Air Handling Units	5.9	20,927	0	0	0	2,466	\$ 19,047	7.7	15	8.8		N	7.7	88.2	313,904	0	0	\$ 44,842	1.4	\$10,396	9.7%
Υ	ECM-10	Replace Rooftop Units	0.0	5,886	0	0	0	706	\$ 47,800	67.7	20.0	2.5		N	67.7	0.0	117,716	0	0	\$ 14,126	(0.7)	(\$37,292)	-9.6%
Υ	ECM-12	Retro-Commission Temperature Controls	0.0	99,936	10,800	0	0	21,280	\$ 69,967	3.3	15.0	99.6		N	3.3	0.0	1,499,040	161,994	0	\$319,200	3.6	\$184,073	29.8%
Υ	ECM-14	Install Kitchen Hood Controller	0.0	227	6,848	0	0	5,917	\$ 30,787	5.2	15.0	36.6		N	5.2	0.0	3,399	102,725	0	\$ 88,752	1.9	\$39,847	17.5%
Υ	ECM-15	Install Walk-in Cooler / Freezer Controls	0.0	1,431	0	0	0	172	\$ 20,625	120.1	15.0	0.6		N	120.1	0.0	21,467	0	0	\$ 2,576	(0.9)	(\$18,575)	-19.1%
Υ	ECM-17	Install Vending Misers	0.0	7,343	0	0	0	881	\$ 840	1.0	15.0	3.1		N	1.0	0.0	110,138	0	0	\$ 13,217	14.72761	\$9,678	104.8%
N	ECM-L1	Lighting Replacements / Upgrades	102.6	242,071	0	0	0	31,345	\$ 454,693	14.5	10.0	101.7	\$ 10,000	N	14.2	1,026.0	2,420,710	0	0	\$373,961	(0.2)	(\$177,314)	-5.9%
N	ECM-L2	Install Lighting Controls (Add Occupancy Sensors)	0.0	73,021	0	0	0	6,937	\$ 10,287	1.5	10.0	30.7	\$ 1,590	N	1.3	0.0	730,210	0	0	\$ 87,625	7.5	\$50,477	79.5%
Υ	ECM-L3	Lighting Replacements with Controls (Occupancy Sensors)	102.6	273,215	0	0	0	34,304	\$ 464,980	13.6	10.0	114.8	\$ 11,590	N	13.2	1,026.0	2,732,150	0	0	\$411,333	(0.1)	(\$160,770)	-4.8%
		Total (Not Including ECMs L1, L2)	108.5	411,778	17,994	0	0	\$ 66,362	\$ 657,550	9.9	15.0	269	\$ 11,590		9.7	1,114	4,840,017	269,917	-	\$903,580	0.4	\$146,263	6.0%
		Recommended Measures (highlighted green above)	108.5	411,778	17,994	0	0	\$ 66,362	\$ 657,550	9.9	15.0	269	\$ 11,590	0	9.7	1,114	4,840,017	269,917	-	\$903,580	0.4	\$146,263	6.0%
		% of Existing	13%	19%	22%	0	0%																

		City:	Newari	k, NJ	1		
	Occupied F	lours/Week	70	70	70	70	50
			Building	Auditorium	Gymnasium	Library	Classrooms
	Enthalpy		Operating	Occupied	Occupied	Occupied	Occupied
Temp	h (Btu/lb)	Bin Hours	Hours	Hours	Hours	Hours	Hours
102.5							
97.5	35.4	6	3	3	3	3	2
92.5	37.4	31	13	13	13	13	9
87.5	35.0	131	55	55	55	55	39
82.5	33.0	500	208	208	208	208	149
77.5	31.5	620	258	258	258	258	185
72.5	29.9	664	277	277	277	277	198
67.5	27.2	854	356	356	356	356	254
62.5	24.0	927	386	386	386	386	276
57.5	20.3	600	250	250	250	250	179
52.5	18.2	730	304	304	304	304	217
47.5	16.0	491	205	205	205	205	146
42.5	14.5	656	273	273	273	273	195
37.5	12.5	1,023	426	426	426	426	304
32.5	10.5	734	306	306	306	306	218
27.5	8.7	334	139	139	139	139	99
22.5	7.0	252	105	105	105	105	75
17.5	5.4	125	52	52	52	52	37
12.5	3.7	47	20	20	20	20	14
7.5	2.1	34	14	14	14	14	10
2.5	1.3	1	0	0	0	0	0
-2.5							
-7.5							

1.027
1.246
1.124

Heating System Efficiency	80%
Cooling Eff (kW/ton)	1.2


He	ating	
Hours	4,427	Hrs
Weighted Avg	40	F
Avg	28	F


Co	Cooling					
Hours	4,333	Hrs				
Weighted Avg	68	F				
Avg	78	F				

	Utility End Use Analysis							
Electric	ity Use (kWh):	Notes/Comments:						
2,220,800	Total	Based on utility analysis						
555,200	Lighting	From Lighting Calculations						
199,872	Motors	Estimated						
666,240	A/C	Estimated						
339,121	Plug Load	Estimated						
55,520	Kitchen	Estimated						
266,496	Computers	Estimated						
138,351	Other	Remaining						
Natural Ga	s Use (Therms):	Notes/Comments:						
80,896	Total	Based on utility analysis						
51,773.44		Therms/SF x Square Feet Served						
20,224	RTU, AHU	Based on utility analysis						
8,899	DHW & Kitchen	Based on utility analysis						

0.25 0.09 0.30 0.15 0.03 0.12 0.06
0.64

0.25 0.11





ECM-1: Install Door Seals

Description: This ECM evaluates the thermal and electrical savings associate with adding door seals and sweeps to prevent infiltration of cold (hot) outdoor air.

Heating System Efficiency Cooling System Efficiency Linear Feet of Door Edge

1.20 kW/ton 200 LF 1.5 cfm/LF Ex Occupied Clng Temp.
Ex Unoccupied Clng Temp. Cooling Occ Enthalpy Setpoint
Cooling Unocc Enthalpy Setpoint 27.5 Btu/lb 27.5 Btu/lb

Ex Occupied Htg Temp. Ex Unoccupied Htg Temp. Electricity Natural Gas

70	*F
60	*F
\$ 0.12	\$/kWh
\$ 0.86	\$/therm

Existing Infiltration Factor*

Proposed Infiltration Factor*

*Infiltration Factor per Carrier Handbook of Air Conditioning System Design

based on average door seal gap calculated below.

					EXISTING	EXISTING LOADS PROPOSED LOADS		COOLING	S ENERGY	HEATING E	ENERGY	
					Occupied	Unoccupied						
Avg Outdoor Air Temp. Bins °F	Avg Outdoor Air Enthalpy	Existing Equipment Bin Hours	Occupied Equipment Bin Hours	Unoccupied Equipment Bin Hours	Door Infiltration Load BTUH	Door Infiltration Load BTUH	Door Infiltration	Door Infiltration Load BTUH	Existing Cooling Energy kWh	Proposed Cooling Energy kWh	Existing Heating Energy therms	Proposed Heating Energy therms
A	7.iii Elitilaipy	В	C	D	E	F	G	H	l I	J	K	L
102.5	0.0	0	0	0	37,125	37,125	11,138		0	0	0	0
97.5	35.4	6	3	4	-10,675	-10,675	-3,202	-3,202	6	2	0	0
92.5	37.4	31	13	18	-13,368	-13,368	-4,010	-4,010	41	12	0	0
87.5	35.0	131	55	76	-10,104	-10,104	-3,031	-3,031	132	40	0	0
82.5	33.0	500	208	292	-7,489	0	-2,247	0	156	47	0	0
77.5	31.5	620	258	362	-5,465	0	-1,639	0	141	42	0	0
72.5	29.9	664	277	387	0	0	0	0	0	0	0	0
67.5	27.2	854	356	498	810	0	243	0	0	0	4	1
62.5	24.0	927	386	541	2,430	0	729	0	0	0	12	4
57.5	20.3	600	250	350	4,050	810	1,215	243	0	0	16	5
52.5	18.2	730	304	426	5,670	2,430	1,701	729	0	0	34	10
47.5	16.0	491	205	286	7,290	4,050	2,187	1,215	0	0	33	10
42.5	14.5	656	273	383	8,910	5,670	2,673	1,701	0	0	58	17
37.5	12.5	1,023	426	597	10,530	7,290		2,187	0	0	110	33
32.5	10.5	734	306	428	12,150	8,910	3,645	2,673	0	0	94	28
27.5	8.7	334	139	195	13,770	10,530	4,131	3,159	0	0	50	15
22.5	7.0	252	105	147	15,390	12,150	•	3,645	0	0	43	13
17.5	5.4	125	52	73	17,010	13,770	5,103	4,131	0	0	24	7
12.5	3.7	47	20	27	18,630	15,390		4,617	0	0	10	3
7.5	2.1	34	14	20	20,250	17,010	6,075	5,103	0	0	8	2
2.5	1.3	1	0	1	21,870	18,630	6,561	5,589	0	0	0	0
-2.5	0.0	0	0	0	23,490	20,250	7,047	6,075	0	0	0	0
-7.5	0.0	0	0	0	25,110	21,870	7,533	6,561	0	0	0	0
TOTALS		8,760	3,650	5,110					477	143	495	148

85 *F

Existing Door Infiltration Existing Unoccupied Door Infiltration Proposed Door Infiltration Proposed Unoccupied Door Infiltration 300 cfm **300** cfm 90 cfm 90 cfm

Savings	346	therms	\$ 298
	334	kWh	\$ 40
-			\$ 338

Door	Width (ft)	Height (ft)	Linear Feet (LF)	gap (in)	gap location	LF of gap	% door w/ gap	Average gap for door (in)
1a	3	7	20	0.25	bottom/seam	3	15%	0.0375
1b	3	7	20	0.25	bottom/seam	3	15%	0.0375
2a	3	7	20	0.25	all sides	15	75%	0.1875
2b	3	7	20	0.25	all sides	15	75%	0.1875
3a	3	7	20	0.125	all sides	10	50%	0.0625
3b	3	7	20	0.125	all sides	10	50%	0.0625
4a	3	7	20	0.125	all sides	10	50%	0.0625
4b	3	7	20	0.0625	all sides	10	50%	0.03125
5	3	7	20	0.25	bottom/seam	3	15%	0.0375
6	3	7	20	0.25	bottom/seam	3	15%	0.0375
Total	30	70	200	0.194		82	41%	0.074

Note: Doors labeled 'a', 'b', etc. are a part of the same door assembly.

Multipliers	
Material:	1.03
Labor:	1.25
Equipment:	1.12

ECM-1: Install Door Seals - Cost

Description	QTY	UNIT	l	JNIT COST	S	SUE	STOTAL CO	STS	TOTAL	REMARKS
Description	QII	UNIT	MAT.	LABOR	EQUIP.	MAT.	LABOR	EQUIP.	COST	REIVIARRS
									\$ -	
Door Weatherization Seals & Sweeps	10	EA	\$ 40	\$ 115	\$ -	\$ 411	\$ 1,433	\$ -	\$ 1,844	RS Means 2012
						\$ -	\$ -	\$ -	\$ -	

^{**}Cost Estimates are for Energy Savings calculations only, do not use for procurement

\$ 1,844	Subtotal
\$ 461	25% Contingency
\$ 2,305	Total

EQUIPME	ENT	AREA/EQUIPMENT SERVED	COOLING CAPACITY (btu/h)	
			` ,	_
Window AC	6x	Classrooms & Offices	108,000	
		Total btu/h of all window A/C Units:	108,000	btu/h

ECM-6: Window A/C Controller

ECM Description : Window A/C units are currently controlled manually by the occupants and are not turned off when the room is unoccupied. This ECM evaluates implementation of a digital timer device that will automatically turn the window A/C unit off at a preset time .

ASSUMPTIC	NS		Comments
Electric Cost	\$0.120	/ kWh	
Average run hours per Week	80	Hours	
Space Balance Point	55	F	
Space Temperature Setpoint	74	deg F	Setpoint.
BTU/Hr Rating of existing DX equipment	108,000	Btu / Hr	Total BTU/hr of Window A/C units
Average EER	10.7		
Existing Annual Electric Usage	6,191	kWh	

<u>Item</u>	<u>Value</u>	<u>Units</u>	<u>Comments</u>
Proposed Annual Electric Usage	3,377	kWh	Unit will cycle on w/ temp of room. Possible operating time shown below

ANNUAL SAVINGS										
Annual Electrical Usage Savings	2,814	kWh								
Annual Cost Savings	\$338									
Total Project Cost	\$1,200									
Simple Payback	4	years								

OAT - DB		Existing		Proposed
Bin	Annual	Hours of	Proposed % of	hrs of
Temp F	Hours	Operation	time of operation	Operation
102.5	0	0	100%	0
97.5	6	3	89%	3
92.5	31	15	79%	12
87.5	131	62	68%	43
82.5	500	238	58%	138
77.5	620	295	47%	140
72.5	664	0	0%	0
67.5	854	0	0%	0
62.5	927	0	0%	0
57.5	600	0	0%	0
52.5	730	0	0%	0
47.5	491	0	0%	0
42.5	656	0	0%	0
37.5	1,023	0	0%	0
32.5	734	0	0%	0
27.5	334	0	0%	0
22.5	252	0	0%	0
17.5	125	0	0%	0
12.5	47	0	0%	0
7.5	34	0	0%	0
2.5	1	0	0%	0
-2.5	0	0	0%	0
-7.5	0	0	0%	0
_				
Total	8,760	613	55%	335

ECM-6: Window A/C Controller - Cost

Multipliers	
Material:	1.03
Labor:	1.25
Equipment:	1.12

Description	QTY	UNIT		UNIT COSTS			JBTOTAL C	OSTS	TOTAL	REMARKS
			MAT.	LABOR	EQUIP.	MAT. LABOR EQUII		EQUIP.	COST	KEWAKKS
						0	\$ -	\$ -	\$ -	
Window AC Controller	6	EA	\$ 150	\$ -	\$ -	924.3	\$ \$ -	\$ -	\$ 924	Estimated
						\$ -	\$ -	\$ -	\$ -	

^{**}Cost Estimates are for Energy Savings calculations only, do not use for procurement

\$	1.200	Total
¢	221	25% Contingency
\$	924	Subtotal

ECM-9: Upgrade to Premium Efficiency Motors and Install Variable Speed Drives

Description: This ECM evaluates the energy (electrical) savings associated with replacing existing motors with high efficiency motors (based on ASHRAE 2010 NEMA ratings) and adding variable frequency drives to control motor speed based on actual load verses constant volume / constant flow.

Variable Inputs
Electric Rate \$0.12 \$/kWh \$0.10 **\$/kW Demand Rate**

	MOTOR SCHEDULE									Savings Factor Existing Motor Energy			Proposed Motor Energy		Energy	Savings	
Motor ID	Motor Type	Qty	НР	Total HP	Upgrade Motor	Load Factor	_	New Motor Eff.	Annual Hours	Demand Savings Factor	Energy Savings Factor	Demand Energy (kW)	Electrical Energy (kWh)	Demand Energy (kW)	Electrical Energy (kWh)	Peak Demand Savings (kW)	Annual Energy Savings (kWh)
Gym units Return fans	FC	2	1.5	3.0	Υ	0.75	84.0%	86.5%	3,560		0.580	2.0	7,113	· · · · ·	-	2.0	7,113
Gym units Supply fans	FC	2	3.0	6.0	Υ	0.75	86.5%	89.5%	3,560		0.580	3.9	13,814	-	-	3.9	13,814
														-	Total:	5.9	20,926.9
																\$ 7	\$ 2,511
																	\$ 2,518

Savings calculation formulas are taken from NJ Protocols document for VFDs

ECM-9: Upgrade to Premium Efficiency Motors and Install Variable Speed Drives

Multipliers	
Material:	1.03
Labor:	1.25
Equipment:	1.12

Description	QTY	ry UNIT	UNIT COSTS			SUBTOTAL COSTS			TOTAL	REMARKS
Description		OIVII	MAT.	LABOR	EQUIP.	MAT.	LABOR	EQUIP.	COST	REWARKS
VFDs for AHU fan motors	2	EA	\$ 1,575	\$ 431		\$ 3,235	\$ 1,074	\$ -	\$ 4,309	RS Means 2012
Motor	2	EA	\$ 295	\$ 79		\$ 606	\$ 197	\$ -	\$ 803	RS Means 2012
Electrical - misc.	1	LS	\$ 3,000	\$ 1,500		\$ 3,081	\$ 1,869	\$ -	\$ 4,950	RS Means 2012
VFDs for AHU fan motors	2	EA	\$ 1,575	\$ 431		\$ 3,235	\$ 1,074	\$ -	\$ 4,309	RS Means 2012
Motor	2	EA	\$ 326	\$ 79		\$ 670	\$ 197	\$ -	\$ 866	RS Means 2012
						\$ -	\$ -	\$ -	\$ -	

^{**}Cost Estimates are for Energy Savings calculations only, do not use for procurement

\$ 15,237	Subtotal
\$ 3,809	25% Contingency
\$ 19,047	Total

		CAPACITY	
EQUIPMENT	AREA SERVED	(MBH)	
(4) RTU's	Various spaces	366	
	Total Electric DX Coolina:	366	 MBF

COOLING

ECM-10: RTU Equipment Replacment

Existing RTU EER =

9.0

ECM Description Summary

By replacing older air handling equipment with newer equipment which uses more efficient fan motors and higher SEER/EER DX condensing units, significant electrical energy can be saved. The fan motors will also be replaced with premium efficiency motors. Control schemes can be incorporated that were not possible with the older equipment as well. It is recommended these units be replaced by more modern AAON units with supply fan

ASSUMPTIC	NS		Comments
Electric Cost	\$0.121	/ kWh	
Average run hours per Week	50	Hours	
Space Balance Point	55	F	
Space Temperature Setpoint	74	deg F	Setpoint.
Existing equipment motor HP	16.0		
Existing motor efficiency	75.0%		Unit is 20+ years old; motor efficiency affected by condition and environment over time
Existing Annual Electric Useage	24,854	kWh	

Proposed BTU/Hr rating of replacment DX e	366,000	Btu / Hr	Total BTU/hr of DX cooling equipment to be added.
Proposed average EER of replacment DX e	14.4		
Proposed equipment motor HP	16.0		Premium efficiency motor with VFD.
Proposed motor efficiency	92.0%		
Proposed Annual Electric Usage	18,968	kWh	

ANNUAL SAVINGS							
Annual Electrical Usage Savings	5,886	kWh					
Annual Cost Savings	\$713						
Total Project Cost	\$238,300						
Simple Payback	334	years					

OAT - DB		Cooling Hrs	Assumed % of	Assumed
Bin	Annual	at Temp Above	time of	hrs of
Temp F	Hours	balance point	operation	Operation
102.5	0	0	100%	0
97.5	3	1	100%	3
92.5	34	10	100%	10
87.5	131	39	100%	39
82.5	500	149	100%	149
77.5	620	185	100%	185
72.5	664	0	100%	0
67.5	854	0	100%	0
62.5	927	0	100%	0
57.5	600	0	100%	0
52.5	610	0	100%	0
47.5	611	0	100%	0
42.5	656	0	100%	0
37.5	1,023	0	100%	0
32.5	734	0	100%	0
27.5	334	0	100%	0
22.5	252	0	100%	0
17.5	125	0	100%	0
12.5	47	0	100%	0
7.5	13	0	100%	0
2.5	0	0	100%	0
-2.5	0	0	100%	0
-7.5	0	0	100%	0
Total	8,738	383	101%	385

Millburn Township Public Schools CHA Project Number: 28330 Hartshorn Elementary School

ECM-10 RTU Replacement

Note: cost is over and above the cost for a standard efficiency model

Multipliers	
Material:	1.10
Labor:	1.35
Equipment:	1.10

Description	QTY	UNIT	UNIT COSTS		SU	BTOTAL COS	STS	TOTAL	REMARKS	
			MAT.	LABOR	EQUIP.	MAT.	LABOR	EQUIP.	COST	KLWAKKS
						\$ -	\$ -	\$ -	\$ -	
										Vendor quote / Eng.
DX cooling and HW heating, 7.5 tons (on average)	4	EA	\$ 2,400	\$ 3,500	\$ 2,000	\$ 10,560	\$ 18,900	\$ 8,800	\$ 38,260	Estimate
						\$ -	\$ -	\$ -	\$ -	

 $Note: Cost\ estimates\ are\ for\ energy\ calculations\ only\mbox{-}\ do\ not\ use\ for\ procurement$

	Subtot
\$ 38,260	al
\$ 9,565	25% Contingency
\$ 47,800	Total

ECM-12: Re-Commission Building Controls System

Summary:

The controls for the building are a combination of both DDC and stand-alone, with major pieces of equipment tied in to the Siemans BAS head end, but smaller pieces of equipment not connected to the BAS and thus individually controlled. Retro-commissioning should address such issues as simultaneous heating and cooling, damper operation and leakage, and equipment scheduling.

Building Infor	mation:		
201,858	Sq Footage	\$0.12	\$/kWh Blended
		\$0.86	\$/Therm


EXISTING CONDITIONS		
Existing Facility Total Electric usage	2,220,800	kWh
Existing Facility Total Gas usage	80,896	Therms
Existing Facility Cooling Electric usage	666,240	kWh ¹
Existing Facility Heating Natural Gas usage	71997.44	Therms ²
PROPOSED CONDITIONS		
Proposed Facility Cooling Electric Savings	99,936	kWh
Proposed Facility Natural Gas Savings	10799.616	Therms
SAVINGS	-	
Retro-Commissioning Electric Savings	99,936	kWh
Retro-Commissioning Natural Gas Savings	10,800	Therms
Total cost savings	\$ 21,279.99	

Assumptions

- 1 30% of facility total electricity dedicated to Cooling based on Building Utility Analysis
- 2 89% of facility total natural gas dedicated to Heating based on Building Utility Analysis
- 3 15% Typical Savings associated with Retro-Commissioning of controls based on EPA Energy Star Report (CH 5 Retrocommissioning)


Figure 5.2: Retrocommissioning results

Building energy system deficiencies: A recent study of retrocommissioning revealed a wide variety of problems—those related to the overall HVAC system were the most common type (A). Energy and non-energy benefits: Retrocommissioning provided both energy and non-energy benefits—the most common of these, noted in one-third of the buildings surveyed, was the extension of equipment life (B).



Note: EMS = energy management system.

B. Energy and non-energy benefits



Courtesy: E SOURCE; data from Lawrence Berkeley National Laboratory, Portland Energy Conservation Inc., and Energy Systems Laboratory, Texas A&M University

Multipliers	
Material:	1.03
Labor:	1.25
Equipment:	1.12

ECM-12: Re-Commission Building Controls System - Cost

Description QTY		UNIT	UNIT COSTS			SUBTOTAL COSTS			TOTAL	REMARKS
Description	QII	UNIT	MAT.	LABOR	EQUIP.	MAT.	LABOR	EQUIP.	COST	REIVIARRO
									\$ -	
Controls and Sensors Retro-Commissioning	201858	SF	\$ 0.27	INC	INC	\$ 55,973	INC	INC	\$ 55,973	EPA Estimate
						\$ -	\$ -	\$ -	\$ -	

^{**}Cost Estimates are for Energy Savings calculations only, do not use for procurement

\$ 55,973	Subtotal
\$ 13,993	25% Contingency
\$ 69,967	Total

ECM-14: Kitchen Hood Control

Description: This ECM evaluates the thermal and electrical energy savings associated with the implementation of a variable flow controlled exhaust hood (Fan) and make-up air unit. The Hood controller uses infrared heat sensors to detect the level of smoke produced by the cooking operations and automatically adjsustes the

	/ Therm		_
¢ 0.12	,		
Φ 0.12	/kWh		
	FORMULA CONSTANTS		
0.746	HP/kW		
1.08	(btu/hr)/CFM·F		
3,412	btu/kWh		
	ELECTRIC FAN SAVINGS		
School			
1			Q
	HP		HP
		NJ Protocols	LF
			FEFF
			RH
0.584			PR
227	kWh		
	HEATING SAVINGS		
Υ			
2,500	ft ²	Estimated	SF
0.70	CFM/ft ²	NJ Protocols	CFM/SF
1.40		NJ Protocols	OF
0.310			FR
2,783		NJ Protocols Table	HDD
80%		AFUE (%)	HEFF
695	MANA		
0,040			
N	COOLING SAVINGS		
- 14		N I Protocols Table	CDD
_			CEFF
			OLI I
-	kWh		
	TOTAL SAVINGS	_	
227			
6,848	Therms		
\$ 5,917			
Ψ 0,017			
	24 1.08 3,412 School 1 1.0 0.90 86.5% 500 0.584 227 Y 2,500 0.70 1.40 0.310 2,783 80% 685 6,848 N 227	School	1.08 (btu/hr)/CFM·F

Savings calculation formulas are taken from NJ Protocols document for Kitchen Hood

ECM-14: Kitchen Hood Control - Cost

Multipliers	
Material:	1.03
Labor:	1.25
Equipment:	1.12

Description	QTY UNIT		UNIT COSTS			SUE	STOTAL CO	STS	TOTAL	REMARKS
Description	QII	UNIT	MAT.	LABOR	EQUIP.	MAT.	LABOR	EQUIP.	COST	REIVIARNS
Me-Link Kitchen Hood Control System	1	ea	\$ 15,000	\$ 2,000		\$ 15,405	\$ 2,492	\$ -	\$ 17,897	Vendor Estimation
5.0 HP VFDs (1-exhaust fan)	1	ea	\$ 1,485	\$ 490		\$ 1,525	\$ 611	\$ -	\$ 2,136	RS Means 2012
5.0 HP Motor	1	ea	\$ 525	\$ 85		\$ 539	\$ 106	\$ -	\$ 645	RS Means 2012
Reprogram DDC system	1	ea	\$ 100	\$ 1,200		\$ 103	\$ 1,495	\$ -	\$ 1,598	RS Means 2012
Electrical - misc.	1	ls	\$ 200	\$ 500		\$ 205	\$ 623	\$ -	\$ 828	RS Means 2012
Remote bulb thermostat	2	ea	\$ 500	\$ 200		\$ 1,027	\$ 498	\$ -	\$ 1,525	RS Means 2012
						\$ -	\$ -	\$ -	\$ -	

^{**}Cost Estimates are for Energy Savings calculations only, do not use for procurement

\$ 24,629	Subtotal
\$ 6,157	25% Contingency
\$ 30,787	Total

ECM-15: Walk-in Cooler & Freezer EC Motor Retrofits

ECM Description:

For kitchens that contain walk-in coolers and freezers, CoolTrol is a controller that reduces energy consumption by controlling off of dewpoint temperature. Compressor cycling is reduced and the evaporator fans run 25% to 80% less. Door and frame heaters are also installed and controlled by store dew point temperature; this can reduce run time by up to 95% in coolers and 60% in freezers. The evaporator fan motors are also replaced with hi-efficiency fan motors saving 40% to 70% in energy. The proposed system comprises of an anti-sweat door controller, evaporator fan motor replacement and CoolTrol Cooler Control System.

Utility Cost

\$0.12 \$/kWh Blended

EXISTING CONDITIONS			
Walk-In Freezer(s)			
Existing Freezer Controls?	N		
Quantity of Walk-In Freezers	C	<mark>)</mark>	
Nameplate Amps of Freezer Evaporator Fan	3	<mark>}</mark>	AmpsEF
Nameplate Volts of Freezer Evaporator Fan	120	<mark>)</mark>	VoltsEF
Phase of Evaporator Fan	1		PhaseEl
Power Factor of Evaporator Fan	0.55		PFEF
Operating Hours	8,760	hrs	
Load Reduction	65%		LR
Electricity Savings (Evaporator Fan)	-	kWh	kWhEF
Electricity Savings (Evaporator Fan Reduced Heat)	-	kWh	kWhRH
Total Walk-In Freezer(s) Electricity Savings	-	kWh	
Walk-In Cooler(s)			
Existing Cooler Controls?	N		
Quantity of Walk-In Coolers	1		
Nameplate Amps of Cooler Evaporator Fan	3		
Nameplate Volts of Cooler Evaporator Fan	120	<mark>)</mark>	
Phase of Evaporator Fan	1		
Power Factor of Evaporator Fan	0.55		
Operating Hours	8,760		
Load Reduction	65%	<mark>)</mark>	
Electricity Savings (Evaporator Fan)	988	kWh	
Electricity Savings (Evaporator Fan Reduced Heat)	443	kWh	
Total Walk-In Cooler(s) Electricity Savings	1,431	kWh	
SAVINGS			
Total Electricity Savings	1,431	kWh	
Total Cost Savings	\$ 172		
Estimated Cost	\$ 20,625		
Simple Payback	120.1	years	

Savings calculation formulas are taken from NJ Protocols document for Walk-in Controller

^{**}Cost Estimates are for Energy Savings calculations only, do not use for procurement

Multipliers	
Material:	1.03
Labor:	1.25
Equipment:	1.12

ECM-15: Walk-in Cooler & Freezer EC Motor Retrofits - Cost

Description	QTY	UNIT	l	JNIT COST	S	SUB	TOTAL CO	STS	TOTAL	REMARKS
Description	QII	ONIT	MAT.	LABOR	EQUIP.	MAT.	LABOR	EQUIP.	COST	REIVIARRO
									\$ -	
Turnkey Walk-In Controller & Equipment	1	EA	\$ 10,000	\$ 5,000	\$ -	\$ 10,270	\$ 6,230	\$ -	\$ 16,500	Vendor Estimate
						\$ -	\$ -	\$ -	\$ -	

^{**}Cost Estimates are for Energy Savings calculations only, do not use for procurement

\$ 16,500	Subtotal
\$ 4,125	25% Contingency
\$ 20,625	Total

ECM-XX: Install Vending Machine Controls

Description: Vending machines generally operate 24/7 regardless of the actual usage. This measure proposes installing vending machine controls to reduce the total run time of these units. Cold beverage machines will cycle on for 15 minutes every two hours in order to keep beverages at a desired temperature. The result is a reduction in total electrical energy usage.

Unit Cost: \$0.120 \$/kWh blended

Energy Savings Calculations:

Existing

Cold Beverage Vending Machine Electric usage
Snack Vending Machine Electric usage
Dual Vending Machine Electric Usage
Total Vending Machine Electric Usage

Proposed

Cold Beverage Vending Machine Electric usage Snack Vending Machine Electric usage Dual Vending Machine Electric Usage Total Vending Machine Electric Usage

Vending Machine Controls Usage Savings Total cost savings Estimated Total Project Cost Simple Payback

100	
315	kWh
0	kWh
1,418	kWh
	_
7,343	kWh
\$ 881	
\$ 840	9
1	vears

7,008 kWh^{1,4,7}

1,752 kWh^{2,5,7}

8,760 kWh

1,103 kWh⁸

 $kWh^{3,6,7}$

Assumptions

- 1 2 Number of cold beverage vending machines
- 2 1 Number of snack vending machines
- 3 Number of dual snack/beverage vending machines
- 4 400 Average wattage, typical of cold beverage machines based on prior project experience
- 5 Average wattage, typical of snack machines based on prior project experience
- 6 300 Average wattage, typical of dual snack/beverage machines based on prior project experience
- 7 8760 Hours per year vending machine plugged in
- 8 3150 Building Occupied Hours
- 9 0.50 Vending Machine Traffic Factor (0.75 for High Traffic, 0.5 for Medium, 0.25 for low)

Multipliers	
Material:	1.03
Labor:	1.25
Equipment:	1.12

ECM-XX: Install Vending Machine Controls - Cost

Description	QTY	UNIT	MAT.	JNIT COST LABOR	S EQUIP.	SUE MAT.	TOTAL CC LABOR	STS EQUIP.	TOTAL COST	REMARKS
									\$ -	
Vending Miser	3	EA	\$ 200	\$ 15	\$ -	\$ 616	\$ 56	\$ -	\$ 672	Vendor Estimation
						\$ -	\$ -	\$ -	\$ -	

^{**}Cost Estimates are for Energy Savings calculations only, do not use for procurement

\$ 672	Subtotal
\$ 168	25% Contingency
\$ 840	Total

New Jersey Pay For Performance Incentive Program

Note: The following calculation is based on the New Jersey Pay For Performance Incentive Program per April, 2012. Building must have a minimum average electric demand of 100 kW. This minimum is waived for buildings owned by local governments or non-profit organizations.

Values used in this calculation are for ALL identified measures except for alternate ECMs, & except for ECM-12 (RCx), regardless of payback or IRR. P4P estimated incentives represent a best case scenario, and will likely be lower depending on which measures are included. The savings displayed here are not guaranteed to qualify for P4P incentives if IRR or payback requirements are not met.

Total Building Area (Square Feet)	201,858
Is this audit funded by NJ BPU (Y/N)	Yes

Incentive	e #1	
Audit is funded by NJ BPU	\$0.10	\$/sqft

Board of Public Utilites (BPU)

	Annual Utilities		
	kWh	Therms	
Existing Cost (from utility)	\$266,271	\$88,656	
Existing Usage (from utility)	2,220,800	80,896	
Proposed Savings	311,842	7,195	
Existing Total MMBtus	15,	15,669	
Proposed Savings MMBtus	1,784		
% Energy Reduction	11.4%		
Proposed Annual Savings	\$66,362		

		Min (Savings = 15%)		Increase (Savings > 15%)		Max Incentive		Achieved Incentive	
		\$/kWh	\$/therm	\$/kWh	\$/therm	\$/kWh	\$/therm	\$/kWh	\$/therm
I	Incentive #2	\$0.09	\$0.90	\$0.005	\$0.05	\$0.11	\$1.25	\$0.00	\$0.00
ľ	Incentive #3	\$0.09	\$0.90	\$0.005	\$0.05	\$0.11	\$1.25	\$0.00	\$0.00

	Incentives \$			
	Elec	Gas	Total	
Incentive #1	\$0	\$0	\$0	
Incentive #2	\$0	\$0	\$0	
Incentive #3	\$0	\$0	\$0	
Total All Incentives	\$0	\$0	\$0	

Total Project Cost	\$657,550

		Allowable	
		Incentive	
% Incentives #1 of Utility Cost*	0.0%	\$0	
% Incentives #2 of Project Cost**	0.0%	\$0	
% Incentives #3 of Project Cost**	0.0%	\$0	
Total Eligible Incentives***	ligible Incentives*** \$0		
Project Cost w/ Incentives	\$657,550		

Project Payback (years)					
w/o Incentives	w/ Incentives				
9.9	9.9				

^{*} Maximum allowable incentive is 50% of annual utility cost if not funded by NJ BPU, and %25 if it is.

Maximum allowable amount of Incentive #3 is 25% of total project cost.

Maximum allowable amount of Incentive #2 & #3 is \$1 million per gas account and \$1 million per electric account; maximum 2 million per project

^{**} Maximum allowable amount of Incentive #2 is 25% of total project cost.

^{***} Maximum allowable amount of Incentive #1 is \$50,000 if not funded by NJ BPU, and \$25,000 if it is.

ECM-L1 Lighting Replacements

Budgetary		Annual Ut	ility Savings		Estimated	Total	New Jersey	Payback	Payback
								(without	
Cost					Maintenance	Savings	Incentive	incentive)	(with incentive)
					Savings				
\$	kW	kWh	therms	\$	\$	\$	\$	Years	Years
\$454,693	102.6	242,071	0	\$31,345	0	\$31,345	\$10,000	14.5	14.2

^{*}Incentive based on New Jersey Smart Start Prescriptive Lighting Measures

ECM-L2 Install Occupancy Sensors

Budgetary		Annual Uti	lity Savings		Estimated	Total	New Jersey	Payback	Payback
								(without	
Cost					Maintenance	Savings	Incentive	incentive)	(with incentive)
					Savings				
\$	kW	kWh	therms	\$	\$	\$	\$	Years	Years
\$10,287	0.0	73,021	0	\$6,937	0	\$6,937	\$1,590	1.5	1.3

^{*}Incentive based on New Jersey Smart Start Prescriptive Lighting Measures

ECM-L3 Lighting Replacements with Occupancy Sensors

Budgetary		Annual Ut	lity Savings		Estimated	Total	New Jersey	Payback	Payback
Cost					Maintenance	Savings	Incentive	(without incentive)	(with incentive)
					Savings				
\$	kW	kWh	therms	\$	\$	\$	\$	Years	Years
\$464,980	102.6	273,215	0	\$34,304	0	\$34,304	\$11,590	13.6	13.2

^{*}Incentive based on New Jersey Smart Start Prescriptive Lighting Measures

5/30/2014 Page 1, Summary

ECM-L1 Lighting	To pade monto		EXISTING CONDITIONS						RETROFIT	CONDITIONS					COST & SAVINGS ANALYSIS		
	Area Description	No. of Fixtures Standard Fixture Code	Watts Fixture Code Fixtu		Exist Control Annual Hour	s Annual kWh	Number of Fixtures	Standard Fixture Code	Fixture Code	Watts per Fixture	kW/Space	Retrofit Control	Annual Hours Annual kWh	Annual kWh Saved Annual kW Sa	ved Annual \$ Saved Retrofit Cost	NJ Smart Start With Ou	
ield Code Unio	que description of the location - Room number/Room name: Floor number (if applicable)		2T Code from Table of Standard Value from			y (kW/space) *	No. of fixtures after	"Lighting Fixture Code" Example 2T 40 R F(U) = 2'x2' Troff 40 w	Code from Table of Standard Fixture	Value from Table of	(Watts/Fixt) * (Number of	Retrofit control	Estimated (kW/space) * annual hours (Annual		ual (kWh Saved) * Cost for	Prescriptive Length of ti	me Length of time for
		lamps U shape	Standard Fixture		usage group			Recess. Floor 2 lamps U shape	Wattages	Standard Fixture	Fixtures)	f.	for the usage Hours) group	Annual kWh) Annual kW)	lighting system	Measures cost to be recovered	be recovered
35LED 35LED	Rm 375 Fine Arts Rm 376	16 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90	1.4	occ 2400 occ 2400	3,456 2,592		T 38 R LED	RTLED38	Wattages 38	0.6	occ	2,400 1,459 2,400 1,094		\$ 257.39 \$ 3,780.00 \$ 193.04 \$ 2,835.00		
4LED 35LED	Stairway Faculty Toilet Mens	2 2B 34 R F 2 (u) (MAG) 1 T 32 R F 3 (ELE)	FU2EE 72 F43ILL/2 90	0.1	occ 2400 breaker 3200 occ 1000	461 90	2	2T XX R LED T 38 R LED	2RTLED RTLED38	25 38	0.1 0.0	occ breaker occ	2,400 1,094 3,200 160 1,000 38	1,498 0.6 301 0.1 3 52 0.1	\$ 36.22 \$ 405.00 \$ 9.17 \$ 236.25	\$0 11.2	11.2
35LED 35LED	Faculty Toilet Womens Corridor	1 T 32 R F 3 (ELE) 13 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90	0.1 1.2	occ 1000 breaker 2280	90 2,668	1 13	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38	0.0 0.5	occ breaker	1,000 38 2,280 1,126	3 52 0.1 5 1,541 0.7	\$ 9.17 \$ 236.25 \$ 201.42 \$ 3,071.25	\$0 15.2	15.2
35LED 35LED 35LED	Rm 374 Rm 373 Rm 372	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90 F43ILL/2 90		occ 2400 occ 2400	2,592 2,592	12 12	T 38 R LED T 38 R LED T 38 R LED	RTLED38 RTLED38 RTLED38	38	0.5 0.5	OCC OCC	2,400 1,094 2,400 1,094 2,400 1,094	1,498 0.6	\$ 193.04 \$ 2,835.00 \$ 193.04 \$ 2,835.00	\$0 14.7	14.7
35LED 35LED	Rm 371 Rm 370	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90 F43ILL/2 90	1.1	occ 2400 occ 2400 occ 2400	2,592 2,592 2,592	12	T 38 R LED T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.5 0.5	000 000	2,400 1,094 2,400 1,094 2,400 1,094	1,498 0.6	\$ 193.04 \$ 2,835.00 \$ 193.04 \$ 2,835.00 \$ 193.04 \$ 2,835.00	\$0 14.7	14.7
35LED 121	Corridor Corridor	2 T 32 R F 3 (ELE) 2 W 34 P F 4	F43ILL/2 90 F44EE 144		breaker 2280 breaker 2280	410 657	2 2	T 38 R LED W 28 P F 4	RTLED38 F44SSILL	38 96	0.1 0.2	breaker breaker	2,280 173 2,280 438	3 237 0.1 3 219 0.1	\$ 30.99 \$ 472.50 \$ 28.60 \$ 283.50	\$0 15.2 \$0 9.9	15.2 9.9
121 35LED	corridor Boys toilet	2 W 34 P F 4 3 T 32 R F 3 (ELE)	F44EE 144 F43ILL/2 90	0.3	breaker 2280 occ 1000	657 270	3	W 28 P F 4 T 38 R LED	F44SSILL RTLED38	96 38	0.2 0.1	breaker occ	2,280 438 1,000 114	156 0.2	\$ 28.60 \$ 283.50 \$ 27.51 \$ 708.75	\$0 25.8	25.8
35LED 35LED 35LED	Girls toilet Custodial closet Corridor	3 T 32 R F 3 (ELE) 1 T 32 R F 3 (ELE) 6 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90 F43ILL/2 90	0.3 0.1	occ 1000 sw 500 breaker 2280	270 45 1,231	1 6	T 38 R LED T 38 R LED T 38 R LED	RTLED38 RTLED38 RTLED38	38 38	0.1	occ sw breaker	1,000 114 500 19 2,280 520	26 0.1	\$ 27.51 \$ 708.75 \$ 6.70 \$ 236.25 \$ 92.96 \$ 1,417.50	\$0 35.3	25.8 35.3 15.2
35LED 35LED	Rm 275 Rm 276	16 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90 F43ILL/2 90	1.4	breaker 2280 occ 2400 occ 2400	3,456 2,592	16 12	T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.6 0.5	OCC OCC	2,280 520 2,400 1,459 2,400 1,094	1,997 0.8	\$ 257.39 \$ 3,780.00 \$ 193.04 \$ 2,835.00	\$0 14.7	14.7
4LED 35LED	Stairway Faculty Toilet Mens	2 2B 34 R F 2 (u) (MAG) 1 T 32 R F 3 (ELE)	FU2EE 72 F43ILL/2 90	0.1 0.1	breaker 3200 occ 1000	461 90	2 1	2T XX R LED T 38 R LED	2RTLED RTLED38	25 38	0.1 0.0	breaker occ	3,200 160 1,000 38	301 0.1 3 52 0.1	\$ 36.22 \$ 405.00 \$ 9.17 \$ 236.25	\$0 11.2 \$0 25.8	11.2 25.8
35LED 35LED	Faculty Toilet Womens Corridor Rm 374	1 T 32 R F 3 (ELE) 13 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90	0.1 1.2	occ 1000 breaker 2280	90 2,668	13	T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.0	occ breaker	1,000 38 2,280 1,126		\$ 9.17 \$ 236.25 \$ 201.42 \$ 3,071.25	\$0 15.2	15.2
35LED 35LED 35LED	Rm 3/4 Rm 273 Rm 272	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90 F43ILL/2 90	1.1	occ 2400 occ 2400 occ 2400	2,592 2,592 2,592	12 12	T 38 R LED T 38 R LED T 38 R LED	RTLED38 RTLED38 RTLED38	38 38	0.5 0.5	occ occ	2,400 1,094 2,400 1,094 2,400 1,094	1,498 0.6 1,498 0.6 1,498 0.6	\$ 193.04 \$ 2,835.00 \$ 193.04 \$ 2,835.00 \$ 193.04 \$ 2,835.00		14.7
35LED 35LED	Rm 271 Rm 270	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90	1.1	occ 2400 occ 2400 occ 2400	2,592 2,592 2,592	12	T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.5 0.5	occ occ	2,400 1,094 2,400 1,094	1,498 0.6	\$ 193.04 \$ 2,835.00 \$ 193.04 \$ 2,835.00	\$0 14.7	14.7
35LED 121	Corridor Corridor	2 T 32 R F 3 (ELE) 2 W 34 P F 4	F43ILL/2 90 F44EE 144		breaker 2280 breaker 2280	410 657	2 2	T 38 R LED W 28 P F 4	RTLED38 F44SSILL	38 96	0.1 0.2	breaker breaker	2,280 173 2,280 438		\$ 30.99 \$ 472.50 \$ 28.60 \$ 283.50	\$0 9.9	
121 35LED	corridor Boys toilet	2 W 34 P F 4 3 T 32 R F 3 (ELE)	F44EE 144 F43ILL/2 90	0.3	breaker 2280 occ 1000	657 270	3	W 28 P F 4 T 38 R LED	F44SSILL RTLED38	96 38	0.2	breaker occ	2,280 438 1,000 114	156 0.2	\$ 28.60 \$ 283.50 \$ 27.51 \$ 708.75	\$0 25.8	25.8
35LED 35LED	Girls toilet Custodial closet Corridor	3 T 32 R F 3 (ELE) 1 T 32 R F 3 (ELE) 6 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90 F43ILL/2 90	0.3 0.1 0.5	occ 1000 sw 500 breaker 2280	270 45 1,231	1	T 38 R LED T 38 R LED T 38 R LED	RTLED38 RTLED38 RTLED38	38 38 38	0.1 0.0 0.2	occ sw breaker	1,000 114 500 19 2,280 520		\$ 27.51 \$ 708.75 \$ 6.70 \$ 236.25 \$ 92.96 \$ 1,417.50	\$0 35.3	35.3
35LED 35LED	Rm 275 Rm 276	16 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90	1.4	occ 2400 occ 2400	3,456 2,592	16	T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.6 0.5	occ occ	2,400 1,459 2,400 1,094	1,997 0.8	\$ 257.39 \$ 3,780.00 \$ 193.04 \$ 2,835.00	\$0 14.7	14.7
4LED 35LED	Stairway Faculty Toilet Mens	2 2B 34 R F 2 (u) (MAG) 1 T 32 R F 3 (ELE)	FU2EE 72 F43ILL/2 90	0.1 0.1	breaker 3200 occ 1000	461 90	1	2T XX R LED T 38 R LED	2RTLED RTLED38	25 38	0.1 0.0	breaker occ	3,200 160 1,000 38	52 0.1	\$ 36.22 \$ 405.00 \$ 9.17 \$ 236.25	\$0 25.8	25.8
35LED 35LED 35LED	Faculty Toilet Womens Corridor Rm 374	1 T 32 R F 3 (ELE) 13 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90 F43ILL/2 90	0.1 1.2	occ 1000 breaker 2280	90 2,668 2,592	13	T 38 R LED T 38 R LED T 38 R LED	RTLED38 RTLED38 RTLED38	38 38	0.0	occ breaker	1,000 38 2,280 1,126 2,400 1,094	1,041 0.7	\$ 9.17 \$ 236.25 \$ 201.42 \$ 3,071.25 \$ 193.04 \$ 2,835.00	\$0 15.2	
35LED 35LED	Rm 273 Rm 272	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90 F43ILL/2 90	1.1	occ 2400 occ 2400 occ 2400	2,592 2,592 2,592	12	T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.5	0CC 0CC	2,400 1,094 2,400 1,094 2,400 1,094	1,498 0.6	\$ 193.04 \$ 2,835.00 \$ 193.04 \$ 2,835.00 \$ 193.04 \$ 2,835.00	\$0 14.7	14.7
35LED 35LED	Rm 271 Rm 270	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90	1.1	occ 2400 occ 2400	2,592 2,592	12 12	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38	0.5 0.5	occ occ	2,400 1,094 2,400 1,094	1,498 0.6 1,498 0.6	\$ 193.04 \$ 2,835.00 \$ 193.04 \$ 2,835.00	\$0 14.7 \$0 14.7	14.7 14.7
35LED 121 121	Corridor Corridor corridor	2 T 32 R F 3 (ELE) 2 W 34 P F 4	F43ILL/2 90 F44EE 144		breaker 2280 breaker 2280	410 657	2	T 38 R LED W 28 P F 4	RTLED38 F44SSILL	38 96	0.1 0.2	breaker breaker	2,280 173 2,280 438		\$ 30.99 \$ 472.50 \$ 28.60 \$ 283.50	\$0 9.9	9.9
35LED 35LED	Boys toilet Girls toilet	2 W 34 P F 4 3 T 32 R F 3 (ELE) 3 T 32 R F 3 (ELE)	F44EE 144 F43ILL/2 90 F43ILL/2 90	0.3	breaker 2280 occ 1000 occ 1000	270 270	3	W 28 P F 4 T 38 R LED T 38 R LED	F44SSILL RTLED38 RTLED38	38	0.2	occ occ	2,280 438 1,000 114 1,000 114	156 0.2	\$ 28.60 \$ 283.50 \$ 27.51 \$ 708.75 \$ 27.51 \$ 708.75	\$0 25.8	25.8
35LED 35LED	Custodial closet Corridor	1 T 32 R F 3 (ELE) 6 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90	0.1 0.5	occ 1000 sw 500 breaker 2280	45 1,231	1 6	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38	0.0	sw breaker	500 19 2,280 520	9 26 0.1 0 711 0.3	\$ 6.70 \$ 236.25 \$ 92.96 \$ 1,417.50	\$0 35.3	35.3
6LED	classroom 140 classroom 142	36 T 34 R F 4 (MAG) 24 T 34 R F 4 (MAG)	F44EE 144 F44EE 144	3.5	sw 2400 sw 2400	12,442 8,294	24	T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50	1.8 1.2	SW SW	2,400 4,320 2,400 2,880	5,414 2.3	\$ 1,046.87 \$ 8,505.00 \$ 697.92 \$ 5,670.00	\$0 8.1	8.1
35LED 35LED	storage classroom 141 classroom 143	4 T 34 R F 4 (MAG) 10 T 32 R F 3 (ELE) 18 T 32 R F 3 (ELE)	F44EE 144 F43ILL/2 90 F43ILL/2 90		sw 500 sw 2400 sw 2400	288 2,160 3,888	10	T 50 R LED T 38 R LED T 38 R LED	RTLED50 RTLED38 RTLED38	38	0.2 0.4 0.7	SW SW	500 100 2,400 912 2,400 1,642	1,248 0.5	\$ 48.45 \$ 945.00 \$ 160.87 \$ 2,362.50 \$ 289.56 \$ 4,252.50	\$0 14.7	14.7
41LED 6LED	Corridor Dance Gym	10 1B 40 R F 2 (MAG) 36 T 34 R F 4 (MAG)	F42SS 94 F44EE 144		breaker 2280 sw 2400	2,143 12,442		4 ft LED Tube T 50 R LED	200732x2 RTLED50	30 50	0.3 1.8	breaker sw	2,280 684 2,400 4,320	1,459 0.6	\$ 190.69 \$ 1,633.50 \$ 1,046.87 \$ 8,505.00	\$0 8.6	8.6
41LED 40LED	Dance Gym Corridor	6 1B 40 R F 2 (MAG) 9 T 32 R F 2 (ELE)	F42SS 94 F42LL 60		sw 2400 breaker 2280	1,354 1,231	6 9	4 ft LED Tube T 38 R LED	200732x2 RTLED38	30 38	0.2 0.3	sw breaker	2,400 432 2,280 780	922 0.4 0 451 0.2	\$ 118.79 \$ 980.10 \$ 59.00 \$ 2,126.25	\$0 8.3 \$0 36.0	8.3 36.0
18LED 18LED 18LED	Rm 137 RM 136 Rm 135	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112 F44ILL 112	1.3	breaker 2400 sw 2400 sw 2400	3,226 3,226	12 12	T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50	50 50	0.6 0.6	breaker sw	2,400 1,440 2,400 1,440 2,400 1,440	1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3	12.3
18LED 18LED	Rm 134 Rm 133	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112	1.3	sw 2400 sw 2400 sw 2400	3,226 3,226	12	T 50 R LED T 50 R LED	RTLED50 RTLED50	50	0.6	SW SW SW	2,400 1,440 2,400 1,440 2,400 1,440	1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3	12.3
18LED 18LED	Rm 132 Rm 131	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112		sw 2400 sw 2400	3,226 3,226	12 12	T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50	0.6 0.6	SW SW	2,400 1,440 2,400 1,440	1,786 0.7 1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3 \$0 12.3	
18LED 18LED	Rm 130 Rm 129	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112 F44ILL 112	1.3	sw 2400 sw 2400	3,226 3,226	12 12	T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50	50 50	0.6	SW SW	2,400 1,440 2,400 1,440 2,400 1,440	1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3	12.3
18LED 18LED 18LED	Rm 232 Rm 233 Rm 234	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112 F44ILL 112	1.3	sw 2400 sw 2400 sw 2400	3,226 3,226 3,226	12	T 50 R LED T 50 R LED	RTLED50 RTLED50	50	0.6 0.6 0.6	SW SW SW	2,400 1,440 2,400 1,440 2,400 1,440	1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3	12.3
18LED 18LED	Rm 235 Rm 236	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112	2 1.3	sw 2400 sw 2400	3,226 3,226	12	T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50	0.6 0.6	SW SW	2,400 1,440 2,400 1,440	1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3 \$0 12.3	12.3 12.3
18LED 18LED	Rm 237 Rm 238	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112	! 1.3 ! 1.3	sw 2400 sw 2400	3,226 3,226	12 12	T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50	50 50	0.6 0.6	SW SW	2,400 1,440 2,400 1,440	1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3	12.3
18LED 18LED	Rm 239 Rm 240 Rm 241	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112 F44ILL 112		sw 2400 sw 2400 sw 2400	3,226 3,226 3,226	12	T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50	50	0.6 0.6	SW SW	2,400 1,440 2,400 1,440 2,400 1,440	1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3	12.3
18LED 18LED	Rm 242 Rm 243	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112		SW 2400 SW 2400 SW 2400 SW 1000	3,226 3,226 3,226 336		T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50	0.6 0.6	sw sw sw	2,400 1,440 2,400 1,440 1,000 150	1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3 \$0 12.3	12.3
18LED 18LED	Boys tollet Girls tollet	3 T 32 R F 4 (ELE) 3 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112		sw 1000	336		T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50	0.2	SW SW	1,000 150	186 0.2 186 0.2 186 0.2	\$ 32.80 \$ 708.75 \$ 32.80 \$ 708.75	\$0 21.6 \$0 21.6	
18LED 18LED 41LED	Boys toilet Girls toilet Corridor	3 T 32 R F 4 (ELE) 3 T 32 R F 4 (ELE) 12 1B 40 R F 2 (MAG)	F44ILL 112 F44ILL 112 F42SS 94		sw 1000 sw 1000 breaker 2280	336 336 2,572		T 50 R LED T 50 R LED 4 ft LED Tube	RTLED50 RTLED50 200732x2	50	0.2 0.2 0.4	sw sw breaker	1,000 150 1,000 150 2,280 821	186 0.2 186 0.2 1,751 0.8	\$ 32.80 \$ 708.75 \$ 32.80 \$ 708.75 \$ 228.83 \$ 1,960.20	\$0 21.6	21.6
41LED 4LED	Corridor Stairway	14 1B 40 R F 2 (MAG) 3 2B 34 R F 2 (u) (MAG)	F42SS 94 FU2EE 72	1.3	breaker 2280 breaker 3200	3,000 691	14	4 ft LED Tube 2T XX R LED	200732x2 200732x2 2RTLED	30 25	0.4	breaker breaker	2,280 958 3,200 240		\$ 266.97 \$ 2,286.90 \$ 54.34 \$ 607.50	\$0 8.6	8.6
4LED 18LED	Stairway classroom 122	3 2B 34 R F 2 (u) (MAG) 12 T 32 R F 4 (ELE)	FU2EE 72 F44ILL 112	1.3	breaker 3200 sw 2400	691 3,226	12	2T XX R LED T 50 R LED	2RTLED RTLED50	25 50	0.1 0.6	breaker sw	3,200 240 2,400 1,440	1,786 0.7	\$ 54.34 \$ 607.50 \$ 230.16 \$ 2,835.00	\$0 11.2 \$0 12.3	12.3
18LED 18LED	classroom 123 classroom 124	16 T 32 R F 4 (ELE) 16 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112 F44ILL 112	1.8	sw 2400 sw 2400	4,301 4,301	16 16	T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50	50	0.8	SW SW	2,400 1,920 2,400 1,920 2,400 1,440	2,381 1.0	\$ 306.89 \$ 3,780.00 \$ 306.89 \$ 3,780.00	\$0 12.3	12.3
18LED 18LED	classroom 125 classroom 126 Rm 226	12 1 32 K F 4 (ELE) 12 T 32 K F 4 (ELE) 12 T 32 K F 4 (ELE)	F44ILL 112 F44ILL 112 F44ILL 112	1.3	sw 2400 sw 2400 sw 2400	3,226 3,226 3,226		T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50	50	0.6 0.6 0.6	SW SW	2,400 1,440 2,400 1,440 2,400 1,440	1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3	12.3
18LED 18LED	Rm 227 Rm 228	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112	2 1.3	sw 2400 sw 2400	3,226 3,226 3,226 3,226	12	T 50 R LED	RTLED50 RTLED50	50 50	0.6	SW SW	2,400 1,440 2,400 1,440	1,786 0.7 1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3 \$0 12.3	12.3 12.3
18LED 18LED	Rm 229 Rm 230	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL 112 F44ILL 112	1.3	sw 2400 sw 2400	3,226 3,226 3,226		T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50	50 50	0.6	sw sw	2,400 1,440 2,400 1,440	1,786 0.7 1,786 0.7	\$ 230.16 \$ 2,835.00 \$ 230.16 \$ 2,835.00	\$0 12.3 \$0 12.3	12.3 12.3
9LED 41LED	Rm 231 New Gymnasium Corridor	12 T 32 R F 4 (ELE) 24 High Bay MH 200 35 Feet High 15 1B 40 R F 2 (MAG)	F44ILL 112 MH200/1 232 F42SS 94	1.3 2 5.6	sw 2400 sw 2912 breaker 2280	3,226 16,214 3,215	24	FXLED78	FXLED78/1	78	0.6 1.9 0.5	sw sw breaker	2,400 1,440 2,912 5,451 2,280 1,026		\$ 230.16 \$ 2,835.00 \$ 1,323.17 \$ 20,260.69 \$ 286.04 \$ 2,450.25	\$3,600 15.3	12.6
35LED 35LED	classroom 115 classroom 117	9 T 32 R F 3 (ELE) 16 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90	0.8	sw 2400 sw 2400	1,944 3,456		4 ft LED Tube T 38 R LED T 38 R LED	200732x2 RTLED38 RTLED38	38	0.3 0.6	SW SW	2,400 821 2,400 1,459	1,123 0.5 1,997 0.8	\$ 144.78 \$ 2,126.25 \$ 257.39 \$ 3,780.00	\$0 14.7 \$0 14.7	14.7 14.7
35LED 35LED	classroom 118 classroom 119	16 T 32 R F 3 (ELE) 16 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90	1.4	sw 2400 sw 2400	3,456 3,456	16 16	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38	0.6 0.6	SW SW	2,400 1,459 2,400 1,459	1,997 0.8 1,997 0.8	\$ 257.39 \$ 3,780.00 \$ 257.39 \$ 3,780.00	\$0 14.7 \$0 14.7	14.7 14.7
35LED 35LED 6LED	classroom 121 classroom 120	16 T 32 R F 3 (ELE) 16 T 32 R F 3 (ELE) 1 T 34 R F 4 (MAG)	F43ILL/2 90 F43ILL/2 90 F44EE 144	1.4	sw 2400 sw 2400 sw 500	3,456 3,456	16	T 38 R LED T 38 R LED T 50 R LED	RTLED38 RTLED38 RTLED50	38 38	0.6 0.6	SW SW	2,400 1,459 2,400 1,459 500 25		\$ 257.39 \$ 3,780.00 \$ 257.39 \$ 3,780.00 \$ 12.11 \$ 236.25	\$0 14.7	14.7
35LED 35LED	storage office office	1 134 K F 4 (MAG) 2 T 32 R F 3 (ELE) 3 T 32 R F 3 (ELE)	F44EE 144 F43ILL/2 90 F43ILL/2 90	0.2	sw 500 sw 2400 sw 2400	432 648		T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.1 0.1 0.1	SW SW SW	2,400 182 2,400 274	2 250 0.1 4 374 0.2	\$ 12.11 \$ 236.25 \$ 32.17 \$ 472.50 \$ 48.26 \$ 708.75	\$0 14.7	14.7
35LED 35LED	office Cafeteria	2 T 32 R F 3 (ELE) 64 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90	0.2 5.8	sw 2400 sw 1600	432 9,216	2 64	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38	0.1 2.4	sw sw	2,400 182 1,600 3,891	2 250 0.1 5,325 3.3	\$ 32.17 \$ 472.50 \$ 776.62 \$ 15,120.00	\$0 14.7 \$0 19.5	14.7 19.5
24LED 41LED	Weight Rm Media Center	24 1B 32 P F 2 (ELE) 48 1B 40 R F 2 (MAG)	F42LL 60 F42SS 94	4.5	sw 2912 sw 2400	4,193 10,829	24 48	4 ft LED Tube 4 ft LED Tube	200732x2 200732x2	30 30	0.7 1.4	sw sw	2,912 2,097 2,400 3,456	7,373 3.1	\$ 257.76 \$ 3,920.40 \$ 950.35 \$ 7,840.80	\$0 8.3	8.3
24LED 24LED 35LED	Boys Locker Rm Girls Locker Rm Music 101	16 1B 32 P F 2 (ELE) 16 1B 32 P F 2 (ELE) 19 7 32 P F 3 (ELE)	F42LL 60 F42LL 60	1.0 1.0	sw 2800 sw 2800	2,688 2,688	16	4 ft LED Tube 4 ft LED Tube T 38 R LED	200732x2 200732x2	30	0.5 0.5	sw sw	2,800 1,344 2,800 1,344 2,400 1,643	1,344 0.5	\$ 166.73 \$ 2,613.60 \$ 166.73 \$ 2,613.60 \$ 289.56 \$ 4.252.50	\$0 15.7	15.7
35LED 35LED	Music 101 Music 100	18 T 32 R F 3 (ELE) 22 T 32 R F 3 (ELE)	F43ILL/2 90 F43ILL/2 90	1.6 2.0	occ 2400 occ 2400	3,888 4,752	22	T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.7	occ	2,400 1,642 2,400 2,006	2 2,246 0.9 3 2,746 1.1	\$ 289.56 \$ 4,252.50 \$ 353.91 \$ 5,197.50	\$0 14.7 \$0 14.7	14.7 14.7

				EXISTING CONDIT	TONS							RETROFIT (CONDITIONS							COST & SAVIN	IGS ANALYSIS			
					Watts per								Watts per		Retrofit			Annual kWh				NJ Smart Start	Simple Payback With Out	(
	Area Description	No. of Fixtures	Standard Fixture Code	Fixture Code	Fixture	kW/Space	Exist Control	Annual Hours	Annual kWh	Number of Fixt	tures Standard Fixture Code	Fixture Code	Fixture	kW/Space		Annual Hours	Annual kWh	Saved	Annual kW Saved	Annual \$ Saved	Retrofit Cost			Simple Pay
ode Uniq	ue description of the location - Room number/Room	No. of fixtures	"Lighting Fixture Code" Example 2T 40 R F(U) = 2'x2' Troff 40 w Recess. Floor 2	Code from Table of Standard	Value from	(Watts/Fixt) * (Fixt		Estimated daily	(kW/space) *	No. of fixtures	after "Lighting Fixture Code" Example	Code from Table of	Value from	(Watts/Fixt) *	Retrofit control		(kW/space) *	(Original Annual	(Original Annual	(kWh Saved) *	Cost for	Prescriptive	Length of time	Length of tir
	name: Floor number (if applicable)	before the retrofit	40 R F(U) = 2'x2' Troff 40 w Recess. Floor 2 lamps U shape	Fixture Wattages	Table of Standard	No.)	control device	hours for the	(Annual Hours)	the retrofit	2T 40 R F(U) = 2'x2' Troff 40 w Recess. Floor 2 lamps U shape	Standard Fixture	Table of Standard	(Number of		annual hours	(Annual		kW) - (Retrofit Annual kW)	(\$/kWh)	renovations to		for renovations	renovations
			lamps o snape		Fixture			usage group			Recess. Floor 2 lamps 0 snape	Wattages	Fixture	Fixtures)		for the usage group	Hours)	Annuai Kvvn)	Annuai KW)		lighting system	weasures	recovered	be recove
					Wattages								Wattages			.								
D	Classroom 102	12	T 32 R F 3 (ELE)	F43ILL/2	90	1.1	occ	2400	2,592	12	T 38 R LED	RTLED38	38	0.5	occ	2,400	1,094				\$ 2,835.00		14.7	14.7
D D	Classroom 103 Corridor	12	T 32 R F 3 (ELE) 1B 32 P F 2 (ELE)	F43ILL/2 F42LL	90 60	1.1	occ breaker	2400 2280	2,592 2,326	12	T 38 R LED 4 ft LED Tube	RTLED38 200732x2	38	0.5	occ breaker	2,400 2,280	1,094	1,498 1,163	0.6	\$ 193.04 \$ 151.96	\$ 2,835.00 \$ 2,776.95	\$0	14.7 18.3	14.7 18.3
D	classroom 208	14	1B 32 P F 2 (ELE)	F42LL	60	0.8	SW	2400	2,016	14	4 ft LED Tube	200732x2	30	0.4	SW	2,400	1,008	1,008	0.4	\$ 129.93	\$ 2,286.90	\$0	17.6	17.6
D	classroom 209	14	1B 32 P F 2 (ELE)	F42LL	60	0.8	SW	2400	2,016	14	4 ft LED Tube	200732x2	30	0.4	sw	2,400	1,008			\$ 129.93			17.6	17.6
D D	classroom 210 classroom 211	14	1B 32 P F 2 (ELE) 1B 32 P F 2 (ELE)	F42LL F42LL	60 60	0.8	sw	2400 2400	2,016 2,016	14	4 ft LED Tube 4 ft LED Tube	200732x2 200732x2	30	0.4	sw sw	2,400 2,400	1,008	1,008 1,008		\$ 129.93 \$ 129.93			17.6 17.6	17.6 17.6
D	classroom 207	14	1B 32 P F 2 (ELE)	F42LL	60	0.8	SW	2400	2,016	14	4 ft LED Tube	200732x2	30	0.4	SW	2,400	1,008		0.4	\$ 129.93			17.6	17.6
D	Boys Rm	4	T 32 R F 4 (ELE)	F44ILL	112	0.4	SW	1000	448	4	T 50 R LED	RTLED50	50	0.2	sw	1,000	200	248	0.2	\$ 43.74			21.6	21.6
D	Girls Rm	4	T 32 R F 4 (ELE)	F44ILL	112	0.4	SW	1000	448	4	T 50 R LED 2T XX R LED	RTLED50 2RTLED RTLED50	50	0.2	sw	1,000	200	248	0.2	\$ 43.74			21.6	21.6
D D	Stairway Toilet rm	2	2B 34 R F 2 (u) (MAG) T 32 R F 4 (ELE)	FU2EE F44ILL	72 112	0.1	breaker sw	3200 1000	461 336	2	T 50 R LED	2RTLED	25	0.1	breaker sw	3,200 1.000	160	301 186		\$ 36.22 \$ 32.80		\$0 \$0	11.2 21.6	11.2 21.6
D	Toilet rm	3	T 32 R F 4 (ELE)	F44ILL	112	0.3	SW	1000	336	3	T 50 R LED	RTLED50	50	0.2	SW	1,000	150	186	0.2	\$ 32.80	\$ 708.75	\$0	21.6	21.6
	front vestibule	18	B CF 36 W	CFT36/1	51	0.9	breaker	2280	2,093	18	B CF 36 W	CFT36/1	51	0.9	breaker	2,280	2,093	-	0.0	\$ -	\$ -	\$0		#DIV/0!
ED	Auditorium Auditorium		PAR 38 SP	H100/1	100	4.8	SW	1820	8,736	48	EVO35/10	EVO35/10	39	1.9	SW	1,820	3,407			\$ 744.47			28.3	28.3
D	Auditorium		PAR 38 SP SQ 13 W CF 2 (MAG)	H100/1 CFQ13/2	100 31	1.5 0.9	SW	1820 1820	2,730 1,693	15	EVO35/10 SQ 13 W CF 2 (MAG)	EVO35/10 CFQ13/2	39	0.6	sw sw	1,820 1.820	1,065			\$ 232.65 \$ -	\$ 6,581.25	\$0	28.3	28.3 #DIV/01
)	Stage	16	T 32 R F 4 (ELE)	F44ILL	112	1.8	SW	1820	3.261	16	T 50 R LED	RTLED50	50	0.8	sw	1,820	1,456	1,805	1.0	\$ 252.23 \$ 289.56			15.0	15.0
1	Music classroom 202	18	T 32 R F 3 (ELE)	F43ILL/2	90	1.6	sw	2400	3,888		T 38 R LED	RTLED38	38	0.7	sw	2,400	1,642	2,246	0.9				14.7	14.7
	Music classroom 201	20	T 32 R F 3 (ELE) T 32 R F 4 (ELE)	F43ILL/2	90	1.8	SW	2400	4,320	20	T 38 R LED T 50 R LED	RTLED38 RTLED50	38	0.8	SW	2,400	1,824 100			\$ 321.73			14.7	14.7
	Storage Corridor	10	T 32 R F 3 (ELE)	F44ILL F43ILL/2	112 90	0.4	sw breaker	500 2280	224 2,052	10	T 38 R LED	RTLED30	38	0.2	sw breaker	500 2,280	866	124 1.186	0.5	\$ 31.96 \$ 154.94	\$ 945.00 \$ 2,362.50	\$0	29.6 15.2	29.6 15.2
1	Old Gymnasium	32	High Bay MH 200 35 Feet High	MH200/1 F42LL	232	7.4	SW	2912 2800	21,619 4,704	32	FXLED78 T 38 R LED	FXLED78/1	78	2.5	sw	2,912	7,268	14,350	4.9	\$ 1,764.22			15.3	12.6
	Old Girls Locker Rm	28	T 32 R F 2 (ELE)	F42LL	60	1.7	SW		4,704	28		RTLED38	38	1.1	sw	2,800	2,979	1,725	0.6	\$ 213.97	\$ 6,615.00	\$0	30.9	30.9
	Old Boys Locker Rm New Girls Locker rm	32	T 32 R F 2 (ELE) T 32 R F 2 (ELE)	F42LL F42LL	60	1.9	SW	2800 2800	5,376 3,360	32	T 38 R LED T 38 R LED	RTLED38	38	1.2	sw sw	2,800	3,405 2,128	1,971 1,232	0.7	\$ 244.54 \$ 152.84	\$ 7,560.00 \$ 4,725.00		30.9 30.9	30.9 30.9
	New Boys Locker rm	20	T 32 R F 2 (ELE)	F42LL F42LL	60	1.2	sw sw	2800		20	T 38 R LED	RTLED38	38	0.8	sw	2,800	2,128	1,232		\$ 152.84			30.9	30.9
	Training Rm	8	T 32 R F 2 (ELE) T 32 R F 2 (ELE)	F42LL	60	0.5	sw	2800	3,360 1,344	8	T 38 R LED	RTLED38	38	0.3	sw	2,800	851	493	0.2	\$ 61.14	\$ 1,890.00	\$0	30.9	30.9
	Corridor	36	1B 32 P F 2 (ELE)	F42LL	60	2.2	breaker	2280	4,925	36	4 ft LED Tube	200732x2	30	1.1	breaker	2,280	2,462	2,462	1.1	\$ 321.80	\$ 5,880.60	\$0	18.3	18.3
	Vestibules Gym storage	12	SQ 13 W CF 2 (MAG) T 32 R F 2 (ELE)	CFQ13/2 F42LL	31 60	0.4	breaker sw	2280 500	848 120	12	SQ 13 W CF 2 (MAG) T 38 R LED	CFQ13/2 RTLED38	31	0.4	breaker sw	2,280 500	848	- 44	0.0	\$ - \$ 11.34	\$ -	\$0	83.3	#DIV/0! 83.3
	Bovs Rm	6	S 32 C F 1 (ELE)	F41LL	32	0.2	SW	1000	192	6	4 ft LED Tube	200732x1	15	0.2	SW	1,000	90	102		\$ 17.99			27.2	27.2
	Girls Rm	6	S 32 C F 1 (ELE)	F41LL	32	0.2	SW	1000	192	6	4 ft LED Tube	200732x1 RTLED38	15	0.1	SW	1,000	90	102	0.1	\$ 17.99		\$0	27.2 14.7	27.2
	Principals office	4	T 32 R F 3 (ELE)	F43ILL/2	90	0.4	SW	2400	864	4	T 38 R LED	RTLED38	38	0.2	SW	2,400	365	499	0.2	\$ 64.35	\$ 945.00	\$0		14.7
1	Asst principals office Conference Rm	4	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	0.4	SW	2400 1200	864 324	4	T 38 R LED	RTLED38 RTLED38	38	0.2	sw sw	2,400 1,200	365	499 187		\$ 64.35 \$ 30.48			14.7 23.3	14.7 23.3
)	Stairway	2	2B 34 R F 2 (u) (MAG)	FU2EE	72	0.1	sw breaker	3200	461	2	2T XX R LED	2RTLED 200732x2	25	0.1	breaker	3,200	160	301		\$ 36.22			11.2	
D	Health classroom	16	1B 32 P F 2 (ELE)	F42LL	60	1.0	SW	2400	2,304	16	4 ft LED Tube		30	0.5	SW	2,400	1,152	1,152	0.5	\$ 148.49	\$ 2,613.60	\$0	17.6	11.2 17.6
D	Team Rm	14	1B 32 P F 2 (ELE) T 32 R F 4 (ELE)	F42LL F44ILL	60 112	0.8	SW	2800 500	2,352 168	14	4 ft LED Tube T 50 R LED	200732x2 RTLED50	30	0.4	sw	2,800 500	1,176			\$ 145.89 \$ 23.97	\$ 2,286.90 \$ 708.75		15.7 29.6	15.7
	Storage Training Rm	4	T 32 R F 2 (ELE)	F42LL	60	0.3	SW	2800	672	4	T 38 R LED	RTLED38	38	0.2	sw sw	2,800	426	93		\$ 23.97			30.9	29.6 30.9
	Storage	3	T 32 R F 4 (ELE)	F44ILL	112	0.3	sw	500	168	3	T 50 R LED	RTLED50	50	0.2	sw	500	75	246 93	0.2	\$ 23.97	\$ 708.75	\$0	29.6	29.6
	Exterior	12	CF 23	CFS23/1	23	0.3	breaker	4368	1,206		CF 23	CFS23/1	23	0.3	breaker	4,368	1,206			\$ -	\$ -	\$0		#DIV/0
)	Exterior Exterior	13	70 W MH Wall Pack	MH70/1 MH100/1	95 128	1.2	breaker breaker	4368 4368	5,394 1,677	13	FXLED18 FXLED39	FXLED18/1 FXLED39/1	18	0.2	breaker breaker	4,368 4.368	1,022		1.0	\$ 496.82 \$ 132.52			11.1 12.6	8.5 10.3
	Exterior	3	INFI TOO	WHTOUT	120	0.4	DIEdkei	4300	1,077	3	FALED39	FALED39/1	39	0.1	Diedkei	4,300	311	1,100	0.3	\$ 132.32	. \$ 1,000.00	\$300	12.0	10.3
-																								
							1	1					1				1							1
		-		+			+	1	-				+				+			-				-
		1					+	+					+	+	+ +		+			<u> </u>				1
		1																						
Total		1.896				180.7			425.079	1.896			7.048	78.1			183,008	242.071	102.6	\$31.345	\$454,693	\$10.000		
Total		1,896				180.7			425,079	1,896			7,048	78.1			Dema	242,071 and Savings h Savings	102.6	\$31,345 102.6 242,071	\$454,693 \$8,348	\$10,000		

5/30/2014 Page 6, ECM-L1

		EXISTING CONDI	ITIONS						RETROFIT	CONDITIONS		T 1		•			COST & SAVINGS	ANALYSIS	NJ Smart Start	Simple Payback
Area Description	No. of Fixtures Standard Fixture Code	Fixture Code	Watts per Fixture	kW/Space Exist C	ontrol Annual Hours	Annual kWh	Number of Fixture	s Standard Fixture Code	Fixture Code	Watts per Fixture	kW/Space	Retrofit Control	Annual Hours	Annual kWh	Annual kWh Saved	Annual kW Saved	Annual \$ Saved	Retrofit Cost	Lighting Incentive	With Out Incentive Simple
Unique description of the location - Room number/Room name: Floor number (if applicable)	n No. of fixtures Lighting Fixture Code	Code from Table of Standard Fixture Wattages	Value from Table of	(Watts/Fixt) * (Fixt Pre-inst. No.)	Estimated annu	ual (kW/space) * (Annual Hours)	No. of fixtures after	"Lighting Fixture Code" Example 2T 40 R F(U) = 2'x2' Troff 40 w	Code from Table of Standard Fixture	Value from Table of	(Watts/Fixt) * (Number of	Retrofit control device	Estimated (annual hours (kW/space) * Annual Hours)	(Original Annual	(Original Annual (Cost for renovations to		Length of time Length renovations
			Standard Fixture		usage group	(Recess. Floor 2 lamps U shape	Wattages	Standard Fixture	Fixtures)		for the usage	,	Annual kWh)	Annual kW)	i	lighting system		cost to be re
Rm 375 Fine Arts	16 T 32 R F 3 (ELE)	F43ILL/2	Wattages 90	1.4 00	2400	3,456.	0 16	T 32 R F 3 (ELE)	F43ILL/2	Wattages 90	1.4	C-OCC	1680 2	2,419.2	1.036.8	0.0	\$98.50	\$270.00	\$35.00	2.7
Rm 376 Stairway	12 T 32 R F 3 (ELE) 2 2B 34 R F 2 (u) (MAG)	F43ILL/2 FU2EE	90	1.1 oc 0.1 brea	2400	2,592. 460.	.0 12	T 32 R F 3 (ELE) 2B 34 R F 2 (u) (MAG)	F43ILL/2 FU2EE	90	1.1	C-OCC none	1680 1	1,814.4 160.8	777.6	0.0	\$73.87		\$35.00 \$0.00	3.7 #E
Faculty Toilet Mens Faculty Toilet Womens	1 T 32 R F 3 (ELE)	F43ILL/2 F43IL1/2	90	0.1 oc 0.1 oc	1000	90.	.0 1	T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.1 0.1	none	1000 9	90.0	0.0	0.0	\$0.00	\$0.00	\$0.00 \$0.00 \$0.00	#E
Corridor Rm 374	13 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	1.2 brea 1.1 oc	er 2280	2,667 2,592	.6 13	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	1.2	none	2280 2	2,667.6	0.0	0.0	\$0.00	\$0.00	\$0.00 \$0.00 \$20.00	#E
Rm 374 Rm 373 Rm 372	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90 90	1.1 0C 1.1 0C	2400	2,592 2,592 2,592	.0 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILU2 F43ILU2 F43ILU2	90	1.1	occ occ	1680 1	,814.4 1,814.4	777.6	0.0	\$73.87	\$128.25 \$128.25	\$20.00 \$20.00 \$20.00	1.7 1.7 1.7
Rm 371 Rm 370	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2	90	1.1 00	2400	2,592.	.0 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2	90	1.1	occ	1680 1	,814.4 ,814.4	777.6	0.0	73.87	\$128.25	\$20.00 \$20.00 \$20.00	1.7
Corridor Corridor	2 T 32 R F 3 (ELE) 2 T 32 R F 3 (ELE) 2 W 34 P F 4	F43ILL/2 F43ILL/2	90	0.2 brea	er 2280	2,592. 410.	.4 2	T 32 R F 3 (ELE) W 34 P F 4	F43ILL/2 F43ILL/2 F44EE	90	0.2	none	2280 4	10.4	0.0	0.0 \$	\$0.00	\$128.25 \$0.00	\$0.00 \$0.00	#[
corridor Boys toilet	2 W 34 P F 4 3 T 32 R F 3 (ELE)	F44EE F44EE F43ILL/2	144 144	0.3 brea	er 2280	656. 656.	.6 2	W 34 P F 4 W 34 P F 4 T 32 R F 3 (ELE)	F44EE F43ILL/2	144 144	0.3	none none	2280 6 2280 6 1000 2	556.6 556.6	0.0	0.0		\$0.00 \$0.00	\$0.00	#
Girls tollet Custodial closet	3 T 32 R F 3 (ELE) 1 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2 F43ILL/2	90	0.3 oc 0.3 oc	1000	270. 270. 45.		T 32 R F 3 (ELE)	F43ILU2 F43ILU2 F43ILU2	90	0.3	none	1000 2	270.0	0.0	0.0		\$0.00 \$0.00	\$0.00 \$0.00	##
Corridor Rm 275	6 T 32 R F 3 (ELE) 16 T 32 R F 3 (FLF)	F43ILL/2 F43ILL/2 F43ILL/2	90 90	0.5 brea	xer 2280	1,231. 3,456	.2 6	T 32 R F 3 (ELE) T 32 R F 3 (ELE) T 32 R F 3 (FLF)	F43ILL/2 F43ILL/2 F43ILL/2	90	0.1 0.5 1.4	none	2280 1	15.0 1,231.2 2.419.2	0.0	0.0	\$0.00	\$0.00 \$0.00 \$128.25	\$0.00 \$0.00 \$20.00	1.3
Rm 276	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE) 2 2B 34 R F 2 (u) (MAG)	F43ILL/2 F43ILL/2 FU2EE	90	1.1 00	2400	2,592.	.0 12	T 32 R F 3 (ELE) 2B 34 R F 2 (u) (MAG)	F43ILU2 F43ILU2 FU2EE	90	1.1	occ	1680 1	,814.4	777.6	0.0 \$	73.87	\$128.25	\$20.00	1.7
Stairway Faculty Toilet Mens	1 T 32 R F 3 (ELE)	F43ILL/2	90	0.1 brea 0.1 oc	1000	460. 90.	.0 1	T 32 R F 3 (ELE)	F43ILL/2	90	0.1	none	1000	160.8 10.0	0.0	0.0	\$0.00	\$0.00 \$0.00	\$0.00	#
Faculty Toilet Womens Corridor	1 T 32 R F 3 (ELE) 13 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.1 oc 1.2 brea	er 2280	2,667	.0 1	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	1.2	none		2,667.6	0.0	0.0	\$0.00	\$0.00 \$0.00	\$0.00 \$0.00	#
Rm 374 Rm 273	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	1.1 oc	2400	2,592. 2,592.		T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	1.1	occ	1680 1	,814.4 ,814.4	777.6 777.6	0.0 \$	73.87	\$128.25 \$128.25	\$20.00 \$20.00	1.7 1.7
Rm 272 Rm 271	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.1 oc 1.1 oc	2400	2,592. 2,592.	.0 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.1	occ	1680 1	,814.4 ,814.4	777.6 777.6	0.0 \$	\$73.87	\$128.25 \$128.25	\$20.00 \$20.00	1.7 1.7
Rm 270 Corridor	12 T 32 R F 3 (ELE) 2 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.1 oc. 0.2 brea		2,592. 410.	.4 2	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.1 0.2	none	2280 4	,814.4 110.4	777.6 0.0	0.0 \$		\$128.25 \$0.00	\$20.00 \$0.00	1.7
Corridor corridor	2 W 34 P F 4 2 W 34 P F 4	F44EE F44EE	144 144	0.3 brea 0.3 brea	er 2280	656. 656.		W 34 P F 4 W 34 P F 4	F44EE F44EE	144 144	0.3 0.3	none none	2280 6	556.6 556.6	0.0	0.0 \$	\$0.00	\$0.00 \$0.00	\$0.00 \$0.00	1
Boys tollet Girls tollet	3 T 32 R F 3 (ELE) 3 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	0.3 oc	1000	270. 270.	.0 3	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	0.3 0.3	none none	1000 2 1000 2	270.0 270.0	0.0	0.0 \$	\$0.00	\$0.00 \$0.00	\$0.00 \$0.00	#
Custodial closet Corridor	1 T 32 R F 3 (ELE) 6 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	0.1 sw 0.5 brea	ker 2280	45. 1,231.		T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	0.1 0.5	none none	2280 1	15.0 1,231.2	0.0	0.0 \$	\$0.00	\$0.00 \$0.00	\$0.00 \$0.00	
Rm 275 Rm 276	16 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.4 oc	2400	3,456. 2,592.	.0 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.4 1.1	occ occ	1680 2 1680 1	2,419.2 1,814.4	1,036.8 777.6	0.0	\$98.50 \$ \$73.87 \$	\$128.25 \$128.25	\$20.00 \$20.00	1.3 1.7
Stairway Faculty Toilet Mens	2 2B 34 R F 2 (u) (MAG) 1 T 32 R F 3 (ELE)	FU2EE F43ILL/2	72 90	0.1 brea 0.1 oc	xer 3200 : 1000	460. 90.	.8 2	2B 34 R F 2 (u) (MAG) T 32 R F 3 (ELE)	FU2EE F43ILL/2	72 90	0.1 0.1	none none		90.0	0.0	0.0	\$0.00 \$	\$0.00 \$0.00	\$0.00 \$0.00	
Faculty Toilet Womens Corridor	1 T 32 R F 3 (ELE) 13 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.1 oc 1.2 brea		90. 2,667.		T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.1 1.2	none		90.0 2,667.6	0.0	0.0 \$	\$0.00	\$0.00 \$0.00	\$0.00 \$0.00	
Rm 374 Rm 273	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.1 oc		2,592. 2,592.	.0 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.1	occ occ		,814.4 ,814.4	777.6 777.6			\$128.25 \$128.25	\$20.00 \$20.00	1.7
Rm 272 Rm 271	12 T 32 R F 3 (ELE) 12 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.1 oc 1.1 oc		2,592. 2,592.	.0 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.1	occ occ		,814.4 ,814.4	777.6 777.6			\$128.25 \$128.25	\$20.00 \$20.00	1.7 1.7
Rm 270 Corridor	12 T 32 R F 3 (ELE) 2 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.1 oc 0.2 brea	2400 ker 2280	2,592 410.	.0 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.1 0.2	occ none		,814.4 110.4	777.6 0.0		\$73.87 \$ \$0.00 \$	\$128.25 \$0.00	\$20.00 \$0.00	1.7
Corridor corridor	2 W 34 P F 4 2 W 34 P F 4	F44EE F44EE	144 144	0.3 brea 0.3 brea	ker 2280 ker 2280	656. 656.		W 34 P F 4 W 34 P F 4	F44EE F44EE	144 144	0.3 0.3	none none	2280 6 2280 6	556.6 556.6	0.0		\$0.00 \$ \$0.00 \$	\$0.00 \$0.00	\$0.00 \$0.00	
Boys toilet Girls toilet	3 T 32 R F 3 (ELE) 3 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	0.3 oc 0.3 oc	1000	270. 270.		T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	0.3	none none	1000 2		0.0	0.0 \$ 0.0 \$			\$0.00 \$0.00	
Custodial closet Corridor	1 T 32 R F 3 (ELE) 6 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.1 sw 0.5 brea	500	270. 45. 1.231		T 32 R F 3 (ELE) T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.1	none none	500 4	15.0 1,231.2	0.0	0.0		\$0.00 \$0.00 \$0.00	\$0.00 \$0.00	
classroom 140 classroom 142	36 T 34 R F 4 (MAG) 24 T 34 R F 4 (MAG)	F44EE F44EE	144 144	5.2 sw 3.5 sw	2400	1,231. 12,441. 8,294.		T 34 R F 4 (MAG) T 34 R F 4 (MAG)	F44EE F44EE	144 144	5.2	occ	1680 8	3,709.1 5,806.1	3,732.5 2,488.3			\$0.00 \$128.25 \$128.25	\$20.00 \$20.00	0.4 0.5
storage classroom 141	4 T 34 R F 4 (MAG) 10 T 32 R F 3 (ELE)	F44EE F43ILL/2	144	0.6 sw 0.9 sw	500	288. 2,160.	.0 4	T 34 R F 4 (MAG) T 32 R F 3 (ELE)	F44EE F43ILL/2	144	0.6	none		288.0 1.512.0	0.0	0.0 \$	\$0.00	\$0.00 \$128.25	\$0.00 \$20.00	
classroom 143 Corridor	18 T 32 R F 3 (ELE) 10 1B 40 R F 2 (MAG)	F43ILL/2 F42SS	90 94	1.6 sw 0.9 brea	2400	3,888. 2,143.	.0 18	T 32 R F 3 (ELE) 1B 40 R F 2 (MAG)	F43ILL/2 F42SS	90 94	1.6	occ none	1680 2 2280 2	2,721.6 2,143.2	1,166.4	0.0 \$	\$110.81	\$128.25 \$0.00	\$20.00 \$0.00	2.1 1.2
Dance Gym Dance Gym	36 T 34 R F 4 (MAG) 6 1B 40 R F 2 (MAG)	F44EE F42SS	144 94	5.2 sw 0.6 sw		12,441. 1,353.	.6 36	T 34 R F 4 (MAG) 1B 40 R F 2 (MAG)	F44EE F42SS	144 94	5.2	none none	2400 1	2,441.6	0.0	0.0 \$	\$0.00	\$0.00	\$0.00 \$0.00	
Corridor Rm 137	9 T 32 R F 2 (ELE) 12 T 32 R F 4 (ELE)	F42LL F44ILL	60 112	0.5 brea 1.3 brea	er 2280	1,231. 3,225.	.2 9	T 32 R F 2 (ELE)	F42LL F44ILL	60 112	0.5 1.3	none	2280 1 1680 2	231.2	0.0 967.7	0.0 \$	\$0.00 \$91.93	\$0.00 \$128.25	\$0.00 \$20.00	1.4
RM 136 Rm 135	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (FLF)	F44ILL F44II I	112	1.3 sw 1.3 sw	2400	3,225. 3,225.	.6 12	T 32 R F 4 (ELE)	F44ILL F44II I	112	1.3	OCC OCC	1680 2 1680 2	2,257.9	967.7 967.7	0.0 \$	\$91.93	\$128.25 \$128.25	\$20.00 \$20.00	1.4
Rm 134 Rm 133	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44ILL	112 112	1.3 sw 1.3 sw	2400	3,225. 3,225.	.6 12 .6 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112 112	1.3	occ occ	1680 2 1680 2	2,257.9	967.7 967.7	0.0 \$		\$128.25 \$128.25	\$20.00 \$20.00	1.4
Rm 132 Rm 131	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44ILL	112	1.3 sw	2400	3,225. 3,225.	6 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112	1.3	occ occ	1680 2 1680 2	2,257.9	967.7 967.7	0.0	\$91.93	\$128.25 \$128.25	\$20.00 \$20.00	1.4
Rm 130 Rm 129	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44ILL	112 112	1.3 sw	2400	3,225. 3,225.	.6 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112	1.3	occ occ		2,257.9	967.7	0.0	\$91.93	\$128.25 \$128.25	\$20.00	1.4
Rm 232 Rm 233	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44II I	112	1.3 sv 1.3 sv	2400	3,225. 3,225.	.6 12	T 32 R F 4 (ELE)	F44ILL F44II I	112	1.3	occ occ	1680 2	2,257.9	967.7	0.0	\$91.93	\$128.25 \$128.25	\$20.00	1.4
Rm 234 Rm 235	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44ILL	112 112	1.3 sw 1.3 sw	2400	3,225. 3,225.	.6 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112 112	1.3	occ occ	1680 2 1680 2	2,257.9	967.7 967.7	0.0	\$91.93	\$128.25 \$128.25	\$20.00 \$20.00 \$20.00	1.4
Rm 236 Rm 237	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44ILL	112 112	1.3 sw 1.3 sw	2400	3,225. 3,225.	.6 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112 112	1.3	occ occ	1680 2	2,257.9	967.7 967.7	0.0	\$91.93	\$128.25	\$20.00 \$20.00	1.4
Rm 238 Rm 239	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44II I	112	1.3 sw 1.3 sw	2400	3,225. 3,225.	.6 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112	1.3	occ occ	1680 2	2,257.9	967.7 967.7	0.0	\$91.93	\$128.25	\$20.00 \$20.00 \$20.00	1.4
Rm 240 Rm 241	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44ILL	112 112 112	1.3 sw	2400	3,225. 3,225.	.6 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112 112 112	1.3	occ	1680 2	2,257.9	967.7 967.7	0.0	\$91.93	\$128.25	\$20.00 \$20.00 \$20.00	1.4
Rm 242 Rm 243	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	112 112 112	1.3 sw 1.3 sw 1.3 sw	2400	3,225. 3,225. 3,225.	.6 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	112 112 112	1.3 1.3	0CC 0CC	1680 2	2,257.9 2,257.9 2,257.9	967.7 967.7	0.0	\$91.93	\$128.25 \$128.25	\$20.00 \$20.00 \$20.00	1.4 1.4 1.4
Boys toilet Girls toilet	3 T 32 R F 4 (ELE) 3 T 32 R F 4 (ELE) 3 T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	112 112 112	0.3 sw	1000	3,225. 336. 336.	.0 3	T 32 R F 4 (ELE) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	112 112 112	0.3	none	1000 3	336.0 336.0	0.0	0.0	\$0.00	\$0.00	\$0.00	1.77
Boys toilet Girls toilet	3 T 32 R F 4 (ELE) 3 T 32 R F 4 (ELE) 3 T 32 R F 4 (ELE)	F44ILL	112	0.3 sw 0.3 sw 0.3 sw	1000	336.	.0 3	T 32 R F 4 (ELE) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	112	0.3 0.3 0.3	none none	1000 3	36.0	0.0	0.0	\$0.00	\$0.00 \$0.00 \$0.00	\$0.00 \$0.00 \$0.00	
Corridor Corridor	3 1 32 R F 4 (ELE) 12 1B 40 R F 2 (MAG) 14 1B 40 R F 2 (MAG)	F44ILL F42SS	94 94	1.1 brea	er 2280	336. 2,571.		1 32 R F 4 (ELE) 1B 40 R F 2 (MAG) 1B 40 R F 2 (MAG)	F42SS	112 94	1.1	none none	1000 3 2280 2	2,571.8	0.0			\$0.00	\$0.00	
Stairway	3 2B 34 R F 2 (u) (MAG)	F42SS FU2EE	72	1.3 brea 0.2 brea	er 3200	3,000. 691.	.2 3	2B 34 R F 2 (u) (MAG)	F42SS FU2EE	94 72	0.2	none		8,000.5 891.2	0.0	0.0			\$0.00 \$0.00	
Stairway classroom 122	3 2B 34 R F 2 (u) (MAG) 12 T 32 R F 4 (ELE) 16 T 32 R F 4 (ELE)	FU2EE F44ILL F44II I	72 112 112	0.2 brea 1.3 sw 1.8 sw	2400	691. 3,225. 4,300.	.6 12	2B 34 R F 2 (u) (MAG) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	FU2EE F44ILL F44II I	72 112 112	0.2 1.3 1.8	none occ	1680 2	91.2 2,257.9 3.010.6	967.7 1.290.2	0.0	\$91.93	\$0.00 \$128.25 \$128.25	\$0.00 \$20.00 \$20.00	1.4
classroom 123 classroom 124	16 T 32 R F 4 (ELE) 16 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	112 112 112	1.8 sw	2400	4,300. 4,300. 3,225.		T 32 R F 4 (ELE) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	112 112 112	1.8	occ	1680	3,010.6 3,010.6 2,257.9	1,290.2		\$122.57	\$128.25 \$128.25 \$128.25	\$20.00 \$20.00 \$20.00	1.0 1.0 1.4
classroom 125 classroom 126 Rm 226	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	112 112 112	1.3 sw	2400	3,225. 3,225. 3,225.	6 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	112 112 112	1.3 1.3 1.3	000 000	1680 2	2,257.9 2,257.9 2,257.9	967.7	0.0	\$91.93	\$128.25 \$128.25 \$128.25	\$20.00 \$20.00	1.4 1.4 1.4
Rm 227	12 1 32 R F 4 (ELE) 12 T 32 R F 4 (ELE) 12 T 32 R F 4 (FLF)	F44ILL F44ILL F44II I	112 112 112	1.3 sw	2400	3,225.	.6 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL F44II I	112 112 112	1.3	000 000	1680 2	2,257.9 2,257.9 2,257.9	967.7		\$91.93	\$128.25 \$128.25 \$128.25	\$20.00	1.4 1.4
Rm 228 Rm 229	12 T 32 R F 4 (ELE)	F44ILL	112	1.3 sw 1.3 sw	2400	3,225. 3,225.	.6 12	T 32 R F 4 (ELE)	F44ILL	112	1.3	occ	1680 2 1680 2	2,257.9	967.7	0.0	\$91.93	\$128.25	\$20.00 \$20.00	1.4
Rm 230 Rm 231	12 T 32 R F 4 (ELE) 12 T 32 R F 4 (ELE)	F44ILL F44ILL	112 112	1.3 sw 1.3 sw	2400	3,225. 3,225.	.6 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112	1.3	occ occ		2,257.9	967.7	0.0 \$	\$91.93	\$128.25 \$128.25	\$20.00 \$20.00	1.4
New Gymnasium Corridor	24 High Bay MH 200 35 Feet High 15 1B 40 R F 2 (MAG)	MH200/1 F42SS	232 94	5.6 sw 1.4 brea	ker 2280	16,214. 3,214.	.8 15	High Bay MH 200 35 Feet High 1B 40 R F 2 (MAG)	MH200/1 F42SS	232 94	5.6 1.4	none		3,214.8	0.0	0.0 \$	\$0.00	\$0.00 \$0.00	\$0.00 \$0.00	
classroom 115 classroom 117	9 T 32 R F 3 (ELE) 16 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	0.8 sw 1.4 sw	2400	1,944. 3,456.	.0 16	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	0.8 1.4	occ occ	1680 1 1680 2	,360.8 2,419.2	583.2 1,036.8		\$98.50	\$128.25 \$128.25	\$20.00 \$20.00	2.3 1.3
classroom 118 classroom 119	16 T 32 R F 3 (ELE) 16 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.4 sw 1.4 sw	2400	3,456. 3,456.	.0 16	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.4 1.4	occ occ	1680 2	2,419.2 2,419.2	1,036.8 1,036.8	0.0	\$98.50	\$128.25 \$128.25	\$20.00 \$20.00	1.3 1.3
classroom 121 classroom 120	16 T 32 R F 3 (ELE) 16 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.4 sw 1.4 sw	2400	3,456. 3,456.	.0 16 .0 16	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	1.4 1.4	occ occ	1680 2 1680 2	2,419.2 2,419.2	1,036.8 1,036.8			\$128.25 \$128.25	\$20.00 \$20.00	1.3 1.3
storage office	1 T 34 R F 4 (MAG) 2 T 32 R F 3 (ELE)	F44EE F43ILL/2	144 90	0.1 sw 0.2 sw	500 2400	72. 432.	.0 1	T 34 R F 4 (MAG) T 32 R F 3 (ELE)	F44EE F43ILL/2	144 90	0.1 0.2	none	500 7 2000 3	72.0 860.0	0.0 72.0	0.0 \$	\$0.00 \$ \$6.84 \$	\$0.00 \$128.25	\$0.00 \$20.00	18.8
office office	3 T 32 R F 3 (ELE) 2 T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.3 sw 0.2 sw	2400	648. 432.	.0 3	T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90 90	0.3	occ occ	2000 5	540.0 860.0	108.0 72.0		\$10.26	\$128.25 \$128.25	\$20.00 \$20.00	12.5 18.8
Cafeteria Weight Rm	64 T 32 R F 3 (ELE) 24 1B 32 P F 2 (ELE)	F43ILL/2 F42LL	90	5.8 sw 1.4 sw	1600	9,216. 4,193.	.0 64	T 32 R F 3 (ELE) 1B 32 P F 2 (ELE)	F43ILL/2 F42LL	90	5.8	none		,216.0	0.0		\$0.00	\$0.00 \$0.00	\$0.00 \$0.00	
Media Center Boys Locker Rm	48 1B 40 R F 2 (MAG) 16 1B 32 P F 2 (ELE)	F42LL F42SS F42LL	94	4.5 sw 1.0 sw	2400	10,828.	.8 48	1B 40 R F 2 (MAG) 1B 32 P F 2 (ELE)	F42LL F42SS F42LL	94	4.5 1.0	OCC OCC	1680 7	7,580.2	3,248.6 384.0		\$308.62	\$128.25	\$20.00 \$20.00 \$20.00	0.4 3.5
	16 1B 32 P F 2 (ELE)	F42LL	60	1.0 sw		2,688.		1B 32 P F 2 (ELE)	F42LL	60	1.0	OCC		2,304.0	384.0				\$20.00	3.5

Part	_				EXISTING CONDIT	TIONS							RETROFIT	CONDITIONS							COST & SAVING	GS ANALYSIS			
						Watts per								Watts per		Retrofit			Annual kWh				NJ Smart Start	Simple Payback With Out	
Part		Area Description	No. of Fixtures	Standard Fixture Code		Fixture	kW/Space	Exist Control	Annual Hours	Annual kWh				Fixture		Control	Annual Hours	Annual kWh	Saved	Annual kW Saved	Annual \$ Saved	Retrofit Cost	Incentive		Simple Payback
The color of the	Field Code			Lighting Fixture Code			(Watts/Fixt) * (Fixt				No. of fixtures a	fter "Lighting Fixture Code" Example												Length of time	Length of time for
Column C		name: Floor number (if applicable)	before the retrofit		Fixture Wattages		No.)	control device		(Annual Hours)	the retrofit							(Annual Hours)			(\$/kWh)				
Company Comp									usage group			recoss. From 2 ramps of shape	···attages		i ixtarco,				Autour Kivii)	Aumau KVI)		ngilling by bloin			De 1000 vereu
Second S	35LED	Olssesses 400	40	T 00 D 5 0 (515)	54011.10	wattagoo	4.4		0400	0.500.0	40	T 00 D E0 (ELE)	E4001170		- 44		0400	0.500.0	0.0	2.0	20.00	60.00	60.00		#DB (O)
1 1 1 1 1 1 1 1 1 1	35LED		12												1.1				0.0	0.0	\$0.00				
## Secretary 1 19 19 19 19 19 19 19	24LED	Corridor	17	1B 32 P F 2 (ELE)	F42LL			breaker				1B 32 P F 2 (ELE)	F42LL	60			2280	2,325.6	0.0	0.0	\$0.00	\$0.00	\$0.00		#DIV/0!
Approx	24LED 24LED		14	1B 32 P F 2 (ELE)	F42LL	60			2400	2,016.0		1B 32 P F 2 (ELE)	F42LL			occ	1680	1,411.2		0.0	\$57.46	\$128.25	\$20.00	2.2	
## Applied 1 10 10 10 10 10 10 10	24LED		14											60		OCC	1680			0.0	\$57.46				
The column The	24LED		14	1B 32 P F 2 (ELE)	F42LL	60	0.8	sw	2400	2,016.0	14	1B 32 P F 2 (ELE)	F42LL	60	0.8	occ	1680			0.0	\$57.46	\$128.25	\$20.00		
## Color Col	24LED 18LED		14		F42LL E44II I	60	0.8	SW	2400	2,016.0	14		F42LL						604.8	0.0	\$57.46	\$128.25	\$20.00	2.2	
## Company Com	18LED	Girls Rm	4	T 32 R F 4 (ELE)	F44ILL				1000	448.0	4	T 32 R F 4 (ELE)	F44ILL				1000	448.0	0.0	0.0	\$0.00	\$0.00	\$0.00		#DIV/0!
Table Tabl	4LED		2		FU2EE	72	0.1				2	2B 34 R F 2 (u) (MAG)	FU2EE	72	0.1				0.0	0.0	\$0.00		\$0.00		#DIV/0!
Second S	18LED 18LED		3				0.3				3				0.3				0.0	0.0	\$0.00	\$0.00	\$0.00		
March Marc	262		18		CFT36/1		0.9				18		CFT36/1		0.9				0.0	0.0	\$0.00	\$0.00	\$0.00		
Market S	261LED		48		H100/1	100	4.8			8,736.0	48	PAR 38 SP	H100/1	100	4.8		1820	8,736.0	0.0	0.0	\$0.00		\$0.00		
10 10 10 10 10 10 10 10	261LED 1		15 30		H100/1 CFQ13/2	31	1.5			2,730.0	15	SQ 13 W CF 2 (MAG)	H100/1 CFQ13/2	100 31			1820		0.0	0.0	\$0.00		\$0.00		#DIV/0! #DIV/0!
10 West 10	18LED	Stage	16	T 32 R F 4 (ELE)	F44ILL			SW	1820	3,261.4		T 32 R F 4 (ELE)	F44ILL				1820		0.0	0.0	\$0.00		\$0.00		#DIV/0!
## State 1	35LED 35LED	Music classroom 202	18								18						1680			0.0					
	18LED		4								20					none			1,296.0	0.0				1.0	#DIV/0!
	35LED	Corridor	10	T 32 R F 3 (ELE)	F43ILL/2	90	0.9	breaker	2280	2,052.0	10	T 32 R F 3 (ELE)	F43ILL/2	90	0.9	none	2280	2,052.0	0.0	0.0	\$0.00	\$0.00	\$0.00		#DIV/0!
Second Content	9LED 40LED		32								32								0.0	0.0	40.00				#DIV/0!
10	40LED 40LED		32		F42LL F42LL		1.7			4,704.0 5,376.0	32								0.0	0.0					#DIV/0!
10	40LED	New Girls Locker rm	20		F42LL	- 00		SW		3,360.0	20			60	1.2	none			0.0	0.0	\$0.00	+	\$0.00		#DIV/0!
Control St. Control St	40LED 40LED	New Boys Locker rm	20		F42LL		1.2	SW	2800	3,360.0	20		F42LL	60	1.2	none	2800		0.0	0.0	\$0.00		\$0.00		
The content of the	24LED	Corridor	36		F42LL		2.2				36			60	2.2				0.0	0.0	\$0.00		\$0.00		
## Part	1	Vestibules	12	SQ 13 W CF 2 (MAG)		31	0.4	breaker	2280	848.2	12	SQ 13 W CF 2 (MAG)	CFQ13/2	31	0.4	none	2280	848.2	0.0	0.0	\$0.00	\$0.00	\$0.00		#DIV/0!
10	40LED 20LED	Gym storage	4		F42LL		0.2	SW	500	120.0	4	T 32 R F 2 (ELE)	F42LL	60	0.2	none	500		0.0	0.0	\$0.00	\$0.00	\$0.00		#DIV/0!
15 Mass Ma	20LED		6			32	0.2				6			32	0.2				0.0	0.0	\$0.00	φ0.00	\$0.00		
Contract 1 12 12 12 12 12 12 12	35LED		4	T 32 R F 3 (ELE)				SW	2400	864.0	4			90		none	2400	864.0	0.0	0.0	\$0.00	\$0.00	\$0.00		#DIV/0!
	35LED 35LED		4			90	0.4				4			90	0.4	none	2400	864.0 270.0	0.0	0.0	\$0.00		\$0.00	25.0	
Column C	4LED	Stairway	2	2B 34 R F 2 (u) (MAG)	FU2EE	72	0.1	breaker			3 2	2B 34 R F 2 (u) (MAG)	FU2EE	72	0.1	none	3200	460.8	0.0	0.0	\$0.00	\$0.00	\$0.00	25.0	
10 Store 3 Fart falls	24LED		16	1B 32 P F 2 (ELE)	F42LL					2,304.0	16	1B 32 P F 2 (ELE)		60		occ	1680		691.2	0.0	\$65.66		\$20.00	2.0	
Column C	18LED		14				0.8				14				0.8				0.0	0.0	\$0.00		\$0.00		
Figure 12 CF32 CF327 22 33 Seeder 488 126.6 12 CF327 22 33 Seeder 488 126.6 12 CF327 22 33 Seeder 489 126.6 12 CF327 22 13 Seeder 489 126.6 12 CF327 22 CF327	40LED		4	T 32 R F 2 (ELE)	F42LL	60	0.2		2800	672.0	4	T 32 R F 2 (ELE)	F42LL	60	0.2		2800	672.0	0.0	0.0	\$0.00		\$0.00		#DIV/0!
Energy 13 Pry Methydright 14 15 15 15 15 15 15 15	18LED		3								3								0.0	0.0	\$0.00	ψ0.00	Q 0.00		
	227LED		13		MH70/1				4368	1,205.6	12		MH70/1						0.0	0.0	\$0.00				#DIV/0!
	142LED	Exterior	3	MH 100	MH100/1	128	0.4	breaker	4368	1,677.3	3	MH 100	MH100/1	128	0.4	none	4368	1,677.3	0.0	0.0	\$0.00	\$0.00	\$0.00		#DIV/0!
																0									
March Marc																0			#VALUE!	#N/A	#VALUE!				#VALUE!
																0	#N/A	#VALUE!	#VALUE!		#VALUE!			#VALUE!	#VALUE!
MALE			1		1		-	1	-						+	0						+			#VALUE! #VALUE!
0 NAVA PAULE																0	#N/A	#VALUE!	#VALUE!	#N/A	#VALUE!			#VALUE!	#VALUE!
		<u> </u>														0				#N/A	#VALUE!				#VALUE!
					- 	1	+	1	+			_		+		0				#N/A	#VALUE!	+			#VALUE!
																0	#N/A	#VALUE!	#VALUE!		#VALUE!			#VALUE!	#VALUE!
			1				1	1	1						+	0						1			#VALUE!
Total Tota			1		- 		1	1							+	0			#VALUE!	#N/A	#VALUE!	+			#VALUE!
																0									#VALUE!
							1	-	+							0					#VALUE!	+			
			 		- 		1	1				 			+	0						+			#VALUE!
																0	#N/A	#VALUE!	#VALUE!	#N/A	#VALUE!				#VALUE!
								-	+							0						+			
Total					<u> </u>					<u> </u>		<u> </u>				0	#N/A	#VALUE!	#VALUE!	#N/A	#VALUE!			#VALUE!	#VALUE!
			1					1	1		1			1	1	0		#VALUE!	#VALUE!	#N/A	#VALUE!	1			#VALUE!
Total			1		- 		1	1	1						+	0						+			
Demand Savings 0.0																Ö	#N/A	#VALUE!	#VALUE!	#N/A	#VALUE!			#VALUE!	#VALUE!
kWh Savings 73,021	To	otal	1,896				180.7			425078.9	1896.0				180.7					0.0	6937.0	10287.0	1590.0		
																		Deman	nd Savings		73.021	\$6 937			
																				1	,			1.5	1.3

5/30/2014 Page 8, ECM-L2

ECM-L3 Ligh	nting Replacements with Occupancy Sensors			EXISTING CONDIT	TIONS						RETROFIT	T CONDITIONS						COST & SAVINGS	ANALYSIS			
					Watts per							Watts per		Retrofit			Annual kWh			NJ Smart Start Lighting	Simple Payback With Out	
Field Code	Area Description Unique description of the location - Room number/Room	No. of Fixtures No. of fixtures	Standard Fixture Code Lighting Fixture Code	Fixture Code Code from Table of Standard	Fixture Value from	kW/Space (Watts/Fixt) * (Fixt	Exist Control Annual Hou Pre-inst. Estimated da	ly (kW/space) *		res Standard Fixture Code fter Lighting Fixture Code	Fixture Code Code from Table of	Fixture Value from	kW/Space (Watts/Fixt) *	Control Retrofit contro		(kW/space) *		(kWh Saved) * Cos	Retrofit Cost t for	Incentive Prescriptive	Incentive Length of time	Simple Payback Length of time for
	name: Floor number (if applicable)	before the retrofit		Fixture Wattages	Table of Standard	No.)	control device hours for the usage group		the retrofit		Standard Fixture Wattages	Table of Standard	(Number of Fixtures)	device	annual hours for the usage	(Annual Hours)	kWh) - (Retrofit Annual kWh) Annual kW)		ovations to ting system	Lighting Measures	for renovations cost to be	renovations cost to be recovered
					Fixture Wattages							Fixture Wattages			group						recovered	
35LED 35LED	Rm 375 Fine Arts Rm 376	16 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90		occ	2400 3,45 2400 2,59	2 12	T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.6 0.5	C-OCC	1,68	30 1,021 30 766	1,826 0.6	\$ 298.97 \$ \$ 224.23 \$	4,050.00 3,105.00		13.5 13.8	13.4 13.7
4LED 35LED	Stairway Faculty Toilet Mens	1	2B 34 R F 2 (u) (MAG) T 32 R F 3 (ELE)	FU2EE F43ILL/2	90	2 0.1 0 0.1	occ	3200 46 1000 9	1 2	2T XX R LED T 38 R LED	2RTLED RTLED38	25 38	0.1	none none	3,20 1,00	00 38	301 0.1 52 0.1	\$ 36.22 \$ \$ 9.17 \$	405.00 236.25	\$ -	11.2 25.8	11.2 25.8
35LED 35LED	Faculty Toilet Womens Corridor Rm 374	13	T 32 R F 3 (ELE) T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2 F43ILL/2	90	0 1.2	occ breaker occ	1000 S 2280 2,66	B 13	T 38 R LED T 38 R LED T 38 R LED	RTLED38 RTLED38 RTLED38	38 38	0.0	none	1,00		52 0.1 1,541 0.7	\$ 9.17 \$ \$ 201.42 \$	236.25 3,071.25 2,963.25	\$ -	25.8 15.2	25.8 15.2 13.1
35LED 35LED 35LED	Rm 373 Rm 372	12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0 1.1		2400 2,59 2400 2,59 2400 2,59		T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38 38	0.5 0.5	occ occ	1,68	30 766 30 766	1,826 0.6 1,826 0.6	\$ 224.23 \$ \$ 224.23 \$ \$ 224.23 \$	2,963.25 2,963.25 2,963.25	\$ 20 \$ 20	13.2 13.2	13.1 13.1
35LED 35LED	Rm 371 Rm 370	12 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0 1.1 0 1.1	occ :	2400 2,56 2400 2,56 2400 2,56		T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38 38	0.5 0.5	occ	1,68	30 766 30 766	1,826 0.6 1,826 0.6 1,826 0.6	\$ 224.23 \$ \$ 224.23 \$ \$ 224.23 \$	2,963.25 2,963.25	\$ 20 \$ 20	13.2 13.2 13.2	13.1
35LED 121	Corridor Corridor	2 2	T 32 R F 3 (ELE) W 34 P F 4	F43ILL/2 F44EE	90	0.2 4 0.3	breaker	2280 41 2280 65	7 2	T 38 R LED W 28 P F 4	RTLED38 F44SSILL	38 38 96	0.1 0.2	none	2,28	30 173 30 438	237 0.1 219 0.1	\$ 30.99 \$ \$ 28.60 \$	472.50 283.50	\$ - \$ -	15.2 9.9	15.2 9.9
121 35LED	corridor Boys toilet	3	W 34 P F 4 T 32 R F 3 (ELE)	F44EE F43ILL/2	144	4 0.3 0 0.3	occ	2280 65 1000 27	7 2	W 28 P F 4 T 38 R LED	F44SSILL RTLED38	96 38	0.2 0.1	none	2,28	00 114	219 0.1 156 0.2	\$ 28.60 \$ \$ 27.51 \$	283.50 708.75	\$ - \$ -	9.9 25.8	9.9 25.8
35LED 35LED	Girls toilet Custodial closet	1	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0 0.3	sw	1000 27 500 4	0 3 5 1	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38	0.1	none	1,00	00 114	156 0.2 26 0.1	\$ 27.51 \$ \$ 6.70 \$	708.75 236.25	\$ -	25.8 35.3	25.8 35.3
35LED 35LED 35LED	Corridor Rm 275 Rm 276	16	T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2 F43ILL/2	90	0.5		2280 1,23 2400 3,45 2400 2,59		T 38 R LED T 38 R LED T 38 R LED	RTLED38 RTLED38 RTLED38	38 38 38	0.2 0.6	none	2,28	30 520 30 1,021	711 0.3 2,435 0.8	\$ 92.96 \$ \$ 298.97 \$	1,417.50 3,908.25 2,963.25	\$ 20	15.2 13.1 13.2	15.2
4LED 35LED	Stairway Faculty Toilet Mens	2	2B 34 R F 2 (u) (MAG) T 32 R F 3 (ELE)	FU2EE F43ILL/2	72	2 0.1	breaker :	2400 2,59 3200 46 1000 9		2T XX R LED T 38 R LED	2RTLED RTLED38	25 38	0.5 0.1 0.0	none none	3,20	00 160	1,826 0.6 301 0.1 52 0.1	\$ 224.23 \$ \$ 36.22 \$ \$ 9.17 \$	405.00 236.25	\$ 20	11.2 25.8	11.2 25.8
35LED 35LED	Faculty Toilet Womens Corridor	1 13	T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0 0.1	occ	1000	0 1 B 13	T 38 R LED	RTLED38 RTLED38	38 38	0.0 0.5	none none	1,00	00 38	52 0.1	\$ 9.17 \$ \$ 201.42 \$	236.25 3,071.25	\$ - \$ -	25.8 15.2	25.8 15.2
35LED 35LED	Rm 374 Rm 273	12 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0 1.1 0 1.1	occ :	2280 2,66 2400 2,59 2400 2,59 2400 2,59	2 12	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38	0.5 0.5	OCC OCC	1,68 1,68	766 766	1,826 0.6 1,826 0.6	\$ 224.23 \$ \$ 224.23 \$	2,963.25 2,963.25	\$ 20 \$ 20	13.2 13.2	13.1 13.1
35LED 35LED	Rm 272 Rm 271	12 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0 1.1 0 1.1		2400 2,59 2400 2,59 2400 2,59	2 12 2 12	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38 38	0.5 0.5	000 000	1,68 1,68	766 766	1,826 0.6 1,826 0.6	\$ 224.23 \$ \$ 224.23 \$	2,963.25 2,963.25	\$ 20 \$ 20	13.2 13.2	13.1 13.1
35LED 35LED	Rm 270 Corridor	12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0 1.1	breaker	2280 41	0 2	T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.5 0.1	none	1,68 2,28	766 30 173	1,826 0.6 237 0.1	\$ 224.23 \$ \$ 30.99 \$	2,963.25 472.50		13.2 15.2	13.1 15.2
121 121 35LED	Corridor corridor	2 2	W 34 P F 4 W 34 P F 4 T 32 R F 3 (FLF)	F44EE F44EE F43ILL/2	14- 14-	4 0.3	breaker	2280 65 2280 65 1000 27	7 2	W 28 P F 4 W 28 P F 4 T 38 R I F D	F44SSILL F44SSILL RTLED38	96 96	0.2 0.2 0.1	none none	2,28	30 438	219 0.1	\$ 28.60 \$ \$ 28.60 \$	283.50 283.50 708.75	\$ - \$ -	9.9 9.9	9.9 9.9
35LED 35LED 35LED	Boys toilet Girls toilet Custodial closet	3	T 32 R F 3 (ELE) T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2 F43ILL/2	90	0 0.3 0 0.3 0 0.1	occ	1000 27 1000 27 500 4	0 3	T 38 R LED T 38 R LED T 38 R LED	RTLED38 RTLED38 RTLED38	38 38 38	0.1 0.1 0.0	none none none	1,00	00 114	156 0.2 156 0.2 26 0.1	\$ 27.51 \$ \$ 27.51 \$ \$ 6.70 \$	708.75 708.75 236.25	\$ -	25.8 25.8 35.3	25.8 25.8 35.3
35LED 35LED	Corridor Rm 275	6	T 32 R F 3 (ELE) T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.5	breaker :	2280 1,23 2400 3,45	1 6	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38	0.0 0.2 0.6	none	2,28		711 0.3	\$ 92.96 \$ \$ 298.97 \$	1,417.50 3,908.25		15.2 13.1	15.2 13.0
35LED 4LED	Rm 276 Stairway	12	T 32 R F 3 (ELE) 2B 34 R F 2 (u) (MAG)	F43ILL/2 FU2EE	90	0 1.1	occ :	2400 2,59	2 12	T 38 R LED 2T XX R LED	RTLED38 2RTLED	38	0.5 0.1	occ none	1,68 3,20	766 00 160	1,826 0.6	\$ 224.23 \$ \$ 36.22 \$	2,963.25 405.00		13.2 11.2	13.1 11.2
35LED 35LED	Faculty Toilet Mens Faculty Toilet Womens	1	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.1	occ	1000	0 1	T 38 R LED T 38 R LED	RTLED38 RTLED38		0.0	none none	1,00	00 38	301 0.1 52 0.1 52 0.1 1,541 0.7	\$ 9.17 \$ \$ 9.17 \$	236.25 236.25	\$ -	25.8 25.8	25.8 25.8
35LED 35LED	Corridor Rm 374	13 12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0 1.2 0 1.1	occ :	2280 2,66 2400 2,59 2400 2,59		T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38 38	0.5 0.5	none	2,28	766	1,541 0.7 1,826 0.6 1,826 0.6	\$ 201.42 \$ \$ 224.23 \$	3,071.25 2,963.25	\$ - \$ 20	15.2 13.2	15.2 13.1
35LED 35LED	Rm 273 Rm 272	12	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0 1.1	occ :	2400 2,59		T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.5 0.5	OCC OCC	1,68	30 766 30 766	1,826 0.6	\$ 224.23 \$ \$ 224.23 \$	2,963.25 2,963.25	\$ 20 \$ 20	13.2 13.2	13.1 13.1
35LED 35LED	Rm 271 Rm 270	12	T 32 R F 3 (ELE) T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2 F43ILL/2	90	0 1.1	occ :	2400 2,59	2 12	T 38 R LED T 38 R LED	RTLED38 RTLED38 RTLED38	38 38 38	0.5 0.5	OCC OCC	1,68	766 766	1,826 0.6 1,826 0.6	\$ 224.23 \$ \$ 224.23 \$	2,963.25 2,963.25	\$ 20	13.2 13.2	13.1 13.1
35LED 121	Corridor Corridor corridor	2 2	W 34 P F 4 W 34 P F 4	F44EE F44EE	144	0.2 4 0.3	breaker :	2280 41 2280 65	7 2	T 38 R LED W 28 P F 4 W 28 P F 4	F44SSILL F44SSILL	96	0.1	none none	2,28	30 438		\$ 30.99 \$ \$ 28.60 \$	472.50 283.50	\$ -	15.2 9.9	15.2 9.9
121 35LED 35LED	Boys toilet Girls toilet	3	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.3	occ occ	2280 65 1000 27 1000 27	0 3	T 38 R LED T 38 R LED	RTLED38	96 38 38	0.1	none	2,28 1,00		156 0.2	\$ 28.60 \$ \$ 27.51 \$ \$ 27.51 \$	283.50 708.75 708.75	\$ -	9.9 25.8 25.8	25.8 25.8
35LED 35LED	Custodial closet Corridor	1 6	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0.1		500 4 2280 1,23	5 1	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38 38	0.0	none	2,28	00 19	26 0.1 711 0.3	\$ 6.70 \$ \$ 92.96 \$	236.25 1,417.50	\$ -	25.8 35.3 15.2	35.3 15.2
6LED	classroom 140 classroom 142	36 24	T 34 R F 4 (MAG) T 34 R F 4 (MAG)	F44EE F44EE	14-	4 5.2 4 3.5	sw	2400 12,44 2400 8,29 500 28	4 24	T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50	1.8 1.2	000	1,68 1,68	3,024 30 2,016	9,418 3.4 6,278 2.3	\$ 1,169.99 \$ \$ 780.00 \$	8,633.25 5,798.25	\$ 20 \$ 20	7.4 7.4	7.4 7.4
6LED 35LED	storage classroom 141	10	T 34 R F 4 (MAG) T 32 R F 3 (ELE)	F44EE F43ILL/2	144			2400 2,16	0 10	T 50 R LED T 38 R LED	RTLED50 RTLED38	50 38 38	0.2 0.4	none	50 1,68	638		\$ 48.45 \$ \$ 186.86 \$	945.00 2,490.75	\$ - \$ 20	19.5 13.3	19.5 13.2
35LED 41LED	classroom 143 Corridor Dance Gym	18	T 32 R F 3 (ELE) 18 40 R F 2 (MAG) T 34 R F 4 (MAG)	F43ILL/2 F42SS F44EE	96	0 1.6 4 0.9	breaker	2280 2,14	3 10	T 38 R LED 4 ft LED Tube T 50 R LED	RTLED38 200732x2	38 30 50	0.7	none	2,28		2,739 0.9 1,459 0.6	\$ 336.35 \$ \$ 190.69 \$	4,380.75 1,633.50	\$ 20 \$ -	13.0 8.6	13.0 8.6
6LED 41LED 40LED	Dance Gym Corridor	6	1B 40 R F 2 (MAG) T 32 R F 2 (ELE)	F42SS F42LL	94	4 0.6 0.5		2400 12,44 2400 1,35 2280 1,23	4 6	4 ft LED Tube T 38 R LED	RTLED50 200732x2 RTLED38	30 38	0.2	none none	2,40	00 4,320 00 432 30 780	8,122 3.4 922 0.4 451 0.2	\$ 1,046.87 \$ \$ 118.79 \$ \$ 59.00 \$	8,505.00 980.10 2,126.25	\$ -	8.1 8.3 36.0	8.3 36.0
18LED 18LED	Rm 137 RM 136	12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112	2 1.3	breaker	2400 3,22 2400 3,22	6 12	T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50	0.6 0.6	OCC OCC	1,68	30 1,008 30 1,008	2,218 0.7	\$ 271.20 \$ \$ 271.20 \$	2,963.25 2,963.25	\$ 20 \$ 20	10.9 10.9	10.9 10.9
18LED 18LED	Rm 135 Rm 134	12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	111		sw	2400 3,22 2400 3,22	6 12	T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50	0.6 0.6	OCC OCC	1,68	30 1,008 30 1,008	2,218 0.7	\$ 271.20 \$ \$ 271.20 \$	2,963.25 2,963.25	\$ 20 \$ 20	10.9	10.9
18LED 18LED	Rm 133 Rm 132	12 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	113	2 1.3 2 1.3	sw :	2400 3,22 2400 3,22	6 12 6 12	T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50	0.6 0.6	OCC OCC	1,68	1,008 1,008	2,218 0.7 2,218 0.7	\$ 271.20 \$ \$ 271.20 \$	2,963.25 2,963.25	\$ 20 \$ 20	10.9 10.9	10.9 10.9
18LED 18LED	Rm 131 Rm 130	12 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112 112 113		sw	2400 3,22 2400 3,22 2400 3,22	6 12 6 12	T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50	50 50 50	0.6 0.6	OCC OCC	1,68 1,68	30 1,008 30 1,008 30 1,008	2.218 0.7	\$ 271.20 \$ \$ 271.20 \$ \$ 271.20 \$	2,963.25 2,963.25	\$ 20 \$ 20	10.9 10.9	10.9 10.9 10.9
18LED 18LED 18LED	Rm 129 Rm 232 Rm 233	12	T 32 R F 4 (ELE) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	111	2 1.3	SW :	2400 3,22 2400 3,22 2400 3,22	6 12	T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50	50 50 50	0.6 0.6 0.6	OCC	1,68	30 1,008 30 1,008 30 1,008		\$ 271.20 \$ \$ 271.20 \$ \$ 271.20 \$	2,963.25 2,963.25 2,963.25	\$ 20 \$ 20	10.9 10.9 10.9	10.9 10.9 10.9
18LED 18LED	Rm 234 Rm 235	12	T 32 R F 4 (ELE) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	112		sw	2400 3,22 2400 3,22 2400 3,22		T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50	50 50 50	0.6 0.6	000 000	1,68	30 1,008 30 1,008	2,218 0.7	\$ 271.20 \$ \$ 271.20 \$ \$ 271.20 \$	2,963.25 2,963.25 2,963.25	\$ 20 \$ 20 \$ 20	10.9	10.9
18LED 18LED	Rm 236 Rm 237	12	T 32 R F 4 (ELE)	F44ILL F44ILL	111	2 1.3	sw	2400 3,22 2400 3,22		T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50	0.6 0.6	OCC OCC	1,68	30 1,008 30 1,008	2,218 0.7	\$ 271.20 \$ \$ 271.20 \$	2,963.25 2,963.25	\$ 20	10.9	10.9
18LED 18LED	Rm 238 Rm 239	12 12	T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	113	2 1.3 2 1.3	sw	2400 3,22	6 12	T 50 R LED T 50 R LED	RTLED50 RTLED50	50	0.6 0.6	000 000	1,68	1,008 1,008	2,218 0.7	\$ 271.20 \$	2,963.25 2,963.25	\$ 20 \$ 20	10.9	10.9
18LED 18LED 18LED	Rm 240 Rm 241	12 12	T 32 R F 4 (ELE)	F44ILL	11: 11:		sw :	2400 3,22 2400 3,22 2400 3,22 2400 3,22	6 12 6 12	T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50 50 50	0.6 0.6	000	1,68	1,008 1,008	2,218 0.7 2,218 0.7	\$ 271.20 \$ \$ 271.20 \$ \$ 271.20 \$ \$ 271.20 \$	2,963.25 2,963.25	\$ 20 \$ 20	10.9 10.9 10.9 10.9	10.9 10.9 10.9 10.9
18LED	Rm 242 Rm 243	12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	113 113	2 1.3	sw	2400 3,22 2400 3,22 1000 33	5 12 6 12	T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50	50 50 50	0.6 0.6	000	1,68	30 1,008 30 1,008 00 150	2,218 0.7 2,218 0.7 186 0.2	\$ 271.20 \$ \$ 271.20 \$ \$ 32.80 \$	2,963.25 2,963.25 708.75	\$ 20 \$ 20	10.9 10.9 21.6	10.9
18LED 18LED 18LED	Boys toilet Girls toilet Boys toilet	3	T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	111	2 0.3 2 0.3 2 0.3	sw	1000 33 1000 33	6 3	T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50	50	0.2 0.2 0.2	none none none	1,00 1,00 1,00	00 150		\$ 32.80 \$ \$ 32.80 \$ \$ 32.80 \$	708.75 708.75 708.75	\$ - \$	21.6 21.6 21.6	21.6 21.6 21.6
18LED 18LED 41LED	Boys toilet Girls toilet Corridor	3 12	T 32 R F 4 (ELE) T 32 R F 4 (ELE) 1B 40 R F 2 (MAG)	F44ILL F44ILL F42SS	112	2 0.3 2 0.3 4 1.1	sw	1000 33	6 3	T 50 R LED T 50 R LED 4 ft LED Tube	RTLED50 200732x2	50 30	0.2 0.2 0.4	none none	1,00	00 150	186 0.2 186 0.2 1,751 0.8	\$ 32.80 \$ \$ 32.80 \$ \$ 228.83 \$	708.75 708.75 1,960.20		21.6	21.6 21.6 8.6
41LED	Corridor Stairway	14	1B 40 R F 2 (MAG) 2B 34 R F 2 (u) (MAG)	F42SS FU2EE	94	4 1.3 2 0.2	breaker breaker	2280 2,57 2280 3,00 3200 69		4 ft LED Tube 2T XX R LED	200732X2 200732X2 2RTLED 2RTLED	30	0.4 0.4 0.1	none	2,28 2,28 3,20		2,043 0.9 451 0.1	\$ 266.97 \$ \$ 54.34 \$	2,286.90	\$ -	8.6 8.6 11.2	8.6 11.2
4LED 4LED 18LED	Stairway classroom 122	3 12	2B 34 R F 2 (u) (MAG) T 32 R F 4 (ELE)	FU2EE F44ILL	72	2 0.2 2 1.3	breaker :	3200 69 2400 3,22	1 3	2T XX R LED T 50 R LED	2RTLED RTLED50 RTLED50	25 25 50 50	0.1 0.6	none	3,20	00 240 30 1,008	451 0.1 2,218 0.7	\$ 54.34 \$ \$ 271.20 \$	607.50 607.50 2,963.25	\$ - \$ 20	11.2 10.9 10.8	11.2 10.9 10.8
18LED 18LED	classroom 123 classroom 124	16 16	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	11:	2 1.8 2 1.8	sw	2400 4,30	1 16	T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50	0.8 0.8	000	1,68	1,344 30 1,344	2,957 1.0	\$ 361.61 \$ \$ 361.61 \$ \$ 271.20 \$	3,908.25 3,908.25	\$ 20 \$ 20	10.8	10.8
18LED 18LED	classroom 125 classroom 126	12	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	112	2 1.3 2 1.3	sw sw	2400 3,22	6 12	T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50 RTLED50 RTLED50	50 50 50	0.6 0.6	OCC OCC	1,68	1,008 1,008	2,218 0.7 2,218 0.7	\$ 271.20 \$	2,963.25 2,963.25	\$ 20	10.9 10.9	10.9 10.9
18LED 18LED	Rm 226 Rm 227 Rm 228	12	T 32 R F 4 (ELE) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	113	2 1.3 2 1.3 2 1.3	sw	2400 3,22	6 12	T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50	50 50 50	0.6 0.6 0.6	000 000	1,68	30 1,008 30 1,008 30 1,008	2,218 0.7	\$ 271.20 \$ \$ 271.20 \$	2,963.25 2,963.25	\$ 20 \$ 20	10.9 10.9	10.9 10.9
18LED 18LED 18LED	Rm 228 Rm 229 Rm 230	12	T 32 R F 4 (ELE) T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL F44ILL	112		sw sw sw	2400 3,22 2400 3,22 2400 3,22	6 12	T 50 R LED T 50 R LED T 50 R LED	RTLED50 RTLED50 RTLED50 RTLED50	50 50 50	0.6 0.6 0.6	000 000	1,68	30 1,008 30 1,008 30 1,008	2,218 0.7	\$ 271.20 \$ \$ 271.20 \$ \$ 271.20 \$	2,963.25 2,963.25 2,963.25	\$ 20 \$ 20	10.9 10.9 10.9	10.9 10.9 10.9
18LED 9LED	Rm 231 New Gymnasium	12 24	T 32 R F 4 (ELE) High Bay MH 200 35 Feet High	F44ILL MH200/1	112			2400 3,22 2400 3,22 2912 16,21	6 12 4 24	T 50 R LED T 50 R LED FXLED78	RTLED50 RTLED50 FXLED78/1	50 50 78	0.6 0.6	occ occ none	1,68	1,008	2,218 0.7 2,218 0.7 10,763 3.7	\$ 271.20 \$ \$ 271.20 \$ \$ 1,323.17 \$	2,963.25 2,963.25 20,260.69	\$ 20 \$ 3,600	10.9	10.9 10.9 12.6
41LED 35LED	Corridor classroom 115	15 9	1B 40 R F 2 (MAG) T 32 R F 3 (ELE)	F42SS F43ILL/2	94	4 1.4 0 0.8	breaker :	2280 3,21 2400 1,94	5 15 4 9	4 ft LED Tube T 38 R LED	200732x2 RTLED38	30	0.5 0.3	none	2,28	30 1,026 30 575	2,189 1.0 1,369 0.5	\$ 286.04 \$ \$ 168.17 \$	2,450.25 2,254.50	\$ - \$ 20	8.6 13.4	8.6 13.3
35LED 35LED	classroom 117 classroom 118	16 16	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	1.4	sw sw	2400 3,45 2400 3,45	6 16 6 16	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38	0.6 0.6	000 000	1,68 1,68	1,021 30 1,021	2,435 0.8 2,435 0.8	\$ 298.97 \$ \$ 298.97 \$	3,908.25 3,908.25	\$ 20 \$ 20	13.1 13.1	13.0 13.0
35LED 35LED	classroom 119 classroom 121	16 16	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	90	0 1.4	sw	2400 3,45	6 16	T 38 R LED T 38 R LED	RTLED38 RTLED38	38	0.6 0.6	000 000	1,68	30 1,021 30 1,021		\$ 298.97 \$ \$ 298.97 \$	3,908.25 3,908.25	\$ 20 \$ 20		13.0
35LED 6LED 35LED	classroom 120 storage office	16	T 32 R F 3 (ELE) T 34 R F 4 (MAG) T 32 R F 3 (ELE)	F43ILL/2 F44EE F43ILL/2	90 144 90	4 0.1	sw	2400 3,45 500 7 2400 43	2 1	T 38 R LED T 50 R LED T 38 R LED	RTLED38 RTLED50 RTLED38	38 50 38	0.6 0.1 0.1	none	1,68 50	1,021 00 25	47 0.1	\$ 298.97 \$ \$ 12.11 \$ \$ 35.06 \$	3,908.25 236.25 600.75	\$ -	13.1 19.5 17.1	13.0 19.5 16.6
35LED 35LED 35LED	office office	3 2	T 32 R F 3 (ELE) T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2 F43ILL/2		0.2 0 0.3 0 0.2		2400 43 2400 64 2400 43	В 3	T 38 R LED T 38 R LED T 38 R LED	RTLED38 RTLED38 RTLED38	38 38 38	0.1 0.1 0.1	OCC OCC	2,00	00 152 00 228 00 152		\$ 35.06 \$ \$ 52.59 \$ \$ 35.06 \$	837.00 600.75			15.5 16.6
35LED 35LED 24LED	Cafeteria Weight Rm	64 24	T 32 R F 3 (ELE) 1B 32 P F 2 (ELE)	F43ILL/2 F43ILL/2 F42LL	90	5.8	sw	1600 9,21 2912 4,19	64	T 38 R LED 4 ft LED Tube	RTLED38 RTLED38 200732x2	38 38 30	2.4 0.7	none none	1,60 2,91		5,325 3.3	\$ 776.62 \$ \$ 257.76 \$	15,120.00 3,920.40	\$ -	19.5 15.2	19.5 15.2
41LED 24LED	Media Center Boys Locker Rm		1B 40 R F 2 (MAG) 1B 32 P F 2 (ELE)	F42SS F42LL	94	4 4.5 0 1.0	SW SW	2400 10,82 2800 2,68	9 48 8 16	4 ft LED Tube 4 ft LED Tube	200732x2 200732x2 200732x2		1.4 0.5	OCC OCC	1,68	30 2,419 00 1,152	8,410 3.1 1,536 0.5	\$ 1,048.85 \$ \$ 184.97 \$	7,969.05 2,741.85	\$ 20 \$ 20	7.6	7.6 14.7
24LED 35LED	Girls Locker Rm Music 101 Music 100	16	1B 32 P F 2 (ELE) T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F42LL F43ILL/2 F43ILL/2	60	0 1.0	sw	2800 2,68 2400 3,88 2400 4,75	B 16	4 ft LED Tube T 38 R LED	200732x2 RTLED38 RTLED38	30 38 38	0.5 0.7	occ none	2,40 2,40	00 1,152 00 1,642 00 2,006	1,536 0.5	\$ 184.97 \$ \$ 289.56 \$ \$ 353.91 \$	2,741.85 4,252.50 5,197.50	\$ 20		14.7 14.7 14.7
35LED	Music 100	22	T 32 R F 3 (ELE)	F43ILL/2	90	2.0	occ :	2400 4,75	2 22	T 38 R LED	RTLED38	38	0.8	none	2,40	2,006	2,746 1.1	\$ 353.91 \$	5,197.50	\$ -	14.7	14.7

Energy Audit of Millburn High School CHA Project No. 28330 ECM-L3 Lighting Replacements with Occupancy Sensors

				EXISTING COND	ITIONS							RETROFIT	CONDITIONS							COST & SAV	INGS ANALYSIS			
					Watts per								Watts per		Retrofit			Annual kWh				NJ Smart Start Lighting	Simple Payback With Out	
	Area Description	No. of Fixtures	Standard Fixture Code	Fixture Code	Fixture	kW/Space	Exist Control	Annual Hours Annual I		Number of Fixtures		Fixture Code	Fixture	kW/Space			rs Annual kWh		Annual kW Save	ed Annual \$ Saved	Retrofit Cost	Incentive	Incentive	Simple Payback
Field Code U	nique description of the location - Room number/Room		Lighting Fixture Code	Code from Table of Standard	Value from	(Watts/Fixt) * (Fix		Estimated daily (kW/space)			Lighting Fixture Code	Code from Table of	Value from	(Watts/Fixt) *		ntrol Estimated	(kW/space) *	(Original Annual	(Original Annual	(kWh Saved) *	Cost for	Prescriptive	Length of time	Length of time for
	name: Floor number (if applicable)	before the retrofi	4	Fixture Wattages	Table of Standard	No.)	control device	hours for the usage group (Annual Hou	urs) tr	he retrofit		Standard Fixture Wattages	Table of Standard	(Number of Fixtures)	device	annual hours for the usage	(Annual Hours)	kWh) - (Retrofit Annual kWh)	kW) - (Retrofit Annual kW)	(\$/kWh)	renovations to lighting system	Lighting Measures	for renovations	renovations cost to be recovered
					Fixture								Fixture			group	,	,	,,				recovered	
35LED	Classroom 102	12	T 32 R F 3 (ELE)	F43ILL/2	Wattages	0 11	000	2400	2.502	12	T 38 R LED	RTLED38	Wattages	0.5	2000	2.4	00 1,094	1 409	3 0.6	\$ 193.04	4 \$ 2,835.0		14.7	14.7
35LED	Classroom 103	12	T 32 R F 3 (ELE)	F43ILL/2	9	0 1.1	000	2400 2400	2,592 2,592		T 38 R LED	RTLED38	38	0.5	none					\$ 193.04			14.7	14.7
24LED	Corridor	17	1B 32 P F 2 (ELE)	F42LL	6	0 1.0	breaker	2280	2,326		4 ft LED Tube	200732x2	30	0.5	none			3 1,163	3 0.5	\$ 151.96	6 \$ 2,776.9	5 \$	18.3	18.3
24LED	classroom 208 classroom 209	14 14	1B 32 P F 2 (ELE) 1B 32 P F 2 (ELE)	F42LL F42LL	6	0.8	sw	2400	2,016		4 ft LED Tube 4 ft LED Tube	200732x2 200732x2	30 30	0.4	000	1,6	80 706 80 706		0.4	\$ 158.66 \$ 158.66			15.2	15.1
24LED 24LED	classroom 210	14	1B 32 P F 2 (ELE)	F42LL	6	0.8	SW	2400 2400	2,016 2,016	14	4 ft LED Tube	200732x2 200732x2	30	0.4	occ	1,6	80 706		0.4	\$ 158.66	6 \$ 2,415.1	5 \$ 20	15.2	15.1 15.1
24LED	classroom 211	14	1B 32 P F 2 (ELE)	F42LL	6	0.8	SW	2400 2400	2,016 2,016	14	4 ft LED Tube	200732x2	30	0.4	OCC	1,6	BO 706	3 1,310 3 1,310	0.4	\$ 158.66	6 \$ 2,415.1	5 \$ 20	15.2	15.1 15.1
24LED 18LED	classroom 207 Boys Rm	14	1B 32 P F 2 (ELE) T 32 R F 4 (ELE)	F42LL F44ILL	6	0.8	sw sw	2400 1000	2,016 448		4 ft LED Tube T 50 R LED	200732x2 RTLED50	30	0.4	000	1,6	00 706 00 200	3 1,310	0.4	\$ 158.66 \$ 43.74				15.1 21.6
18LED	Girls Rm	4	T 32 R F 4 (ELE)	F44ILL	11	2 0.4	SW	1000	448	4	T 50 R LED	RTLED50	50 50	0.2	none	1,0	00 200	248	3 0.2	\$ 43.74		\$	21.6	21.6
4LED	Stairway	2	2B 34 R F 2 (u) (MAG)	FU2EE	7	2 0.1	breaker	3200	461	2	2T XX R LED T 50 R LED	2RTLED RTLED50	25 50	0.1	none	3,2	00 160	301	0.1 0.2	\$ 36.22	2 \$ 405.0) \$.	11.2	11.2 21.6
18LED 18LED	Toilet rm Toilet rm	3	T 32 R F 4 (ELE) T 32 R F 4 (ELE)	F44ILL F44ILL	11	2 0.3	SW	1000	336	3	T 50 R LED T 50 R LED	RTLED50 RTLED50	50	0.2	none	1,0		186	5 0.2 5 0.2	\$ 32.80 \$ 32.80			21.6	21.6 21.6
262	front vestibule	18	B CF 36 W	CFT36/1	5	1 0.9	breaker	2280	2,093		B CF 36 W	CFT36/1	51	0.9	none	2,2		3 .	- 0.0	\$ -	\$ -	\$.		
261LED	Auditorium Auditorium	48	PAR 38 SP PAR 38 SP	H100/1 H100/1	10	0 4.8	SW	1820 1820	8,736	48	EVO35/10	EVO35/10	39	1.9	none	1,8				\$ 744.47			28.3	28.3
261LED 1	Auditorium Auditorium	15	SQ 13 W CF 2 (MAG)	H100/1 CFQ13/2	10	1.5	SW SW	1820	2,730 1,693	15 30	EVO35/10 SQ 13 W CF 2 (MAG)	EVO35/10 CFQ13/2	39 31	0.6	none		20 1,065 20 1,693		5 0.9 - 0.0	\$ 232.65	5 \$ 6,581.2	5 \$	28.3	28.3
18LED	Stage	16	T 32 R F 4 (ELE)	F44ILL	11	2 1.8	SW	1820	3,261	16	T 50 R LED	RTLED50	50	0.8	none		20 1,456	1,805	5 1.0	\$ 252.23	3 \$ 3,780.0		15.0	15.0
35LED 35LED	Music classroom 202 Music classroom 201	18 20	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	9	0 1.6 0 1.8	sw	2400	3,888 4,320	18	T 38 R LED T 38 R LED	RTLED38 RTLED38	38 38	0.7	OCC	1,6	BO 1,149 BO 1,277	2,739	9 0.9 3 1.0	\$ 336.35 \$ 373.72	5 \$ 4,380.7	5 \$ 20	13.0	13.0 12.9
18LED	Music classroom 201 Storage	20	T 32 R F 4 (ELE)	F43ILL/2 F44ILL	9	2 0.4	SW SW				T 50 R LED	RTLED38	50	0.8	none	1,6				\$ 373.72				
35LED	Corridor	10	T 32 R F 3 (ELE)	F43ILL/2	9	0.9	breaker	500 2280	224 2,052	10	T 38 R LED	RTLED38	38	0.4	none	2,2	80 866	1,186	6 0.5	\$ 154.94	4 \$ 2,362.5	\$.	29.6	29.6 15.2
9LED 40LED	Old Gymnasium	32	High Bay MH 200 35 Feet High T 32 R F 2 (ELE)	MH200/1	23	7.4	SW	2912 2800	21,619 4,704	32	FXLED78 T 38 R LED	FXLED78/1 RTLED38	78 38	2.5	none	2,9	12 7,268 00 2,979	3 14,350 9 1,725	0 4.9	\$ 1,764.22 \$ 213.97	2 \$ 27,014.2 7 \$ 6,615.0	6 \$ 4,800		12.6 30.9
40LED 40LED	Old Girls Locker Rm Old Boys Locker Rm	32	T 32 R F 2 (ELE)	F42LL F42LL	6	0 1.7	sw sw			28	T 38 R LED	RTLED38		1.1	none		00 2,979			\$ 213.97	7 \$ 6,615.0 4 \$ 7,560.0		30.9	
40LED	New Girls Locker rm	20	T 32 R F 2 (ELE)	F42LL	6	0 1.2	sw	2800	5,376 3,360	20	T 38 R LED	RTI FD38	38 38	0.8	none	2,8	00 2,128	1,232		\$ 244.54 \$ 152.84	4 \$ 4,725.0	\$.	30.9	30.9 30.9
40LED	New Boys Locker rm	20	T 32 R F 2 (ELE)	F42LL	6	1.2	sw	2800 2800	3,360 1,344	20	T 38 R LED	RTLED38 RTLED38	38 38	0.8	none	2,8		3 1,232	2 0.4	\$ 152.84	4 \$ 4,725.0) \$.	30.9	30.9 30.9
40LED 24LED	Training Rm Corridor	8	T 32 R F 2 (ELE) 1B 32 P F 2 (ELE)	F42LL F42LL	6	0.5	sw breaker	2800 2280	1,344 4,925	8 36	T 38 R LED 4 ft LED Tube	RTLED38 200732x2	38	0.3	none		00 851 80 2,462		3 0.2	\$ 61.14 \$ 321.80			30.9	30.9 18.3
1	Vestibules	12	SQ 13 W CF 2 (MAG)	CFQ13/2	3	1 0.4	breaker	2280	848		SQ 13 W CF 2 (MAG)	CFQ13/2	31	0.4	none		80 848	3	- 0.0	\$ -	\$ -	\$.		
40LED	Gym storage Bovs Rm	4	T 32 R F 2 (ELE) S 32 C F 1 (ELE)	F42LL F41LL	6	0.2	SW	2280 500 1000	120	4	T 38 R LED	RTLED38	38	0.2	none		00 76		4 0.1	\$ 11.34			83.3	83.3
20LED 20LED	Boys Rm Girls Rm	6	S 32 C F 1 (ELE)	F41LL F41LL	3	2 0.2	sw		192	6	4 ft LED Tube 4 ft LED Tube	200732x1 200732x1	15 15	0.1	none	1,0			2 0.1	\$ 17.99 \$ 17.99			27.2	27.2
35LED	Principals office	4	T 32 R F 3 (ELE)	F43ILL/2	9	0.4	SW	1000 2400	864	4	T 38 R LED	RTLED38	38	0.2	none	2,4	00 365	5 499	2 0.1 9 0.2	\$ 64.35	5 \$ 945.0	\$.	27.2	27.2 14.7
35LED	Asst principals office Conference Rm	4	T 32 R F 3 (ELE) T 32 R F 3 (ELE)	F43ILL/2 F43ILL/2	9	0.4	SW	2400 1200	864	4	T 38 R LED	RTLED38	38	0.2	none	2,4		5 499	9 0.2	\$ 64.35			14.7	14.7
35LED 4LED	Stairway	2	2B 34 R F 2 (u) (MAG)	F43ILL/2 FU2EE	7	0.3	sw breaker		324 461	3	T 38 R LED 2T XX R LED	RTLED38 2RTLED	38 25	0.1	none	3,2	00 114	1 210	0.2	\$ 32.64 \$ 36.22			25.6	25.0 11.2
24LED	Health classroom	16	1B 32 P F 2 (ELE)	F42LL	6	0 1.0	SW	3200 2400	2,304		4 ft LED Tube	200732x2	30	0.5	000	1,6	808	1,498	3 0.5	\$ 181.32	2 \$ 2,741.8	5 \$ 20	11.2	11.2 15.0
24LED 18LED	Team Rm	14	1B 32 P F 2 (ELE) T 32 R F 4 (ELE)	F42LL F44ILL	6	0.8	SW	2800 500	2,352 168	14	4 ft LED Tube T 50 R LED	200732x2 RTLED50	30 50	0.4	none		00 1,176	1,176	6 0.4 3 0.2	\$ 145.89 \$ 23.97	9 \$ 2,286.9 7 \$ 708.7) \$.	15.7	15.7 29.6
40LED	Storage Training Rm	4	T 32 R F 2 (ELE)	F44ILL F42LL	11	0.3	sw	2800	672	4	T 38 R LED	RTLED30	38	0.2	none					\$ 23.97			30.9	30.9
18LED	Storage	3	T 32 R F 4 (ELE)	F44ILL	11	2 0.3	SW	500	168	3	T 50 R LED	RTLED50	50	0.2	none	5	00 75		6 0.1 3 0.2	\$ 23.97	7 \$ 708.7	5 \$.	29.6	29.6
117 227LED	Exterior Exterior	12	CF 23 70 W MH Wall Pack	CFS23/1 MH70/1	2	0.3 15 1.2	breaker breaker	4368 4368	1,206 5,394	12	CF 23 FXLED18	CFS23/1 FXLED18/1	23 18	0.3	none	4,3 4,3		2 4,372	- 0.0	\$ 496.82	\$ - 2 \$ 5,501.9	\$ 1,300	11.1	8.5
142LED	Exterior	3	MH 100	MH100/1	12	8 0.4	breaker	4368	1,677	3	FXLED18	FXLED39/1	39	0.1	none		68 511	1 1,166	3 0.3	\$ 132.52	2 \$ 1,668.6	300		10.3
															0	#N/A								#VALUE!
															0	#N/A #N/A								#VALUE!
															ő	#N/A								#VALUE!
															0	#N/A								#VALUE!
															0	#N/A #N/A								#VALUE!
															0	#N/A								#VALUE!
															0	#N/A								#VALUE!
															0	#N/A #N/A								#VALUE! #VALUE!
															0	#N/A								#VALUE!
		+			1	1									0	#N/A			1		1	1	1	#VALUE!
				 											0	#N/A #N/A				+			+	#VALUE!
															0	#N/A								#VALUE!
												_			0	#N/A #N/A	+		1	+	1		1	#VALUE!
				 											0	#N/A				+			+	#VALUE!
															0	#N/A								#VALUE!
					1										0	#N/A #N/A		1		1	1	1	1	#VALUE!
				 											0	#N/A				+			+	#VALUE!
															0	#N/A								#VALUE!
		1	+		1										0	#N/A #N/A					1	1	1	#VALUE!
s Tot	al	1,896	<u> </u>	- 	+	180.7	†	425,07	79	1,896		-	<u> </u>	78.1	0	#IN/A	151,864	1	102.6	34,304	464,980	\$11,590	1	#VALUE!
s		•	•		•		•	+				•	-	-	-	-	Dem	and Savings		102.6	\$8,348	7,220		<u> </u>
S																	kW	Vh Savings	1	273,215	\$25,955		1	
S																	To	tal Savings	1	1	\$34,304	1	13.6	13.2

5/30/2014 Page 10, ECM-L3

APPENDIX D

New Jersey Board of Public Utilities Incentives

- i. Smart Start
- ii. Direct Install
- iii. Pay for Performance (P4P)
- iv. Energy Savings Improvement Plan (ESIP)

I. SMART START



Your Power to Save

At Home, for Business, and for the Future

About Us | Press Room | Library

HOME

RESIDENTIAL

COMMERCIAL, NOUS TRIAL AND LOGAL GOVERNMENT





Home » Commercial & Industrial » Programs

NJ SmartStart Buildings

Program Overview



HURRICANE SANDY

PROGRAMS

NJ SMARTSTART BUILDINGS

EQUIPMENT INCENTIVES

FOOD SERVICE EQUIPMENT

APPLICATION FORMS

TOOLS AND RESOURCES

PAY FOR PERFORMANCE

COMBINED HEAT & POWER AND FUEL CELLS

LOCAL GOVERNMENT ENERGY AUDIT

LARGE ENERGY USERS PROGRAM

ENERGY SAVINGS IMPROVEMENT PROGRAM

DIRECT INSTALL

ENERGY BENCHMARKING

OIL, PROPANE & MUNICIPAL **ELECTRIC CUSTOMERS**

EDA PROGRAMS

SBC CREDIT PROGRAM



With New Jersey SmartStart Buildings ...

... A smart start now means better performance later! Whether you're starting a commer industrial project from the ground up, renovating existing space, or upgrading equipmenunique opportunities to upgrade the energy efficiency of the project.

Special Notice

Enhanced incentives are available for NJ SmartStart Building upgrades in buildings im-Hurricane Sandy. Eligible projects receive an additional 50% and new incentives have added for high efficiency food service equipment.

Visit the Sandy web page for details and important links.

New Jersey SmartStart Buildings can provide a range of support — at no cost to you substantial energy savings, both now and for the future. Learn more about:

> **Project Categories Custom Measures**

Incentives for Qualifying Equipment and Projects

Program Terms and Conditions

Find a Trade Ally

Please note: pre-approval is required for almost all energy efficiency incentives. I you must submit an application form (and applicable worksheets) and receive an approv from the program before any equipment is installed (click here for complete Terms and (Upon receipt of an approval letter, you may proceed to install the equipment listed on yo approved application. Equipment installed prior to the date of the approval letter is not e an incentive. Any customer and/or agent who purchases equipment prior to the rec incentive approval letter does so at his/her own risk.

Getting Started

Submit your project application form as soon as you know you will be doing a constructive or replacing/adding equipment.

PAST PROGRAMS

TOOLS AND RESOURCES

PROGRAM UPDATES

CONTACT US

Apply for pre-approval by submitting an application for the type of equipment you have c install. The application should be accompanied by a related worksheet, where applicable manufacturer's specification sheet (refer to the specific program requirements on the ba application for specs needed for your project) for the equipment you are planning to inst (Program representatives will review your application package and approve it, reject it, advise you of upgrades in equipment that will save energy costs and/or increase your in

Support for Custom Energy-Efficiency Measures

Custom measures allows program participants the opportunity to receive an incentive fo energy-efficiency measures that are not on the prescriptive equipment Incentive list, but project/facility specific.

Incentives for Qualifying Equipment and Projects

Financial incentives are available for large and small projects. These incentives offset so maybe even all! — of the added cost to purchase qualifying energy-efficient equipment, provides significant long-term energy savings. Ranges of incentives are available for quequipment (depending on type, size, and efficiency) in several categories.

Find out more about equipment incentives

For specific details on equipment requirements and financial incentives, including ince equipment not listed here, contact a program representative. Fiscal year financial incent be limited to a maximum of \$500,000 per customer utility account and are available as fi permits.

Home | Residential | Commercial & Industrial | Renewable Energy About Us | Press Room | Library | FAQs | Calendar | Newsletters | Contact Us | Site



Your Power to Save

At Home, for Business, and for the Future

About Us | Press Room | Library

HOME

RESIDENTIAL

BOMMERGIAL, INDUSTRIAL





COMMERCIAL, INDUSTRIAL AND LOCAL GOVERNMENT

HURRICANE SANDY

PROGRAMS

NJ SMARTSTART BUILDINGS

EQUIPMENT INCENTIVES

FOOD SERVICE EQUIPMENT

APPLICATION FORMS

TOOLS AND RESOURCES

PAY FOR PERFORMANCE

COMBINED HEAT & POWER AND FUEL CELLS

LOCAL GOVERNMENT ENERGY AUDIT

LARGE ENERGY USERS PROGRAM

ENERGY SAVINGS IMPROVEMENT PROGRAM

DIRECT INSTALL

ENERGY BENCHMARKING

OIL, PROPANE & MUNICIPAL **ELECTRIC CUSTOMERS**

EDA PROGRAMS

SBC CREDIT PROGRAM

Home » Commercial & Industrial » Programs » NJ SmartStart Buildings

AND LOGAL GOVERNMENT

Equipment Incentives

Special Notice


Enhanced incentives are available for NJ SmartStart Building upgrades in buildings imp Hurricane Sandy. Eligible projects receive an additional 50% and new incentives have added for high efficiency food service equipment.

Visit the Sandy web page for details and important links.

More reasons for a smart start on your next project!

New Jersey SmartStart Buildings provides financial incentives for qualifying equipment. These incentives were developed to help our customers offset some of the added cost to purchase qualifying energy-efficient equipment, which provides significant long-term energy savings. A wide range of incentives are available for qualifying equipment (depending on type, size and efficiency).

Listed below are the types of qualifying equipment and ranges of incentives. For details on equipment requirements and full listings of incentives, refer to the online application forms.



(click for exceptions) To start the pre-approval process,

submit an Equipment Application, and appropriate Equipment Worksheets, for the type (types of equipment you are planning to install along with equipment specification sheets (refer to the specific program requirements on the back of the application for specificatic needed for your project) and a current utility bill(s).

In order to be eligible to receive financial incentives under this Program, Applicants mus receive electric and/or gas service from one of the regulated electric and/or gas utilities in the State of New Jersey. They are: Atlantic City Electric, Jersey Central Power & Light, Rockland Electric Company, New Jersey Natural Gas, Elizabethtown Gas, PSE&G, and South Jersey Gas.

Electric Chillers

Water-cooled chillers (\$12 - \$170 per ton) Air-cooled chillers (\$8 - \$52 per ton)

Gas Cooling

Gas absorption chillers (\$185-\$450 per ton) Gas Engine-Driven Chillers (Calculated through Custom Measure F **PAST PROGRAMS**

TOOLS AND RESOURCES

PROGRAM UPDATES

CONTACT US

Desiccant Systems (\$1.00 per cfm - gas or electric)

Electric Unitary HVAC

Unitary AC and split systems (\$73 - \$92 per ton)
Air-to-air heat pumps (\$73 - \$92 per ton)
Water-source heat pumps (\$81 per ton)
Packaged terminal AC & HP (\$65 per ton)
Central DX AC Systems (\$40 - \$72 per ton)
Dual Enthalpy Economizer Controls (\$250)
Occupancy Controlled Thermostats (\$75 each)
A/C Economizing Controls (\$85 - \$170 each)

Ground Source Heat Pumps

Closed Loop (\$450-750 per ton)

Gas Heating

Gas-fired boilers < 300 MBH (\$300 per unit)
Gas-fired boilers ≥ 300 MBH - 1500 MBH (\$1.75 per MBH)
Gas-fired boilers ≥ 1500 MBH - ≤ 4000 MBH (\$1.00 per MBH)
Gas-fired boilers > 4000 MBH (Calculated through Custom Measure
Gas furnaces (\$300-\$400 per unit)
Gas infrared heaters - indoor only (\$300 - \$500 per unit)
Boiler economizing controls (\$1,200 - \$2,700 per unit)

Variable Frequency Drives

Variable air volume (\$65 - \$155 per hp) Chilled-water pumps (\$60 per hp) Compressors (\$5,250 to \$12,500 per drive)

Natural Gas Water Heating

Gas water heaters ≤ 50 gallons (\$50 per unit)
Gas-fired water heaters > 50 gallons (\$1.00 - \$2.00 per MBH)
Tankless water heaters replacing a free standing water heater > 82
energy factor (\$300 per heater)

Gas-fired booster water heaters (\$17 - \$35 per MBH)

Premium Motors

Three-phase motors (\$45 - \$700 per motor) (Incentive was discor effective March 1, 2013 except for buildings impacted by Hurric Sandy. Approved applications will have the standard timeframyear from the program commitment date to complete the instal

Refrigerator/Freezer Case Premium Efficiency Motors (ECM)

Fractional (< 1 HP) Electronic Commutated Motors (ECM) (\$40 per for replacement of existing shaded-pole motor in refrigerated/freeze

Prescriptive Lighting

New Linear Fluorescent

T-12, HID and Incandescent to T-5 and T-8 (\$25 - \$200 pt fixture) (Note: T12 replacements are only available for buildings impacted by Hurricane Sandy)

New Induction (\$70 per replaced HID fixture)

New LED

Screw-in/Plug-in (\$10 - \$20 per lamp)

Refrigerator/Freezer Case (\$30 - \$65 per fixture)

Outdoor pole/arm/wall-mounted luminaires (\$100 - \$175 p fixture)

Display case (\$30 per case)

Shelf-mounted display and task (\$15 per linear foot)

Wall-wash, desk, recessed (\$20 - \$35 per fixture)

Parking garage luminaires (\$100 per fixture)

Track or Mono-Point directional (\$50 per fixture)

Stairwell and Passageway luminaires (\$40 per fixture)

High-Bay, Low-Bay (\$150 per fixture)

Bollard (\$50 per fixture)

luminaires for Ambient Lighting of Interior Commercial Spa

Linear panels (\$50 per fixture)

Fuel pump canopy (\$100 per fixture)

LED retrofit kits (custom measures)

New Pulse-Start Metal Hallide (\$25 per fixture)

Linear Fluorescent Retrofit (\$10 - \$20 per fixture)

Induction Retrofit (\$50 per retrofitted HID fixture)

New Construction/Complete Renovation (performance-based)

Note: Incentives for T-12 to T-5 and T-8 lamps with electronic ballast in facilities (\$10 per fixture, 1-4 lamps) and T-5/T-8 high bay fixtures (\$16 per fixture) were discontinued effective March 1, 2013 for T-12 retrofits replacements except for buildings impacted by Hurricane Sandy, Appro applications will have the standard timeframe of one year from the proc commitment date to complete the installation

Lighting Controls

Occupancy Sensors

Wall mounted (\$20 per control)

Remote mounted (\$35 per control)

Daylight dimmers (\$25 per fixture controlled, \$50 per fixture office applications only)

Occupancy controlled hi-low fluorescent controls (\$25 per controlled)

HID or Fluorescent Hi-Bay Controls

Occupancy hi-low (\$35 per fixture controlled)

Daylight dimming (\$45 per fixture controlled)

Refrigeration

Covers and Doors

Energy-Efficient doors for open refrigerated doors/covers

Aluminum Night Curtains for open refrigerated cases (\$3.5 linear foot)

Controls

Door Heater Control (\$50 per control)

Electric Defrost Control (\$50 per control)

Evaporator Fan Control (\$75 per control)

Novelty Cooler Shutoff (\$50 per control)

Food Service Equipment

Cooking

Combination Electric Oven/Steamer (\$1,000 per oven)

Combination Gas Oven/Steamer (\$750 per oven)

Electric Convection Oven (\$350 per oven)

Gas Convection Oven (\$500 per oven)

Gas Rack Oven (\$1,000 single, \$2,000 double)

Gas Conveyor Oven (\$500 small deck, \$750 large deck)

Electric Fryer (\$200 per vat)

Gas Fryer (\$749 per vat)

Electric Large Vat Fryer (\$200 per vat)

Gas Large Vat Fryer (\$500 per vat)

Electric Griddle (\$300 per griddle)

Gas Griddle (\$125 per griddle)

Electric Steam Cooker (\$1,250 per steamer)

Gas Steam Cooker (\$2,000 per steamer)

Holding

Full Size Insulated Cabinets (\$300 per cabinet)

Three Quarter Size Insulated Cabinets (\$250 per cabinet)

Half Size Insulated Cabinets (\$200 per cabinet)

Cooling

Glass Door Refrigerators (\$75 - \$150 per unit)

Solid Door Refrigerators (\$50 - \$200 per unit)

Glass Door Freezers (\$200 - \$1,000 per unit)

Solid Door Freezers (\$100 - \$600 per unit)

Ice Machines (\$50 - \$500 per unit)

Cleaning

Dishwashers (\$400 - \$1,500 per unit)

Other Equipment Incentives*

Performance Lighting (\$1.00 per watt per square foot below prograi incentive threshold, currently 5% more energy efficient than ASHRA 2007 for New Construction only.)

Custom electric and gas equipment incentives (not prescriptive)

*Equipment incentives are calculated based on type, efficiency, size, and apand are evaluated on a case-by-case basis. Contact us for details.

Home | Residential | Commercial & Industrial | Renewable Energy About Us | Press Room | Library | FAQs | Calendar | Newsletters | Contact Us | Site

II. DIRECT INSTALL



Your Power to Save

At Home, for Business, and for the Future

About Us | Press Room | Library

HOME

RESIDENTIAL

COMMERCIAL, INDUSTRIAL AND LOCAL GOVERNMENT





Home » Commercial & Industrial » Programs

Direct Install



HURRICANE SANDY

PROGRAMS

NJ SMARTSTART BUILDINGS

PAY FOR PERFORMANCE

COMBINED HEAT & POWER AND FUEL CELLS

LOCAL GOVERNMENT ENERGY AUDIT

LARGE ENERGY USERS PROGRAM

ENERGY SAVINGS IMPROVEMENT PROGRAM

DIRECT INSTALL

PARTICIPATION STEPS

PARTICIPATING CONTRACTORS

SUSTAINABLE JERSEY

ENERGY BENCHMARKING

OIL, PROPANE & MUNICIPAL ELECTRIC CUSTOMERS

EDA PROGRAMS

SBC CREDIT PROGRAM



Let us pay up to 70% of your energy efficiency upgrade.

Sometimes, the biggest challenge to improving energy efficiency is knowing where to and how to get through the process. Created specifically for existing small to medium facilities, Direct Install is a turnkey solution that makes it easy and affordable to upgrahigh efficiency equipment. Direct Install is designed to cut your facility's energy costs replacing lighting, HVAC and other outdated operational equipment with energy efficient alternatives. The program pays up to 70% of retrofit costs, dramatically improving yo payback on the project. There is a \$125,000 incentive cap on each project.

ELIGIBILITY



Existing small to mid-sized commercial and industrial fawith a peak electric demand that did not exceed 200 k any of the preceding 12 months are eligible to participa Direct Install. Applicants will submit the last 12 months electric utility bills indicating that they are below the deithreshold and have occupied the building during that till Buildings must be located in New Jersey and served by the state's public, regulated electric or natural gas utility companies.

SYSTEMS & EQUIPMENT ADDRESSED BY THE PROGRAM

Lighting
Heating, Cooling & Ventilation (HVAC)
Refrigeration

Motors

Natural Gas

Variable Frequency Drives



Measures eligible for Direct Install are limited to specific equipment categories, types capacities. Boilers may not exceed 500,000 Btuh and furnaces may not exceed 140,

III. PAY FOR PERFORMANCE (P4P)



Your Power to Save

At Home, for Business, and for the Future

About Us | Press Room | Library

HOME

RESIDENTIAL





Home » Commercial & Industrial » Programs » Pay for Performance

Pay for Performance - Existing Buildings

Download program applications and incentive forms.

The Greater the Savings, the Greater Your Incentives

Take a comprehensive, whole-building approach to saving energy in your existing facilities earn incentives that are directly linked to your savings. Pay for Performance relies on a

COMMERCIAL, INDUSTRIAL AND LOCAL GOVERNMENT

HURRICANE SANDY

PROGRAMS

NJ SMARTSTART BUILDINGS

PAY FOR PERFORMANCE

EXISTING BUILDINGS

PARTICIPATION STEPS

APPLICATIONS AND FORMS

APPROVED PARTNERS

NEW CONSTRUCTION

FAQS

BECOME A PARTNER

COMBINED HEAT & POWER AND FUEL CELLS

LOCAL GOVERNMENT ENERGY **AUDIT**

LARGE ENERGY USERS PROGRAM

ENERGY SAVINGS IMPROVEMENT PROGRAM

DIRECT INSTALL

ENERGY BENCHMARKING



program partners who provide technical services under direct you. Acting as your energy expert, your partner will develop ε reduction plan for each project with a whole-building technica component of a traditional energy audit, a financial plan for fu energy efficient measures and a construction schedule for ins

Eligibility

Existing commercial, industrial and institutional buildings with demand over 100 kW for any of the preceding twelve months to participate including hotels and casinos, large office buildir family buildings, supermarkets, manufacturing facilities, schoshopping malls and restaurants. Buildings that fall into the fol customer classes are not required to meet the 100 kW demai

to participate in the program: hospitals, public colleges and universities, 501(c)(3) non-p affordable multifamily housing, and local governmental entities. Your energy reduction p define a comprehensive package of measures capable of reducing the existing energy consumption of your building by 15% or more.

Exceptions to the 15% threshold requirement may be made for certain industrial, manufwater treatment and datacenter building types whose annual energy consumption is her weighted on process loads. Details are available in the high energy intensity section of t

ENERGY STAR Portfolio Manager

Pay for Performance takes advantage of the ENERGY STAR Program with Portfolio Manager, EPA's interactive tool that allows facility managers to track and evaluate energy and water consumption across all of their buildings. The tool provides the opportunity to load in the characteristics and energy usage of your buildings and determine an energy performance benchmark score. You can then assess energy management goals over time, identify strategic opportunities for savings, and receive EPA recognition for superior energy performance



This rating system assesses building performance by tracking and scoring energy use in facilities and comparing it to similar buildings. That can be a big help in locating opportui cost-justified energy efficiency upgrades. And, based on our findings, you may be invited participate in the Building Performance with ENERGY STAR initiative and receive specirecognition as an industry leader in energy efficiency.

Incentives

OIL, PROPANE & MUNICIPAL ELECTRIC CUSTOMERS

EDA PROGRAMS

SBC CREDIT PROGRAM

PAST PROGRAMS

TOOLS AND RESOURCES

PROGRAM UPDATES

CONTACT US

Pay for Performance incentives are awarded upon the satisfactory completion of three p milestones:

Incentive #1 - Submittal of complete energy reduction plan prepared by an app program partner - Contingent on moving forward, incentives will be between \$5 \$50,000 based on approximately \$.10 per square foot, not to exceed 50% of the annual energy expense.

Incentive #2 - Installation of recommended measures - Incentives are based on the projected level of electricity and natural gas savings resulting from the installation of comprehensive energy-efficiency measures.

Incentive #3 - Completion of Post-Construction Benchmarking Report - A completed report verifying energy reductions based on one year of post-

implementation results. Incentives for electricity and natural gas savings will be based on actual savings, provided that the minimum performance threshold of savings has been achieved.

A detailed Incentive Structure document is available on the applications and form

Steps to Participation

Click here for a step-by-step description of the program.

Home | Residential | Commercial & Industrial | Renewable Energy
About Us | Press Room | Library | FAQs | Calendar | Newsletters | Contact Us | Site





PAY FOR PERFORMANCE APPLICATION FORM

July 1, 2013 - June 30, 2014

Utility Serving Applicant: New Jersey Natural Gas Other Electric Service Pro Other Fuel Provider:	□ Eliz ovider (ple				nd Elec	l Power & tric Co.		□ PSE&G □ South Jersey Gas
Instructions							interversion and second in a supervision	
Read the program material to detern Read the Participation Agreement a. Fill out all applicable spaces on this Provide a copy of the customer's cor Provide the most recent consecutive for the project.	ind sign whe form. mpany W-9	ere indicated.	7. Part DIR Approv	ner mus ECTLY al of thi of work	t submit to the M s Applications only a	Market Mana ation is not a oproved upor	on package via iger – see back n approval of th	ne project's scope of work. e Energy Reduction Plan.
Customer/Owner In	forma	ation (payme	nt will	be m		o entity (Contact/Title	entered ho	ere)
Company Address			C	iţy			State	Zip
Phone/Fax	E-mail					Federal ID/S	SN	
Partner Informatio	n				Project	: Contact/Title		
Company Address				City			State	Zip
Phone	Fax		11.00	E-mail	**************************************		MONTH CONTROL OF THE SECTION OF THE	A characteristic control of the cont
Project Information Project Name			1					
Building Address	***************************************			City	and the second section of the section of the second section of the sect		State	Zip
Utility Account Number(s): Electric	.)			(Sas			A CONTRACTOR OF THE PROPERTY O
° Note: Please use the back of this page for additional Annual Peak kW Demand		if quantity exceeds space allotme Building Type	ent.				Number of B	buildings
Size of Building(s) (gross sq/ft)		······································		Direct, M	aster or S	ub Metered		
Funding Check the box if an Energy Savin							allows gover	nment
agencies to pay for energy related	•	_			-		V1	
Do you expect to receive funding Utility Program #1 – Utility:			•					ecity below:
Utility Program #2 - Utility:				-	-			
Federal Program #1 – Organizati	ion:			Pro	gram N	lame:		
Federal Program #2 – Organizati	ion:			Pro	gram N	lame:		
Other Program – Organization: _			-4	Pro	gram N	lame:		

Additional Project inf	ormation
Additional Utility Account(s)	
Additional Other Account(s)	
Account type	Account number
dditional Comments:	

Complete this application form and send it directly to the Commercial/Industrial Market Manager by e-mail, mail or fax.

New Jersey's Clean Energy Program c/o TRC Energy Services-P4P 900 Route 9 North, Suite 404 • Woodbridge, NJ 07095

> Phone: 866-657-6278 • Fax: 732-855-0422 E-mail: P4P@NJCleanEnergy.com

0

Pay For Performance-Existing Buildings

Participation Agreement

Definitions:

Design Incentives – Incentives that may be offered to design professionals by the Program.

Design Services – Services that may be offered to design professionals under the Program.

Energy-Efficient Measures – Any device eligible to receive a Program Incentive payment through the NJ Clean Energy Commercial and Industrial Program (New Jersey SmartStart Buildings).

New Jersey Utilities – The regulated electric and/or gas utilities in the State of New Jersey. They are: Atlantic City Electric, Jersey Central Power & Light, Rockland Electric Company, New Jersey Natural Gas, Elizabethtown Gas, PSE&G, and South Jersey Gas.

Administrator – New Jersey Board of Public Utilities, Office of Clean Energy

Participating Customers – Those non-residential electric and/or gas service customers of the New Jersey Utilities who participate in this Program.

Product Installation or Equipment Installation – Installation of the Energy-Efficient Measures.

Projects with a contract threshold of \$14,187 (increasing to \$15,444 effective July 1, 2014) are required to pay no less than prevailing wage rate to workers employed in the performance of any construction undertaken in connection with Board of Public Utilities financial assistance, or undertaken to fulfill any condition of receiving Board of Public Utilities financial assistance, including the performance of any contract to construct, renovate or otherwise prepare a facility, the operations of which are necessary for the receipt of Board of Public Utilities financial assistance. By submitting an application, or accepting program incentives, applicant agrees to adhere to New Jersey Prevailing Wage requirements, as applicable.

Program – The Commercial and Industrial Energy-Efficient Construction Program (New Jersey SmartStart Buildings) offered herein by the New Jersey Board of Public Utilities, Office of Clean Energy pursuant to state regulatory approval under the New Jersey Electric Discount and Energy Competition Act, NJSA 48:3-49, et seq.

Program Incentives – Refers to the amount or level of incentive that the Program provides to Participating Customers pursuant to the Program offered herein (see description under "Incentive Amount" heading).

Program Offer – Program Incentives are available to nonresidential retail electric and/or gas service customers of the New Jersey Utilities identified above.

Program Manager - TRC Energy Services.

Application and Eligibility Process - The Program pays incentives after the installation of qualified energy-efficient

measures that were pre-approved (for exceptions to this condition, please refer to "Exceptions for Approval".) In order to be eligible for Program Incentives, a Customer, or an agent (contractor/vendor) authorized by a Customer, must submit a properly completed application package. The package must include an application signed by the customer; a complete (current) utility bill; and technology worksheet and manufacturer's cut sheets (where appropriate). This information must be submitted to the Program Manager before equipment is installed. Applications for measures that are self installed by customers must be submitted by the customer and not the sales vendor of the measure, however, the customer may elect to assign payment of the incentive to the sales vendor. This application package must be received by the Program Manager on or before June 30, 2014 in order to be eligible for the fiscal year July 1, 2013-June 30, 2014 incentives. The Program Manager will review the application package to determine if the project is eligible for a Program Incentive. If eligible, the Customer will receive an approval letter with the estimated authorized incentive amount and the date by which the equipment must be installed in order for the approval to remain in effect. Upon receipt of an approval letter, the Customer may then proceed to install the equipment listed on the approved application. Equipment installed prior to the date of the Program Manager's approval letter is not eligible for an incentive. The Program Manager reserves the right to conduct a pre-inspection of the facility prior to the installation of equipment. This will be done prior to the issuance of the approval letter. All equipment must be purchased within 12 months of date of application. Any Customer and/ or agent who purchases equipment prior to the receipt of an incentive approval letter does so at his/her own risk.

Exceptions for Approval – The Application and Eligibility Process pertains to all projects except for those involving either Gas Heating, Unitary HVAC or Motors having an incentive amount less than \$5,000 that were installed within 12 months of receipt of the application. These measures, at this incentive level, may be installed without prior approval. In addition, but at the sole discretion of the Program Manager, emergency replacement of equipment may not require a prior approval determination and letter. In such cases, please notify the Program Manager of such emergencies as early as possible, that an application will soon be sent in that was not pre-approved.

Post-Installation Approval — After installation is completed, the Customer, or an agent authorized by the Customer, must finalize and submit an invoice for the purchase of the equipment (material cost must be broken out from labor costs), and any other required documentation as specified on the equipment application or in the Program Manager's initial approval letter.

Please refer to the program guide on the NJCleanEnergy.com/ ssb website for the complete Application and Eligibility Process.

The Program Manager reserves the right to verify sales transactions and to have reasonable access to Participating Customer's facility to inspect both pre-existing product or equipment (if applicable) and the Energy-Efficient Measures installed under this Program, either prior to issuing incentives or at a later time.

Energy-Efficient Measures must be installed in buildings located within a New Jersey Utilities' service territory and designated on the Participating Customer's incentive application. Program Incentives are available for qualified Energy-Efficient Measures as listed and described in the Program materials and incentive applications. The Participating Customer must ultimately own the equipment, either through an up-front purchase or at the end of a short-term lease. Design Incentives are available to design professionals as described in the Program materials and applications. A different and separate agreement must be executed by participating design professionals to be eligible for this type of incentive. The design professional does not need to be based in New Jersey.

Equipment procured by Participating Customers through another program offered by New Jersey's Clean Energy Program or the New Jersey Utilities, as applicable, is not eligible for incentives through this program. Customers who have not contributed to the Societal Benefits Charge of the applicable New Jersey Utility are not be eligible for incentives offered through this program.

Incentive Amount – Program Incentives will equal either: a) the approved Program Incentive amount, or b) the actual equipment cost of the Energy-Efficient Measure, whichever is less, as determined by the Program Manager. Products offered at no direct cost to the customer are ineligible. Incomplete application submissions, applications requiring inspections and unanticipated high volume of activities may cause processing delays. Program Incentives are limited to \$500,000 per utility account in a calendar year. Contact the Program Manager regarding any questions.

Tax Liability – The Program Manager will not be responsible for any tax liability that may be imposed on any Participating Customer as a result of the payment of Program Incentives. All Participating Customers must supply their federal tax identification number or social security number to the Program Manager on the application form in order to receive a Program Incentive. In addition, Participating Customers must also provide a Tax Clearance Form (entitled "Business Assistance or Incentive Clearance Certificate") that is dated within 90 days of equipment installation.

Endorsement – The Program Manager and Administrator do not endorse, support or recommend any particular manufacturer, product or system design in promoting this Program.

Warranties – THE PROGRAM MANAGER AND ADMINISTRATOR DO NOT WARRANT THE PERFORMANCE OF INSTALLED EQUIPMENT, AND/OR SERVICES RENDERED AS PART OF THIS PROGRAM, EITHER EXPRESSLY OR IMPLICITLY. NO WARRANTIES OR REPRESENTATIONS OF ANY KIND, WHETHER STATUTORY, EXPRESSED, OR IMPLIED, INCLUDING, WITHOUT LIMITATIONS, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE REGARDING EQUIPMENT OR SERVICES PROVIDED BY A MANUFACTURER OR VENDOR. CONTACT YOUR VENDOR/SERVICES PROVIDER FOR DETAILS REGARDING PERFORMANCE AND WARRANTIES.

Limitation of Liability – By virtue of participating in this Program, Participating Customers agree to waive any and all claims or damages against the Program Manager or the Administrator, except the receipt of the Program Incentive. Participating Customers agree that the Program Manager's and Administrator's liability, in connection with this Program, is limited to paying the Program Incentive specified. Under no circumstances shall the Program Manager, its representatives, or subcontractors, or the Administrator, be liable for any lost profits, special, punitive, consequential or incidental damages or for any other damages or claims connected with or resulting from participation in this Program. Further, any liability attributed to the Program Manager under this Program shall be individual, and not joint and/or several.

Assignment – The Participating Customer may assign Program Incentive payments to a specified vendor.

Participating Customer's Certification – Participating Customer certifies that he/she purchased and installed the equipment listed in their application at their defined New Jersey location. Participating Customer agrees that all information is true and that he/she has conformed to all of the Program and equipment requirements listed in the application.

Termination – The New Jersey Board of Public Utilities reserves the right to extend, modify (this includes modification of Program Incentive levels) or terminate this Program without prior or further notice.

Acknowledgement – I have read, understood and am in compliance with all rules and regulations concerning this incentive program. I certify that all information provided is correct to the best of my knowledge, and I give the Program Manager permission to share my records with the New Jersey Board of Public Utilities, and contractors it selects to manage, coordinate or evaluate the NJ SmartStart Buildings Program. Additionally, I allow reasonable access to my property to inspect the installation and performance of the technologies and installations that are eligible for incentives under the guidelines of New Jersey's Clean Energy Program.

CUSTOMER'S SIGNATURE

PARTNER SIGNATURE

By signing, I certify that I have read, understand and agree to the Participation Agreement listed above.

IV. ENERGY SAVINGS IMPROVEMENT PLAN (ESIP)



Your Power to Save

At Home, for Business, and for the Future

About Us | Press Room | Library

HOME

RESIDENTIAL

COMMERCIAL, INDUSTRIAL AND L€CAL GOVERNMENT





COMMERCIAL, INDUSTRIAL AND LOCAL GOVERNMENT

HURRICANE SANDY

PROGRAMS

NJ SMARTSTART BUILDINGS

PAY FOR PERFORMANCE

COMBINED HEAT & POWER AND FUEL CELLS

LOCAL GOVERNMENT ENERGY AUDIT

LARGE ENERGY USERS PROGRAM

ENERGY SAVINGS IMPROVEMENT PROGRAM

DIRECT INSTALL

ENERGY BENCHMARKING

OIL, PROPANE & MUNICIPAL **ELECTRIC CUSTOMERS**

EDA PROGRAMS

SBC CREDIT PROGRAM

PAST PROGRAMS

TOOLS AND RESOURCES

PROGRAM UPDATES

CONTACT US

Home » Commercial & Industrial » Programs

Energy Savings Improvement Program

A new State law allows government agencies to make energy related improvements to t facilities and pay for the costs using the value of energy savings that result from the imp Under Chapter 4 of the Laws of 2009 (the law), the "Energy Savings Improvement Program" (ESIP), provides all government agencies in New Jersey with a flexible tool to and reduce energy usage with minimal expenditure of new financial resources.

This Local Finance Notice outlines how local governments can develop and implement a their facilities. Below are two sample RFPs:

> Local Government School Districts (K-12)

All RFPs must be submitted to the Board for approval at ESIP@bpu.state.nj.us.

The Board also adopted protocols to measure energy savings:

Measuring Energy Savings Procedures for Implementation

The ESIP approach may not be appropriate for all energy conservation and energy effic improvements. Local units should carefully consider all alternatives to develop an approbest meets their needs. Local units considering an ESIP should carefully review the Loc Notice, the law, and consult with qualified professionals to determine how they should a task.

The NJ Board of Public Utilities sponsored Sustainable Jersey in the creation of an ESIF Guidebook that explains how to implement the program. The guidebook also includes ca of successful projects and a list of helpful resources.

FIRST STEP - ENERGY AUDIT

For local governments interested in pursuing an ESIP, the first step is to perform an ene as prescribed in P.L.2012 c.55.

ENERGY REDUCTION PLANS

If you have an ESIP plan that needs to be submitted to the Board of Public Utilities, plea to ESIP@bpu.state.nj.us. Please limit the file size to 3MB (or break it into smaller files).

Frankford Township School District


Northern Hunterdon-Voorhees Regional High School

Manalapan Township (180 MB - Right Click, Save As)

BPU RULES

- 1. Public Entity must decide if they will use an ESCO or DIY method or Hybrid thereof prior to issuing the RFP and the RFP must state the intended method. A change in the project procurement model after the RFP closing date will be cause for immediate rejection and disqualification of potential Clean Energy program incentives.
- 2. RFP procedures shall be adhered to as per the legislation, including the use of BPU approved forms. Any alteration of the forms, without prior approval from the BPU shall be grounds for rejection.
- 3. RFP must include copy of an audit (ASHRAE Level II w/Level III for lighting) and audit must be prepared by a firm classified by DPMC in the 036 discipline.
- 4. All firms, including professional services, whether using ESCO or DIY model, must be DPMC classified.
- 5. If an Architect is engaged by the public entity, the architectural fees are the responsibility of the public entity and must be paid directly to the firm. These fees may be included in the energy cost savings analysis and payback.
 - ESCO's may contract directly with an architectural firm, in which case the architectural firm serves as a subcontractor to the ESCO and the project related service costs may be included within the project's economic model.
- 6. Public entity shall conduct pre-bid meetings and site visits per existing statutes.
 - In the interest of open public bidding transparency, it is a requirement of the BPU that all proposers must attend the pre-proposal bid meeting.
- 7. There shall be no negative cash flow in any year of the program. section 7 (1)(a)
 - "the energy savings resulting from the program will be sufficient to cover the cost of the program's energy conservation measures."
- 8. SREC values are not permitted to be used in the energy cost savings calculations.
- 9. Capital cost avoidance values are not to be used in the energy savings calculations.
- 10. Operational and Maintenance (O&M) cost savings may be permitted in the cost savings calculations, but only with supporting documentation.
- 11. Blended utility rates shall not be permitted. Use the actual utility tariff or local contracted rates if there is a third party supplier.
 - For the RFP proposals, the public entity shall define the utility rates in the RFP

- 12. Contracted third party utility rates may only be used for the term of the contract (5 yr. maximum) Subsequent years are to be projected at the utility tariff rates plus the annual BPU escalation rates.
- 13. Public entity shall conduct M&V (measurement and verification) at the one (1) year operational date and shall provide a copy of the M&V report to the Board of Public Utilities.
 - For the RFP proposals, the ESCO shall provide the cost for the one (1) year M&V only. For comparative purposes, the one year M&V pricing shall be indicated on the proposal Form VI, under the "Annual Service Costs" column. Additional M&V costs are at the discretion of the local unit and are not to be included in the proposal.
- 14. The decisions made by BPU staff regarding compliance or other issues that arise in connection with the RFP procurement process shall be considered a final decision of the BPU. Any appeal will need to be through the New Jersey Superior Court, Appellate Division.
- 15. For the RFP proposals only, Demand Response (DR) revenues claimed by ESCO's can only be projected for a maximum period of three (3) years. DR revenue projections beyond three years will not be permitted. DR revenues must be included and presented under the "Energy Rebates/Incentives" column of FORM VI.
- 16. ESCO "fees" proposed during the RFP phase of the project cannot increase post-award. ESCO's are required to maintain the fee percentages through final contract negotiations and construction of the Board approved Energy Savings Plan
- 17. Public Bid openings shall be held on the due date of the proposal submissions. The public entity shall announce the name of the bidder and the total dollar amount. After award of a contract, all proposals received will be made available by the owner for public inspection
- 18. Rejection of bids by the public entity shall be conducted in accordance with the appropriate sections of the applicable legislation, as stated in Title 40A:11-13.2. Additionally all proposals must be returned to the respective ESCO's upon rejection.
- 19. Field changes that exceed 5% of the project cost require BPU approval.
- 20. Energy Savings Plans (ESP) that is dependent upon incentives from the Clean Energy Program must review the current program requirements, at the time of application, for each incentive to insure eligibility. If any program incentive is denied, resubmission of all ESIP related forms will be necessary to remain ESIP qualified.



Millburn Township Public School District Millburn High School

Cost of Electricity /kWh Electricity Usage kWh/yr System Unit Cost /kW \$4,000

Photovoltaic (PV) Solar Power Generation - Screening Assessment

Budgetary	Budgetary Annual Utility Savings Cost			Estimated	Total	Federal Tax	New Jersey Renewable	Payback (without	Payback (with	
Cost				Maintenance	Savings	Credit	** SREC	incentive)	incentive)	
					Savings					
\$	kW	kWh	therms	\$	\$	\$	\$	\$	Years	Years
\$1,080,000	270.0	351,900	0	\$42,192	0	\$42,192	\$0	\$61,583	25.6	10.4
** = 1					A . = =	/				

^{**} Estimated Solar Renewable Energy Certificate Program (SREC) SREC for 15 Years= \$175 /1000kwh

Area Output*

7,333 m2 78.935 ft2

Perimeter Output*

3.849 ft

Available Roof Space for PV:

(Area Output - 10 ft x Perimeter) x 85%

34,375 ft2

Approximate System Size: Is the roof flat? (Yes/No) Yes

watt/ft2 274,998 DC watts

kW Enter into PV Watts 270

PV Watts Inputs*** Enter into PV Watts (always 20 if flat, if Array Tilt Angle pitched - enter estimated roof angle)

Array Azimuth Enter into PV Watts (default) Zip Code Enter into PV Watts DC/AC Derate Factor 0.83

PV Watts Output

351,900 annual kWh calculated in PV Watts program

Enter info PV Watts

% Offset Calc


Usage 2,220,800 (from utilities) PV Generation 351,900 (generated using PV Watts)

% offset 16%

http://www.freemaptools.com/area-calculator.htm

http://www.flettexchange.com_

http://gisatnrel.nrel.gov/PVWatts_Viewer/index.html





AC Energy & Cost Savings



(Type comments here to appear on printout; maximum 1 row of 90 characters.)

Station Identification					
Cell ID:	0268370				
State:	New Jersey				
Latitude:	40.9 ° N				
Longitude:	74.2 ° W				
PV System Specifications					
DC Rating:	270.0 kW				
DC to AC Derate Factor:	0.830				
AC Rating:	224.1 kW				
Array Type:	Fixed Tilt				
Array Tilt:	20.0 °				
Array Azimuth:	180.0 °				
Energy Specifications					
Cost of Electricity:	12.0 ¢/kWh				
	·				

Results						
Month	Solar Radiation (kWh/m²/day)	AC Energy (kWh)	Energy Value (\$)			
1	2.65	18862	2263.44			
2	3.47	22339	2680.68			
3	4.83	33154	3978.48			
4	5.28	33983	4077.96			
5	5.93	38773	4652.76			
6	6.32	38931	4671.72			
7	5.87	36645	4397.40			
8	5.55	34886	4186.32			
9	5.04	31226	3747.12			
10	4.14	27459	3295.08			
11	2.82	18441	2212.92			
12	2.46	17202	2064.24			
Year	4.54	351900	42228.00			

Output Hourly Performance Data

(Gridded data is monthly, hourly output not available.)

Saving Text from a Browser

Output Results as Text

Run PVWATTS v.2 for another location


Run PVWATTS v.1

Please send questions and comments to Webmaster

Disclaimer and copyright notice.



RReDC home page (http://rredc.nrel.gov)





1: Millburn High School front exterior



2: Trane rooftop unit vintage 1996




3: Kitchen hood



4: Vending machines



5: Window AC unit Industrial Arts wing





ENERGY STAR® Statement of Energy Performance

43

Millburn High School

Primary Property Function: K-12 School

Gross Floor Area (ft²): 201,858

Built: 1955

ENERGY STAR® Score¹

For Year Ending: February 28, 2014 Date Generated: May 22, 2014

1. The ENERGY STAR score is a 1-100 assessment of a building's energy efficiency as compared with similar buildings nationwide, adjusting for climate and business activity.

climate and business	activity.				
Property & Con	tact Information				
Property Address Millburn High Sch 462 Millburn Aven Millburn, New Jers Property ID: 4057	ool uue sey 07041	Property Owner Millburn Township Public Schools 434 Millburn Avenue Millburn, NJ 07041 ()		Primary Contact	
Energy Consun	nption and Energy U	se Intensity (EUI)			
Site EUI 76.3 kBtu/ft² Source EUI 158.6 kBtu/ft²	76.3 kBtu/ft² Electric - Grid (kBtu) 7, Natural Gas (kBtu) 7,		% Diff from National Annual Emissions	ite EUI (kBtu/ft²) ource EUI (kBtu/ft²) al Median Source EUI	72.1 149.9 6% 1,375
Signature & S	Stamp of Verifyin	g Professional			
Ι	(Name) verify tha	t the above information	is true and correct t	o the best of my knowledge	э.
Signature:		Date:			
, ()	_				

Professional Engineer Stamp (if applicable)