

The US standard railroad gauge (distance between the rails) is 4 feet, 8.5 inches. That's an exceedingly odd number. Why was that gauge used? Because that's the way they built them in England and English expatriates built the US railroads.

Why did the English build them like that? Because the first rail lines were built by the same people who built the pre-railroad tramways, and that's the gauge they used.

Why did "they" use that gauge then? Because the people who built the tramways used the same jigs and tools that they used for building wagons, which used that wheel spacing.

Why did the wagons have that particular odd wheel spacing? Well, if they tried to use any other spacing, the wagon wheels would break on some of the old, long distance roads in England, because that's the spacing of the wheel ruts.

So who built those old rutted roads? Imperial Rome built the first long distance roads in (and Europe England) for their legions. The roads have been used ever since. And the ruts in the roads? Roman war chariots formed the initial


ruts, which everyone else had to match for fear of destroying their wagon wheels. Since the chariots were made for Imperial Rome, they were all alike in the matter of wheel spacing. Therefore, the United States standard railroad gauge of 4 feet, 8.5 inches is derived from the original specifications for an Imperial Roman war chariot. Bureaucracies live forever.

So the next time you are handed a Specification/ Procedure/ Process and wonder "What horse's ass came up with it?" you may be exactly right. >Imperial Roman army chariots were made just wide enough to accommodate the rear ends of two war horses (two horses' asses).

Now, the twist to the story:

When you see a Space Shuttle sitting on its launch pad, there are two big booster rockets attached to the sides of the main fuel tank. These are solid rocket boosters, or SRBs. The SRBs are made by Thiokol at their factory at Utah. The engineers who designed the SRBs would have preferred to make them a bit fatter, but the SRBs had to be shipped by train from the factory to the launch site. The railroad line from the factory happens to run through a tunnel in the mountains, and the SRBs had to fit through that tunnel. The tunnel is slightly wider than the railroad track, and the railroad track, as you now know, is about as wide as two horses' behinds.

So, a major Space Shuttle design feature of what is arguably the world's most advanced transportation system was determined over two thousand years ago by the width of a horse's ass. And you thought being a horse's ass wasn't important? Ancient horse's asses control almost everything....and CURRENT Horses Asses are controlling everything most everything else!!



All Kinds of GM Specialty Parts & Service
 Corvette, Camaro, Chevelle, Impala, Nova, Cheyenne
Cool Cars, Nice People!

CORVETTE

HIGH PERFORMANCE

2840 Black Lake Blvd #D • Olympia, WA 98512 • 360-754-7890
 Tuesday - Friday 9 to 5:30, Saturday 9 to 3 • www.corwhp.com



GOULD CHIROPRACTIC CENTER P.S.

FAMILY CHIROPRACTIC CARE

- Auto Accident Injuries
- Workman's Compensation
- Chronic & Difficult Cases
- Will Accept Emergencies
- Most Insurance Accepted

24 HOUR TEL. NO. **456-4488**
 704 SOUTH LILLY ROAD

Cornerstone RV Center
 Jim F. Elliott Sr., Manager
 8500 A Old Highway 99 SE
 Olympia, WA 98501

Phone: 360 704-4441 Cell: 360 791-1872
 Toll Free: 866 715-4441 Fax: 360 704-4443
 www.cornerstonervcenter.com jimatcornerstone@comcast.net

"Building foundations for family, fun, and relaxing lifestyles"

Classy Chassis
 autobody & paint

Butch Kingery, Owner
 (360) 866-9074
 FAX 866-6639

Custom & Commercial Paint
Collision Repair for Cars, Boats & Bikes
Corvette Specialists

10415 Summit Lake Road N.W. • Olympia, WA 98502