

SAFETY DATA SHEET

DOW AGROSCIENCES LLC

Product name: GOAL™ 2XL Herbicide

Issue Date: 10/28/2015

Print Date: 11/02/2015

DOW AGROSCIENCES LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: GOAL™ 2XL Herbicide

Recommended use of the chemical and restrictions on use

Identified uses: End use herbicide product

COMPANY IDENTIFICATION

DOW AGROSCIENCES LLC
9330 ZIONSVILLE RD
INDIANAPOLIS IN 46268-1053
UNITED STATES

Customer Information Number:

800-992-5994

info@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 800-992-5994

Local Emergency Contact: 352-323-3500

2. HAZARDS IDENTIFICATION

Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Skin irritation - Category 2

Eye irritation - Category 2A

Skin sensitisation - Sub-category 1B

Carcinogenicity - Category 2

Reproductive toxicity - Category 1B

Specific target organ toxicity - single exposure - Category 3

Aspiration hazard - Category 1

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
Suspected of causing cancer.
May damage fertility or the unborn child.

Precautionary statements

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Wear eye protection/ face protection.
Wear protective gloves.
Use personal protective equipment as required.

Response

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
IF ON SKIN: Wash with plenty of soap and water.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
Do NOT induce vomiting.
If skin irritation or rash occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Mixture

This product is a mixture.

Component	CASRN	Concentration
Oxyfluorfen	42874-03-3	22.3%
2-Methylnaphthalene	91-57-6	15.0%
N-Methyl-2-pyrrolidone	872-50-4	10.0%
Benzenesulfonic acid, dodecyl-, calcium salt	26264-06-2	9.1%
Naphthalene	91-20-3	>= 0.4 - < 8.6 %
1-Methylnaphthalene	90-12-0	7.2%
Isobutanol	78-83-1	>= 1.0 - <= 1.6 %

4. FIRST AID MEASURES

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If person is not breathing, call an emergency responder or ambulance, then give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask etc). Call a poison control center or doctor for treatment advice.

Skin contact: Take off contaminated clothing. Wash skin with soap and plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. Wash clothing before reuse. Shoes and other leather items which cannot be decontaminated should be disposed of properly. Suitable emergency safety shower facility should be available in work area.

Eye contact: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a poison control center or doctor for treatment advice. Suitable emergency eye wash facility should be immediately available.

Ingestion: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and

special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Repeated excessive exposure may aggravate preexisting lung disease. Skin contact may aggravate preexisting dermatitis. Maintain adequate ventilation and oxygenation of the patient. May cause asthma-like (reactive airways) symptoms. Bronchodilators, expectorants, antitussives and corticosteroids may be of help. If burn is present, treat as any thermal burn, after decontamination. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. The decision of whether to induce vomiting or not should be made by a physician. Administer 100% oxygen to relieve headache and a general sense of weakness. Determine methemoglobin concentration of blood every 3 to 6 hours for first 24 hours. It should return to normal within 24 hours. The treatment of toxic methemoglobinemia may include the intravenous administration of methylene blue. If methemoglobin >10-20% consider methylene blue 1-2 mg/kg body weight as 1% solution intravenously over 5 minutes followed by 15-30 cc flush (Price D, Methemoglobinemia, Goldfrank Toxicologic Emergencies, 5th ed., 1994). Also provide 100% oxygen. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: Do not use direct water stream. May spread fire.

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Hydrogen fluoride. Hydrogen chloride. Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is produced when product burns.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Consider feasibility of a controlled burn to minimize environment damage. Foam fire extinguishing system is preferred because uncontrolled water can spread possible contamination. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers,

boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to section 7, Handling, for additional precautionary measures. Keep upwind of spill. Keep personnel out of low areas. Ventilate area of leak or spill. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. Spills or discharge to natural waterways is likely to kill aquatic organisms.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Small spills: Absorb with materials such as: Clay. Dirt. Sand. Sweep up. Collect in suitable and properly labeled containers. Large spills: Contact Dow AgroSciences for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Keep out of reach of children. Do not swallow. Avoid contact with eyes, skin, and clothing. Avoid breathing vapor. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Keep container closed. Use with adequate ventilation. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Store in a dry place. Store in original container. Keep container tightly closed. Do not store near food, foodstuffs, drugs or potable water supplies.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
Oxyfluorfen	Dow IHG	TWA	0.2 mg/m ³
2-Methylnaphthalene	ACGIH	TWA	0.5 ppm
N-Methyl-2-pyrrolidone	US WEEL	TWA	10 ppm
	US WEEL	TWA	SKIN
Naphthalene	Dow IHG	TWA	10 ppm
	Dow IHG	TWA	SKIN
	Dow IHG	STEL	15 ppm
	Dow IHG	STEL	SKIN
	ACGIH	TWA	10 ppm
	ACGIH	TWA	SKIN
1-Methylnaphthalene	OSHA Z-1	TWA	50 mg/m ³ 10 ppm
	ACGIH	TWA	0.5 ppm

Isobutanol	ACGIH	TWA	50 ppm
	OSHA Z-1	TWA	300 mg/m ³ 100 ppm
	OSHA P0	TWA	150 mg/m ³ 50 ppm

RECOMMENDATIONS IN THIS SECTION ARE FOR MANUFACTURING, COMMERCIAL BLENDING AND PACKAGING WORKERS. APPLICATORS AND HANDLERS SHOULD SEE THE PRODUCT LABEL FOR PROPER PERSONAL PROTECTIVE EQUIPMENT AND CLOTHING.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Styrene/butadiene rubber. Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	Liquid.
Color	Yellow to brown
Odor	Sweet
Odor Threshold	No test data available
pH	7 pH Electrode
Melting point/range	Not applicable
Freezing point	No test data available

Boiling point (760 mmHg)	201.7 °C (395.1 °F)
Flash point	closed cup 98 °C (208 °F) <i>Setaflash Closed Cup ASTM D3828</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Flammable liquid
Lower explosion limit	1.3 % vol Solvent
Upper explosion limit	11.8 % vol Solvent
Vapor Pressure	0.29 hPa at 20 °C (68 °F)
Relative Vapor Density (air = 1)	5.2
Relative Density (water = 1)	1.077 at 20 °C (68 °F) <i>Digital Density Meter (Oscillating Coil)</i>
Water solubility	emulsifiable
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	346 °C (655 °F)
Decomposition temperature	290 °C (554 °F)
Dynamic Viscosity	5.9 mPa.s at 39.9 °C (103.8 °F)
Kinematic Viscosity	No data available
Explosive properties	No
Oxidizing properties	yes
Liquid Density	1.077 g/cm ³ at 20 °C (68 °F) <i>Digital density meter</i>
Molecular weight	No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability: Thermally stable at typical use temperatures.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Some components of this product can decompose at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems.

Incompatible materials: Avoid contact with: Acids. Amines. Bases. Halogens.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Carbon monoxide. Carbon dioxide. Hydrogen chloride. Hydrogen fluoride. Nitrogen oxides. Toxic gases are released during decomposition.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

As product:

LD50, Rat, female, 3,129 mg/kg

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product:

LD50, Rat, male and female, > 5,000 mg/kg

Acute inhalation toxicity

No adverse effects are anticipated from single exposure to mist. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs.

As product:

LC50, Rat, male and female, 4 Hour, dust/mist, > 5.12 mg/l OECD Test Guideline 403 No deaths occurred at this concentration.

Skin corrosion/irritation

Brief contact may cause severe skin irritation with pain and local redness.
May cause drying and flaking of the skin.
Prolonged contact may cause skin irritation, even a burn.

Serious eye damage/eye irritation

May cause moderate eye irritation which may be slow to heal.
May cause slight corneal injury.

Sensitization

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause respiratory irritation.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

For the active ingredient(s):

In animals, effects have been reported on the following organs:

Liver.

Blood.

Spleen.

Contains component(s) which have been reported to cause effects on the following organs in animals:

Blood-forming organs (Bone marrow & Spleen).

Excessive exposure may cause hemolysis, thereby impairing the blood's ability to transport oxygen.

Liver.

Cataracts and other eye effects have been reported in humans repeatedly exposed to naphthalene vapor or dust.

Ingestion of naphthalene by humans has caused hemolytic anemia.

Central nervous system.

Excessive exposure to solvent(s) may cause respiratory irritation and central nervous system depression.

Carcinogenicity

Contains naphthalene which has caused cancer in some laboratory animals. In humans, there is limited evidence of cancer in workers involved in naphthalene production. Limited oral studies in rats were negative.

For the active ingredient(s): An increase in spontaneously occurring tumors observed in mice is of questionable relevance. No increases in tumors were observed in rats.

Teratogenicity

For the active ingredient(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Active ingredient did not cause birth defects in laboratory animals.

For the solvent(s): Did not cause birth defects or any other fetal effects in laboratory animals.

N-methyl pyrrolidone has caused toxic effects to the fetus in laboratory animals at high dose levels with either mild or undetectable maternal toxicity.

Reproductive toxicity

For the active ingredient(s): In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

Mutagenicity

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Based on information for component(s): In vitro genetic toxicity studies were negative in some cases and positive in other cases.

Aspiration Hazard

May be fatal if swallowed and enters airways.

Carcinogenicity

Component

Naphthalene

List

IARC

US NTP

ACGIH

Classification

Group 2B: Possibly carcinogenic to humans

Reasonably anticipated to be a human carcinogen

A3: Confirmed animal carcinogen with unknown relevance to humans.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Oxyfluorfen

Acute toxicity to fish

Material is very highly toxic to aquatic organisms on an acute basis (LC50/EC50 <0.1 mg/L in the most sensitive species).

LC50, Rainbow trout (*Oncorhynchus mykiss*), static test, 96 Hour, 0.25 mg/l

Acute toxicity to aquatic invertebrates

EC50, water flea *Daphnia magna*, 48 Hour, 0.072 mg/l

Acute toxicity to algae/aquatic plants

EbC50, diatom *Navicula* sp., static test, 96 Hour, Biomass, 0.031 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to fish

NOEC, *Pimephales promelas* (fathead minnow), flow-through test, 33 d, survival, 0.038 mg/l

NOEC, *Pimephales promelas* (fathead minnow), flow-through test, 265 d, survival, 0.005 mg/l

NOEC, *Cyprinodon variegatus* (sheepshead minnow), flow-through test, 34 d, growth, 0.0047 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, water flea *Daphnia magna*, flow-through test, 21 d, 0.013 mg/l

Toxicity to Above Ground Organisms

Material is practically non-toxic to birds on an acute basis (LD50 > 2000 mg/kg).

Material is practically non-toxic to birds on a dietary basis (LC50 > 5000 ppm).

LD50, *Colinus virginianus* (Bobwhite quail), > 2,150 mg/kg

LC50, *Anas platyrhynchos* (Mallard duck), 8 d, > 5,000 mg/kg

oral LD50, *Apis mellifera* (bees), 48 Hour, > 100micrograms/bee

contact LD50, *Apis mellifera* (bees), 48 Hour, > 100.0micrograms/bee

dietary LC50, *Colinus virginianus* (Bobwhite quail), > 5,000 mg/kg

2-Methylnaphthalene

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, *Oncorhynchus mykiss* (rainbow trout), 96 Hour, 1.5 mg/l

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna* (Water flea), 48 Hour, 1.5 mg/l

N-Methyl-2-pyrrolidone

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, *Oncorhynchus mykiss* (rainbow trout), static test, 96 Hour, > 5,000 mg/l

LC50, *Pimephales promelas* (fathead minnow), static test, 96 Hour, 1,072 mg/l

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna* (Water flea), static test, 24 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, *Desmodesmus subspicatus* (green algae), static test, 72 Hour, Growth rate inhibition, > 500 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to aquatic invertebrates

NOEC, *Daphnia magna* (Water flea), semi-static test, 21 d, 12.5 mg/l

Benzenesulfonic acid, dodecyl-, calcium salt

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, *Cyprinus carpio* (Carp), 96 Hour, 2.8 - 4.2 mg/l, Method Not Specified.

LC50, *Oryzias latipes* (Orange-red killifish), 48 Hour, 3.0 - 5.3 mg/l, Method Not Specified.

Naphthalene

Acute toxicity to fish

Material is highly toxic to aquatic organisms on an acute basis (LC50/EC50 between 0.1 and 1 mg/L in the most sensitive species tested).

LC50, *Oncorhynchus mykiss* (rainbow trout), 96 Hour, 0.11 mg/l

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna* (Water flea), static test, 48 Hour, 1.6 - 24.1 mg/l

Acute toxicity to algae/aquatic plants

ErC50, *Skeletonema costatum* (marine diatom), Growth rate inhibition, 72 Hour, 0.4 mg/l

Chronic toxicity to fish

NOEC, Other, flow-through, 40 d, mortality, 0.37 mg/l

1-Methylnaphthalene

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, *Pimephales promelas* (fathead minnow), 96 Hour, 9 mg/l

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna* (Water flea), 48 Hour, 1.2 - 1.4 mg/l

Isobutanol

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, *Pimephales promelas* (fathead minnow), flow-through test, 96 Hour, 1,430 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, *Daphnia pulex* (Water flea), static test, 48 Hour, 1,100 mg/l

Acute toxicity to algae/aquatic plants

ErC50, *Pseudokirchneriella subcapitata* (green algae), static test, 72 Hour, Growth rate inhibition, 1,799 mg/l

Toxicity to bacteria

IC50, activated sludge, static test, 16 Hour, Growth inhibition, > 1,000 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, 20 mg/l

MATC (Maximum Acceptable Toxicant Level), Daphnia magna (Water flea), 21 d, number of offspring, 28 mg/l

Persistence and degradability

Oxyfluorfen

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

Theoretical Oxygen Demand: 1.305 mg/mg

Stability in Water (1/2-life)

Hydrolysis, 3.9 d, pH 5 - 9, Half-life Temperature 20 °C

2-Methylnaphthalene

Biodegradability: Expected to degrade slowly in the environment.

N-Methyl-2-pyrrolidone

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 91 %

Exposure time: 28 d

Method: OECD Test Guideline 301B or Equivalent

10-day Window: Not applicable

Biodegradation: 73 %

Exposure time: 28 d

Method: OECD Test Guideline 301C or Equivalent

10-day Window: Not applicable

Biodegradation: > 90 %

Exposure time: 8 d

Method: OECD Test Guideline 302B or Equivalent

Theoretical Oxygen Demand: 2.58 mg/mg

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitizer: OH radicals

Atmospheric half-life: 0.486 d

Method: Estimated.

Benzenesulfonic acid, dodecyl-, calcium salt

Biodegradability: For similar material(s): Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 95 %

Exposure time: 28 d

Method: OECD Test Guideline 301E or Equivalent

Naphthalene

Biodegradability: Biodegradation under aerobic static laboratory conditions is high (BOD20 or BOD28/ThOD > 40%).

Theoretical Oxygen Demand: 3.00 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	57.000 %
10 d	71.000 %
20 d	71.000 %

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitizer: OH radicals

Atmospheric half-life: 5.9 Hour

Method: Estimated.

1-Methylnaphthalene

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Not applicable

Biodegradation: 0 - 2 %

Exposure time: 28 d

Method: OECD Test Guideline 301C or Equivalent

Isobutanol

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 70 - 80 %

Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

10-day Window: Not applicable

Biodegradation: 90 %

Exposure time: 14 d

Method: OECD Test Guideline 301C or Equivalent

Theoretical Oxygen Demand: 2.59 mg/mg Estimated.

Chemical Oxygen Demand: 2.29 mg/mg Dichromate

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	64 - 69 %
10 d	73 - 79 %
20 d	72 - 81 %

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitizer: OH radicals

Atmospheric half-life: 1.55 d

Method: Estimated.

Bioaccumulative potential

Oxyfluorfen

Bioconcentration factor (BCF): 184 - 1,151 Lepomis macrochirus (Bluegill sunfish) 168 Hour

2-Methylnaphthalene

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 3.86 Estimated.

N-Methyl-2-pyrrolidone

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -0.38 Measured

Benzenesulfonic acid, dodecyl-, calcium salt

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Partition coefficient: n-octanol/water(log Pow): 6.78 estimated

Naphthalene

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 3.3 Measured

Bioconcentration factor (BCF): 40 - 300 Fish 28 d Measured

1-Methylnaphthalene

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 3.87 Estimated.

Isobutanol

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.76 Measured

Bioconcentration factor (BCF): 2 Estimated.

Mobility in soil

Oxyfluorfen

Expected to be relatively immobile in soil (Koc > 5000).

Partition coefficient(Koc): 6831

2-Methylnaphthalene

No relevant data found.

N-Methyl-2-pyrrolidone

Potential for mobility in soil is very high (Koc between 0 and 50).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient(Koc): 21 Estimated.

Benzenesulfonic acid, dodecyl-, calcium salt

No relevant data found.

Naphthalene

Potential for mobility in soil is medium (Koc between 150 and 500).

Partition coefficient(Koc): 240 - 1300 Measured**Isobutanol**

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient(Koc): 2 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: If wastes and/or containers cannot be disposed of according to the product label directions, disposal of this material must be in accordance with your local or area regulatory authorities. This information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. If the material as supplied becomes a waste, follow all applicable regional, national and local laws.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.(Naphthalene)
UN number	UN 3082
Class	9
Packing group	III
Reportable Quantity	Naphthalene

Classification for SEA transport (IMO-IMDG):

Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(Oxyfluorfen, Naphthalene)
UN number	UN 3082
Class	9
Packing group	III
Marine pollutant	Oxyfluorfen, Naphthalene
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.(Oxyfluorfen, Naphthalene)
UN number	UN 3082
Class	9

Packing group

III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Acute Health Hazard
Chronic Health Hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

Components

Components	CASRN
N-Methyl-2-pyrrolidone	872-50-4
Naphthalene	91-20-3
Oxyfluorfen	42874-03-3

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause birth defects or other reproductive harm.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Components	CASRN
2-Methylnaphthalene	91-57-6
N-Methyl-2-pyrrolidone	872-50-4
Benzenesulfonic acid, dodecyl-, calcium salt	26264-06-2
Naphthalene	91-20-3
1-Methylnaphthalene	90-12-0
Isobutanol	78-83-1

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

United States TSCA Inventory (TSCA)

This product contains chemical substance(s) exempt from U.S. EPA TSCA Inventory requirements. It is regulated as a pesticide subject to Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) requirements.

Federal Insecticide, Fungicide and Rodenticide Act

EPA Registration Number: 62719-424

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

WARNING

- Causes skin irritation
- Causes moderate eye irritation
- Harmful or fatal if swallowed or absorbed through the skin

16. OTHER INFORMATION

Hazard Rating System

NFPA

Health	Fire	Reactivity
2	1	0

Revision

Identification Number: 101223292 / A211 / Issue Date: 10/28/2015 / Version: 5.0

DAS Code: GF-1243

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
Dow IHG	Dow Industrial Hygiene Guideline
OSHA P0	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
SKIN	Absorbed via skin
STEL	Short term exposure limit
TWA	Time weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW AGROSCIENCES LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.