

MODEL NO.: 980

DESCRIPTION: Electronic Lube Meter

PRODUCT AND PACKAGING SPECIFICATIONS:

| | |
|-------------------------------|--|
| Maximum Flow: | 8 GPM / 30 LPM |
| Minimum Flow: | 0.25 GPM / 1 LPM |
| Operating Pressure (Maximum): | 1500 PSI / 10,350kPa / 103.5 Bar |
| Operating Temperature: | -4° F (-20° C) to 140° F (60° C) |
| Fluids Applicable: | Motor Oils (SAE 5 through 30), Gear Oils (SAE 80 through 240), Automatic Transmission Fluid, Engine Coolant, Windshield Wiper Fluid Solution |
| Fluid Contacted Material: | Aluminum, Acetal, Nitrile (NBR), Mild Steel |
| Accuracy: | +/- 0.5% |
| Display Unit(s): | Pints, Quarts, Gallons, or Liters |
| Inlet & Outlet Connections: | ½" FNPT |
| Weight: | 3.7lbs. (1.7kg) |
| Unit Carton Qty: | 1 ea. |
| Unit Carton Size: | 7-3/4"H x 5-1/2"W x 26"L |
| Pkg Languages: | English |
| UPC Code: | 095992100999 |
| SCC Code: | 10095992100996 |
| Harmonization Code: | 9026.10.2040 |
| Service Parts Available: | Yes |
| CE Approved: | Yes |



APPLICATION:

- Standard /Heavy duty applications: Vehicle maintenance, lube trucks, industrial environment.

KEY FEATURES:

- Large six digit LCD display with two decimal point precision
- Unit of measure selectable from the front of register
- Totalization in gallons or liters
- Resettable and non-resettable totalizer
- Low battery indicator
- Long life, field replaceable, top load battery
- 90° flex hose with swivel and manual tip
- 1/2" ball bearing swivel
- Built-in trigger guard
- Locking trigger

INCLUDES:

- Control valve, meter, flexible 90° extension, manual tip and instruction manual