

## MODEL 1152 FULLY AUTOMATIC PNEUMATIC GREASE GUN

The variable speed trigger provides excellent grease flow control while the advanced pump design eliminates traditional priming issues

- Outstanding durability and dependability
- Fully automatic, continuous operation
- Variable-speed trigger
- Accessible check valve assembly
- Comfortable grip
- 30" high-pressure hose with coupler and attachment clip
- Includes a combination filler nipple and bleeder valve
- Superior flow performance obtained through advanced design

Pump Ratio:	40:1 at	150 psi

Max. Grease Pressure: 6,000 psi (414 bar)

Air Pressure Range: 40 - 150 psi (2.8 - 10.3 bar)

Weight: 5.375 lbs. (2.4 kg)



LINCOLN



## 

Designed to provide an affordable option to draining, transferring and evacuating used oil quickly and safely

- All-steel design includes reinforced taster supports for durability and dependability.
- 18-gallon tank includes a preset air regulator that allows the use of standard shop air up to 150 psi.
- 14-inch telescoping bowl with a height adjustment range of 45 to 72 inches.
- Reinforced dispensing hose doubles as a sight gauge to prevent overfilling.
- Includes safety valve

3601 Used Fluid	Receiver	
Capacity:	18 gallons (68 L)	
Fluid Types:	Motor oils, transmission fluids, power steering fluids	
Weight:	66 lbs. (30 kg)	



