

BP-15 Steel



The BP-15 Steel is designed for medium-to-large jobs including ship decks, storage tanks and other horizontal steel applications. The BP-15 Steel is an electric self-propelled walk behind machine with a 15" blast pattern, an advanced air wash separation system, and is equipped with high quality electrical components.

*Production Capacity:	SSPC-SP6 525 up to 800 sq. ft./hr. SSPC-SP10 300 up to 600 sq. ft./hr.
Blast Pattern:	15"
Travel Speed:	0-100 ft. /min.
Blast Motor:	20 hp
Voltage:	208/230/460 3 phase
Amperage:	70/34 amps
Minimum Generator:	60 kw
Dimensions (L x W x H):	72"x23"x41"
Weight:	847 lbs.
Power Cord Length:	55 ft.
Seals:	Floating Side Seal / Skirt & Brush
Distance to edge:	2.5"
Dust Collector:	BP-9-54

- The new AC inverter controlled drive motor maintains a constant speed on inclines and declines providing better control of the blasting process.
- It features an integrated brake that holds the machine in place when idle.
- The newly incorporated blast motor soft start device dramatically reduces mechanical start-up trauma and reduces start up current.



BP-9-54, the recommended dust collector
(See separate data sheet for specifications)



BlastPro Manufacturing, Inc.
6021 Melrose Lane, Oklahoma City, OK 73127
Toll Free 877-495-6464 Phone 405-491-6464
Fax 405-495-1331
Website: www.blastpromfg.com



*Production rates are estimates only. Production rates are dependent on job site and application variables.