

# BP-15 Super

The BP-15 Super is designed for medium-to-large jobs including industrial plant and warehouse floors, parking garages, bridge decks and other horizontal applications. The BP-15 Super is an electric self-propelled walk behind machine with a 15" blast pattern, an advanced air wash separation system, and is equipped with high quality electrical components. The BP-15 travels up to 100 ft. per minute and has a production capacity of up to 1,950 sq. ft. per hour.



*Production Capacity:	Up to 1,950 sq. ft. /hr.
Blast Pattern:	15"
Travel Speed:	0-100 ft. /min.
Blast Motor:	20 hp
Voltage:	208/230/460 3phase
Amperage:	58.3/28.0 amps
Minimum Generator:	60 kw
Dimensions (L x W x H):	72"x23"x41"
Weight:	847 lbs.
Power Cord Length:	55 ft.
Seals:	Magnetic / wrap around seal
Distance to edge:	2.5"
Dust Collector:	BP-9-54

- The new AC inverter controlled drive motor maintains a constant speed on inclines and declines providing better control of the blasting process.
- It features an integrated brake that holds the machine in place when idle.
- The newly incorporated blast motor soft start device dramatically reduces mechanical start-up trauma and reduces start up current.



BP-9-54, the recommended dust collector  
(See separate data sheet for specifications)



BlastPro Manufacturing, Inc.  
6021 Melrose Lane, Oklahoma City, OK 73127  
Toll Free 877-495-6464 Phone 405-491-6464  
Fax 405-495-1331  
Website: [www.blastpromfg.com](http://www.blastpromfg.com)



\*Production rates are estimates only. Production rates are dependent on job site and application variables.