

SAFETY DATA SHEET

Date Revised: 8/15/2016

SECTION 1 - IDENTIFICATION

MANUFACTURER: DiamaPro Systems, Inc. EMERGENCY PHONE: 1-800-424-9300
ADDRESS : 325 West Front Street INFORMATION PHONE: 1-800-622-2048
Erie, PA 16507 NAME OF PREPARER: Safety Director

PRODUCT NAME: DiamaPro UV-HS Plus with Microban Gloss
PRODUCT CODE: DPUVHSG

SECTION 2 - HAZARDS IDENTIFICATION

HAZARD RISK CLASSIFICATION
SIGNAL WORD: WARNING
PICTOGRAM:
GHS07 - EXCLAMATION MARK

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY	CATEGORY 5 ORAL
ACUTE TOXICITY	CATEGORY 5 DERMAL
SKIN CORROSION / IRRITATION	CATEGORY 2
SERIOUS EYE DAMAGE / EYE IRRITATION	CATEGORY 2 AND 2A
SKIN SENSITIZER	CATEGORY 1

HAZARD STATEMENTS:

H303 May be harmful if swallowed
H305 May be harmful if swallowed and enters airways
H313 May be harmful in contact with skin
H316 Causes mild skin irritation
H317 May cause allergic skin reaction
H319 Causes serious eye irritation.

PRECAUTIONARY STATEMENTS:

PREVENTION:

P261 Avoid breathing dust/fume/gas/mist/vapor/ spray.
P264 Wash hands and any exposed area thoroughly after handling.
P270 Do not eat, drink or smoke while using this product.
P272 Contaminated work clothing should not be allowed out of the workplace
P280 Wear protective impervious gloves/ OSHA approved eye protection/face protection.

RESPONSE:

P301+P310 If swallowed: Immediately call a Poison Center / doctor.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P302+P352 If on skin: Wash with plenty of water.
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor/emergency responder.
P321 Specific treatment (see on this label)
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.

STORAGE:

P405 Store locked up.

DISPOSAL:

P501 Store separately. Dispose of contents/ container in accordance with local/ regional/national /international regulations.

SAFETY DATA SHEET

Date Revised: 8/15/2016

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS NUMBER	WEIGHT PERCENT	EXPOSURE LIMITS		
			OSHA PEL	ACGIH TLV	OTHER
* Hexanediol Diacrylate	13048-33-4	25-50			
* Oligomer Urethane Acrylate		10-25			
NOT ESTABLISHED					
* Trimethylolpropane Triacrylate	15625-89-5	10-25			

* Chemical(s) that are chronic health hazards. Refer to section 3 for further information.

PRIMARY ROUTES OF EXPOSURE:

Skin contact.

EFFECTS OF ACUTE EXPOSURE:

EYES: Direct contact with eyes may cause irritation.

SKIN: Prolonged or repeated contact may cause irritation. **INHALATION:** Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and nausea.

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful.

CHRONIC HEALTH EFFECTS:

Although some components may indicate chronic exposure effects, no effects are anticipated under normal use conditions due to the relatively low proportion in the total mixture.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

SECTION 4 - FIRST AID MEASURES

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention.

SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing.

INGESTION: If a large amount is ingested, give water or milk and induce vomiting. Seek medical attention.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Greater than 200 F **METHOD USED:** N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A **UPPER:** N/A

EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

Isolate danger area, keep unauthorized personnel out.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

SECTION 7 - HANDLING AND STORAGE

HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance with 1910.1200 of the Hazard Communication Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

STORAGE INFORMATION:

Keep containers tightly closed. Use and store material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post "No smoking or open flame" sign. Store only in approved containers. Keep away from incompatible materials (see section 10). Protect containers against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.

SAFETY DATA SHEET

Date Revised: 8/15/2016

OTHER PRECAUTIONS:

All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

===== SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION =====

RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

VENTILATION:

General room ventilation is adequate.

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing.

Laundry contaminated clothing before reuse.

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

===== SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES =====

PHYSICAL STATE:	Liquid	COLOR:	Various colors
ODOR:	Amine or ammonia odor	SOLUBILITY IN WATER:	Dilutable
SPECIFIC GRAVITY (H₂O=1):	1.08	VAPOR DENSITY:	Heavier than air.
BOILING RANGE:		EVAPORATION RATE:	Slower than nBuAc

COATING V.O.C.: 3 g/l (0.03 lb/gl)

===== SECTION 10 - STABILITY AND REACTIVITY DATA =====

STABILITY:

Stable under normal conditions and handling.

CONDITIONS TO AVOID:

None known

INCOMPATIBILITY (MATERIALS TO AVOID):

None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

HAZARDOUS POLYMERIZATION:

Will not occur.

===== SECTION 11 - TOXICOLOGICAL INFORMATION =====

SENSITIZATION:

None known.

CARCINOGENICITY:

There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard.

REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

TERATOGENICITY (BIRTH DEFECTS):

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

===== SECTION 12 - ECOLOGICAL INFORMATION =====

ENVIRONMENTAL DATA:

Contains ammonia or amines which may be toxic to aquatic life.

SAFETY DATA SHEET

Date Revised: 8/15/2016

===== SECTION 13 - DISPOSAL CONSIDERATIONS =====

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminate solids in accordance with local, state, and federal regulations.

===== SECTION 14 - TRANSPORT INFORMATION =====

SHIPPING NAME:

Not regulated.

===== SECTION 15 - REGULATORY INFORMATION =====

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory.

This product does not contain a chemical subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372) above de minimis concentrations.

STATE SPECIFIC REQUIREMENTS:

This product does not contain a chemical known to the state of California to cause cancer, birth defects or reproductive harm, subject to the requirements of California Proposition 65.

STATE LISTED COMPONENTS	CAS NUMBER	STATE CODE	.
-------------------------	------------	------------	---

===== SECTION 16 - OTHER INFORMATION =====

HMIS CODES:	H	F	R	P
	2*	0	1	I