



Constant Current Shop

The constant current chargers are designed to have a nearly flat charge curve. It provides a near constant current output while tapering slightly to maintain the AC amp draw as the battery voltage rises.

Max. Cells	Amp hr. Rating	DC Amps	SINGLE PHASE						
			Model	Control 046-0368	AC Input Amps				Case
					120	208	240	480	
24	510	40	CCS24-510A1	\$2,240	22.4	12.9	11.2	-	500
40	680	50	CCS36-680B1	\$3,398	-	24.0	21.0	10.5	501
40	1000	75	CCS36-1000B1	\$4,039	-	36.0	31.5	15.8	501
40	1350	100	CCS36-1350B1	\$4,464	-	48.5	42.0	21.0	501

Max. Cells	Amp hr. Rating	DC Amps	THREE PHASE						
			Model	Control 046-0368	AC Input Amps				Case
					120	208	240	480	
40	950	75	CCS36-950B3	\$4,532	-	21.0	18.2	9.1	501
40	1400	100	CCS36-1400B3	\$5,201	-	28.0	24.2	12.1	501
40	2000	150	CCS36-2000B3	\$7,030	-	42.0	36.3	18.1	502

* Requires 60Hz Voltage Code

A= 120/208/240

B= 208/240/480

F.O.B. First Destination, Continental USA

Prices and Specifications subject to change

All Prices in US Dollars



Automatic start/stop control

Reliable Ferro-resonant technology

Charges wide range of batteries

Ideal for shop charging

Orders with ship dates beyond 60 days are subject to price change.

Effective Date
March 1,2018

