



Multi-Cell Loaner MC6/24-60C1

No charger is safer for your battery fleet.

USA Made!

Although ferroresonant technology has been around for many years, improvements are constantly being made and today, our charger boasts a high efficiency, 87% and power factor > .90% close to that of many other manufacturers high frequency chargers. Charge control monitors battery throughout the charge and delivers a safe, complete charge.



Rugged 16 GA. case 500
H: 20.5" x W: 17.25" x D: 14.75" WGT #90



Charge 2 - 24 Cells
Jumper setting inside for 12V, 24V, 36V or 48V battery.
Ideal for Rental Fleets/Loaner Applications

BENEFITS

- Trustworthy ferroresonant technology.
- Lightweight and Portable.
- Charge 6-24 Cells.
- Maximum start rate of 60 Amps tapers to 25A at finish.

FEATURES

- Fail Safe charge for your battery.
- Automatic start and stop .
- DC Volts: Selectable 12,24,36 or 48.
- 8' DC Cable with SB175 gray connector .
- 10' AC cord with molded 3-prong plug.
- AC Volts 120/1/60. AC Amp draw 12.6 .
- Output Display : LED Display alt between DC Volts and Amp Status Indicators: 3 individual LED .



Standard control 046-267



Option: DUAL CABLE/CONNECTORS 175 & 350 GREY #038-199



Charging Technologies, Inc.
4328 Bridgeton Industrial Drive
Bridgeton, Missouri 63044

Phone: 314-739-1414
Fax: 314-739-1277
E-mail: sales@chargingti.com
www.chargingtechnologiesinc.com