

Ferro Magnetics Charger



CONSTANT CURRENT CHARGER



AVAILABLE WITH FULLY AUTOMATIC CONTROL OR MECHANICAL TIMER

PORTABLE

IMPROVED SERVICEABILITY

CHARGE 6, 12, 18, or 24 CELLS AT A CONSTANT 28 DC AMP OUTPUT

Description

This versatile charger has the ability to maintain a constant DC output current (+/- 1% at nominal line voltage); regardless of the number of cells connected (6 to 24 cells). It is an ideal purchase choice for situations where several batteries of different cell and amp-hour sizes are being charged

Ideal for Rental Fleets and as a Loaner

There are several applications such as: rental fleets, service loaners, and shop applications that make this a real money saver. It's no longer necessary to stock all the variations of charger sizes that tie up money, or cause you to deal with a logistics nightmare. This unit will provide the maximum output current possible from a 120 volt / 15 amp receptacle. Simply connect the battery and set the mechanical timer.

Specifications

Model number LS2/24-28C1 includes the heavy-duty wheeled cart.
120 VAC input, 15 amps maximum AC line draw
Fixed output current of 28 amps DC for 6 to 24 lead-acid cells
Weight: 120 lbs. including cart
Overall dimensions: 36"H, 27"W, 17-3/4"D
Control: Mechanical timer (Settable for 16 hour maximum charge)
AC power cord: 8-foot of 14/3 SJTOW cord w/molded 15-amp plug
DC cables: 10-foot
Finish: Industrial gray finish.
Connector: SB 175 gray connector
Optional connector: Dual plug w/HD guard (175/350) PN 038-199
UL cUL Listed

Ferro Magnetics Corporation

4328 Bridgeton Industrial Drive • St. Louis, MO 63044 • 314-739-1414