



Multicell Loaner Charger MC6/24-60C1



Description

The MC6/24-60C1 was designed specifically for loaner fleets. This versatile charger is supplied with an automatic control and DC voltage selection jumpers. Perfect for sending with a lift truck for short term rentals. 120/1/60 AC cord and molded plug, heavy duty wheel and handle are standard features. Rugged 16 ga. cabinet. Jumper setting inside for 12V, 24V, 36V or 48V battery. Maximum start rate of 60 Amps tapers to 25A at finish.

Specifications:

DC Volts: Selectable 12, 24, 36 or 48.

DC Amps: 60 max start to 25A finish.

DC Cable with SB175 gray connector .

AC Volts 120/1/60.

AC Amp draw 12.6 .

10' AC cord with molded 3-prong plug.

Output Display : LED Display alt between DC Volts and Amp

Status Indicators: 3 individual LED .

Weight 90#

Case 500 H: 20.5" x W: 17.25" x D: 14.75"

8'

All prices are US Dollars. FOB 1st destination, Continental USA. Prices and specifications subject to change.

Orders with ship dates beyond 60 days are subject to price change.

Ferro Magnetics Corporation

4328 Bridgeton Industrial Drive • St. Louis, MO 63044 • 314-739-1414

www.ferromc.com