

# Commercial Flow Control

Hayward® Flow Control has been manufacturing industrial thermoplastic valves and process control products since the inception of the thermoplastic valve industry. For more than 40 years, we have remained committed to producing the highest-quality products while providing outstanding service that exceeds customer expectations.

## Compact Ball Valves – QVC Series (Gray and White)

- Pressure Rating 150 PSI
- EPDM Seals
- Santoprene® Seat

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
QVC1005SSEGG	.5" Socket Gray	10	2.0
QVC1010SSEGG	1" Socket Gray	10	5.0
QVC1015SSEGG	1.5" Socket Gray	5	5.5
QVC1020SSEGG	2" Socket Gray	5	7.5
QVC1025SSEGG	2.5" Socket Gray	1	2.8
QVC1030SSEGG	3" Socket Gray	1	5.2
QVC1040SSEGG	4" Socket Gray	1	7.3
QVC1005SSEWW	.5" Socket White	10	2.0
QVC1010SSEWW	1" Socket White	10	5.0
QVC1015SSEWW	1.5" Socket White	5	5.5
QVC1020SSEWW	2" Socket White	5	7.5
QVC1025SSEWW	2.5" Socket White	1	2.8
QVC1030SSEWW	3" Socket White	1	5.2
QVC1040SSEWW	4" Socket White	1	7.3
QVC1005TSEGG	.5" Threaded Gray	10	2.0
QVC1010TSEGG	1" Threaded Gray	10	5.0
QVC1015TSEGG	1.5" Threaded Gray	5	5.5
QVC1020TSEGG	2" Threaded Gray	5	7.5
QVC1025TSEGG	2.5" Threaded Gray	1	2.8
QVC1030TSEGG	3" Threaded Gray	1	5.2
QVC1040TSEGG	4" Threaded Gray	1	7.3
QVC1005TSEWW	.5" Threaded White	10	2.0
QVC1010TSEWW	1" Threaded White	10	5.0
QVC1015TSEWW	1.5" Threaded White	5	5.5
QVC1020TSEWW	2" Threaded White	5	7.5
QVC1025TSEWW	2.5" Threaded White	1	2.8
QVC1030TSEWW	3" Threaded White	1	5.2
QVC1040TSEWW	4" Threaded White	1	7.3



## True Union Compact Ball Valves – QTA Series (Gray and White)

- Pressure Rating 150 PSI
- EPDM Seals
- Santoprene Seat

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
QTA1010CSEGG	1" Socket / Threaded Gray	1	0.9
QTA1015CSEGG	1.5" Socket / Threaded Gray	1	2.0
QTA1020CSEGG	2" Socket / Threaded Gray	1	3.2
QTA1010CSEWW	1" Socket / Threaded White	1	0.9
QTA1015CSEWW	1.5" Socket / Threaded White	1	2.1
QTA1020CSEWW	2" Socket / Threaded White	1	3.5



## True Union PVC Ball Valves – TBB Series

- Pressure Rating 225 PSI
- EPDM Seals
- PTFE Seat
- Double O-Ring Stem Seals

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
TBB1005CPEG	.5" Socket / Threaded	1	0.5
TBB1007CPEG	.75" Socket / Threaded	1	0.8
TBB1010CPEG	1" Socket / Threaded	1	1.2
TBB1012CPEG	1.25" Socket / Threaded	1	1.9
TBB1015CPEG	1.5" Socket / Threaded	1	2.8
TBB1020CPEG	2" Socket / Threaded	1	4.9



Santoprene is a registered trademark of Advanced Elastomer Systems.

## True Union PVC Ball Valves – TB Series

- Pressure Rating  
250 PSI: ½" – 2"  
235 PSI: 2½" – 4"  
150 PSI: 6"
- EPDM or FPM Seals
- PTFE Seat
- Double O-Ring Stem Seals
- Easily Automated
- Full Port Design Through 4"
- NSF/ANSI Standard 61 Certified

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
TB1050STE	.5" Socket / Threaded	1	0.8
TB1050ST	.5" Socket / Threaded	1	0.8
TB1075STE	.75" Socket / Threaded	1	1.1
TB1075ST	.75" Socket / Threaded	1	1.1
TB1100STE	1" Socket / Threaded	1	1.5
TB1100ST	1" Socket / Threaded	1	1.5
TB1125STE	1.25" Socket / Threaded	1	2.9
TB1125ST	1.25" Socket / Threaded	1	2.9
TB1150STE	1.5" Socket / Threaded	1	3.0
TB1150ST	1.5" Socket / Threaded	1	3.0
TB1200STE	2" Socket / Threaded	1	4.3
TB1200ST	2" Socket / Threaded	1	4.3
TB1250TE or TB1250SE	2.5" Socket or Threaded	1	11.0
TB1250T or TB1250S	2.5" Socket or Threaded	1	11.0
TB1300TE or TB1300SE	3" Socket or Threaded	1	11.2
TB1300T or TB1300S	3" Socket or Threaded	1	11.2
TB1400TE or TB1400SE	4" Socket or Threaded	1	19.1
TB1400T or TB1400S	4" Socket or Threaded	1	19.1
TB1600FE (Flanged Only)	6" Flanged	1	33.7
TB1600F (Flanged Only)	6" Flanged	1	33.7



## True Union Ball Valves (Actuated)

- Pressure Rating 150 PSI
- True Union Design
- One-Piece Molded Body
- EPDM or FPM Seals
- PTFE Seats
- Double O-Ring Stem Seals
- Includes Mounting Kit and Actuator

### Electric Actuator Details

- 90-Degree Operation
- UL/CSA Listed Motor
- Standard 120 Volt

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
EAUTB105STE	.5" EPDM Socket / Threaded	1	5.4
EAUTB107STE	.75" EPDM Socket / Threaded	1	5.7
EAUTB110STE	1" EPDM Socket / Threaded	1	6.7
EAUTB115STE	1.5" EPDM Socket / Threaded	1	7.9
EAUTB120STE	2" EPDM Socket / Threaded	1	8.2
EAUTB105STV	.5" FPM Socket / Threaded	1	6.2
EAUTB107STV	.75" FPM Socket / Threaded	1	5.7
EAUTB110STV	1" FPM Socket / Threaded	1	6.8
EAUTB115STV	1.5" FPM Socket / Threaded	1	7.3
EAUTB120STV	2" FPM Socket / Threaded	1	9.5



## True Union Three-Way Ball Valves – TW Series

- Pressure Rating 150 PSI
- One-Piece Molded Body
- EPDM Seals
- PTFE Seats
- Double O-Ring Stem Seals
- Actuator Ready Available (HCTN Series)

(Lateral three-way valves also available)

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
TW1050STE	.5" Socket / Threaded	1	1.2
TW1075STE	.75" Socket / Threaded	1	1.8
TW1100STE	1" Socket / Threaded	1	2.5
TW1125STE	1.25" Socket / Threaded	1	7.4
TW1150STE	1.5" Socket / Threaded	1	6.8
TW1200STE	2" Socket / Threaded	1	7.1
TW1250SE	2.5" Socket	1	17.1
TW1250TE	2.5" Threaded	1	17.3
TW1300SE	3" Socket	1	17.1
TW1300TE	3" Threaded	1	17.3
TW1400SE	4" Socket	1	27.7
TW1400TE	4" Threaded	1	27.9
TW1600FE	6" Flanged	1	51.0



**Three-Way Ball Valves (Actuated)**

- Pressure Rating 150 PSI
- True Union Design
- One-Piece Molded Body
- EPDM Seals
- PTFE Seats
- Double O-Ring Stem Seals
- Includes Mounting Kit and Actuator

*Electric Actuator Details*

- 180-Degree Operation
- UL/CSA Listed Motor
- Standard 120 Volt
- Additional Voltage Available

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
EAUTN105STE	.5" Socket / Threaded	1	8.0
EAUTN107STE	.75" Socket / Threaded	1	9.0
EAUTN110STE	1" Socket / Threaded	1	10.0
EAUTN1125STE	1.25" Socket / Threaded	1	15.0
EAUTN115STE	1.5" Socket / Threaded	1	15.0
EAUTN120STE	2" Socket / Threaded	1	15.0
EM3TN125SE	2.5" Socket	1	26.0
EM3TN125TE	2.5" Threaded	1	26.0
EM3TN13SE	3" Socket	1	26.0
EM3TN13TE	3" Threaded	1	26.0
EM8TN14SE	4" Socket	1	29.8
EM8TN14TE	4" Threaded	1	29.8
EM8TN16FF (Flanged Only)	6" Flanged	1	80.0



**True Union PVC Check Valves – TC Series**

- Pressure Rating 150 PSI
- EPDM Seals
- For Horizontal or Vertical Installation
- NSF/ANSI Standard 61 Certified

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
TC10050STE	.5" Socket / Threaded	1	0.7
TC10075STE	.75" Socket / Threaded	1	0.9
TC10100STE	1" Socket / Threaded	1	1.3
TC10125STE	1.25" Socket / Threaded	1	2.5
TC10150STE	1.5" Socket / Threaded	1	2.7
TC10200STE	2" Socket / Threaded	1	4.1
TC1250TE or TC1250SE	2.5" Socket or Threaded	1	9.8
TC1300TE or TC1300SE	3" Socket or Threaded	1	10.1
TC1400TE or TC1400SE	4" Socket or Threaded	1	17.5
TC1600FE (Flanged Only)	6" Flanged	1	33.0



**Full Pattern PVC Wafer Check Valves – WCV Series**

- Pressure Rating 150 PSI
- One-Piece Disk and Shaft Design
- FPM or EPDM Gasket of Face Seal
- Full Pattern Body – No Need for Spacers or Specialty Flanges
- Contoured Inlet Port for Easy Flow
- Can Be Installed in Vertical or Horizontal Position

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
WCV1200E	2" EPDM Wafer Check	1	1.3
WCV1250E	2.5" EPDM Wafer Check	1	1.9
WCV1300E	3" EPDM Wafer Check	1	2.2
WCV1400E	4" EPDM Wafer Check	1	4.4
WCV1600E	6" EPDM Wafer Check	1	6.0
WCV1800E	8" EPDM Wafer Check	1	14.0
WCV1200V	2" FPM Wafer Check	1	1.3
WCV1250V	2.5" FPM Wafer Check	1	1.9
WCV1300V	3" FPM Wafer Check	1	2.2
WCV1400V	4" FPM Wafer Check	1	4.6
WCV1600V	6" FPM Wafer Check	1	6.8
WCV1800V	8" FPM Wafer Check	1	14.7



**Full Pattern PVC Wafer Check Valves – WCV Series**

- Pressure Rating 150 PSI
- One-Piece Disk and Shaft Design
- FPM or EPDM Gasket of Face Seal
- Full Pattern Body – No Need for Spacers or Specialty Flanges
- Contoured Inlet Port for Easy Flow
- Can Be Installed in Vertical or Horizontal Position
- 316 SS Disc Spring

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
WCV1200ES	2" EPDM Wafer Check w/ Spring	1	1.2
WCV1250ES	2.5" EPDM Wafer Check w/ Spring	1	1.9
WCV1300ES	3" EPDM Wafer Check w/ Spring	1	2.2
WCV1400ES	4" EPDM Wafer Check w/ Spring	1	4.4
WCV1600ES	6" EPDM Wafer Check w/ Spring	1	6.2
WCV1800ES	8" EPDM Wafer Check w/ Spring	1	14.4
WCV1200VS	2" FPM Wafer Check w/ Spring	1	1.3
WCV1250VS	2.5" FPM Wafer Check w/ Spring	1	1.9
WCV1300VS	3" FPM Wafer Check w/ Spring	1	2.2
WCV1400VS	4" FPM Wafer Check w/ Spring	1	4.5
WCV1600VS	6" FPM Wafer Check w/ Spring	1	6.1
WCV1800VS	8" FPM Wafer Check w/ Spring	1	14.5





## Full Pattern CPVC Wafer Check Valves – WCV Series

- Pressure Rating 150 PSI
- One-Piece Disk and Shaft Design
- FPM or EPDM Gasket of Face Seal
- Full Pattern Body – No Need for Spacers or Specialty Flanges
- Contoured Inlet Port for Easy Flow
- Can Be Installed in Vertical or Horizontal Position

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
WCV2200E	2" EPDM Wafer Check	1	2.0
WCV2250E	2.5" EPDM Wafer Check	1	1.3
WCV2300E	3" EPDM Wafer Check	1	2.3
WCV2400E	4" EPDM Wafer Check	1	4.6
WCV2600E	6" EPDM Wafer Check	1	7.2
WCV2800E	8" EPDM Wafer Check	1	15.1
WCV2200V	2" FPM Wafer Check	1	2.0
WCV2250V	2.5" FPM Wafer Check	1	2.0
WCV2300V	3" FPM Wafer Check	1	2.4
WCV2400V	4" FPM Wafer Check	1	4.7
WCV2600V	6" FPM Wafer Check	1	7.3
WCV2800V	8" FPM Wafer Check	1	15.1



## Full Pattern CPVC Wafer Check Valves – WCV Series

- Pressure Rating 150 PSI
- One-Piece Disk and Shaft Design
- FPM or EPDM Gasket of Face Seal
- Full Pattern Body – No Need for Spacers or Specialty Flanges
- Contoured Inlet Port for Easy Flow
- Can Be Installed in Vertical or Horizontal Position
- 316 SS Disc Spring

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
WCV2200ES	2" EPDM Wafer Check w/ Spring	1	2.0
WCV2250ES	2-1/2" EPDM Wafer Check w/ Spring	1	2.0
WCV2300ES	3" EPDM Wafer Check w/ Spring	1	2.3
WCV2400ES	4" EPDM Wafer Check w/ Spring	1	4.6
WCV2600ES	6" EPDM Wafer Check w/ Spring	1	7.1
WCV2800ES	8" EPDM Wafer Check w/ Spring	1	16.5
WCV2200VS	2" FPM Wafer Check w/ Spring	1	2.0
WCV2250VS	2-1/2" FPM Wafer Check w/ Spring	1	2.0
WCV2300VS	3" FPM Wafer Check w/ Spring	1	2.4
WCV2400VS	4" FPM Wafer Check w/ Spring	1	4.7
WCV2600VS	6" FPM Wafer Check w/ Spring	1	7.3
WCV2800VS	8" FPM Wafer Check w/ Spring	1	16.5



## Butterfly Valves (Lever Operated) – Pure-Blu™ BYCN Series

- Pressure Rating 150 PSI
- PVC Body and Disc
- EPDM Liner
- 316 SS Stem
- 9-Position Throttle Plate
- NSF/ANSI Standard 61 Certified

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
BYCN1020E1LGB	2" Lever	1	5.0
BYCN1025E1LGB	2.5" Lever	1	5.0
BYCN1030E1LGB	3" Lever	1	6.1
BYCN1040E1LGB	4" Lever	1	8.3
BYCN1050E1LGB	5" Lever	1	12.0
BYCN1060E1LGB	6" Lever	1	15.0
BYCN1080E1LGB	8" Lever	1	20.0



**Butterfly Valve (Gear Operated) – Pure-Blu™ BYCN Series**

- Pressure Rating 150 PSI
- PVC Body and Disc
- EPDM Liner
- 316 SS Stem
- 9-Position Throttle Plate
- NSF/ANSI Standard 61 Certified

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
BYCN1020E1GGB	2" Gear	1	11.0
BYCN1025E1GGB	2.5" Gear	1	11.0
BYCN1030E1GGB	3" Gear	1	16.6
BYCN1040E1GGB	4" Gear	1	19.0
BYCN1050E1GGB	5" Gear	1	21.0
BYCN1060E1GGB	6" Gear	1	23.2
BYCN1080E1GGB	8" Gear	1	30.0



**Butterfly Valves (Lever Operated) – BY Series**

- Pressure Rating 150 PSI
- PVC Body and Disc
- EPDM Liner
- 316 SS Stem
- Fully Supported Bolt Holes
- 316 SS Lugs Available
- NSF/ANSI Standard 61 Certified

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
BY110200ELA	1.5" Lever	1	5.0
BY110200ELA	2" Lever	1	5.0
BY110300EL	3" Lever	1	6.1
BY110400EL	4" Lever	1	8.3
BY110600EL	6" Lever	1	15.0
BY110800EL	8" Lever	1	20.0



**Butterfly Valves (Gear Operated) – BY Series**

- Pressure Rating 150 PSI
- PVC Body and Disc
- EPDM Liner
- 316 SS Stem
- Fully Supported Bolt Holes
- 316 SS Lugs Available
- NSF/ANSI Standard 61 Certified

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
BY110200EGA	1.5" Gear	1	11.0
BY110200EGA	2" Gear	1	11.0
BY110300EG	3" Gear	1	16.6
BY110400EG	4" Gear	1	19.0
BY110600EG	6" Gear	1	23.2
BY110800EG	8" Gear	1	30.0
BY41100EG	10" Gear	1	35.5



**Diaphragm Valves – DAB Series**

- Pressure Rating 150 PSI ½" – 4" 75 PSI – 6"
- PVC Body with EPDM Diaphragm and Seals
- Sure-Grip Handwheel with Position Indicator
- True Union End Connections Through 2"
- Flanged End Connections in 2½" Through to 6" sizes

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
DAB1005UEE	.5" Socket / Threaded	1	1.9
DAB1007UEE	.75" Socket / Threaded	1	2.3
DAB1010UEE	1" Socket / Threaded	1	2.9
DAB1012UEE	1.25" Socket / Threaded	1	3.0
DAB1015UEE	1.5" Socket / Threaded	1	6.3
DAB1020UEE	2" Socket / Threaded	1	9.1
DAB1025FEK	2.5" Flanged	1	15.0
DAB1030FEK	3" Flanged	1	18.0
DAB1040FEK	4" Flanged	1	29.7
DAB1060FEK	6" Flanged	1	71.8



## PVC Bulkhead Fittings – BFA Series

- Pressure Rating 150 PSI
- Long Pattern/Barrel
- PVC Body and Nut
- FPM or EPDM Gasket Seal
- Left-Hand Threads
- Hex Body for One-Person Installation
- Full Buttress Threads

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
BFA1005CFS	.5" Socket x Threaded	1	0.3
BFA1005SFS	.5" Socket x Socket	1	0.3
BFA1005TFS	.5" Threaded x Threaded	1	0.3
BFA1005CES	.5" Socket x Threaded	1	0.3
BFA1005SES	.5" Socket x Socket	1	0.3
BFA1005TES	.5" Threaded x Threaded	1	0.3
BFA1007CFS	.75" Socket x Threaded	1	0.4
BFA1007SFS	.75" Socket x Socket	1	0.4
BFA1007TFS	.75" Threaded x Threaded	1	0.4
BFA1007CES	.75" Socket x Threaded	1	0.4
BFA1007SES	.75" Socket x Socket	1	0.3
BFA1007TES	.75" Threaded x Threaded	1	0.4
BFA1010CFS	1" Socket x Threaded	1	0.5
BFA1010SFS	1" Socket x Socket	1	0.5
BFA1010TFS	1" Threaded x Threaded	1	0.5
BFA1010CES	1" Socket x Threaded	1	0.5
BFA1010SES	1" Socket x Socket	1	0.5
BFA1010TES	1" Threaded x Threaded	1	0.5
BFA1012CFS	1.25" Socket x Threaded	1	0.8
BFA1012SFS	1.25" Socket x Socket	1	0.8
BFA1012TFS	1.25" Threaded x Threaded	1	0.8
BFA1012CES	1.25" Socket x Threaded	1	1.0
BFA1012SES	1.25" Socket x Socket	1	0.9
BFA1012TES	1.25" Threaded x Threaded	1	0.9
BFA1015CFS	1.5" Socket x Threaded	1	0.8
BFA1015SFS	1.5" Socket x Threaded	1	0.8
BFA1015TFS	1.5" Threaded x Threaded	1	0.8
BFA1015CES	1.5" Socket x Threaded	1	0.8
BFA1015SES	1.5" Socket x Socket	1	0.8
BFA1015TES	1.5" Threaded x Threaded	1	0.8
BFA1020CFS	2" Socket x Threaded	1	1.4
BFA1020SFS	2" Socket x Socket	1	1.4
BFA1020TFS	2" Threaded x Threaded	1	1.4
BFA1020CES	2" Socket x Threaded	1	1.4
BFA1020SES	2" Socket x Socket	1	1.3
BFA1020TES	2" Threaded x Threaded	1	1.4
BFA1030CFS	3" Socket x Threaded	1	2.7
BFA1030SFS	3" Socket x Socket	1	2.3
BFA1030TFS	3" Threaded x Threaded	1	2.7
BFA1030CES	3" Socket x Threaded	1	2.7
BFA1030SES	3" Socket x Socket	1	2.3
BFA1030TES	3" Threaded x Threaded	1	2.7
BFA1040CFS	4" Socket x Threaded	1	7.0
BFA1040SFS	4" Socket x Socket	1	7.0
BFA1040TFS	4" Threaded x Threaded	1	7.0
BFA1040CES	4" Socket x Threaded	1	6.6
BFA1040SES	4" Socket x Socket	1	6.6
BFA1040TES	4" Threaded x Threaded	1	7.0
BFA1060CFS	6" Socket x Threaded	1	17.2
BFA1060SFS	6" Socket x Socket	1	17.2
BFA1060TFS	6" Threaded x Threaded	1	17.2
BFA1060CES	6" Socket x Threaded	1	16.9
BFA1060SES	6" Socket x Socket	1	16.0
BFA1060TES	6" Threaded x Threaded	1	17.1



**PVC Bulkhead Fittings – BFAS Series**

- Pressure Rating 150 PSI
- Short Pattern/Barrel
- PVC Body and Nut
- FPM or EPDM Gasket Seal
- Left-Hand Threads
- Hex Body for One-Person Installation
- Full Buttress Threads
- NSF/ANSI Standard 61 Certified

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
BFAS1005CFS	.5" Socket x Threaded	1	0.3
BFAS1005TFS	.5" Threaded x Threaded	1	0.3
BFAS1005CES	.5" Socket x Threaded	1	0.2
BFAS1005TES	.5" Threaded x Threaded	1	0.2
BFAS1007CFS	.75" Socket x Threaded	1	0.4
BFAS1007TFS	.75" Threaded x Threaded	1	0.4
BFAS1007CES	.75" Socket x Threaded	1	0.4
BFAS1007TES	.75" Threaded x Threaded	1	0.3
BFAS1010CFS	1" Socket x Threaded	1	0.5
BFAS1010TFS	1" Threaded x Threaded	1	0.5
BFAS1010CES	1" Socket x Threaded	1	0.4
BFAS1010TES	1" Threaded x Threaded	1	0.4
BFAS1012CFS	1.25" Socket x Threaded	1	0.8
BFAS1012TFS	1.25" Threaded x Threaded	1	0.8
BFAS1012CES	1.25" Socket x Threaded	1	0.9
BFAS1012TES	1.25" Threaded x Threaded	1	0.8
BFAS1015CFS	1.5" Socket x Threaded	1	0.8
BFAS1015TFS	1.5" Threaded x Threaded	1	0.8
BFAS1015CES	1.5" Socket x Threaded	1	0.6
BFAS1015TES	1.5" Threaded x Threaded	1	0.6
BFAS1020CFS	2" Socket x Threaded	1	1.3
BFAS1020TFS	2" Threaded x Threaded	1	1.2
BFAS1020CES	2" Socket x Threaded	1	1.1
BFAS1020TES	2" Threaded x Threaded	1	1.2
BFAS1030CFS	3" Socket x Threaded	1	2.3
BFAS1030TFS	3" Threaded x Threaded	1	2.3
BFAS1030CES	3" Socket x Threaded	1	2.3
BFAS1030TES	3" Threaded x Threaded	1	2.1
BFAS1040CFS	4" Socket x Threaded	1	6.3
BFAS1040TFS	4" Threaded x Threaded	1	6.4
BFAS1040CES	4" Socket x Threaded	1	6.3
BFAS1040TES	4" Threaded x Threaded	1	6.4



**PVC Self-Aligning Bulkhead Fittings – SF Series**

- Pressure Rating 75 PSI
- PVC Body and Nut
- EPDM Gasket Seal
- Easy Connection
- Ideal for Domed Tanks

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
SF10100T	1" Threaded x Threaded	1	1.5
SF10200T	2" Threaded x Threaded	1	2.1
SF10300T	3" Threaded x Threaded	1	6.2



**Tank-Tite™ – CCP Series**

- Pressure Rating 150 PSI
- Robust Upper and Lower PVC Body
- 17.4 PH SS Wave Spring
- Compatible With All Bulkhead Fitting Materials

Part Number	Size / Description	Carton Quantity	Carton Weight (lbs.)
CCP1005	.5" Compression Ring with 17-7 Spring	1	0.1
CCP1007	.75" Compression Ring with 17-7 Spring	1	0.1
CCP1010	1" Compression Ring with 17-7 Spring	1	0.1
CCP1015	1.25"-1.5" Compression Ring with 17-7 Spring	1	0.2
CCP1020	2" Compression Ring with 17-7 Spring	1	0.3
CCP1030	3" Compression Ring with 17-7 Spring	1	.05

