

Essential

Essential Power Vent gas water heaters offer up to 150 foot vent runs, energy efficiency and the flammable vapor detection system

EFFICIENCY

- .61 - .69 UEF
- ENERGY STAR® rated

PERFORMANCE

- FHR: up to 78 gallons for 50-gallon models and up to 86 gallons for 40-gallon models
- Recovery: 32.4 to 42.4 GPH at a 90° F rise, depending on model

SELF-DIAGNOSTIC SYSTEM

- Electronic gas control for improved monitoring and service

LOW EMISSIONS

- Eco-friendly burner, low NOx design

FEATURES

- Uses indoor air for combustion; blower exhausts the flue gases
- Standard 120 VAC electrical connection
- Whisper quiet blower

FLAMMABLE VAPOR DETECTION SYSTEM

- Exclusive air/fuel shut-off device for double protection
- Maintenance free – no filter to clean
- Disables the heater in the presence of flammable vapor accumulation

FLEXIBLE VENTING OPTIONS

- Long venting lengths up to 100 equivalent feet
- 2" or 3" PVC, ABS, or CPVC vent pipe options
- Vertical or horizontal termination

LONGER LIFE

- Premium grade anode rod provides long-lasting tank protection

HIGH ALTITUDE COMPLIANT

- All models certified for applications up to 7,800 ft. above sea level

PLUS...

- Temperature and pressure relief valve included
- Low lead compliant
- Durable Silicon Nitride Ignitor (HSI)
- EverKleen™ patented system fights sediment build-up
- Standard replacement parts

WARRANTY

- 6-Year limited tank and parts warranty*

*See Residential Warranty Certificate for complete information

Units meet or exceed ANSI requirements and have been tested according to D.O.E. procedures. Units meet or exceed the energy efficiency requirements of NAECA, ASHRAE standard 90, ICC Code and all state energy efficiency performance criteria.



*Essential
Power Vent*
40 and 50-Gallon Capacities
Up to 42,000 BTU/h
Natural and LP Gas



LEED Point = 1

See specifications chart on back.


Essential

Power Vent Specifications

TYPE	DESCRIPTION			FEATURES						ROUGHING IN DIMENSIONS (SHOWN IN INCHES)							ENERGY INFO.		
	NOMINAL GALLON CAPACITY	RATED GALLON CAPACITY	MODEL NUMBER	GAS INPUT IN THOUS. BTU/H		RECOVERY IN G.P.H. 90° F RISE		FIRST HR. DELIVERY G.P.H.		HT. TO TOP OF ASSEMBLY A	TANK HEIGHT B	DIAM. C	HT. TO GAS CONN. D	WATER CONN. CENTER E	HT. TO SIDE T&P VALVE F	WATER CONN. SIZE G	SHIP WEIGHT (LBS)	UNIFORM ENERGY FACTOR (UEF)	ESTIMATED YEARLY ENERGY COST
				NAT.	LP	NAT.	LP	NAT.	LP										
Tall	40	38	★ 6GR40PVE2-40	40	-	40.4	-	86	-	66-1/4	59	19-3/4	14	8	53-1/2	3/4	140	0.69	\$267
Tall	40	38	★ 6GR40PVE2-36P	-	36	-	36.4	-	86	66-1/4	59	19-3/4	14	8	53-1/2	3/4	140	0.69	\$647
Tall	50	48	★ 6GR50PVE2-42	42	-	42.4	-	78	-	65-1/2	58	21-3/4	14	8	52-1/2	3/4	170	0.68	\$271
Tall	50	48	★ 6GR50PVE2-42P	-	42	-	42.4	-	78	65-1/2	58	21-3/4	14	8	52-1/2	3/4	170	0.68	\$657
Short	40	38	★ 6GR40SPVE2-36	36	-	36.4	-	66	-	58-1/4	51-1/4	21-3/4	14	8	44-1/4	3/4	161	0.61	\$198
Short	40	38	★ 6GR40SPVE2-32P	-	32	-	32.4	-	66	58-1/4	51-1/4	21-3/4	14	8	44-1/4	3/4	161	0.61	\$479
Short	50	48	★ 6GR50SPVE2-36	36	-	36.4	-	78	-	58-1/4	51-1/4	23-3/4	14	8	44	3/4	185	0.65	\$284
Short	50	48	★ 6GR50SPVE2-32P	-	32	-	32.4	-	78	58-1/4	51-1/4	23-3/4	14	8	44	3/4	185	0.65	\$687

Uniform Energy Factor and rated gallon capacity based on Department of Energy (DOE) requirements.

★ ENERGY STAR® compliant model.



Maximum and Minimum Vent Lengths for 2 - 3" Vents up to 2,000 Ft. (609 m) Above Sea Level								
Model	Gas	Heater input	Vent System Diameter	Min. Allowed Equivalent Vent Length		Max Allowed Equivalent Vent Length		Vent System Termination
		Btu/hr.		Inches	Feet	Meters	Feet	
All	Natural & Propane	42,000, 40,000, 36,000, 32,000	2	7	2.1	55	16.7	45° Elbow
			3	7	2.1	150	45.7	45° Elbow

Maximum and Minimum Vent Lengths for 2 - 3" Vents From 2,000 Ft. (609 m) through 7,800 Ft. (2,377 m) Above Sea Level								
Model	Gas	Heater Input	Vent System Diameter	Min. Allowed Equivalent Vent Length		Max Allowed Equivalent Vent Length		Vent System Termination
		Btu/hr.		Inches	Feet	Meters	Feet	
40 Gallon	Natural	40,000	2	7	2.1	25	7.6	45° Elbow
			3	7	2.1	150	45.7	45° Elbow
40 Gallon	Propane	36,000	2	7	2.1	35	10.6	45° Elbow
			3	7	2.1	150	45.7	45° Elbow
40 Gallon	Natural & Propane	36,000, 32,000	2	7	2.1	40	12.2	45° Elbow
			3	7	2.1	150	45.7	45° Elbow
50 Gallon	Natural & Propane	42,000, 36,000, 32,000	2	7	2.1	35	10.6	45° Elbow
			3	7	2.1	150	45.7	45° Elbow

For the 2" and 3" vent, one 90° elbow is approximately equal to 5 feet of pipe. One 45° elbow is approximately equal to 2.5 feet of pipe.