

# CONFIDENCE IN YOUR CHOICE

#### RHEEM'S EHG ELECTRIC STORAGE WATER HEATER SERIES

Rheem's EHG Electric Storage Water Heater series is the perfect range of water heaters to cater to all your unique water heating needs. Enjoy functionality, versatility and durability with Rheem's EHG Electric Storage Water Heater series.





#### **Resistored Anode Rod**


Counters aggressive water to prolong the lifespan of the storage water heater

#### **Components Secured** with 5-Bolt Flange

Allows for easy access to internal components during regular maintenance

#### Water Inlet with Whirl Flow Diffuser

Helps regulate incoming water flow to optimise heating and provide more hot water



#### **High Density Polyurethane Insulation**

Promotes better heat retention, which saves more energy and reduces heating time

#### **Blue Diamond Enamel** Coating

Provides protection for inner tank to resist corrosion and ensures long-lasting performance

#### **Incoloy Heating Element**

Withstands high temperatures and resists dry firing while ensuring fast heating









#### **Thermal Cut Off**

Ensures prevention of overheating or scalding from occurring



#### **Universal Service Panel**

Provides flexibility during installation and easier maintenance



#### **Universal Mounting Bracket**

Allows for simple and easy mounting and installation



#### **ELCB** (optional)

Helps provide protection against electrical shock



#### EHG Smart WiFi Storage Water Heater Series

Download 'Rheem SEA' mobile application free below





## INTUITIVE, VERSATILE AND SOPHISTICATED

Elevate your shower experience and enjoy greater convenience

Elevate your shower experience by utilising the EHG Smart WiFi's smart heating capabilities, heating schedule options and temperature adjustment functions, which can be controlled seamlessly and effortlessly through your mobile phone.

Simply download the Rheem SEA mobile application to unlock all the benefits the EHG Smart WiFi series has to offer. With its simple and intuitive interface, you can easily navigate through the different modes available and make quick and easy adjustments to suit your shower preferences and needs.



#### **Eco Smart Mode**

Optimise your water heater by enabling 'Eco Smart Mode' and letting your water heater learn your shower habits to operate more efficiently



#### **Timer Mode**

Use the timer mode to set your desired start and end heating time for your water heater



#### **STD Mode**

Use the STD mode to choose your desired heating temperature from 30°C to 75°C



#### **Power Status Notifications**


Receive real-time notifications on your phone whenever your water heater power status has changed





Rheem SEA Mobile Application



### Slim Design suitable for tight ceiling spaces







	MODEL		TANK	MOUNTING	DIMENSIONS (mm)					HEATING	PRESET	HEATING ELEMENT	EMPTY TANK	OPERATING TANK
	WIFI	CLASSIC	CAPACITY (LITRES)	MOUNTING	А	В	С	D	Е	TIME (MINS)	TEMP. (°C)	INPUT kW (230V)	WEIGHT (KG)	WEIGHT (KG)
SO	EHG-25S (WIFI)	EHG-25S	25	Horizontal	616	340	230	270	360	22	60	3	16	41
	EHG-40S (WIFI)	EHG-40S	40	Horizontal	739	340	230	400	360	34	60	3	21	61
	EHG-55S (WIFI)	EHG-55S	55	Horizontal	853	340	230	410	360	47	60	3	23	78
	EHG-30 (WIFI)	EHG-30	30	Horizontal	540	380	270	165	400	24	60	3	17	47
	EHG-40 (WIFI)	EHG-40	40	Horizontal	640	380	270	280	400	32	60	3	21	61
	EHG-50 (WIFI)	EHG-50	50	Horizontal	740	380	270	400	400	40	60	3	22	72
	EHG-60 (WIFI)	EHG-60	60	Horizontal	860	380	270	500	400	48	60	3	24	84
	EHG-80 (WIFI)	EHG-80	80	Horizontal	970	410	300	500	430	64	60	3	29	109
	EHG-90 (WIFI)	EHG-90	90	Horizontal	1055	410	300	500	430	72	60	3	30	120
	EHG-100 (WIFI)	EHG-100	100	Horizontal	1155	410	300	500	430	80	60	3	32	132

Product images and specifications are subject to change without prior notice



Rheem Manufacturing Company

f Rheem.SG

Rheem\_SG

in Rheem Asia

Website: www.RheemAsia.com

**Authorised Dealer** 

<sup>\*</sup>Approximate time taken to heat up to 60°C at inlet water temperature of 25°C. All connection in 1/2" BSP thread.