

CONSEW Since 1898

MODEL 289RB-HLP-1

WITH
CENTRA-LUBE® - SEMI-AUTOMATIC LUBRICATION SYSTEM
LARGE VERTICAL AXIS ROTARY HOOK AND BOBBIN
REVERSE FEED
SAFETY CLUTCH

WALKING FOOT



POST BED

HIGH SPEED
EXTRA HIGH POST TYPE
SINGLE NEEDLE
DROP FEED, NEEDLE FEED
WALKING FOOT
ALTERNATING PRESSER FEET
LOCKSTITCH MACHINE

Model 289RB-HLP-1

APPLICATIONS

- For sewing medium to heavy weight fabrics, leather, canvas, vinyl, synthetics and various coated and laminated materials
- For stitching uneven, hollow, tubular and curved articles
- Designed for stitching such products as boots, shoes, gloves, luggage, handbags, overalls, raincoats, bags, umbrellas, awnings, covers, tarpaulins, tents, sports and camping equipment, wearing apparel, outdoor clothing, etc.
- Suitable for edge stitching operations

FEATURES

- Centra-Lube® semi-automatic lubrication system
- Oil fed take-up
- Extra high post
- Safety clutch prevents the hook from being damaged
- Large bobbin allows for longer operation
- Large vertical axis hook allows for use of thick thread and therefore ornamental stitching can be obtained
- Compound feed, walking foot mechanism assures even feeding of material
- Reverse stitching
- Simple adjustment permits raising and lowering of the center foot which allows for sewing different thicknesses of material

SPECIFICATIONS

Speed, Max. (S.P.M.) *		2200*	Hook	14119
		(* Speed depends on operation, material and thread.)		
Clearance	Hand	5/16" (8.5 mm)	Bed Size	7" x 20 3/8" (178 mm x 518 mm)
	Foot	5/8" (16 mm)	Work Surface	2 1/8" x 2" (54 mm x 51 mm)
Needle Bar Stroke		1-13/32" (35.3 mm)	Post Height	17-7/16" (443 mm)
Stitch Length, Max.		4 s.p.i. (6.2 mm)	Stitch Type	301
Bobbin	Metal	15408	Needle	135 x 17
	Pre-wound	S and U		