

CONSEW® Since 1898


MODEL 329RB-1

WITH
CENTRA-LUBE® SEMI-AUTOMATIC LUBRICATION SYSTEM
LARGE VERTICAL AXIS ROTARY HOOKS AND BOBBINS
DISENGAGEABLE RIGHT AND LEFT NEEDLE BARS
REVERSE FEED
SAFETY CLUTCH
SPLIT BAR



**LARGE
BOBBIN**

**Double Needle
Split Bar**



ANGULAR STITCHING

HEAVY DUTY
HIGH SPEED
POST TYPE
TWO NEEDLE
ANGULAR STITCHING

(SPLIT NEEDLE BAR)

DROP FEED, NEEDLE FEED
LOCKSTITCH MACHINE

POST BED

Model 329RB-1

APPLICATIONS

- For sewing medium to medium heavy-weight fabrics, leather, canvas, vinyl, synthetics and various coated and laminated materials
- Designed for sewing operations which require decorative or functional angular stitching such as collars, pockets, shoe uppers, auto, boat and furniture upholstery, slacks, shirts, etc.
- General / parallel two-needle stitching, for top stitching and reinforcement.
- Suitable for stitching uneven, hollow, tubular and curved articles
- Also for secondary operations on finished articles such as attaching braids, pockets, tapes, etc.

FEATURES

- Centra-Lube® semi-automatic lubrication system
- Oil fed take-up
- One-touch lever easily disengages right and left needle bars
- Stitches per minute - 2400
- Large vertical axis rotary hooks and bobbins
- Reverse stitching
- Safety clutch prevents the hooks from being damaged
- Compound feed mechanism assures even feeding of material

SPECIFICATIONS

Model 329RB-1

Speed, Max. (S.P.M.) *	2400*
Clearance Under Foot	11/32" (8.5 mm)
Needle Bar Stroke	1-1/4" (32 mm)
Stitch Length, Max.	5 s.p.i. (5 mm)
Needle	135 x 17
Bobbin	Metal 16408
	Pre-wound U
Hook	14005
Bed Size	7" dia x 20 3/8" (177 mm x 518mm)
Work Space	2 1/8" x 2" (54 x 50 mm)
Post Height	7" (178mm)
Stitch Type	301
Needle gauges available	1/8" - 3/4" (3.2 - 19mm)

(* Speed depends on operation, material and thread.)

Specifications subject to change without notice.

©2007 Consew USA -107