

CONSEW Since 1898

MODELS


3321/3322/3323
3324/3325/3326

LONGER STITCH


Available: "S" Series
2-1/2 S.P.I. (10mm)

WITH
FULLY AUTOMATIC LUBRICATION
SIMPLIFIED LOOPER THROW-OUT
SAFETY BALANCE WHEEL

**MODELS 3321P/3322P/
3323P/3324P/3325P/3326P**
Equipped with
Puller Feed Device



Model 3324P



Model 3324

**ALSO AVAILABLE:
3400 SERIES
CYLINDER BED
MACHINES**

HIGH SPEED
DROP FEED, NEEDLE FEED
(COMPOUND FEED)
WALKING PRESSER FEET
DOUBLE CHAINSTITCH MACHINES
1 - 2 - 3 - 4 - 5 - 6 NEEDLE VARIETIES

Models 3321/3322/3323/3324/3325/3326

APPLICATIONS

- For sewing medium to heavy weight fabrics such as vinyl, leather, canvas, denim, synthetics and various coated and laminated materials
- Suitable, for stitching operations on such products as awnings, tents, tarpaulins, auto, marine and furniture- upholstery, auto interiors, auto tops, handbags, luggage, belts, curtains, draperies, bed spreads, blankets, bathing trunks, boxer shorts, trousers, uniforms, walking shorts, jackets, work clothes, slippers, women's shoes, canvas shoes, sports equipment, carpets, mattresses, mattress pads, gloves and numerous other articles
- Machines can be used for seaming, binding, welting, banding, bibbing, lap seam felling and taping with appropriate attachments

FEATURES

- Fully automatic lubrication with recirculating pump
- Simplified looper throw-out
- Easy accessibility for threading loopers
- Compound feed, walking foot mechanism ensures even feeding of article being sewn
- No bobbin winding or changing
- Attachments easily installed
- Stitches per minute – 4000*
- Special order up to 25" long arm

CONFIGURATIONS

Number of Needles	Model	Model with Puller	Special Large-Stitch Model
Single	3321	3321P	3321S
Two	3322	3322P	3322S
Three	3323	3323P	3322S
Four	3324	3324P	3324S
Five	3325	3325P	3325S

SPECIFICATIONS

Speed, Max. (S.P.M.)* Without Puller	4000	(S Series)
With Puller	3000	2500
Clearance Under Foot	5/16" (8mm)	5/16" (8mm)
Needle Bar Stroke	1-11/32" (34 mm)	1-11/32" (34 mm)
Stitch Length, Max.	3 s.p.i. (8.5 mm)	2-1/2 s.p.i. (10 mm)
Needle	62 x 59	62 x 59
* Speed depends on thread, material and operation.		

Looper	20301
Bed Size	7" x 20-3/8" (177 x 518 mm)
Work Space	10-5/8" (270 mm)
Needle Distances	3/16" (4.7 mm) – 2" (50.8 mm)
Stitch Type	401

Specifications subject to change without notice.

©2007 Consew USA -307



CONSOLIDATED SEWING MACHINE CORP.

INDUSTRIAL SEWING & CUTTING EQUIPMENT

NEW YORK • MIAMI • LOS ANGELES • JAPAN