

CONSEW 333RB-3



OVERVIEW

High Speed, Two Needle, Drop Feed, Needle Feed, Lockstitch Machine

With: Centra-Lube® Semi-Automatic Lubrication System, Large Vertical Axis Hooks and Bobbins, Reverse Feed, Safety Clutch

APPLICATIONS

- Designed for stitching medium to medium-heavy weight fabrics, leather, canvas, vinyl, synthetics and various laminated and coated materials
- Suitable for sewing auto, boat and furniture upholstery, boat covers, sails, awnings, tents, light tarpaulins, camping equipment, cot and beach chair covers, slip covers, draperies, mattress binding, luggage, travel ware accessories, wearing apparel, coats, work clothes, foundation garments, etc.
- Designed for stitching reinforced and parallel stitches
- Suitable for such operations as attaching zippers, lap seam felling, staying shoe linings, and general double needle seaming, binding, taping and piping

FEATURES

- Large vertical axis hooks and bobbins assures longer operation between bobbin changes
- The compound feed mechanism assures perfect and uniform stitching and eliminates slippage
- Centra-Lube® semi-automatic lubrication system
- Automatic hook lubrication
- Oil fed take-up
- Reverse stitching - Models 333RB-3 /333RBL-25
- Large range of gauge sets available
- Safety clutch prevents the hooks from being damaged
- Synchronized puller available (add suffix -P)
- 333RB-3: Large hooks and bobbins and reverse feed
- 333RBL-25: Large hooks and bobbins, reverse feed and LONG ARM

SPECIFICATIONS

Number of Needles	2 (Double)
Feeding Mechanism	Needle Feed
Workspace	Standard Workspace
Standard or Full Function	Standard Functions
Speed, Max (S.P.M.)	2800
Clearance Under Presser Foot	2 1/64" (8.5mm)
Stitch Length	4 s.p.i. (6.5mm)
Work Space	10" (254mm)
Needle	135 x 17
Bobbin	Pre-Wound S or U
Bed Size	7" 20-3/8" (177mm x 518mm)
Stitch Type	301
Needle Bar Stroke	1 5/16" (33mm)
Available Needle Spacings	1/16" (1.6mm) - 1 1/2" (38.1mm)
Standard Needle Spacing	1/4" (6.4mm)
Hook	15502

**CONTACT:
TEAMWORKSALES INC.
3363 E. 15TH STREET
LOS ANGELES CA. 90023
P: 818 919-9009**