

**CONSEW** Since 1898

# MODELS 339RB-3 / 339RBL-25


**FLAT BED**

WITH  
CENTRA-LUBE®  
SEMI-AUTOMATIC LUBRICATION SYSTEM  
LARGE VERTICAL AXIS HOOKS AND BOBBINS  
REVERSE FEED  
SAFETY CLUTCH

**DOUBLE NEEDLE**



**LARGE BOBBIN**




Top Load Hook



339RB-3

Built-in bobbin winder



339RBL-25

Added Arm Support

640mm (25")

**HEAVY DUTY  
HIGH SPEED  
TWO NEEDLE  
LOCKSTITCH MACHINE**

*DROP FEED, NEEDLE FEED and  
ALTERNATING (WALKING) PRESSER FEET*


**Models 339RB-3 / 339RBL-25**

**APPLICATIONS**

- For sewing light to heavy-weight materials such as leather, vinyl, upholstery, synthetics, canvas, vinyl and various coated and laminated products
- Designed for stitching such products as auto, boat and furniture upholstery, tarpaulins, covers, sails, tents, camping trailer covers, awnings, umbrellas, tops, bags, luggage, handbags, travelware accessories, sports and camping equipment, wearing apparel, outdoor clothing, canvas shoes, slippers, orthopedic appliances, etc.
- Suitable for double needle seaming, binding, taping and piping operations

**FEATURES**

- Two needle mechanism readily makes two parallel lines of stitches
- Compound feed, walking foot mechanism insures even feeding of material
- Large hooks and bobbins assures longer operation between bobbin changes
- Centra-Lube® semi-automatic lubrication system
- Automatic hook lubrication
- Oil fed take-up
- Simple adjustment permits raising and lowering of the center foot which allows for sewing different thicknesses of material
- Safety clutch protects the hooks from being damaged
- Various needle gauges available
- Synchronized puller available (add suffix -P)



**339RB-3** – Large hooks and bobbins and reverse feed / Long Stitch – 2½ S.P.I.  
**339RBL-25** – Large hooks and bobbins, reverse feed and LONG ARM/Long Stitch – 2½ S.P.I.  
**339RBL-USA** – Special order, custom made in USA, up to 30" LONG ARM

**SPECIFICATIONS**

Speed, Max. (S.P.M.) *339RB-3	3000
339RBL-25	2400
Clearance Under Foot	9/16" (14mm)
Needle Bar Stroke	1-5/16" (33 mm)
Stitch Length, Max.	339RB-3 4 s.p.i. (6.5 mm)
339RBL-25	4 s.p.i. (6.5 mm)
Needle	135 x 17
Bobbin	Metal 15041
	Pre-wound S or U

Hook	15502
Bed Size	339RB-3 7" x 20-3/8" (177 x 518 mm)
339RBL-25	7" x 28-1/4" (177 x 718 mm)
Work Space	339RB-3 10" (258mm)
339RBL-25	25" (640 mm)
Standard Needle Spacing	1/4" (6.4 mm)
Available Needle Spacings	1/8" (3.2mm) – 1-1/2" (38.1mm)
Stitch Type	301
* Speed depends on operation, material and thread	

Specifications subject to change without notice.