

**CONSEW** Since 1898

# Model 3421UX-1

(same as 300UX5)

**TAPE EDGE  
CHAINSTITCH MACHINE**

**CHAINSTITCH**

High Speed, Heavy Duty  
Single Needle, Two Thread  
Drop Feed, Needle Feed  
(Compound Feed)  
Alternating Presser Feet  
Double Chainstitch Machine  
with  
Semi-Automatic Lubrication



## APPLICATIONS

- Tape Edge on mattress, etc.

## FEATURES

- Semi-automatic lubrication system.
- Compound feed and pneumatic alternating pressers assures equal pressure when sewing varying thicknesses of material
- Designed to run with a lower noise level

## SPECIFICATIONS 3421UX-1

Speed, Max. (S.P.M.)	3000*
Clearance Under Foot	7/16" (11mm)
Needle Bar Stroke	1-7/16" (36.5 mm)
Stitch Length, Max.	3 s.p.i. (7.6 mm)
Needle	62x59
Needle to left side of bed	slightly more than 1/4" (6.9 mm)
Room on right side of needle	10" (254 mm)
Stitch Type	401

\* Speed depends on thread, material and operation.


Since 1898  
**CONSEW**

# Model 3321-194

(same as 300U194A)

## CHAINSTITCH MACHINE

High Speed, Heavy Duty  
Single Needle, Two Thread  
Drop Feed, Needle Feed  
(Compound Feed)  
Alternating Presser Feet  
Double Chainstitch Machine  
With Semi-Automatic Lubrication  
Positive In-Line Looper System



### APPLICATIONS

- Binding, welting and seaming. Automobile upholstery, work gloves, luggage, canvas shoes, etc.

### FEATURES

- Semi-automatic lubrication system.
- Compound feed and pneumatic alternating pressers assures equal pressure when sewing varying thicknesses of material
- Machine fitted with anti-reversing device to minimize skip stitching when crossing extra heavy seams.
- Designed to run with a lower noise level
- Positive in-line looper system

### SPECIFICATIONS 3321-194

Speed, Max. (S.P.M.)	4000 *
Clearance Under Foot	7/16" (11mm)
Needle Bar Stroke	1-7/16" (36.5 mm)
Stitch Length, Max.	3 s.p.i. (7.6 mm)
Needle	62x59
Looper	K281208
Work Space	10-5/8" (270 mm)
Bed Size	7" x 20-3/8" (177 x 518 mm)
Stitch Type	401

\* Speed depends on thread, material and operation.