### LONSEV 8

### Model CP146R

## PORTABLE, WALKING FOOT, ZIG-ZAG MACHINE

Single Needle, Drop Feed,
Walking Foot, Zig-Zag,
Lockstitch Machine with
Horizontal Oscillating Hook
Reverse Stitching
Built-in 110vac Motor
Link type thread take-up lever
Foot Pedal & Carrying Case



### PORTABLE WALKING FOOT MACHINE


Single Needle, Drop Feed Walking foot Lockstitch Machine with

Horizontal Oscillating Hook Reverse Stitching

Built-in 110vac Motor

Link type thread take-up lever Foot Pedal & Carrying Case






- For sewing elastic and other stretch materials and on such materials as canvas, nylon, vinyl, leather, synthetics and similar materials.
- For such materials and products as wet suits, shoes, boots, leather, tarpaulins.
- For stitching such products as boat and truck covers, tents, awnings, sails, parachutes, tarpaulins wet suits, leather, shoes, boots and similar products
- · Use where reinforced Zig-Zag stitch is necessary.







 Designed for stitching such products as auto, boat and furniture upholstery, tarpaulins, covers, sails, tents, camping trailer covers, awnings, umbrellas, tops, bags, luggage, handbags, travelware accessories, sports and camping equipment, wearing apparel, outdoor clothing, canvas shoes, slippers, orthopedic appliances etc.

#### **SPECIFICATIONS**

Speed, Max. spm: 800\* Stitch Length, Max: 6 mm

Max. Zig-Zag Width: 5 mm (13/64") Needle Bar Stroke: 34 mm Needle: DP x 17 18-23

Motor: 1/10th HP, 110 vac, 1.5 amp Bed Size: 14-1/2" x 7" Underarm Space: 7" x 4-1/2" Net Weight: 19 kg (42 lbs.)

Stitch Type: 304

Comes with Deluxe Foot Control



Comes with hard plastic carrying case. (20.75" x 13.5" x 10")

#### **SPECIFICATIONS**

Speed, Max. spm: 800\* Stitch Length, Max: 6 mm Needle Bar Stroke: 30 mm Needle: DP x 17 18-23

Motor: 1/10th HP, 110 vac, 1.5 amp Bed Size: 14-1/2" x 7"

Underarm Space: 7" x 4-1/2" Net Weight: 18.6 kg (41 lbs)

# MODEL 75T

ALL PURPOSE, PORTABLE, SINGLE THREAD, CHAINSTITCH, BLINDSTITCH MACHINE

#### with

SKIP AND NON-SKIP STITCH LEVER ADJUSTABLE THREAD TENSION
1 to 1 NON-SKIP STITCH AND

2 to 1 SKIP STITCH

#### Plus...

Stitch penetration and stitch length adjustment dials give you big-machine features in a light-weight, compact and fully portable unit

Featuring
SWING-DOWN
CYLINDER ARM
with
METAL SWING PLATE

Standard 110V. Motor and Foot Control Included

**SPECIFICATIONS** 

Stitch Type

Table clamp included



Speed, Max. (S.P.M.)	1000 *
Stitch Length, Max.	3 <sup>1</sup> / <sub>2</sub> s.p.i. (7mm)
Needle Style	LWX 6T
Looper	471
Cylinder Diameter	15/8" (40 mm)

\* Speed depends on materials, operation and thread

103

Work Space (Needle to Arm) 4" (100 mm)

Ideal for alteration rooms, tailors, clothing rentals, dry cleaners, department stores, dressmakers and home use

Perfect or sewing all weights of materials including synthetics, woolens, cottons, fabrics and knits

- 1 to 1 non-skip stitches, typical operations include felling edge tapes, bottoms of trousers, cuffs, wigging in sleeves, facings to canvas and knit goods, turnedup bottoms of fully lined coats, padding collars and lapels, and reinforcing trouser seats
- 2 to 1 skip stitch for hemming dresses, skirts, slacks, trousers, sportswear, ladies coats, draperies, blouses and other articles

Suitable for felling operations requiring a skip stitch to simulate hand-stitching

2 to 1 skip stitch is recommended for synthetics and other lightweight materials and 1 to 1 for heavier cotton, woolen and linen goods

Specifications subject to change without notice.

©2007 Consew USA -307

