


CONSEW Since 1898

Model TE-6

(Roller Presser Foot Available)


WITH
LONG BEAK SHUTTLE



SINGLE NEEDLE
CYLINDER ARM
DROP FEED
LOCKSTITCH
MACHINE

Model TF-6

WITH
LONG BEAK SHUTTLE
ROLLER PRESSER FOOT
LEFT HANDED ARM & BED



SINGLE NEEDLE
CYLINDER ARM
DROP FEED
LOCKSTITCH
MACHINE

CYLINDER ARM

Model TE-6

RIGHT HAND

APPLICATIONS

- This machine is specially designed for hollow and uneven work on light to medium duty material
- Suitable for sewing such products as leather or vinyl bags, pouches, suitcases, purses, briefcases, various sports equipment and other curved work

FEATURES

- Cylinder arm
- Stitches per minute – 1400
- Long Beak Shuttle
- Roller Presser Foot available

SPECIFICATIONS

Speed, Max. (S.P.M.)	1400*
Clearance Under Foot	9/32" (7mm)
Needle Bar Stroke	1 27/64" (36 mm)
Stitch Length, Max.	5 s.p.i. (5 mm)
Needle	16 x 231
Bobbin	Metal 8096
	Pre-wound I
Hook	8028
Cylinder Bed Length	10 1/2" (266 mm)
Stitch Type	301

* Speed depends on materials, thread and operation

Model TF-6

LEFT HAND

APPLICATIONS

- This left hand design facilitates special purpose applications that a standard right hand machine will not do
- Specially designed for stitching shoe upper leather as well as stitching other varieties of uneven work
- Suitable for stitching light to medium weight materials
- For sewing such products as leather or vinyl bags, pouches, suitcases, purses, briefcases, various sports equipment, etc.

FEATURES

- Cylinder arm
- Stitches per minute - 1800
- Roller presser foot

SPECIFICATIONS

Speed, Max. (S.P.M.)	1800*
Clearance Under Foot	9/32" (7mm)
Needle Bar Stroke	1 27/64" (36 mm)
Stitch Length, Max.	5 s.p.i. (5 mm)
Needle	16 x 2
Bobbin	Metal 8096
	Pre-wound I
Hook	8028
Cylinder Bed Length	10 1/2" (266 mm)
Cylinder Bed	1 7/8" (48mm) dia.
Stitch Type	301

* Speed depends on materials, thread and operation

CYLINDER ARM