

# MSDS *Material Safety Data Sheet*

The Penray Companies Inc



## PENRAY FUEL PREP DIESEL FUEL CONDITIONER 100032

MSDS Number: 100032

Revision Date: 06/01/12

Page 1 of 5

1

### PRODUCT AND COMPANY IDENTIFICATION

**Manufacturer**

The Penray Companies, Inc.  
440 Denniston Ct.  
Wheeling, IL 60090

**Contact:** EH&S Manager  
**Phone:** 847-459-5000  
**Fax:** 847-459-5043  
**Web:** www.penray.com

**Product Name:** PENRAY FUEL PREP DIESEL FUEL CONDITIONER 100032  
**Revision Date:** 06/01/12  
**Version:** 1  
**MSDS Number:** 100032  
**Common Name:** FUEL ADDITIVE PRODUCT CONTAINING KEROSENE

EMERGENCY PHONE NUMBER (800) 752-7869

NFPA 704M RATING :

HEALTH:1 FIRE:2 REACTIVITY:0 SPECIAL:

O=INSIGNIFICANT 1=SLIGHT 2=MODERATE 3=HIGH 4=EXTREME

2

### HAZARDS IDENTIFICATION

**Route of Entry:** Skin absorption, Eye Contact, Inhalation, Ingestion

**Target Organs:** Not given

**Inhalation:** Respiratory irritation and dizziness

**Skin Contact:** Prolonged contact with skin can cause irritation. Repeated skin contact may cause persistent irritation and dermatitis

**Eye Contact:** Will cause irritation upon contact.

**Ingestion:** Product may cause discomfort, nausea, vomiting and diarrhea.

CARCINOGENICITY: Product is not considered a carcinogen by OSHA, NTP or IARC

MEDICAL CONDITIONS: Pre-existing eye or skin conditions may be aggravated by over-exposure to this product.

CHRONIC HEALTH EFFECTS: Overexposure to the ingredients in this product may cause liver abnormalities and kidney damage

## PENRAY FUEL PREP DIESEL FUEL CONDITIONER 100032

MSDS Number: 100032

Revision Date: 06/01/12

Page 2 of 5

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

#### Ingredients:

INGREDIENT	CAS NUMBER	PERCENT WEIGHT
KEROSENE	8008-20-6	93%-97%
SOLVENT NAPHTHA, LIGHT AROMATIC	64742-95-6	.01%-02%
SOLVENT NAPHTHA, HEAVY AROMATIC	64742-94-5	.01%-02%
BENZENE, 1, 2, 4-TRIMETHYL	95-63-6	.01%-02%
2-ETHYL HEXANOL	100-76-7	.01%-02%
Benzene, 1, 3, 5 TRIMETHYL	108-67-8	.01%-02%
N-PROPYLBENZENE	103-65-1	.01%-02%
NAPHTHALENE	91-20-3	.01%-02%
XYLENE	1330-20-7	.01%-02%
CUMENE	98-82-8	.01%-02%

### 4 FIRST AID MEASURES

- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. Seek medical attention. Inhalation hazard unlikely due to low volatility of product.
- Skin Contact:** Wash area with soap and water. seek medical attention if irritation persists
- Eye Contact:** Immediately flush eyes with plenty of water for 15 minutes. Seek medical attention.
- Ingestion:** DO NOT induce vomiting. Only give CONSCIOUS victim two glasses of water and seek medical attention. NEVER give UNCONSCIOUS anything by mouth.

### 5 FIRE FIGHTING MEASURES

**Flash Point:** 104-111 F  
**Flash Point Method:** TCC

**EXTINGUISHING MEDIA:** Carbon Dioxide ( CO2) Dry Chemical, Foam.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Vapors are heavier than air and can collect in low areas

**FIRE FIGHTING INSTRUCTIONS:** Containers can build up pressure if exposed to fire. Containers should be cooled with water supply.

**FIRE FIGHTING EQUIPMENT:** Self- contained breathing apparatus with full face piece operated in positive pressure mode.

### 6 ACCIDENTAL RELEASE MEASURES

**SPILL/LEAK PROCEDURES:** Notify safety personnel ,evacuate all unnecessary personnel and provide adequate ventilation. If feasible, and without risk, clean-up personnel should stop leak. All clean up personnel should wear proper personal protective equipment.

**SMALL SPILLS:** Clean with inert absorbent and place in recovery drums for disposal.

**LARGE SPILLS:** Dike to prevent further migration of material. DO NOT release into waterways or sewers. Follow applicable federal and state regulations.

## PENRAY FUEL PREP DIESEL FUEL CONDITIONER 100032

MSDS Number: 100032

Revision Date: 06/01/12

Page 3 of 5

### 7 HANDLING AND STORAGE

- Handling Precautions:** Wash thoroughly after handling. Do not get into eyes, on skin or on clothing. Do not smoke while using this product. Do not use near excessive heat, sparks, or open flame.
- Storage Requirements:** Store in clean, dry locations away from excessive heat. Store in areas designated for the storage of flammable liquids according to NFPA 30 ( Flammable and Combustible Liquids Code)

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering Controls:** Eye wash station and safety shower.  
General ventilation. Material non - volatile
- Personal Protective Equip:** EYE: Chemical splash goggles with indirect or no ventilation.  
SKIN :Chemical resistant gloves, such as nitrile.  
RESPIRATORY: Organic vapor air purifying respirator if vapors are a nuisance or if the concentrations are above PEL or TLV.

Never eat, drink or smoke in work area

### 9 PHYSICAL AND CHEMICAL PROPERTIES

- |                            |                 |                       |                      |
|----------------------------|-----------------|-----------------------|----------------------|
| <b>Appearance:</b>         | amber colored   | <b>Odor:</b>          | petroleum distillate |
| <b>Physical State:</b>     | liquid          | <b>Solubility:</b>    | Not soluble in water |
| <b>Spec Grav./Density:</b> | BT 0..81 - 0.91 | <b>Vapor Density:</b> | >1                   |
| <b>Boiling Point:</b>      | BT >320 F       | <b>VOC:</b>           | 100                  |
| <b>Vapor Pressure:</b>     | <5.0 mmHG       |                       |                      |
| <b>Evap. Rate:</b>         | >1.0            |                       |                      |

### 10 STABILITY AND REACTIVITY

- Stability:** Material is stable.
- Conditions to Avoid:** Excessive heat and open flame.
- Materials to Avoid:** Strong oxidizing agents.
- Hazardous Decomposition:** Carbon Monoxide and Carbon Dioxide
- Hazardous Polymerization:** Cannot occur.

# MSDS *Material Safety Data Sheet*

The Penray Companies Inc



## PENRAY FUEL PREP DIESEL FUEL CONDITIONER 100032

MSDS Number: 100032

Revision Date: 06/01/12

Page 4 of 5

11

### TOXICOLOGICAL INFORMATION

LD50

KEROSENE 28 ml/kg (oral)  
XYLENE: 7.53 g/kg (oral)

12

### ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

ENVIRONMENTAL FATE: This product contains components which may be persistent in the environment.

13

### DISPOSAL CONSIDERATIONS

As a waste, this product in its raw form DOES MEET the criteria of a hazardous waste as defined by RCRA (40CFR361). Dispose of in accordance with all applicable state, federal and local regulations.

14

### TRANSPORT INFORMATION

DOMESTIC:  
CONSUMER COMMODITY ORM-D

EXPORT:  
PETROLEUM DISTILLATES, N.O.S. (KEROSENE), CLASS 3, UN 1268, PGIII,  
FP 40 DEGREES Ccc., LIMITED QUANTITY

## PENRAY FUEL PREP DIESEL FUEL CONDITIONER 100032

MSDS Number: 100032

Revision Date: 06/01/12

Page 5 of 5

15

### REGULATORY INFORMATION

#### U.S. FEDERAL REGULATIONS

OSHA: Considered to be a hazardous material as defined by 29CFR1910.1200

#### EPA SARA TITLE III

Section 311-312 (40CFR370): If stored in excess of the threshold quantities, this product should be reported as a(n):

IMMEDIATE (acute) HEALTH HAZARD

DELAYED (chronic) HEALTH HAZARD

FIRE HAZARD

Section 313(40CFR372) This product contains ingredients which are subject to the reporting requirements of SARA 313:

Trimethylbenzene 0.750%

Naphthalene 0.125%

Xylene 0.125%

Cumene 0.125%

Benzo[a]pyrene 0.0125%

16

### OTHER INFORMATION

CALIFORNIA PROPOSITION 65: This product does contain ingredients for which the state of California has found to cause cancer, birth defects, or other reproductive harm.

Benzene

Naphthalene

Benzo[a]pyrene

Ethylbenzene

#### Notes:

NG= NOT GIVEN

BT= BETWEEN

<= LESS THAN

>= GREATER THAN

USERS RESPONSIBILITY; This MSDS provides environmental, health and safety information. This product is to be used in applications consistent with our product literature and container label. Individuals handling this product should be informed to the recommended safety precautions and have access to this MSDS. Please contact your local sales representative or our EH&S Department for further information.

END OF MSDS