Permatex.

SAFETY DATA SHEET

Revision Date 18-Apr-2016 Version 3

1. IDENTIFICATION

Product identifier

Product Name 14AR THREAD SEALANT W/PTFE 1 OZ.

Other means of identification

Product Code 80631 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address Distributor

ITW Permatex Canada
6875 Parkland Blvd. 35 Brownridge Road, Unit 1
Solon, OH 44139 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Danger

Harmful if swallowed May cause cancer Causes damage to organs Flammable liquid and vapor



Appearance White Physical state Paste Odor Alcoholic

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician

Specific treatment (see supplemental first aid instructions on this label)

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

In case of fire: Use Water spray, fog or regular foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

Unknown acute toxicity

65.99515 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
ETHANOL	64-17-5	10 - 30	*
2-PROPANOL	67-63-0	1 - 5	*
METHANOL	67-56-1	1 - 5	*
METHYL ISOBUTYL KETONE	108-10-1	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Revision Date 18-Apr-2016

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Wash with soap and water. If symptoms persist, call a physician.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required. Ensure

adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or clothing.

Wash thoroughly after handling.

Environmental precautions

Environmental precautionsDo not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). Store locked up.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ETHANOL	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m ³
		(vacated) TWA: 1900 mg/m ³	
2-PROPANOL	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	
METHANOL	STEL: 250 ppm	TWA: 200 ppm	IDLH: 6000 ppm
67-56-1	TWA: 200 ppm	TWA: 260 mg/m ³	TWA: 200 ppm
	S*	(vacated) TWA: 200 ppm	TWA: 260 mg/m ³
		(vacated) TWA: 260 mg/m ³	STEL: 250 ppm
		(vacated) STEL: 250 ppm	STEL: 325 mg/m ³
		(vacated) STEL: 325 mg/m ³	
		(vacated) S*	
METHYL ISOBUTYL KETONE	STEL: 75 ppm	TWA: 100 ppm	IDLH: 500 ppm
108-10-1	TWA: 20 ppm	TWA: 410 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 205 mg/m ³
		(vacated) TWA: 205 mg/m ³	STEL: 75 ppm
		(vacated) STEL: 75 ppm	STEL: 300 mg/m ³
		(vacated) STEL: 300 mg/m ³	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protectionUse NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Paste
Appearance White
Odor Alcoholic

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point / freezing point No information available

Boiling point / boiling range 82 °C / 180 °F

Flash point $25 \, ^{\circ}\text{C} \, / \, 77 \, ^{\circ}\text{F}$ Tag Closed Cup Evaporation rate < 1 Butyl acetate = 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: 12.7% Lower flammability limit: 2.3%

Vapor pressure 33 mm Hg @ 68°F

Vapor density 33 mm Hg @ 66 F

Relative density 1.06-1.10
Water solubility Partially soluble

No information available Solubility in other solvents Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available Oxidizing properties No information available

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) 29.5%%

Density No information available Bulk density No information available

10. STABILITY AND REACTIVITY

Air = 1

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides Fluorides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ETHANOL	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
64-17-5			
2-PROPANOL	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
67-63-0			
METHANOL	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 64000
67-56-1			ppm (Rat)4h
METHYL ISOBUTYL KETONE	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h
108-10-1			

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicityNo information available.
No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
ETHANOL	A3	Group 1	Known	X
64-17-5				
METHYL ISOBUTYL	A3	Group 2B	-	X
KETONE		-		
108-10-1				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans Not classifiable as a human carcinogen NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity May cause adverse effects on the bone marrow and blood-forming system. May cause

adverse liver effects. Contains a known or suspected reproductive toxin.

Target Organ Effects Blood, Central nervous system, Central Vascular System (CVS), Eyes, Gastrointestinal

tract (GI), Liver, Reproductive System, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1811 mg/kg
ATEmix (dermal) 6521 mg/kg
ATEmix (inhalation-dust/mist) 11.7 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

35.44605 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
ETHANOL	-	12.0 - 16.0: 96 h Oncorhynchus	9268 - 14221: 48 h Daphnia magna
64-17-5		mykiss mL/L LC50 static 100: 96 h	mg/L LC50 2: 48 h Daphnia magna
		Pimephales promelas mg/L LC50	mg/L EC50 Static 10800: 24 h
		static 13400 - 15100: 96 h	Daphnia magna mg/L EC50
		Pimephales promelas mg/L LC50	
		flow-through	
2-PROPANOL	1000: 96 h Desmodesmus	9640: 96 h Pimephales promelas	13299: 48 h Daphnia magna mg/L
67-63-0	subspicatus mg/L EC50 1000: 72 h	mg/L LC50 flow-through 11130: 96	EC50
	Desmodesmus subspicatus mg/L	h Pimephales promelas mg/L LC50	
	EC50	static 1400000: 96 h Lepomis	
		macrochirus µg/L LC50	
METHANOL	-	28200: 96 h Pimephales promelas	-
67-56-1		mg/L LC50 flow-through 100: 96 h	
		Pimephales promelas mg/L LC50	
		static 19500 - 20700: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		flow-through 13500 - 17600: 96 h	
		Lepomis macrochirus mg/L LC50	
		flow-through 18 - 20: 96 h	
		Oncorhynchus mykiss mL/L LC50	
145717/1/10001/77/1/1/5701/5		static	
METHYL ISOBUTYL KETONE	400: 96 h Pseudokirchneriella	496 - 514: 96 h Pimephales	170: 48 h Daphnia magna mg/L
108-10-1	subcapitata mg/L EC50	promelas mg/L LC50 flow-through	EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
ETHANOL 64-17-5	-0.32
2-PROPANOL 67-63-0	0.05
METHANOL 67-56-1	-0.77
METHYL ISOBUTYL KETONE 108-10-1	1.19

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHANOL	-	Included in waste stream:	-	U154

80631 - 14AR THREAD SEALANT W/PTFE 1 OZ.

67-56-1		F039		
METHYL ISOBUTYL KETONE 108-10-1	-	Included in waste stream: F039	-	U161

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
ETHANOL	Toxic	
64-17-5	Ignitable	
2-PROPANOL	Toxic	
67-63-0	Ignitable	
METHANOL	Toxic	
67-56-1	Ignitable	

14. TRANSPORT INFORMATION

DOT

UN/ID no 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group III
Emergency Response Guide 128

Number

IATA

UN/ID no ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

IMDG

UN/ID no 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group III
EmS-No F-E, S-D

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies Not Listed. **EINECS/ELINCS ENCS** Not Listed. **IECSC** Complies Complies **KECL PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0
METHANOL - 67-56-1	1.0

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHANOL	5000 lb	=	RQ 5000 lb final RQ
67-56-1			RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE	5000 lb	-	RQ 5000 lb final RQ
108-10-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
ETHANOL - 64-17-5	Carcinogen	
	Developmental	
TITANIUM DIOXIDE - 13463-67-7	Carcinogen	
METHANOL - 67-56-1	Developmental	
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen	
	Developmental	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
TALC	X	X	X
14807-96-6			
ETHANOL	X	X	X
64-17-5			
2-PROPANOL	X	X	X
67-63-0			
TITANIUM DIOXIDE	X	X	X
13463-67-7			
WATER	ı	-	X
7732-18-5			
METHANOL	X	X	X
67-56-1			
POLYTETRAFLUOROETHYLENE	-	-	X
9002-84-0			
METHYL ISOBUTYL KETONE	X	X	X
108-10-1			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 -

HMIS Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 18-Apr-2016

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet