

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Issue date: 11/1/2022 Revision date: 1/30/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Trade name : 2003, 22255 Long-Life Grease + MoS2

Product code :

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Lubricant
Restrictions on use : None known

1.3. Supplier

Liqui Moly GmbH Jerg-Wieland-Strasse 4 Ulm D-89081 Germany T +49 731 1420 0

info@liqui-moly.de - www.liqui-moly.us

1.4. Emergency telephone number

Emergency number : INFOTRAC

+1800 535 5053 (USA, Canada); +1352 323 3500 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labeling

No labeling applicable

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Highly refined mineral oil (C15-C50)	CAS-No.: Proprietary	80 – 100

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Name	Product identifier	%
Graphite	CAS-No.: 7782-42-5	2.5 – 5
Calcium Carbonate	CAS-No.: 1317-65-3	< 2.5
Naphthenic acids, zinc salts	CAS-No.: 12001-85-3	< 1

Full text of hazard classes and H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with mild soap and water.

First-aid measures after eye contact : Rinse eyes with water as a precaution. Get medical attention if irritation develops and persists.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : No adverse effects expected.

Inhalation : Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation.

Skin : Repeated or prolonged skin contact may cause dermatitis and defatting.

Eyes : May cause minor eye irritation. Ingestion : Abdominal pain. Diarrhoea.

Chronic symptoms : None known.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide. Unsuitable extinguishing media : Use of heavy stream of water may spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard : This product is not classified as flammable or combustible.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon oxides (CO, CO2). Fire will produce dense black smoke.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Cool down the containers exposed to heat with a water spray.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

1/30/2024 (Revision date) EN (English US) 2/9

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact

with eyes. Avoid repeated or prolonged skin contact.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

Incompatible materials : Strong oxidizers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Graphite (7782-42-5)			
USA - ACGIH - Occupational Exposure Limits			
Local name	Graphite (all forms excepte graphite fibers)		
ACGIH OEL TWA	2 mg/m³ (R - Respirable particulate matter)		
Remark (ACGIH)	TLV® Basis: Pneumoconiosis		
Regulatory reference ACGIH 2023			
USA - OSHA - Occupational Exposure Limits			
Local name Graphite (Natural)			
OSHA PEL (TWA)	15 mppcf		
Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.		
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts		
Calcium Carbonate (1317-65-3)			
USA - OSHA - Occupational Exposure Limits			
Local name Calcium Carbonate (Limestone; Marble)			
OSHA PEL (TWA)	15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)		
Regulatory reference (US-OSHA)	ory reference (US-OSHA) OSHA Annotated Table Z-1		

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Highly refined mineral oil (C15-C50) (Proprietary)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA 5 mg/m³ inhalable			
USA - OSHA - Occupational Exposure Limits			
OSHA PEL (TWA) 5 mg/m³			

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

In case of repeated or prolonged contact wear gloves. Consult supplier for specific recommendations.

Eye protection:

Not required for normal conditions of use

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance Paste. Gel. Color Black Odor Characteristic : No data available Odor threshold pН : No data available Melting point : No data available Freezing point : No data available Boiling point : No data available : > 150 °C (302F) Flash point Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapor pressure : No data available Relative vapor density at 20°C : No data available Relative density

Solubility : Insoluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosion limits : No data available

Explosive properties : None.

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Oxidizing properties : None.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Naphthenic acids, zinc salts (12001-85-3)		
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: other:, Guideline: other:, Guideline: other:	
LD50 dermal rabbit	> 2000 mg/kg Source: HSDB	

Skin corrosion/irritation : Not classified

Naphthenic acids, zinc salts (12001-85-3)		
	На	5 – 9 Source: HSDB

Serious eye damage/irritation : Not classified

Naphthenic acids, zinc salts (12001-85-3)	
рН	5 – 9 Source: HSDB
Respiratory or skin sensitization	Not classified

Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

Safety Data Sheet

Ingestion

Chronic symptoms

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

STOT-repeated exposure : Not classified **Graphite (7782-42-5)** 0.000279 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: NOAEC (inhalation,rat,dust/mist/fume,90 days) Aspiration hazard : Not classified Viscosity, kinematic : No data available Symptoms/effects : No adverse effects expected. Inhalation : Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation. Skin : Repeated or prolonged skin contact may cause dermatitis and defatting. Eves : May cause minor eye irritation.

: Abdominal pain. Diarrhoea.

: None known.

SECTION 12: Ecological information

12.1. Toxicity	
3, 0	The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Graphite (7782-42-5)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna

EC50 72h - Algae [1]	19 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 72h - Algae [2]	7.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
NOEC (chronic)	47 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
Naphthenic acids, zinc salts (12001-85-3)		

LC50 - Fish [1]	> 100 mg/l Source: ECHA	
EC50 - Crustacea [1]	35 mg/l	
EC50 72h - Algae [1]	4 mg/l	

12.2. Persistence and degradability

2003, 22255 Long-Life Grease + MoS2			
Persistence and degradability	Rapidly degradable		
Graphite (7782-42-5)			
Persistence and degradability	Rapidly degradable		
Calcium Carbonate			
Persistence and degradability	Rapidly degradable		
Highly refined mineral oil (C15-C50) (Proprietary)			
Persistence and degradability	Rapidly degradable		
Naphthenic acids, zinc salts (12001-85-3)			
Persistence and degradability	Not rapidly degradable		

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

12.3. Bioaccumulative potential

Naphthenic acids, zinc salts (12001-85-3)

Partition coefficient n-octanol/water (Log Pow) 0.8 Source: ECHA

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

: Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA		
14.1. UN number	14.1. UN number				
Not regulated for transport					
14.2. Proper Shipping Name					
Not regulated	Not regulated	Not regulated	Not regulated		
14.3. Transport hazard class(es	14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated		
14.4. Packing group					
Not regulated	Not regulated	Not regulated	Not regulated		
14.5. Environmental hazards					
Not regulated	Not regulated	Not regulated	Not regulated		
No supplementary information available					

14.6. Special precautions for user

DOT

Not regulated

TDO

Not regulated

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

SECTION 15: Regulatory information

15.1. US Federal regulations

2	2003	22255	Lond	ı-Life	Grease	÷	MoS ₂

SARA Section 311/312 Hazard Classes Refer to Section 2 for OSHA Hazard Classification.

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Graphite (7782-42-5)

Listed on the Canadian DSL (Domestic Substances List)

Calcium Carbonate

Listed on the Canadian NDSL (Non-Domestic Substances List)

Naphthenic acids, zinc salts (12001-85-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

2003, 22255 Long-Life Grease + MoS2

Listed on the Canadian DSL (Domestic Substances List)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Graphite(7782-42-5)	U.S New Jersey - Right to Know Hazardous Substance List
Calcium Carbonate(1317-65-3)	U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015) Revision date : 1/30/2024

Safety Data Sheet

Data sources

NFPA health hazard

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

RTECS, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB. : 0 - Materials that, under emergency conditions, would offer no hazard

: This safety data sheet was compiled with data and information from the following sources:

beyond that of ordinary combustible materials.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur. NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire

conditions.



Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.