
Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and

GHS

Printing date 1/15/2014

Revision: 1/15/2014



(Contd. of page 1)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and

GHS

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H227.

H227: Combustible Liquid. (General GHS and USA only)

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling: Kerosine (petroleum), hydrodesulfurized naphthalene Hazard statements H351 Suspected of causing cancer. H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects. Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. Read label before use. P103 Use personal protective equipment as required. P281 P264 Wash thoroughly after handling. Avoid breathing mist/vapours/sprav. P261 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301+P310 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. P308+P313 P331 Do NOT induce vomiting. P302+P352 IF ON SKIN: Wash with plenty of soap and water. P403+P235 Store in a well-ventilated place. Keep cool. Hazard description: · WHMIS-symbols: B3 - Combustible liquid

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side D2A - Very toxic material causing other toxic effects

 \mathbf{O}

· NFPA ratings (scale 0 - 4)

220

Health = 2 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH *2	Health = *2
	Fire = 2
	Reactivity = 0
	•

* - Indicates a long term health hazard from repeated or prolonged exposures.

· HMIS Long	Term Health Hazard Substances
64742 04 5	Solvent perhthe (netroloum) heavy

64742-94-5 Solvent naphtha (petroleum), heavy arom.

91-20-3 naphthalene

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Mixtures
- \cdot **Description:** Mixture of substances listed below with nonhazardous additions.

CAS: 64742-81-0	Kerosine (petroleum), hydrodesulfurized	50-100%
EINECS: 265-184-9	🔀 Xn R65	
Index number: 649-423-0		
	🐼 Asp. Tox. 1, H304	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	<10%
EINECS: 265-199-0	🔀 Xn R65	
Index number: 649-356-0	0-4 Carc. Cat. 2	
	🚸 Asp. Tox. 1, H304	
CAS: 64742-94-5	Solvent naphtha (petroleum), heavy arom.	<10%
EINECS: 265-198-5	🔀 Xn R65	
Index number: 649-424-0	0-3 🐼 Asp. Tox. 1, H304	

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side

EINECS: 248-363-6 Xn R20/21/22; N R50 Aquatic Acute 1, H400; Aquatic Chronic 2, H411 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 CAS: 95-63-6 EINECS: 202-436-9 Index number: 601-043-00-3 Flam. Liq. 3, H226 Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 CAS: 91-20-3 EINECS: 202-049-5 Index number: 601-052-00-2		(Con	td. of page 3
EINECS: 202-436-9 Xn R20; Xi R36/37/38; N R51/53 Index number: 601-043-00-3 R10 Index number: 601-052-00-2 R10 Index number: 601-052-00-2 Index number: 601-052-00-2		Xn R20/21/22; BN R50 Quatic Acute 1, H400; Aquatic Chronic 2, H411	<10%
EINECS: 202-049-5 Index number: 601-052-00-2	EINECS: 202-436-9	Xn R20; Xi R36/37/38; N R51/53 R10 Flam. Liq. 3, H226 Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;	<10%
Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302	EINECS: 202-049-5	Xn R22-40; B N R50/53 Carc. Cat. 3 Carc. 2, H351 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<5,0%

4 First aid measures

- · 4.1 Description of first aid measures
- General information: Take affected persons out into the fresh air.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

· 4.2 Most important symptoms and effects, both acute and delayed

- Coughing
- Dizziness
- **Breathing difficulty**
- Nausea
- Cramp
- · Hazards
- Danger of pulmonary oedema.
- Danger of impaired breathing.
- Danger of convulsion.
- **4.3 Indication of any immediate medical attention and special treatment needed** If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

(Contd. on page 5)

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side

If necessary oxygen respiration treatment. Medical supervision for at least 48 hours. Later observation for pneumonia and pulmonary oedema.

5 Firefighting measures

· 5.1 Extinguishing media · Suitable extinguishing agents: Alcohol resistant foam Foam Fire-extinguishing powder Gaseous extinguishing agents Water haze or fog · For safety reasons unsuitable extinguishing agents: Water with full jet Water spray · 5.2 Special hazards arising from the substance or mixture In case of fire, the following can be released: Carbon monoxide (CO) Nitrogen oxides (NOx) Under certain fire conditions, traces of other toxic gases cannot be excluded. · 5.3 Advice for firefighters · Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information Cool endangered receptacles with water fog or haze.

6 Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Use respiratory protective device against the effects of fumes/dust/aerosol. Ensure adequate ventilation Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away. Particular danger of slipping on leaked/spilled product. 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. 	
	d. on page 6)

(Contd. of page 4)

(Contd. of page 5)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and

GHS

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side

See Section 13 for disposal information.

7 Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

· Requirements to be met by storerooms and receptacles: Store in a cool location. Avoid storage near extreme heat, ignition sources or open flame. Provide ventilation for receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs. Store away from oxidizing agents.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Store receptacle in a well ventilated area.
- · 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control p	parameters
· Ingredients w	vith limit values that require monitoring at the workplace:
64742-81-0 K	Cerosine (petroleum), hydrodesulfurized
REL (USA)	100 mg/m ³ Kerosene only
TLV (USA)	200 mg/m³ as total hydrocarbon vapor; Skin; P
EV (Canada)	200(G) mg/m³ as total hydrocarbon vapour, Skin
95-63-6 1,2,4	-trimethylbenzene
IOELV (EU)	100 mg/m³, 20 ppm
REL (USA)	125 mg/m³, 25 ppm
TLV (USA)	123 mg/m³, 25 ppm
91-20-3 naph	thalene
IOELV (EU)	30 mg/m ³ , 10 ppm
PEL (USA)	50 mg/m³, 10 ppm
	(Contd. on page 7)

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side

	(Contd. of page 6)
REL (USA)	Short-term value: 75 mg/m ³ , 15 ppm
	Long-term value: 50 mg/m ³ , 10 ppm
TLV (USA)	Short-term value: (79) mg/m ³ , (15) ppm
	Long-term value: (52) NIC-25 mg/m ³ , (10) NIC-5 ppm Skin; NIC-A3
EL (Canada)	
	Long-term value: 10 ppm
	Skin; IARC 2B
EV (Canada)	Short-term value: 78 mg/m ³ , 15 ppm
,	Long-term value: 52 mg/m ³ , 10 ppm
	urther relevant information available.
	urther relevant information available.
· Additional ir	nformation: The lists valid during the making were used as basis.
· 8.2 Exposur	e controls
	otective equipment:
	tective and hygienic measures:
	rom foodstuffs, beverages and feed.
	before breaks and at the end of work.
	e gases / fumes / aerosols. or long term contact with the skin.
	t with the eyes.
· Respiratory	
	respiratory protective device in case of insufficient ventilation.
Use suitable	respiratory protective device when aerosol or mist is formed.
	spiratory protection may be advisable.
 Protection o 	of hands:
Prote	ective gloves
Due to miss	aterial has to be impermeable and resistant to the product/ the substance/ the preparation. sing tests no recommendation to the glove material can be given for the product/ the the chemical mixture.
	the glove material on consideration of the penetration times, rates of diffusion and the
degradation.	
· Material of g	
	n of the suitable gloves does not only depend on the material, but also on further marks of
	varies from manufacturer to manufacturer. As the product is a preparation of several
	the resistance of the glove material can not be calculated in advance and has therefore to be
	r to the application. time of glove material
	eak through time has to be found out by the manufacturer of the protective gloves and has to
be observed.	
	(Contd. on page 8)

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side

(Contd. of page 7)

· Eye protection:

Contact lenses should not be worn.



Safety glasses

- · Body protection: Solvent resistant protective clothing
- · Limitation and supervision of exposure into the environment
- No further relevant information available.
- · Risk management measures

See Section 7 for additional information.

No further relevant information available.

9 Physical and chemical properties

• 9.1 Information on basic physical and	I chemical properties	
General Information Appearance:		
Form:	Liquid	
Colour:	Green	
· Odour:	Petroleum-like	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Not Determined.	
Boiling point/Boiling range:	> 199 ° F / > 92 °C	
· Flash point:	>140 ° F / > 60 °C	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not self-igniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapour pressure:	Not determined.	
· Density at 20 °C:	0,84 g/cm ³	
Relative density	Not determined.	
 Vapour density 	Not determined.	
 Evaporation rate 	Not determined.	
		(Contd. on page 9)

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side

		(Contd. of page
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octano	l/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	Not determined.	
Solids content:	Not determined.	
 9.2 Other information 	No further relevant information available.	

10 Stability and reactivity

- · 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

• **10.3 Possibility of hazardous reactions** Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised. Used empty containers may contain product gases which form explosive mixtures with air. Reacts with oxidizing agents.

- 10.4 Conditions to avoid Store away from oxidizing agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

Nitrogen oxides

(Contd. on page 10)

GHS

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side

(Contd. of page 9)

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful

Danger through skin adsorption.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

• Repeated dose toxicity: May cause damage to organs through prolonged or repeated exposure.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Carc. 2

12 Ecological information

· 12.1 Toxicity

· Aquatic toxicity: The material is harmful to the environment.

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential Does not accumulate in organisms.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark:
- Harmful to fish

Due to mechanical actions of the product (e.g. agglutinations) damages may occur.

The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.

- Additional ecological information:
- · General notes:

This statement was deduced from the properties of the single components.

Avoid transfer into the environment.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. Contact waste processors for recycling information.

(Contd. on page 11)

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side

(Contd. of page 10)

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
DOT, ADR, ADN, IMDG, IATA	Not Regulated	
14.2 UN proper shipping name		
DOT, ADR, ADN, IMDG, IATA	Not Regulated	
14.3 Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA		
Class	Not Regulated	
14.4 Packing group		
DOT, ADR, IMDG, IATA	Not Regulated	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Ann	ex II of	
MARPOL73/78 and the IBC Code	Not applicable.	

15 Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · United States (USA)

·SARA	
· Section 3	355 (extremely hazardous substances):
108-05-4	vinyl acetate
· Section 3	313 (Specific toxic chemical listings):
95-63-6	1,2,4-trimethylbenzene
91-20-3	naphthalene
108-05-4	vinyl acetate
· TSCA (To	oxic Substances Control Act):
All ingred	ients are listed.
· Propositi	ion 65 (California):
· Chemica	Is known to cause cancer:
91-20-3 r	naphthalene
<u>.</u>	(Contd. on page 12)

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side

	(Contd. of page
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
\cdot Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
\cdot Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic Categories	
· EPA (Environmental Protection Agency)	
91-20-3 naphthalene	CBI
 IARC (International Agency for Research on Cancer) 	
91-20-3 naphthalene	21
108-05-4 vinyl acetate	21
 TLV (Threshold Limit Value established by ACGIH) 	
64742-81-0 Kerosine (petroleum), hydrodesulfurized	A
91-20-3 naphthalene	A
108-05-4 vinyl acetate	A
\cdot NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
· Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
95-63-6 1,2,4-trimethylbenzene	
Canadian Ingredient Disclosure list (limit 1%)	
91-20-3 naphthalene	
· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been cal	rried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

(Contd. on page 13)

Printing date 1/15/2014

Revision: 1/15/2014

Trade name: Rislone® Diesel Treat Left Side

H335	May cause respiratory irritation. (Contd. of page
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
R10	Flammable.
R20	Harmful by inhalation.
R20/21/2 R22	2 Harmful by inhalation, in contact with skin and if swallowed. Harmful if swallowed.
	8 Irritating to eyes, respiratory system and skin.
R40	Limited evidence of a carcinogenic effect.
R50	Very toxic to aquatic organisms.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquat environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
	epartment of Transportation ational Air Transport Association
ACGIH: Am EINECS: E ELINCS: Eu CAS: Cherr NFPA: Nati HMIS: Hazz WHMIS: W DNEL: Deri PNEC: Preu LC50: Letha	Ational Air Transport Association Ally Harmonized System of Classification and Labelling of Chemicals erican Conference of Governmental Industrial Hygienists uropean Inventory of Existing Commercial Chemical Substances iropean List of Notified Chemical Substances ical Abstracts Service (division of the American Chemical Society) onal Fire Protection Association (USA) urdous Materials Identification System (USA) orkplace Hazardous Materials Information System (Canada) ved No-Effect Level (REACH) dicted No-Effect Concentration (REACH) al concentration, 50 percent
ACGIH: Am EINECS: E ELINCS: E CAS: Chem NFPA: Nati HMIS: Nati HMIS: W DNEL: Deri PNEC: Pree LC50: Letha LD50: Letha	Ational Air Transport Association Ally Harmonized System of Classification and Labelling of Chemicals erican Conference of Governmental Industrial Hygienists uropean Inventory of Existing Commercial Chemical Substances ical Abstracts Service (division of the American Chemical Society) onal Fire Protection Association (USA) urdous Materials Identification System (USA) orkplace Hazardous Materials Information System (Canada) ved No-Effect Level (REACH) dicted No-Effect Concentration (REACH)
ACGIH: Am EINECS: E ELINCS: Eu CAS: Cherr NFPA: Nati HMIS: Hazz WHMIS: W DNEL: Deri PNEC: Preu LC50: Letha LD50: Letha	Autional Air Transport Association Ally Harmonized System of Classification and Labelling of Chemicals erican Conference of Governmental Industrial Hygienists uropean Inventory of Existing Commercial Chemical Substances iropean List of Notified Chemical Substances ical Abstracts Service (division of the American Chemical Society) onal Fire Protection Association (USA) urdous Materials Identification System (USA) orkplace Hazardous Materials Information System (Canada) ved No-Effect Level (REACH) dicted No-Effect Concentration (REACH) al concentration, 50 percent
ACGIH: Am EINECS: E ELINCS: Eu CAS: Chem NFPA: Nati HMIS: Nati HMIS: W DNEL: Deri PNEC: Preu LC50: Letha LD50: Letha Sources SDS Preu	Autional Air Transport Association Ally Harmonized System of Classification and Labelling of Chemicals erican Conference of Governmental Industrial Hygienists uropean Inventory of Existing Commercial Chemical Substances iropean List of Notified Chemical Substances ical Abstracts Service (division of the American Chemical Society) onal Fire Protection Association (USA) urdous Materials Identification System (USA) orkplace Hazardous Materials Information System (Canada) ved No-Effect Level (REACH) dicted No-Effect Concentration (REACH) al concentration, 50 percent al dose, 50 percent
ACGIH: Am EINECS: E ELINCS: Eu CAS: Chem NFPA: Nati HMIS: Nati HMIS: W DNEL: Deri PNEC: Preu LC50: Letha LD50: Letha Sources SDS Prey ChemTel	Ational Air Transport Association Ally Harmonized System of Classification and Labelling of Chemicals erican Conference of Governmental Industrial Hygienists uropean Inventory of Existing Commercial Chemical Substances iropean List of Notified Chemical Substances ical Abstracts Service (division of the American Chemical Society) onal Fire Protection Association (USA) urdous Materials Identification System (USA) orkplace Hazardous Materials Information System (Canada) ved No-Effect Level (REACH) dicted No-Effect Concentration (REACH) al concentration, 50 percent al dose, 50 percent boared by: Inc.
ACGIH: Am EINECS: E ELINCS: Eu CAS: Chem NFPA: Nati HMIS: Haza WHMIS: W DNEL: Deri PNEC: Pree LC50: Letha LD50: Letha SOURCES SDS Prep Chem Tel 1305 Nor	Ational Air Transport Association Ally Harmonized System of Classification and Labelling of Chemicals erican Conference of Governmental Industrial Hygienists uropean Inventory of Existing Commercial Chemical Substances iropean List of Notified Chemical Substances ical Abstracts Service (division of the American Chemical Society) onal Fire Protection Association (USA) urdous Materials Identification System (USA) orkplace Hazardous Materials Information System (Canada) ved No-Effect Level (REACH) dicted No-Effect Concentration (REACH) al concentration, 50 percent al dose, 50 percent boared by: Inc. th Florida Avenue
ACGIH: Am EINECS: E ELINCS: Eu CAS: Chem NFPA: Nati HMIS: Haza WHMIS: W DNEL: Deri PNEC: Pred LC50: Letha LD50: Letha SOURCES SDS Pred Chem Tel 1305 Nor Tampa, F Toll Free	Ational Air Transport Association Ally Harmonized System of Classification and Labelling of Chemicals erican Conference of Governmental Industrial Hygienists uropean Inventory of Existing Commercial Chemical Substances iropean List of Notified Chemical Substances ical Abstracts Service (division of the American Chemical Society) onal Fire Protection Association (USA) urdous Materials Identification System (USA) orkplace Hazardous Materials Information System (Canada) ved No-Effect Level (REACH) dicted No-Effect Concentration (REACH) al concentration, 50 percent al dose, 50 percent boared by: Inc.


Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and

GHS

Printing date 1/24/2013

Revision: 1/24/2013



Printing date 1/24/2013

Revision: 1/24/2013

Trade name: Rislone® Diesel Treat Right Side

(Contd. of page 1)

· NFPA ratings (scale 0 - 4)



• HMIS-ratings (scale 0 - 4)

 $\begin{array}{c|c} \text{HEALTH} & 1 \\ \text{FIRE} & 1 \\ \hline \end{array} \quad \text{Fire} = 1 \\ \end{array}$

Reactivity = 0

· HMIS Long Term Health Hazard Substances

None of the ingredients is listed.

2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 64741-65-7	Naphtha (petroleum), heavy alkylate	<10%
EINECS: 265-067-2	🗙 Xn R65	
Index number: 649-275-00-4	Carc. Cat. 2, Muta. Cat. 2	
	🚸 Flam. Liq. 3, H226	
	🗞 Asp. Tox. 1, H304	

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· 4.1 Description of first aid measures

- General information: Take affected persons out into the fresh air.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)

Printing date 1/24/2013

Revision: 1/24/2013

Trade name: Rislone® Diesel Treat Right Side

(Contd. of page 2)

A person vomiting while laying on their back should be turned onto their side.

• 4.2 Most important symptoms and effects, both acute and delayed

- Dizziness
- Nausea

Cramp

· Hazards No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

5 Firefighting measures

 5.1 Extinguishing media • Suitable extinguishing agents: Foam Alcohol resistant foam Fire-extinguishing powder Gaseous extinguishing agents Water haze or fog • For safety reasons unsuitable extinguishing agents: Water with full jet Water sprav 5.2 Special hazards arising from the substance or mixture In case of fire, the following can be released: Carbon monoxide (CO) Under certain fire conditions, traces of other toxic gases cannot be excluded. 5.3 Advice for firefighters Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit.

• Additional information Cool endangered receptacles with water fog or haze.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 1/24/2013

Revision: 1/24/2013

Trade name: Rislone® Diesel Treat Right Side

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. • Information about fire - and explosion protection: No special measures required.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

• Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

- Provide ventilation for receptacles.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Store away from oxidizing agents.

· Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.
- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

(Contd. on page 5)

GHS

Printing date 1/24/2013

Revision: 1/24/2013

Trade name: Rislone® Diesel Treat Right Side

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses

- · **Body protection:** Protective work clothing
- Limitation and supervision of exposure into the environment No further relevant information available.
- · Risk management measures
- See Section 7 for additional information.
- No further relevant information available.

9.1 Information on basic physical General Information Appearance:	and chemical properties	
Form:	Liquid	
Colour:	Light yellow	
Odour:	Petroleum-like	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	>500 ° F / >260 °C	
Flash point:	>199 ° F / >93 °C	
		(Contd. on page

Printing date 1/24/2013

Revision: 1/24/2013

Trade name: Rislone® Diesel Treat Right Side

		(Contd. of page
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	669 ° F / 354 °C	
Decomposition temperature:	Not determined.	
Self-igniting:	Product is not self-igniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	0.7 Vol %	
Upper:	6.5 Vol %	
Vapour pressure at 20 °C:	1.1 hPa	
Density at 20 °C:	0.86 g/cm ³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	iter): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	Not determined.	
Solids content:	Not determined.	
9.2 Other information	No further relevant information available.	

10 Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with strong oxidizing agents.
- 10.4 Conditions to avoid Store away from oxidizing agents.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
- Carbon monoxide and carbon dioxide
- Nitrogen oxides

(Contd. on page 7)

Printing date 1/24/2013

Revision: 1/24/2013

Trade name: Rislone® Diesel Treat Right Side

(Contd. of page 6)

11 Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity:

· LD/LC50 values relevant for classification:

64741-65-7 Naphtha (petroleum), heavy alkylate

Oral LD50 > 6000 mg/kg (rat)

- Dermal LD50 > 3000 mg/kg (rabbit)
- Inhalative LC50/4 h > 7.8 mg/l (rat)

· Primary irritant effect:

• on the skin: Slight irritant effect on skin and mucous membranes.

· on the eye: Slight irritant effect on eyes.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: The material is harmful to the environment.
- **12.2 Persistence and degradability** The product is partly biodegradale. Significant residuals remain.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark:

Due to mechanical actions of the product (e.g. agglutinations) damages may occur.

The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.

· Additional ecological information:

· General notes:

This statement was deduced from the properties of the single components.

Avoid transfer into the environment.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

• 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

(Contd. on page 8)

Printing date 1/24/2013

Revision: 1/24/2013

Trade name: Rislone® Diesel Treat Right Side

(Contd. of page 7)

13 Disposal considerations

13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. Contact waste processors for recycling information.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

4 Transport information		
· 14.1 UN-Number · DOT, ADR, ADN, IMDG, IATA	N/A	
 14.2 UN proper shipping name DOT, ADR, ADN, IMDG, IATA 	N/A	
· 14.3 Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA · Class	N/A	
 14.4 Packing group DOT, ADR, IMDG, IATA 	N/A	
 14.5 Environmental hazards: Marine pollutant: 	No	
· 14.6 Special precautions for user	Not applicable.	
 14.7 Transport in bulk according to Ann MARPOL73/78 and the IBC Code 	ex II of Not applicable.	
· UN "Model Regulation":	-	

15 Regulatory information

\cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot United States (USA)

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

(Contd. on page 9)

Printing date 1/24/2013

Revision: 1/24/2013

Trade name: Rislone® Diesel Treat Right Side

	(Contd. of page
TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
Proposition 65 (California):	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
 Chemicals known to cause reproductive toxicity for males: 	
None of the ingredients is listed.	
 Chemicals known to cause developmental toxicity: 	
None of the ingredients is listed.	
· Carcinogenic Categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· IARC (International Agency for Research on Cancer)	
None of the ingredients is listed.	
 TLV (Threshold Limit Value established by ACGIH) 	
None of the ingredients is listed.	
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
· Canadian Ingredient Disclosure list (limit 1%)	
None of the ingredients is listed.	
• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carr	ried out.
6 Other information	
This information is based on our present knowledge. However, this shall not constitute	a quarantee for a
specific product features and shall not establish a legally valid contractual relationship.	

· Relevant phrases

H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways.

R65 Harmful: may cause lung damage if swallowed.

(Contd. on page 10)

Printing date 1/24/2013

Revision: 1/24/2013

Trade name: Rislone® Diesel Treat Right Side

(Contd. of page 9) · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) WHMIS: Workplace Hazardous Materials Information System (Canada) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent · Sources SDS Prepared by: ChemTel Inc. **ChemTel** 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com