

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Spray Gun Lube
Part Number: DeVilbiss Automotive Refinishing Part No. 803888
Product Description: Spray Gun and Paint Mixing Equipment Lube.
SDS #: SDS-176
Chemical Formula: A proprietary soy-based organic solvent.
CAS Number: Not Applicable.
Article Code: Not Applicable.
General Use: A solution of proprietary chemicals that is used as a spray gun lubricant and protectant.

Relevant identified uses of the substance or mixture and uses advised against:
Not applicable.

Company Information:
DeVilbiss Automotive Refinishing
11360 S. Airfield Rd.
Swanton, Ohio 43558
Customer Service Phone: 1-800-445-3988

Emergency telephone number - CHEMTREC (24 HOURS): 1-800-424-9300

2. HAZARDS IDENTIFICATION

Potential Acute Health Effects

Ingestion: Not Hazardous

Skin Contact: Prolonged or repeated skin contact is not likely to cause significant skin irritation.

Eye Contact: May cause irritation. Irrigate eye with water for 10 – 20 minutes. Seek medical attention if irritation persists.

Inhalation: Vapors or mists may cause irritation of the mucous membranes, dizziness and nausea.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Components:

CHEMICAL NAME	CAS#	% Wt	Hazardous
Soy Methyl Ester, Methyl Soyate	67784-80-9	95 – 99%	Not Hazardous
Misc. Additives		1 – 5%	Not Hazardous

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. Get medical attention if irritation persists.

- Ingestion:** Give one or two glasses of water to drink. If gastrointestinal symptoms develop seek medical attention. Never give anything by mouth to an unconscious person.
- Skin Contact:** Wash exposed area of the body with soap and water.
- Eye Contact:** Remove any contact lenses. If irritation develops, flush eyes with plenty of water for at least 15 minutes.

5. FIRE-FIGHTING MEASURES

- NFPA Rating:** Health 1, Flammability 1, Reactivity 0
- Flash Point:** 130°C (ASTM 93)
- Flammability Limits:** None known
- Extinguishing Media:** Water fog, Foam, Dry chemical, Halon or Carbon Dioxide CO2
Water may splash the burning liquid and spread the fire.
- Special Fire Fighting Procedures:** Treat as an oil fire
- Hazardous Combustion Products:** Oil soaked rags can cause spontaneous combustion if not properly handled. Wash rags with soap and water then dry in a well ventilated area.
- Fire Fighting Equipment:** Wear SCBA self-contained breathing apparatus to avoid exposure to smoke and vapor.

6. ACCIDENTAL RELEASE MEASURES

- Small Spills/Leaks:** Remove any sources of ignition. Find the source and stop the leak. Pick up small spills with absorbent materials such as paper towels, "Oil Dry", sand or dirt.
- Large Spills: Containment:** Remove large spills for salvage or disposal. Dispose of unusable material in accordance to local and State governmental guidelines. Wash hard surfaces with a safety solvent or detergent to remove remaining oil film. Dispose of unusable material in accordance with local and State governmental guidelines.

7. HANDLING AND STORAGE

Precautions for safe handling

- Storage:** Store in closed containers between 50F and 120F.
Keep away from oxidizing agents, excessive heat and ignition sources.
Store and use in well ventilated areas.
Do not store or use near heat, spark, or flame.
Store out of the sun.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering Controls:** Use process enclosures, local exhaust ventilation
- Personal Protection:** Safety glasses, goggles, or face shields are recommended to protect eyes from mists or splashing. PVC coated gloves are recommended to prevent skin contact.

- Respiratory Protection:** If vapors or mists are generated, wear NIOSH approved organic vapor/mist respirator.
- Other Protective Measures:** Employees must practice good personal hygiene, washing exposed areas of skin several times daily and laundering contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State / Appearance:	Pale orange liquid
Solubility in water:	Insoluble
Odor:	Mild organic
Boiling Point:	>200C
Melting Point:	< -13C
Flash Point:	130 C (ASTM 93)
Specific Gravity:	0.85 – 0.90 at 15 C
Vapor Pressure:	< 2 mm Hg
Vapor Density:	> 1, air = 1
Viscosity:	3.5 – 5.0 mm ² /s (40 C)
Evaporation Rate:	< 1, butyl acetate = 1
Volatility:	< 2, % by volume

10. STABILITY AND REACTIVITY

- Stability:** Stable under ordinary conditions of use and storage
- Incompatibility:** Strong oxidizing agents
- Special Notes on Reactivity:** None
- Hazardous Decomposition or Byproducts:** Combustion produces carbon monoxide, along with thick smoke.
- Hazardous Polymerization:** Will not occur

11. TOXICOLOGICAL INFORMATION

Toxicological Information:

- Acute Fish Toxicity:** LC50 > 100 mg RME / L
- Bacteria Toxicity:** EC50 > 100 mg RME / L
- Chronic Effects on Humans:** Not Available
- Other Toxic Effects on Humans:** Slightly hazardous in case of skin contact (irritant).
Slightly hazardous in case of ingestion, of inhalation.

12. ECOLOGICAL INFORMATION

- Toxicity**
- Environmental Degradation:** This product is biodegradable

13. DISPOSAL CONSIDERATIONS

The generator of a waste is always responsible for making proper hazardous waste determinations and needs to consider state and local requirements in addition to federal regulations.

Waste may be disposed of by a licensed waste disposal company. Contaminated absorbent material may be disposed of in an approved landfill. Follow local, state and federal disposal regulations.

14. TRANSPORT INFORMATION

UN HAZARD CLASS: N/A
PROPER SHIPPING NAME: Fatty acid ester
NMFC IDENTIFICATION NUMBER: 144920
SHIPPING CLASSIFICATION: 65

US FEDERAL:
TSCA: This product is listed on TSCA

15. REGULATORY INFORMATION

Federal Regulations

OSHA STATUS: This product is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, thermal processing and decomposition fumes from this product may be hazardous as noted in Sections 2 and 3.

CERCLA (Comprehensive Response Compensation and Liability Act): NOT Reportable

Health and Safety Reporting List

SARA TITLE III (Superfund Amendments and Reauthorization Act):

Section 312 Extremely Hazardous Substances: None
Section 311/312 Hazard Categories: None
Section 313 Toxic Chemicals: None

RCRA STATUS: If discarded in purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCLA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. (40 CFR 261.20-24)

CALIFORNIA PROP 65:

The following statement s made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act 1986. This product contains no chemicals known to the state of California to cause cancer.

HMIS (USA): Health Hazard 1, Fire 1, Reactivity 0

NFPA: Health 1, Flammability 1, Reactivity 0

16. OTHER INFORMATION

Date Revised: 08/31/2015
Date Prepared: 06/19/2015

SDS PREPARED BY: Director of Chemical Safety

The information contained herein is based on data available to us and is accurate and reliable to the best of our knowledge and belief. However, DeVilbiss makes no representations as to its completeness or accuracy. Information is supplied on condition that persons receiving such information will make their own determination as to its suitability for their purposes prior to use. In no event will DeVilbiss be responsible for damages of any nature whatsoever resulting from the use of or reliance upon the information contained herein.

*** END OF SDS ***

©2015 Carlisle Fluid Technologies, Inc., dba Finishing Brands. All rights reserved.
DeVilbiss is part of Finishing Brands, a global leader of innovative spray finishing technologies.