

SUS 42, 42-1, 42-5  
**MATERIAL SAFETY DATA SHEET**

**Smitty's Supply Inc.**

63399 Hwy 51 North; Roseland, LA 70456 • (985) 748-9687

**MATERIAL SAFETY DATA SHEET**

May be used to comply OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

**U.S. DEPARTMENT OF LABOR**

Occupational Safety and Health Administration.  
 (Non-Mandatory Form) Form Approved OMB  
 No 1218-0072

**SECTION I**

**GENERAL INFORMATION**

PRODUCT NAME

Super S TYPE A AUTOMATIC TRANSMISSION FLUID

**SECTION II**

**HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

COMPONENT	WT. %	C.A.S. No	TLV (ACGIHxx OSHA--)
Petroleum Distillates, Hydrotreated Light Naphthenic Petroleum Distillates.	Blend	64742-53-6	5 mg/m3 (Mist)
Hydrotreated Heavy Naphthenic	Blend	64742-52-5	5 mg/m3 (Mist)

Comments: The maximum percentage of the petroleum distillate and/or residual oil blend contained in this product is: 100%.

All mineral oils used in this product have been severely hydrotreated and/or solvent refined. Exact composition of this product will vary with availability of materials. All ingredients listed above may not be always included in final product. This product is considered not hazardous according to 29 CFR 1910.1200 (Hazard Communication).

**SECTION III**

**PHYSICAL/CHEMICAL CHARACTERISTICS**

Specific Gravity (H <sub>2</sub> O=1)	0.91	Appearance and Odor	Red liquid with petroleum odor
Solubility in Water	Negligible	pH	N/A
Flash Point (COC), °F (°C)	340 (171)	Solubility in Solvent	Hydrocarbons
Melting Point, °F	N/A	%Volatiles By Wt.	Nil
Vapor Pressure (mmHg)	N/A	Pour Point, °F (°C)	-15 (-26)
Evaporation Rate (Butyl Acetate=1)	N/A	Vapor Density (Air=1)	Heavier than air

**SECTION IV**

**FIRE AND EXPLOSION HAZARD DATA**

EXTINGUISHING MEDIA:

Water xx      Foam xx      CO<sub>2</sub> xx      Dry Chemicals xx

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained, positive pressure breathing apparatus and impervious protective clothing. Avoid inhaling any combustion products.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Water steam may spread fire. Direct water spray or foam may cause frothing and spattering. Use water to cool fire-exposed containers and to protect personnel. If a leak or spill has not ignited, use water spray to disperse vapors and to flush spills away from exposure.

**SECTION V**

**REACTIVITY DATA**

Stable xx    Unstable    Corrosive No    Hazardous Polymerization?    Yes    No xx

Incompatibilities: Strong oxidizing agents (peroxides, chlorine, strong acids).

Hazardous Decomposition or Byproducts: Decomposition and combustion products may include fumes, smoke, sulfur dioxide, oxides of zinc, boron, magnesium, calcium, phosphorus, carbon monoxide, carbon dioxide and other low molecular weight hydrocarbons.

Effective Date: 01/01/2000

Date Printed: 19/09/2002

**SECTION VI HEALTH HAZARD INFORMATION**

Recommended TLV of Product

N/A

EYE  
CONTACT May cause irritation.SKIN  
CONTACT May cause irritation.  
Irritation or dermatitis with  
prolonged and /or  
repeated exposure.INHA-  
LATION An unlikely way of exposure at  
standard temperatures and pressures.  
Inhalation of oil mists or fumes can  
cause irritation of the nose, throat and  
upper respiratory tract. Repeated and  
prolonged overexposure to oil mist  
may result in droplet deposition, oil  
granuloma formation, inflammation and  
increased incidence of infection.INGESTION May cause nausea,  
vomiting, and diarrhea.  
Small amount of this  
product, if aspirated into  
lungs, may cause mild to  
severe pulmonary injury,  
possibly death.

OTHER None known.

**SECTION VII EMERGENCY AND FIRST AID PROCEDURES**EYE CONTACT Flush with large amount of water for 15 minutes. Get medical attention if eye  
irritation develops or persists.SKIN CONTACT Wash immediately with soap and water. Remove contaminated clothing and  
wash before re-use. Get medical attention if skin disorder develops.INHALATION Remove individual to fresh air. If the affected person is not breathing, apply  
artificial respiration. Get medical attention if symptoms persist.

INGESTION DO NOT INDUCE VOMITING. Get medical attention or advice.

**SECTION VIII SPECIAL PROTECTION INFORMATION**RESPIRATORY PROTECTION CONSUMER BULK HANDLING (Prolonged Exposure)  
N/A If mist is generated (heating, spraying) and  
engineering control are not sufficient, wear approved  
organic vapor respirator suitable for oil mist.  
GeneralVENTILATION Use with  
adequate  
ventilation.

EYE PROTECTION N/A Goggles or full-face shield.

PROTECTIVE CLOTHING N/A Neoprene gloves and apron.

**SECTION IX PRECAUTIONS FOR SAFE HANDLING AND USE**SPILL OR LEAK  
PROCEDURE Observing health hazards described above, ventilate area. Remove  
ignition sources. Absorb with inert absorbent such as clay, sand or  
diatomaceous earth, commercial sorbents, or recover using pumps.  
Scoop up used absorbent into drums.WASTE DISPOSAL  
METHOD Dispose in accordance with all local, state and federal regulations.  
Keep this product out of sewers and waterways.STORAGE AND  
HANDLING  
PRECAUTIONS Do not store this material in open or unlabeled containers. Do not  
store near heat sparks, open flame or strong oxidizing agents.  
"Empty" containers retain product residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose  
such containers to heat, flame, sparks, static electricity, or other  
source of ignition: they may explode.OTHER PRECAUTIONS Wearing contact lenses is inadvisable. Keep away from children  
and animals.

*While Smitty's Supply Inc. believes this data is accurate as of revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for your information, investigation, and verification.*