SAFETY DATA SHEET

1. Identification

Product identifier Battery Protector Coating

Other means of identification

Product code 00237, 00319, 01253, 01940, 50752, 06064

Recommended useBattery protector **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name East Penn Manufacturing Co.

Address 102 Deka Road

Lyon Station, PA 19536

United States

Telephone General Information

Customer Service 610-682-4231

Website www.dekabatteries.com

E-mail Not available.

Emergency phone number 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)

610-682-6361

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air

supply during use and while product is drying. Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	60 - 70
Distillates (petroleum), solvent-refined heavy paraffinic		64741-88-4	10 - 20
n-Butyl stearate		123-95-5	3 - 5
Fatty Acids, C18-unsatd., Dimers		61788-89-4	1 - 3
Petrolatum		8009-03-8	1 - 3
Sorbitan monooleate		68910-94-1	1 - 3

Material name: Battery Protector Coating

SDS US

00237, 00319, 01253, 01940, 50752, 06064 Version #: 01 Issue date: 05-28-2015

Chemical name	Common name and synonyms	CAS number	%
Sorbitan oleate		1338-43-8	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately. Ingestion

Direct contact with eyes may cause temporary irritation.

Most important

symptoms/effects, acute and

delayed

Treat symptomatically. Indication of immediate

medical attention and special treatment needed

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Specific hazards arising from

Unsuitable extinguishing

media

During fire, gases hazardous to health may be formed.

Foam. Dry powder. Carbon dioxide (CO2).

the chemical Special protective equipment

and precautions for firefighters

Fire-fighting

Move containers from fire area if you can do so without risk.

Do not use water jet as an extinguisher, as this will spread the fire.

equipment/instructions General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

7. Handling and storage

Precautions for safe handling Conditions for safe storage, including any incompatibilities Use care in handling/storage. For product usage instructions, please see the product label. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

Components	Туре	Value	Form	
Fatty Acids, C18-unsatd., Dimers (CAS 61788-89-4)	TWA	5 mg/m3	Respirable	

Avoid discharge into drains, water courses or onto the ground.

Material name: Battery Protector Coating

Components	or Air Contaminants (29 CFR 1910.10 Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	PEL	5 mg/m3	Mist.
,		2000 mg/m3	
		500 ppm	
Petrolatum (CAS 8009-03-8)	PEL	5 mg/m3	Mist.
ACGIH			_
Components	Туре	Value	Form
Fatty Acids, C18-unsatd., Dimers (CAS 61788-89-4)	STEL	10 mg/m3	Respirable
	TWA	5 mg/m3	Respirable
US. ACGIH Threshold Limit Components	Values Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	TWA	5 mg/m3	Inhalable fraction.
n-Butyl stearate (CAS 123-95-5)	TWA	10 mg/m3	
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
,	STEL	10 mg/m3	Mist.
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	Ceiling	1800 mg/m3	
paramino (0/10 07/71-00-4)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
•	TWA	5 mg/m3	Mist.
ogical limit values	No biological exposure limits noted fo	r the ingredient(s).	
ropriate engineering trols	Good general ventilation (typically 10 should be matched to conditions. If apor other engineering controls to maint exposure limits have not been established.)	oplicable, use process enclosu ain airborne levels below reco	res, local exhaust ventilation mended exposure limits.
vidual protection measures, Eye/face protection	such as personal protective equipme Wear safety glasses with side shields		
	* * *		

Other Wear suitable protective clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Form Liquid.

Color Clear. Colorless.

Odor Mild petroleum.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Initial boiling point and boiling -5 °F (-20.6 °C) estimated 212 °F (100 °C) estimated

range

Flash point > 350 °F (> 176.7 °C) Cleveland Open Cup

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Not available.

Vapor pressure 0.6 hPa estimated

Vapor density > 1 (air = 1)

Relative density 0.9

Solubility (water) Negligible.

Partition coefficient Not available.

(n-octanol/water)

.....

Auto-ignition temperature 500 °F (260 °C) estimated

Decomposition temperature Not available.

Viscosity (kinematic) $> 20.5 \text{ mm}^2/\text{s} (104 \text{ °F} (40 \text{ °C}))$

Percent volatile 90.8 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation.

Material name: Battery Protector Coating

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not available.

Product Species Test Results

Battery Protector Coating

Acute Dermal

LD50 Rabbit 2077 mg/kg estimated

Oral

LD50 Rat 5173 mg/kg estimated

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Spacias

Specific target organ toxicity -

single exposure

Product

Specific target organ toxicity -

repeated exposure
Aspiration hazard

Not classified.

Not classified.

Not an aspiration hazard.

Further information This product has no known adverse effect on human health.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Fiduct		Species	rest ivesuits		
Battery Protector Coating					
Aquatic					
Crustacea	EC50	Daphnia	5088.2964 mg/l, 48 hours estimated		
Acute					
Fish	LC50	Fish	4746.7349 ppm, 96 hours estimated		
Components		Species	Test Results		

Toet Results

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Aquatic

Acute

Fish LC50 Pimephales promelas > 30000 mg/l, 96 hours

Sorbitan oleate (CAS 1338-43-8)

Aquatic

Acute

Fish LC50 Rainbow trout, donaldson trout > 1000 mg/l, 96 hours

(Oncorhynchus mykiss)

Material name: Battery Protector Coating

^{*} Estimates for product may be based on additional component data not shown.

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Fatty Acids, C18-unsatd., Dimers 1 - 2.5, logKow

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste residues / unused products

disposal site. Dispose in accordance with all applicable regulations.

Not regulated. Hazardous waste code

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard **US federal regulations**

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - No Delayed Hazard - No **Hazard categories**

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

No

Material name: Battery Protector Coating

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)

Petrolatum (CAS 8009-03-8)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

US. Massachusetts RTK - Substance List

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

None.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

100 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

VOC content (CA)

VOC content (OTC)

Not regulated

0 %

0 %

International Inventories

Country(s) or region	Inventory name On inventory	/ (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all compor	nents of this product comply with the inventory requirements administered by the governing country(s))

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

Issue date 05-28-2015

Version # 01

Further information Control # 09985/551B

HMIS® ratings Health: 1

Flammability: 1 Physical hazard: 0 Personal protection: B

16. Other information, including date of preparation or last revision

Material name: Battery Protector Coating

country(s).

NFPA ratings

Health: 1 Flammability: 1 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of our knowledge or obtained from sources believed to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or East Penn Manufacturing Company.